

Specification

Curve Lighting System

AS3535-05T180





AS3535-05T180




Features






- Various installation ways: pendant, recessed and surface mounted
- Ever-changing shapes generated by means of super free application and connections of lines and arcs
- Flexible diffuser making it easy for installation without connections for over length application and light leakage
- Specially designed light source with diffusers producing homogeneous and soft lighting
- AL6063-T5 aluminum profile with high-quality surface treatment and three optional colors of black, white and silver






Details



Optional Accessories



Picture	Item	Parameter
	①Profile	Material : AL6063-T5 Profile weight : 0.4kg/ 500mm , 180° Size : 35x35mm , 500mm , 180° Surface processing: Spray
	②Cover	Size : L20000*W32*H3.5mm Light transmittance: 60%
	③End cap	Size : L35*W35*H1.5mm
	④Flexible modular DT8140-24V-20mm	Material : AL,CCT:1900/2300/2700/3000/3500/4000/5000/6000K ; CRI > 80 ; Voltage : 24V ; Power : 19.2W/M ; Lumen : 2490Lm/M ; Width : 20mm ; Minimum cutting unit : 14LEDs/50mm ;
	⑤Screw set	Size : M3.5*40mm



Picture	Item	Parameter
	Pendant cable PN-WA2/4	Steel cable: D1.5*2000\4000mm\maximum load bearing:13Kg
	Pendant cable PN-CA2/4	Size:20AWG\2000mm\maximum load bearing:6.5Kg
	Surface mounted buckle CL-05	

Optical Parameter

AS3535-05T180 module/DT8140-24V-20mm light source, frosted diffuser



Package



Components	Packaging material	Size(mm)	NW(kg)	GW(kg)	Content
05T180	Hat box	640*390*210mm	8kg	9.44kg	20PCS/BOX

