


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.3121A P:7.490W PF:1.000 Freq:0Hz Lamp Flux:818.495x1 lm		
NAME: D61402408NO	TYPE:	WEIGHT:
SPEC.:D61402408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 109.28 lm/W			
MODEL	D6140248NO	I _{max} (cd)	271.6	S/MH(C0/180)	1.27
NOMINAL POWER(W)	7.3	LOR(%)	100.0	S/MH(C90/270)	1.27
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	818.50	h UP,DN(C0-180)	0.9,49.4
NOMINAL FLUX(lm)	818.495	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,48.9
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.4	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	266.8	267.8	268.0	268.3	267.4	267.1	266.5	266.2	0- 10	25.71	25.71	3.14,3.14
20	253.8	255.6	256.1	256.8	255.1	254.2	253.3	252.6	10- 20	73.98	99.70	12.2,12.2
30	232.4	234.9	235.8	237.0	234.7	233.4	232.0	230.9	20- 30	113.1	212.8	26.26
40	203.1	206.3	207.5	209.1	206.4	204.9	203.0	201.4	30- 40	137.9	350.7	42.8,42.8
50	166.4	170.0	171.6	173.8	170.9	169.3	167.1	164.6	40- 50	145.0	495.7	60.6,60.6
60	123.2	127.1	128.8	131.9	129.1	127.5	124.8	121.7	50- 60	132.9	628.6	76.8,76.8
70	75.21	78.78	80.81	84.56	82.30	80.96	77.78	74.24	60- 70	102.3	730.9	89.3,89.3
80	28.07	31.15	32.49	36.42	35.26	34.45	31.08	27.90	70- 80	58.25	789.1	96.4,96.4
90	2.362	3.385	1.253	4.115	3.584	3.981	0.9196	2.106	80- 90	15.94	805.1	98.4,98.4
100	0.9685	1.042	0.9284	0.9493	0.6215	0.5596	0.6557	0.6279	90-100	1.335	806.4	98.5,98.5
110	1.563	1.565	1.367	1.378	1.290	1.134	1.316	1.262	100-110	1.119	807.5	98.7,98.7
120	2.329	2.239	2.110	1.997	1.924	1.710	1.851	1.895	110-120	1.672	809.2	98.9,98.9
130	2.865	2.793	2.671	2.546	2.538	2.304	2.252	2.338	120-130	2.043	811.2	99.1,99.1
140	3.332	3.180	3.099	3.013	3.033	2.845	2.599	2.638	130-140	2.140	813.4	99.4,99.4
150	3.633	3.407	3.386	3.500	3.354	3.405	3.027	2.831	140-150	1.968	815.3	99.6,99.6
160	4.001	3.621	3.813	3.948	3.728	3.827	3.775	3.279	150-160	1.625	817.0	99.8,99.8
170	4.255	4.128	4.402	4.336	3.847	4.248	4.403	4.040	160-170	1.122	818.1	99.9,99.9
180	4.175	4.756	4.903	4.916	4.161	4.742	4.896	4.916	170-180	0.4156	818.5	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.3121A P:7.490W PF:1.000 Freq:0Hz Lamp Flux:818.495x1 lm		
NAME: D61402408NO	TYPE:	WEIGHT:
SPEC.:D61402408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	14902	18405
80	20210	23390
75	24552	27087
70	27487	29533
65	29491	31166
60	30805	32210
55	31733	32917
50	32368	33369
45	32823	33673


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.3121A P:7.490W PF:1.000 Freq:0Hz Lamp Flux:818.495x1 lm		
NAME: D61402408NO	TYPE:	WEIGHT:
SPEC.:D61402408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.79	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.60	.68	.63	.59	.57
4.0	.70	.61	.54	.68	.60	.53	.65	.58	.52	.63	.57	.52	.60	.55	.51	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.45	.54	.49	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.42	.35	.50	.41	.35	.48	.40	.35	.46	.40	.34	.45	.39	.34	.32
8.0	.46	.37	.32	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.29
9.0	.42	.34	.28	.41	.34	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.26
10.0	.39	.31	.26	.38	.31	.26	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.3121A P:7.490W PF:1.000 Freq:0Hz Lamp Flux:818.495x1 lm		
NAME: D61402408NO	TYPE:	WEIGHT:
SPEC.:D61402408NO-9NWN5A012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.313	.178	.056	.305	.174	.055	.291	.167	.053	.278	.160	.051	.266	.154	.050	
2.0	.294	.161	.049	.287	.158	.049	.275	.153	.047	.263	.148	.046	.252	.143	.045	
3.0	.272	.145	.043	.266	.142	.043	.255	.138	.042	.244	.134	.041	.235	.130	.040	
4.0	.251	.130	.038	.245	.128	.038	.236	.125	.037	.226	.122	.037	.218	.118	.036	
5.0	.232	.118	.034	.227	.117	.034	.218	.114	.033	.210	.111	.033	.202	.108	.032	
6.0	.215	.108	.031	.210	.106	.031	.203	.104	.030	.195	.101	.030	.188	.099	.029	
7.0	.200	.099	.028	.196	.098	.028	.189	.095	.027	.182	.093	.027	.176	.091	.027	
8.0	.186	.091	.026	.183	.090	.025	.177	.088	.025	.171	.086	.025	.165	.085	.025	
9.0	.175	.084	.024	.172	.084	.023	.166	.082	.023	.160	.080	.023	.155	.079	.023	
10.0	.164	.079	.022	.161	.078	.022	.156	.076	.022	.151	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.203	.203	.203	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.193	.169	.147	.165	.145	.126	.113	.100	.087	.065	.058	.051	.021	.019	.016	
2.0	.185	.145	.110	.159	.124	.095	.109	.086	.067	.063	.050	.039	.020	.016	.013	
3.0	.178	.127	.087	.152	.110	.075	.105	.076	.053	.060	.044	.031	.019	.014	.010	
4.0	.170	.114	.071	.146	.098	.062	.100	.069	.043	.058	.040	.026	.019	.013	.008	
5.0	.163	.104	.060	.140	.090	.052	.096	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.156	.095	.052	.134	.082	.045	.092	.058	.032	.053	.034	.019	.017	.011	.006	
7.0	.149	.088	.046	.128	.077	.040	.088	.054	.028	.051	.032	.017	.017	.010	.006	
8.0	.142	.083	.042	.122	.072	.036	.085	.050	.026	.049	.030	.015	.016	.010	.005	
9.0	.136	.078	.038	.117	.067	.033	.081	.047	.024	.047	.028	.014	.015	.009	.005	
10.0	.130	.073	.035	.112	.064	.031	.078	.045	.022	.045	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.3121A P:7.490W PF:1.000 Freq:0Hz Lamp Flux:818.495x1 lm											
NAME: D61402408NO						TYPE:		WEIGHT:			
SPEC.:D61402408NO-9NWN5A012WC0100						DIM.: 1000*8*1.5mm		SERIAL No.:			
MFR.: COLORS						SUR.:1000*8mm		Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.5	27.1	25.8	27.3	27.5	25.7	27.2	26.0	27.4	27.7	
	3H	27.0	28.4	27.3	28.7	29.0	27.2	28.6	27.6	28.9	29.2
	4H	27.6	28.9	27.9	29.2	29.5	27.8	29.2	28.2	29.5	29.8
	6H	27.9	29.2	28.3	29.5	29.8	28.3	29.5	28.6	29.8	30.1
	8H	28.0	29.2	28.4	29.5	29.8	28.4	29.6	28.7	29.9	30.2
	12H	28.0	29.2	28.4	29.5	29.8	28.4	29.6	28.8	29.9	30.2
4H	2H	26.2	27.5	26.5	27.8	28.1	26.3	27.6	26.6	27.9	28.2
	3H	27.8	29.0	28.2	29.3	29.7	28.0	29.2	28.4	29.5	29.8
	4H	28.5	29.6	28.9	29.9	30.3	28.7	29.8	29.1	30.2	30.5
	6H	28.9	29.9	29.4	30.3	30.7	29.3	30.2	29.7	30.6	31.0
	8H	29.1	29.9	29.5	30.3	30.8	29.4	30.3	29.9	30.7	31.1
	12H	29.1	29.9	29.6	30.4	30.8	29.5	30.3	30.0	30.7	31.2
8H	4H	28.8	29.6	29.2	30.0	30.5	29.0	29.9	29.4	30.2	30.7
	6H	29.3	30.1	29.8	30.5	31.0	29.6	30.4	30.1	30.8	31.3
	8H	29.5	30.2	30.0	30.6	31.1	29.9	30.5	30.3	31.0	31.4
	12H	29.7	30.2	30.2	30.7	31.2	30.0	30.6	30.5	31.1	31.6
12H	4H	28.8	29.6	29.2	30.0	30.4	29.0	29.8	29.4	30.2	30.6
	6H	29.4	30.0	29.9	30.5	31.0	29.7	30.3	30.2	30.8	31.3
	8H	29.6	30.2	30.1	30.7	31.2	29.9	30.5	30.4	31.0	31.5
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 818.5 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.7)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.3121A P:7.490W PF:1.000 Freq:0Hz Lamp Flux:818.495x1 lm		
NAME: D61402408NO	TYPE:	WEIGHT:
SPEC.:D61402408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	45	38	56	44	38	54	44	37	31
0.80	66	55	47	65	54	47	63	53	47	40
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	81	71	64	78	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	82	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	101	94	89	99	93	88	95	90	85	76
4.00	106	100	95	103	98	94	99	94	91	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.3121A P:7.490W PF:1.000 Freq:0Hz Lamp Flux:818.495x1 lm		
NAME: D61402408NO	TYPE:	WEIGHT:
SPEC.:D61402408NO-9NWSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.3121A P:7.490W PF:1.000 Freq:0Hz Lamp Flux:818.495x1 lm		
NAME: D61402408NO	TYPE:	WEIGHT:
SPEC.:D61402408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Flux out:603.9 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.3121A P:7.490W PF:1.000 Freq:0Hz Lamp Flux:818.495x1 lm		
NAME: D61402408NO	TYPE:	WEIGHT:
SPEC.:D61402408NO-9NWN5A012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-01-08

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.3121A P:7.490W PF:1.000 Freq:0Hz Lamp Flux:818.495x1 lm		
NAME: D61402408NO	TYPE:	WEIGHT:
SPEC.:D61402408NO-9NWN5A012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	271	272	271	271	271	272	271	271										
5	270	271	271	271	270	270	270	270										
10	267	268	268	268	267	267	267	266										
15	261	263	263	264	262	262	261	261										
20	254	256	256	257	255	254	253	253										
25	244	246	247	248	246	245	244	243										
30	232	235	236	237	235	233	232	231										
35	219	222	223	224	221	220	218	217										
40	203	206	207	209	206	205	203	201										
45	186	189	190	192	189	188	186	184										
50	166	170	172	174	171	169	167	165										
55	146	149	151	154	151	149	147	144										
60	123	127	129	132	129	128	125	122										
65	99.7	103	105	109	106	105	102	98.4										
70	75.2	78.8	80.8	84.6	82.3	81.0	77.8	74.2										
75	50.8	54.2	56.1	59.9	58.3	57.1	53.8	50.1										
80	28.1	31.1	32.5	36.4	35.3	34.5	31.1	27.9										
85	10.4	12.8	12.8	16.6	15.4	15.6	12.5	10.4										
90	2.36	3.38	1.25	4.11	3.58	3.98	0.92	2.11										
95	1.43	1.33	0.95	1.47	1.13	0.76	0.34	0.67										
100	0.97	1.04	0.93	0.95	0.62	0.56	0.66	0.63										
105	1.25	1.26	1.04	1.12	0.94	0.85	1.00	0.95										
110	1.56	1.57	1.37	1.38	1.29	1.13	1.32	1.26										
115	1.91	1.90	1.79	1.70	1.60	1.45	1.60	1.57										
120	2.33	2.24	2.11	2.00	1.92	1.71	1.85	1.90										
125	2.58	2.53	2.43	2.27	2.25	1.99	2.06	2.12										
130	2.87	2.79	2.67	2.55	2.54	2.30	2.25	2.34										
135	3.17	3.00	2.93	2.78	2.80	2.54	2.45	2.55										
140	3.33	3.18	3.10	3.01	3.03	2.84	2.60	2.64										
145	3.49	3.30	3.27	3.25	3.21	3.12	2.76	2.75										
150	3.63	3.41	3.39	3.50	3.35	3.41	3.03	2.83										
155	3.81	3.50	3.53	3.75	3.55	3.62	3.40	2.98										
160	4.00	3.62	3.81	3.95	3.73	3.83	3.77	3.28										
165	4.15	3.81	4.17	4.12	3.91	4.04	4.09	3.61										
170	4.25	4.13	4.40	4.34	3.85	4.25	4.40	4.04										
175	4.09	4.48	4.68	4.62	3.85	4.49	4.68	4.51										
180	4.17	4.76	4.90	4.92	4.16	4.74	4.90	4.92										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: