


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.4737A P:11.37W PF:1.000 Freq:0Hz Lamp Flux:1218.8x1 lm		
NAME: D62102408NO	TYPE:	WEIGHT:
SPEC.:D62102408NO-9NWSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 107.21 lm/W			
MODEL	D62102408NO	I _{max} (cd)	405.6	S/MH (C0/180)	1.27
NOMINAL POWER (W)	10.9	LOR (%)	100.0	S/MH (C90/270)	1.27
RATED VOLTAGE (V)	24	TOTAL FLUX (lm)	1218.8	h UP,DN (C0-180)	0.9,49.3
NOMINAL FLUX (lm)	1218.8	CIE CLASS	DIRECT	h UP,DN (C180-360)	0.8,49.0
LAMPS INSIDE	1	h up (%)	1.7	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	24	h down (%)	98.3	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	398.2	397.5	399.6	398.3	397.4	399.0	396.3	397.8	0~ 10	38.36	38.36	3.15,3.15
20	378.9	379.0	381.5	381.0	379.2	380.2	377.0	377.8	10~ 20	110.2	148.5	12.2,12.2
30	347.3	348.2	351.3	351.4	348.9	349.6	345.7	345.6	20~ 30	168.5	317.0	26.26
40	303.4	305.5	308.9	310.1	307.0	306.9	302.8	301.6	30~ 40	205.5	522.5	42.9,42.9
50	248.6	251.7	255.4	257.8	254.5	253.9	249.4	247.2	40~ 50	216.2	738.8	60.6,60.6
60	182.9	187.9	190.7	195.6	192.3	190.1	186.4	181.6	50~ 60	197.9	936.7	76.9,76.9
70	111.4	116.4	119.6	125.6	122.8	120.7	116.1	110.7	60~ 70	152.0	1089	89.3,89.3
80	41.30	45.59	47.72	54.31	52.65	51.01	45.86	41.44	70~ 80	86.47	1175	96.4,96.4
90	3.659	4.784	1.973	6.627	5.584	5.588	0.8918	3.421	80~ 90	23.50	1199	98.3,98.3
100	1.449	1.538	1.343	1.423	0.9294	0.8683	0.9851	1.052	90~100	2.032	1201	98.5,98.5
110	2.411	2.374	2.067	2.072	1.917	1.730	2.011	1.962	100~110	1.691	1202	98.7,98.7
120	3.412	3.340	3.164	3.034	2.886	2.635	2.846	2.899	110~120	2.532	1205	98.9,98.9
130	4.295	4.097	3.906	3.801	3.754	3.425	3.495	3.620	120~130	3.069	1208	99.1,99.1
140	5.007	4.636	4.488	4.503	4.483	4.279	3.988	4.055	130~140	3.192	1211	99.4,99.4
150	5.417	4.943	4.889	5.211	4.937	5.120	4.503	4.381	140~150	2.932	1214	99.6,99.6
160	5.956	5.270	5.629	5.832	5.478	5.770	5.538	4.875	150~160	2.406	1217	99.8,99.8
170	6.226	6.139	6.438	6.379	5.631	6.285	6.413	6.083	160~170	1.657	1218	99.9,99.9
180	6.058	7.054	7.147	7.200	6.071	7.054	7.154	7.180	170~180	0.6107	1219	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-08

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.4737A P:11.37W PF:1.000 Freq:0Hz Lamp Flux:1218.8x1 lm		
NAME: D62102408NO	TYPE:	WEIGHT:
SPEC.:D62102408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	21856	27112
80	29729	34349
75	36242	39940
70	40708	43718
65	43700	46116
60	45715	47684
55	47428	49036
50	48337	49676
45	49045	50168


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.4737A P:11.37W PF:1.000 Freq:0Hz Lamp Flux:1218.8x1 lm		
NAME: D62102408NO	TYPE:	WEIGHT:
SPEC.:D62102408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.90	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.79	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.60	.68	.63	.59	.57
4.0	.70	.61	.54	.68	.60	.53	.65	.58	.52	.63	.57	.52	.60	.55	.51	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.45	.54	.49	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.39	.36
7.0	.50	.42	.35	.50	.41	.35	.48	.40	.35	.46	.40	.34	.45	.39	.34	.32
8.0	.46	.37	.32	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.29
9.0	.42	.34	.28	.42	.34	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.26
10.0	.39	.31	.26	.38	.31	.26	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.4737A P:11.37W PF:1.000 Freq:0Hz Lamp Flux:1218.8x1 lm		
NAME: D62102408NO	TYPE:	WEIGHT:
SPEC.:D62102408NO-9NWN5A012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)									
0.0																
1.0	.312	.178	.056	.305	.174	.055	.291	.167	.053	.278	.160	.051	.266	.154	.050	
2.0	.294	.161	.049	.287	.158	.049	.275	.153	.047	.263	.147	.046	.252	.143	.045	
3.0	.272	.145	.043	.266	.142	.043	.255	.138	.042	.244	.134	.041	.235	.130	.040	
4.0	.251	.130	.038	.245	.128	.038	.235	.125	.037	.226	.121	.037	.218	.118	.036	
5.0	.232	.118	.034	.227	.116	.034	.218	.113	.033	.210	.111	.033	.202	.108	.032	
6.0	.215	.108	.031	.210	.106	.031	.202	.104	.030	.195	.101	.030	.188	.099	.029	
7.0	.200	.099	.028	.196	.098	.028	.189	.095	.027	.182	.093	.027	.176	.091	.027	
8.0	.186	.091	.026	.183	.090	.025	.177	.088	.025	.171	.086	.025	.165	.085	.025	
9.0	.175	.084	.024	.172	.084	.023	.166	.082	.023	.160	.080	.023	.155	.079	.023	
10.0	.164	.079	.022	.161	.078	.022	.156	.076	.022	.151	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.203	.203	.203	.174	.174	.174	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.193	.169	.147	.165	.145	.126	.113	.100	.087	.065	.058	.051	.021	.019	.016	
2.0	.185	.145	.111	.159	.125	.096	.109	.086	.067	.063	.050	.039	.020	.016	.013	
3.0	.178	.127	.087	.152	.110	.075	.105	.076	.053	.060	.044	.031	.019	.014	.010	
4.0	.170	.114	.071	.146	.098	.062	.100	.069	.043	.058	.040	.026	.019	.013	.008	
5.0	.163	.104	.060	.140	.090	.052	.096	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.156	.095	.052	.134	.082	.045	.092	.058	.032	.054	.034	.019	.017	.011	.006	
7.0	.149	.088	.046	.128	.077	.040	.088	.054	.028	.051	.032	.017	.017	.010	.006	
8.0	.142	.083	.042	.122	.072	.036	.085	.050	.026	.049	.030	.015	.016	.010	.005	
9.0	.136	.078	.038	.117	.067	.033	.081	.047	.024	.047	.028	.014	.015	.009	.005	
10.0	.130	.073	.035	.112	.064	.031	.078	.045	.022	.046	.027	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.4737A P:11.37W PF:1.000 Freq:0Hz Lamp Flux:1218.8x1 lm											
NAME: D62102408NO					TYPE:			WEIGHT:			
SPEC.:D62102408NO-9NWN5A012WC0100					DIM.: 1000*8*1.5mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*8mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	25.5	27.0	25.8	27.3	27.5	25.7	27.2	26.0	27.4	27.6	
	3H	27.0	28.4	27.3	28.7	28.9	27.2	28.6	27.5	28.9	29.1
	4H	27.5	28.9	27.9	29.1	29.4	27.8	29.1	28.1	29.4	29.7
	6H	27.9	29.1	28.2	29.4	29.7	28.2	29.5	28.6	29.8	30.1
	8H	27.9	29.2	28.3	29.5	29.8	28.3	29.5	28.7	29.8	30.2
	12H	28.0	29.1	28.4	29.5	29.8	28.4	29.5	28.7	29.9	30.2
4H	2H	26.2	27.5	26.5	27.8	28.1	26.3	27.6	26.6	27.9	28.2
	3H	27.8	29.0	28.2	29.3	29.6	28.0	29.1	28.4	29.5	29.8
	4H	28.5	29.5	28.9	29.9	30.2	28.7	29.8	29.1	30.1	30.5
	6H	28.9	29.8	29.3	30.2	30.6	29.2	30.1	29.6	30.5	30.9
	8H	29.0	29.9	29.5	30.3	30.7	29.4	30.2	29.8	30.6	31.1
	12H	29.1	29.9	29.5	30.3	30.7	29.5	30.3	29.9	30.7	31.1
8H	4H	28.7	29.6	29.2	30.0	30.4	28.9	29.8	29.4	30.2	30.6
	6H	29.3	30.0	29.8	30.5	30.9	29.6	30.3	30.0	30.7	31.2
	8H	29.5	30.1	30.0	30.6	31.1	29.8	30.4	30.3	30.9	31.4
	12H	29.6	30.2	30.1	30.6	31.1	30.0	30.5	30.5	31.0	31.5
12H	4H	28.7	29.5	29.2	29.9	30.4	28.9	29.7	29.4	30.1	30.6
	6H	29.3	30.0	29.8	30.4	30.9	29.6	30.3	30.1	30.7	31.2
	8H	29.6	30.1	30.1	30.6	31.1	29.9	30.4	30.4	30.9	31.4
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2				+ 0.1 / - 0.2						
1.5H	+ 0.2 / - 0.3				+ 0.2 / - 0.3						
2.0H	+ 0.2 / - 0.3				+ 0.2 / - 0.3						

CIE Pub.117, 1219 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.7)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.4737A P:11.37W PF:1.000 Freq:0Hz Lamp Flux:1218.8x1 lm		
NAME: D62102408NO	TYPE:	WEIGHT:
SPEC.:D62102408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	45	38	56	44	38	54	44	37	31
0.80	67	55	47	65	54	47	63	53	47	40
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	81	71	64	78	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	82	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	102	95	89	99	93	88	95	90	85	76
4.00	106	100	95	103	98	94	99	94	91	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.4737A P:11.37W PF:1.000 Freq:0Hz Lamp Flux:1218.8x1 lm		
NAME: D62102408NO	TYPE:	WEIGHT:
SPEC.:D62102408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-01-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.4737A P:11.37W PF:1.000 Freq:0Hz Lamp Flux:1218.8x1 lm		
NAME: D62102408NO	TYPE:	WEIGHT:
SPEC.:D62102408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Flux out:900.0 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.4737A P:11.37W PF:1.000 Freq:0Hz Lamp Flux:1218.8x1 lm		
NAME: D62102408NO	TYPE:	WEIGHT:
SPEC.:D62102408NO-9NWSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-01-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.4737A P:11.37W PF:1.000 Freq:0Hz Lamp Flux:1218.8x1 lm		
NAME: D62102408NO	TYPE:	WEIGHT:
SPEC.:D62102408NO-9NWN5A012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Table--1

UNIT: cd

C (DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	405	406	405	405	405	406	405	405										
5	404	405	404	405	404	404	404	403										
10	398	397	400	398	397	399	396	398										
15	390	390	392	391	390	391	388	389										
20	379	379	381	381	379	380	377	378										
25	365	365	368	368	366	366	363	363										
30	347	348	351	351	349	350	346	346										
35	327	328	331	332	329	329	326	325										
40	303	306	309	310	307	307	303	302										
45	277	280	284	285	282	282	277	276										
50	249	252	255	258	255	254	249	247										
55	218	221	225	228	225	224	219	216										
60	183	188	191	196	192	190	186	182										
65	148	153	156	161	158	156	152	147										
70	111	116	120	126	123	121	116	111										
75	75.0	79.8	82.7	89.2	87.0	84.9	80.0	74.7										
80	41.3	45.6	47.7	54.3	52.6	51.0	45.9	41.4										
85	15.2	18.2	18.9	24.7	23.2	22.6	17.6	15.5										
90	3.66	4.78	1.97	6.63	5.58	5.59	0.89	3.42										
95	2.18	1.94	1.37	2.29	1.78	1.30	0.51	1.08										
100	1.45	1.54	1.34	1.42	0.93	0.87	0.99	1.05										
105	1.86	1.87	1.60	1.69	1.41	1.33	1.50	1.47										
110	2.41	2.37	2.07	2.07	1.92	1.73	2.01	1.96										
115	2.93	2.87	2.64	2.59	2.40	2.17	2.48	2.44										
120	3.41	3.34	3.16	3.03	2.89	2.64	2.85	2.90										
125	3.89	3.75	3.54	3.45	3.33	3.02	3.19	3.30										
130	4.29	4.10	3.91	3.80	3.75	3.43	3.49	3.62										
135	4.67	4.41	4.25	4.15	4.14	3.85	3.77	3.86										
140	5.01	4.64	4.49	4.50	4.48	4.28	3.99	4.05										
145	5.23	4.80	4.70	4.85	4.74	4.68	4.20	4.21										
150	5.42	4.94	4.89	5.21	4.94	5.12	4.50	4.38										
155	5.68	5.08	5.21	5.54	5.21	5.45	5.03	4.57										
160	5.96	5.27	5.63	5.83	5.48	5.77	5.54	4.88										
165	6.18	5.61	6.05	6.09	5.72	5.98	5.99	5.41										
170	6.23	6.14	6.44	6.38	5.63	6.28	6.41	6.08										
175	5.99	6.63	6.81	6.76	5.60	6.62	6.82	6.70										
180	6.06	7.05	7.15	7.20	6.07	7.05	7.15	7.18										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: