


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:875.588x1 lm		
NAME: AH5060-15N90上	TYPE:	WEIGHT:
SPEC.:AH5060-15N90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 44.22 lm/W			
MODEL	AH5060-15N90上	I _{max} (cd)	267.0	S/MH(C0/180)	8.10
NOMINAL POWER(W)	19.53	LOR(%)	100.0	S/MH(C90/270)	7.01
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	875.59	h UP,DN(C0-180)	1.0,1.3
NOMINAL FLUX(lm)	875.588	CIE CLASS	DIFFUSE	h UP,DN(C180-360)	42.2,55.5
LAMPS INSIDE	1	h up(%)	43.2	CIBSE SHR NOM	0.00
TEST VOLTAGE(V)	24	h down(%)	56.8	CIBSE SHR MAX	1.00

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-08

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	4.190	4.582	4.622	4.355	36.18	27.81	26.53	26.86	0~ 10	1.171	1.171	0.13,0.13
20	3.388	3.920	4.028	3.807	76.53	54.85	52.51	53.11	10~ 20	7.069	8.240	0.94,0.94
30	3.140	3.614	3.687	3.507	117.5	82.39	78.88	79.90	20~ 30	18.28	26.52	3.03,3.03
40	2.792	3.505	3.634	3.486	157.6	109.7	105.0	106.3	30~ 40	34.17	60.69	6.93,6.93
50	2.445	3.447	3.540	3.453	195.0	135.6	129.8	130.9	40~ 50	53.30	114.0	13,13
60	2.164	3.547	3.540	3.508	227.2	158.2	151.7	152.3	50~ 60	73.52	187.5	21.4,21.4
70	2.350	3.641	3.627	3.567	251.8	175.4	168.5	168.6	60~ 70	92.14	279.6	31.9,31.9
80	4.152	3.814	3.714	3.694	265.6	183.6	176.5	176.0	70~ 80	106.0	385.6	44,44
90	6.517	3.987	3.841	3.767	266.6	183.5	176.1	175.2	80~ 90	111.8	497.4	56.8,56.8
100	5.845	3.271	3.174	3.086	247.5	169.2	162.5	160.9	90~100	109.2	606.6	69.3,69.3
110	5.284	2.830	2.739	2.686	197.3	133.6	127.2	125.0	100~110	89.61	696.2	79.5,79.5
120	4.110	2.211	2.171	2.104	159.1	101.0	96.10	94.76	110~120	64.52	760.7	86.9,86.9
130	3.407	2.017	1.957	1.924	127.6	82.40	78.53	77.12	120~130	47.07	807.8	92.3,92.3
140	2.913	1.723	1.770	1.703	102.9	65.36	62.65	61.51	130~140	32.70	840.5	96,96
150	2.071	1.242	1.270	1.221	74.83	47.43	45.84	44.74	140~150	20.67	861.2	98.4,98.4
160	1.564	0.9417	1.015	0.9549	47.76	29.13	28.15	27.29	150~160	10.41	871.6	99.5,99.5
170	0.7415	1.055	0.7682	0.7280	21.35	12.35	11.80	11.12	160~170	3.605	875.2	100,100
180	0.4342	1.069	0.4809	0.4542	0.4074	0.7481	0.7214	0.4542	170~180	0.4155	875.6	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-08

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:875.588x1 lm		
NAME: AH5060-15N90上	TYPE:	WEIGHT:
SPEC.:AH5060-15N90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	850	569
80	319	285
75	155	187
70	92	141
65	68	114
60	58	94
55	52	82
50	51	73
45	49	67


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:875.588x1 lm		
NAME: AH5060-15N90上	TYPE:	WEIGHT:
SPEC.:AH5060-15N90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.09	1.09	1.09	1.01	1.01	1.01	.87	.87	.87	.74	.74	.74	.62	.62	.62	.57
1.0	.86	.79	.73	.79	.73	.68	.67	.62	.58	.55	.52	.48	.45	.42	.40	.34
2.0	.71	.62	.55	.65	.57	.51	.55	.48	.43	.45	.40	.35	.36	.32	.28	.24
3.0	.60	.50	.43	.55	.47	.39	.46	.39	.33	.37	.32	.27	.30	.25	.21	.17
4.0	.52	.42	.34	.48	.39	.32	.40	.32	.26	.32	.26	.22	.25	.21	.17	.13
5.0	.46	.36	.28	.42	.33	.26	.35	.27	.22	.28	.22	.18	.22	.17	.13	.10
6.0	.40	.31	.24	.37	.28	.22	.31	.23	.18	.25	.19	.15	.19	.15	.11	.08
7.0	.36	.27	.20	.33	.24	.18	.27	.20	.15	.22	.17	.12	.17	.13	.09	.06
8.0	.32	.23	.17	.30	.21	.16	.25	.18	.13	.20	.15	.11	.16	.11	.08	.05
9.0	.29	.21	.15	.27	.19	.14	.23	.16	.11	.18	.13	.09	.15	.10	.07	.05
10.0	.27	.18	.13	.25	.17	.12	.21	.14	.10	.17	.12	.08	.13	.09	.06	.04



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:875.588x1 lm		
NAME: AH5060-15N90上	TYPE:	WEIGHT:
SPEC.:AH5060-15N90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.463	.263	.083	.443	.252	.080	.404	.232	.074	.369	.213	.068	.336	.195	.063	
2.0	.378	.207	.064	.359	.198	.061	.324	.180	.056	.291	.164	.051	.262	.148	.047	
3.0	.325	.173	.052	.308	.165	.050	.275	.149	.045	.246	.135	.041	.218	.121	.037	
4.0	.286	.149	.044	.270	.141	.042	.241	.128	.038	.214	.115	.035	.188	.102	.031	
5.0	.256	.130	.038	.242	.124	.036	.215	.112	.033	.189	.100	.030	.166	.089	.027	
6.0	.232	.116	.033	.219	.110	.032	.194	.099	.029	.170	.089	.026	.149	.078	.023	
7.0	.212	.105	.030	.200	.099	.028	.177	.089	.026	.155	.079	.023	.135	.070	.021	
8.0	.195	.095	.027	.184	.090	.026	.162	.081	.023	.142	.072	.021	.123	.063	.018	
9.0	.180	.087	.024	.170	.083	.023	.150	.074	.021	.132	.066	.019	.114	.058	.017	
10.0	.168	.081	.022	.158	.076	.021	.140	.069	.019	.122	.061	.017	.106	.053	.015	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.520	.520	.520	.444	.444	.444	.303	.303	.303	.174	.174	.174	.056	.056	.056	
1.0	.523	.487	.454	.447	.418	.391	.306	.287	.270	.176	.166	.157	.056	.054	.051	
2.0	.518	.466	.422	.443	.401	.364	.304	.277	.254	.175	.161	.149	.056	.052	.049	
3.0	.511	.451	.402	.438	.389	.349	.301	.270	.245	.174	.158	.144	.056	.051	.047	
4.0	.503	.439	.390	.432	.379	.339	.297	.264	.239	.172	.155	.141	.055	.050	.046	
5.0	.495	.430	.382	.426	.372	.332	.293	.260	.235	.170	.153	.139	.055	.050	.046	
6.0	.488	.423	.376	.419	.366	.327	.289	.256	.232	.168	.151	.138	.054	.049	.045	
7.0	.481	.417	.372	.413	.361	.324	.286	.253	.230	.166	.149	.137	.054	.049	.045	
8.0	.474	.411	.369	.408	.357	.321	.282	.251	.228	.164	.148	.136	.053	.048	.045	
9.0	.467	.407	.366	.403	.353	.319	.279	.248	.227	.162	.147	.135	.053	.048	.045	
10.0	.461	.403	.364	.398	.350	.318	.276	.246	.226	.161	.146	.135	.052	.048	.045	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:875.588x1 lm											
NAME: AH5060-15N90上					TYPE:			WEIGHT:			
SPEC.:AH5060-15N90上					DIM.: 1500*50*60			SERIAL No.:			
MFR.: COLORS					SUR.:1500*50			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		-10.6	-9.4	-9.8	-8.5	-7.5	-8.9	-7.7	-8.1	-6.9	-5.8
	3H	-7.7	-6.6	-6.9	-5.7	-4.6	-5.6	-4.5	-4.8	-3.7	-2.6
	4H	-5.5	-4.4	-4.6	-3.5	-2.4	-3.8	-2.7	-3.0	-1.9	-0.7
	6H	-2.4	-1.4	-1.5	-0.5	0.7	-1.7	-0.7	-0.8	0.2	1.3
	8H	-0.4	0.6	0.5	1.5	2.6	-0.5	0.4	0.3	1.3	2.5
	12H	1.9	2.8	2.8	3.7	4.9	0.8	1.7	1.7	2.6	3.8
4H	2H	-9.0	-8.0	-8.2	-7.1	-6.0	-8.0	-6.9	-7.1	-6.0	-4.9
	3H	-5.9	-5.0	-5.1	-4.1	-2.9	-4.5	-3.6	-3.7	-2.7	-1.5
	4H	-3.7	-2.9	-2.8	-1.9	-0.8	-2.5	-1.7	-1.7	-0.8	0.4
	6H	-0.7	0.1	0.2	1.0	2.2	-0.3	0.5	0.6	1.4	2.6
	8H	1.3	2.0	2.2	2.9	4.1	1.0	1.7	1.9	2.7	3.9
	12H	3.6	4.2	4.5	5.2	6.4	2.4	3.1	3.3	4.0	5.3
8H	4H	-2.6	-1.9	-1.7	-1.0	0.2	-1.8	-1.1	-0.9	-0.1	1.1
	6H	0.5	1.2	1.5	2.1	3.4	0.7	1.4	1.7	2.3	3.6
	8H	2.6	3.1	3.5	4.1	5.4	2.2	2.8	3.1	3.7	5.0
	12H	5.0	5.5	6.0	6.5	7.7	3.8	4.3	4.8	5.3	6.6
12H	4H	-2.3	-1.7	-1.4	-0.7	0.5	-1.6	-0.9	-0.6	0.1	1.3
	6H	0.9	1.5	1.9	2.5	3.7	1.1	1.7	2.1	2.6	3.9
	8H	3.0	3.5	4.0	4.5	5.8	2.7	3.2	3.6	4.1	5.4
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.3 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.4 / - 0.5					+ 0.3 / - 0.4					

CIE Pub.117, 875.6 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.5)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:875.588x1 lm		
NAME: AH5060-15N90上	TYPE:	WEIGHT:
SPEC.:AH5060-15N90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	34	21	13	33	20	13	30	19	12	5
0.80	43	28	19	40	27	18	36	24	17	7
1.00	50	34	25	47	33	24	41	32	22	11
1.25	56	41	31	53	39	29	46	35	27	14
1.50	62	47	36	58	44	34	50	39	31	16
2.00	70	56	45	65	52	43	56	46	38	21
2.50	75	62	52	70	58	49	60	51	43	24
3.00	79	67	57	74	63	54	63	55	48	28
4.00	85	74	66	79	70	62	68	60	54	32
5.00	89	79	71	82	74	67	71	64	58	35
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:875.588x1 lm		
NAME: AH5060-15N90上	TYPE:	WEIGHT:
SPEC.:AH5060-15N90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:875.588x1 lm		
NAME: AH5060-15N90上	TYPE:	WEIGHT:
SPEC.:AH5060-15N90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

Flux out:95.87 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:875.588x1 lm		
NAME: AH5060-15N90上	TYPE:	WEIGHT:
SPEC.:AH5060-15N90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:875.588x1 lm		
NAME: AH5060-15N90上	TYPE:	WEIGHT:
SPEC.:AH5060-15N90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	3829
L_0~180(75)av	6785
L_0~180(85)av	20852
L_90~270(65)av	2595
L_90~270(75)av	4574
L_90~270(85)av	13791
L_45(65)av	2651
L_45(75)av	4663
L_45(85)av	14053

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-04-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:875.588x1 lm		
NAME: AH5060-15N90上	TYPE:	WEIGHT:
SPEC.:AH5060-15N90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	5.40	5.73	5.58	5.39	5.40	5.73	5.58	5.39										
5	4.74	4.98	4.96	4.65	16.7	14.8	14.1	14.3										
10	4.19	4.58	4.62	4.35	36.2	27.8	26.5	26.9										
15	3.70	4.25	4.30	4.05	56.2	41.2	39.5	39.9										
20	3.39	3.92	4.03	3.81	76.5	54.9	52.5	53.1										
25	3.33	3.67	3.81	3.58	97.0	68.6	65.7	66.5										
30	3.14	3.61	3.69	3.51	117	82.4	78.9	79.9										
35	2.96	3.55	3.68	3.51	138	96.2	92.0	93.2										
40	2.79	3.51	3.63	3.49	158	110	105	106										
45	2.61	3.45	3.55	3.44	177	123	118	119										
50	2.45	3.45	3.54	3.45	195	136	130	131										
55	2.24	3.47	3.54	3.46	212	147	141	142										
60	2.16	3.55	3.54	3.51	227	158	152	152										
65	2.15	3.60	3.62	3.55	241	168	161	161										
70	2.35	3.64	3.63	3.57	252	175	168	169										
75	3.01	3.71	3.63	3.61	260	181	174	174										
80	4.15	3.81	3.71	3.69	266	184	176	176										
85	5.56	3.89	3.72	3.71	267	184	177	176										
90	6.52	3.99	3.84	3.77	267	184	176	175										
95	6.13	3.62	3.51	3.41	264	181	174	173										
100	5.84	3.27	3.17	3.09	247	169	162	161										
105	5.44	3.06	2.97	2.89	221	152	146	144										
110	5.28	2.83	2.74	2.69	197	134	127	125										
115	4.64	2.38	2.30	2.24	177	113	107	105										
120	4.11	2.21	2.17	2.10	159	101	96.1	94.8										
125	3.67	2.10	2.06	1.98	142	92.3	88.3	86.9										
130	3.41	2.02	1.96	1.92	128	82.4	78.5	77.1										
135	3.18	1.90	1.92	1.87	115	73.4	69.6	68.4										
140	2.91	1.72	1.77	1.70	103	65.4	62.6	61.5										
145	2.51	1.50	1.52	1.45	89.3	57.4	55.0	54.0										
150	2.07	1.24	1.27	1.22	74.8	47.4	45.8	44.7										
155	1.86	1.06	1.12	1.03	61.3	38.2	36.7	36.0										
160	1.56	0.94	1.02	0.95	47.8	29.1	28.2	27.3										
165	1.08	0.95	0.87	0.82	34.4	21.0	20.1	19.3										
170	0.74	1.06	0.77	0.73	21.3	12.3	11.8	11.1										
175	0.54	1.06	0.66	0.63	8.06	3.96	3.72	3.13										
180	0.43	1.07	0.48	0.45	0.41	0.75	0.72	0.45										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: