


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.8140A P:19.53W PF:1.000 Freq:0Hz Lamp Flux:1152.46x1 lm		
NAME: AH5060-15N90下	TYPE:	WEIGHT:
SPEC.:AH5060-15N90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 59.01 lm/W			
MODEL	AH5060-15N90下	I _{max} (cd)	347.4	S/MH(C0/180)	0.35
NOMINAL POWER(W)	19.53	LOR(%)	100.0	S/MH(C90/270)	0.43
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1152.5	h UP,DN(C0-180)	42.6,56.0
NOMINAL FLUX(lm)	1152.46	CIE CLASS	DIFFUSE	h UP,DN(C180-360)	0.7,0.7
LAMPS INSIDE	1	h up(%)	43.3	CIBSE SHR NOM	0.00
TEST VOLTAGE(V)	24	h down(%)	56.7	CIBSE SHR MAX	1.00

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-08

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	57.38	41.70	40.41	36.06	6.645	7.483	7.465	7.723	0- 10	1.915	1.915	0.17,0.17
20	109.5	79.62	77.56	69.62	3.072	3.837	3.799	4.197	10- 20	10.09	12.01	1.04,1.04
30	162.4	117.6	114.7	103.3	1.723	1.746	1.693	2.083	20- 30	25.04	37.05	3.22,3.22
40	213.3	153.7	150.1	135.3	2.071	1.022	1.022	1.163	30- 40	45.95	83.00	7.2,7.2
50	259.6	186.3	182.0	164.3	2.632	1.908	1.892	1.502	40- 50	70.88	153.9	13.4,13.4
60	298.7	213.6	208.8	188.5	3.047	2.211	2.252	2.224	50- 60	96.81	250.7	21.8,21.8
70	327.7	233.9	228.8	206.5	3.361	2.458	2.492	2.338	60- 70	120.0	370.6	32.2,32.2
80	344.2	245.9	240.5	217.2	3.654	2.759	2.765	2.551	70- 80	137.1	507.8	44.1,44.1
90	346.9	248.9	243.9	220.5	3.807	2.979	2.879	2.726	80- 90	145.8	653.6	56.7,56.7
100	334.5	238.3	233.7	210.9	3.299	2.559	2.437	2.365	90-100	144.2	797.8	69.2,69.2
110	299.3	207.5	203.2	179.9	2.852	2.251	2.238	2.204	100-110	128.4	926.3	80.4,80.4
120	249.7	167.4	165.6	148.7	2.558	2.344	2.338	2.450	110-120	101.9	1028	89.2,89.2
130	192.1	104.7	94.15	55.47	2.311	2.425	2.485	2.571	120-130	70.38	1099	95.3,95.3
140	134.3	28.37	27.11	18.56	1.889	2.565	2.632	2.882	130-140	30.51	1129	98.98
150	85.74	15.52	14.87	10.66	1.383	2.765	2.752	3.051	140-150	13.66	1143	99.2,99.2
160	50.65	9.212	8.876	6.461	1.035	2.706	2.665	2.953	150-160	6.433	1149	99.7,99.7
170	21.67	14.88	15.78	15.92	0.6809	2.206	2.198	2.485	160-170	2.678	1152	99.9,99.9
180	1.049	1.189	1.583	1.703	1.015	1.363	1.389	1.797	170-180	0.6275	1152	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.8140A P:19.53W PF:1.000 Freq:0Hz Lamp Flux:1152.46x1 lm		
NAME: AH5060-15N90下	TYPE:	WEIGHT:
SPEC.:AH5060-15N90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.8140A P:19.53W PF:1.000 Freq:0Hz Lamp Flux:1152.46x1 lm		
NAME: AH5060-15N90下	TYPE:	WEIGHT:
SPEC.:AH5060-15N90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.09	1.09	1.09	1.01	1.01	1.01	.87	.87	.87	.74	.74	.74	.62	.62	.62	.57
1.0	.86	.79	.73	.79	.73	.68	.67	.62	.58	.55	.52	.49	.45	.42	.40	.34
2.0	.71	.62	.55	.65	.58	.51	.55	.48	.43	.45	.40	.36	.36	.32	.29	.24
3.0	.61	.51	.43	.56	.47	.40	.46	.39	.33	.38	.32	.27	.30	.25	.22	.17
4.0	.52	.42	.34	.48	.39	.32	.40	.33	.27	.32	.27	.22	.25	.21	.17	.13
5.0	.46	.36	.28	.42	.33	.26	.35	.28	.22	.28	.22	.18	.22	.17	.14	.10
6.0	.40	.31	.24	.37	.28	.22	.31	.24	.18	.25	.19	.15	.20	.15	.11	.08
7.0	.36	.27	.20	.33	.25	.19	.28	.21	.16	.22	.17	.12	.18	.13	.09	.07
8.0	.32	.23	.17	.30	.22	.16	.25	.18	.13	.20	.15	.11	.16	.11	.08	.06
9.0	.29	.21	.15	.27	.19	.14	.23	.16	.12	.19	.13	.09	.15	.10	.07	.05
10.0	.27	.19	.13	.25	.17	.12	.21	.14	.10	.17	.12	.08	.13	.09	.06	.04



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:24.00V I:0.8140A P:19.53W PF:1.000 Freq:0Hz Lamp Flux:1152.46x1 lm		
NAME: AH5060-15N90下	TYPE:	WEIGHT:
SPEC.:AH5060-15N90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.461	.262	.083	.440	.251	.080	.401	.230	.074	.366	.211	.068	.333	.193	.062	
2.0	.376	.206	.063	.357	.197	.061	.322	.179	.056	.290	.162	.051	.260	.147	.046	
3.0	.323	.172	.052	.306	.164	.049	.274	.149	.045	.244	.134	.041	.217	.120	.037	
4.0	.285	.148	.044	.269	.141	.042	.240	.127	.038	.212	.114	.034	.187	.102	.031	
5.0	.255	.130	.038	.241	.124	.036	.214	.111	.033	.189	.099	.030	.165	.088	.026	
6.0	.231	.116	.033	.218	.110	.032	.193	.099	.029	.170	.088	.026	.148	.078	.023	
7.0	.211	.104	.030	.199	.099	.028	.176	.089	.026	.154	.079	.023	.134	.070	.020	
8.0	.194	.095	.027	.183	.090	.025	.162	.081	.023	.142	.072	.021	.123	.063	.018	
9.0	.180	.087	.024	.170	.083	.023	.150	.074	.021	.131	.066	.019	.114	.058	.017	
10.0	.168	.080	.022	.158	.076	.021	.139	.068	.019	.122	.061	.017	.106	.053	.015	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.520	.520	.520	.445	.445	.445	.303	.303	.303	.174	.174	.174	.056	.056	.056	
1.0	.523	.487	.455	.448	.418	.392	.306	.288	.271	.176	.167	.157	.056	.054	.051	
2.0	.518	.466	.423	.444	.401	.365	.304	.278	.255	.175	.162	.149	.056	.052	.049	
3.0	.511	.451	.403	.438	.389	.350	.301	.270	.245	.174	.158	.145	.056	.051	.047	
4.0	.504	.440	.391	.432	.380	.340	.297	.265	.239	.172	.155	.142	.055	.051	.047	
5.0	.496	.431	.383	.426	.373	.333	.293	.260	.235	.170	.153	.139	.055	.050	.046	
6.0	.488	.423	.377	.420	.367	.328	.290	.257	.232	.168	.151	.138	.054	.049	.046	
7.0	.481	.417	.373	.414	.362	.325	.286	.254	.230	.166	.149	.137	.054	.049	.045	
8.0	.474	.412	.369	.408	.357	.322	.283	.251	.228	.164	.148	.136	.053	.049	.045	
9.0	.468	.408	.367	.403	.354	.320	.279	.249	.227	.163	.147	.135	.053	.048	.045	
10.0	.462	.404	.365	.398	.350	.318	.276	.247	.226	.161	.146	.135	.052	.048	.045	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.8140A P:19.53W PF:1.000 Freq:0Hz Lamp Flux:1152.46x1 lm											
NAME: AH5060-15N90下						TYPE:		WEIGHT:			
SPEC.:AH5060-15N90下						DIM.: 1500*50*60		SERIAL No.:			
MFR.: COLORS						SUR.:1500*50		Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	19.0	20.2	19.8	21.0	22.1	17.4	18.6	18.2	19.4	20.5	
	3H	22.9	24.0	23.7	24.9	25.9	21.0	22.1	21.9	23.0	24.1
	4H	25.0	26.1	25.9	27.0	28.1	23.1	24.1	23.9	25.0	26.1
	6H	27.4	28.4	28.2	29.2	30.4	25.3	26.3	26.1	27.1	28.3
	8H	28.6	29.6	29.5	30.5	31.6	26.5	27.4	27.3	28.3	29.5
	12H	30.1	31.0	30.9	31.9	33.1	27.9	28.8	28.7	29.7	30.8
4H	2H	19.7	20.8	20.5	21.6	22.7	18.6	19.7	19.5	20.6	21.7
	3H	23.7	24.6	24.6	25.5	26.7	22.3	23.2	23.2	24.1	25.3
	4H	26.0	26.9	26.9	27.8	29.0	24.4	25.3	25.3	26.2	27.3
	6H	28.5	29.3	29.4	30.2	31.4	26.7	27.5	27.6	28.4	29.6
	8H	29.9	30.6	30.8	31.6	32.8	28.0	28.7	28.9	29.7	30.9
	12H	31.5	32.2	32.4	33.1	34.3	29.5	30.1	30.4	31.1	32.3
8H	4H	26.5	27.2	27.4	28.2	29.4	25.3	26.0	26.2	26.9	28.1
	6H	29.3	29.9	30.2	30.9	32.1	27.8	28.4	28.7	29.4	30.6
	8H	30.9	31.4	31.8	32.4	33.6	29.3	29.8	30.2	30.8	32.0
	12H	32.7	33.2	33.6	34.1	35.4	30.9	31.4	31.9	32.4	33.7
12H	4H	26.6	27.3	27.6	28.3	29.5	25.6	26.2	26.5	27.2	28.4
	6H	29.5	30.0	30.4	31.0	32.3	28.2	28.7	29.1	29.7	31.0
	8H	31.2	31.7	32.1	32.6	33.9	29.7	30.2	30.7	31.2	32.5
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.2					+ 0.2 / - 0.3					
2.0H	+ 0.3 / - 0.3					+ 0.3 / - 0.4					

CIE Pub.117, 1152 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.5)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.8140A P:19.53W PF:1.000 Freq:0Hz Lamp Flux:1152.46x1 lm		
NAME: AH5060-15N90下	TYPE:	WEIGHT:
SPEC.:AH5060-15N90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	34	21	13	33	20	13	30	19	12	5
0.80	43	28	19	40	27	18	36	24	17	8
1.00	50	34	25	47	33	24	41	32	22	11
1.25	57	41	31	53	39	30	46	35	27	14
1.50	62	47	36	58	44	34	50	39	31	17
2.00	70	56	45	65	52	43	56	46	38	21
2.50	75	62	52	70	58	49	60	51	43	25
3.00	80	67	58	74	63	54	64	55	48	28
4.00	85	75	66	79	70	62	68	60	54	32
5.00	89	80	72	82	74	67	71	64	58	35
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.8140A P:19.53W PF:1.000 Freq:0Hz Lamp Flux:1152.46x1 lm		
NAME: AH5060-15N90下	TYPE:	WEIGHT:
SPEC.:AH5060-15N90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.8140A P:19.53W PF:1.000 Freq:0Hz Lamp Flux:1152.46x1 lm		
NAME: AH5060-15N90下	TYPE:	WEIGHT:
SPEC.:AH5060-15N90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

Flux out:153.9 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.8140A P:19.53W PF:1.000 Freq:0Hz Lamp Flux:1152.46x1 lm		
NAME: AH5060-15N90下	TYPE:	WEIGHT:
SPEC.:AH5060-15N90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.00V I:0.8140A P:19.53W PF:1.000 Freq:0Hz Lamp Flux:1152.46x1 lm		
NAME: AH5060-15N90下	TYPE:	WEIGHT:
SPEC.:AH5060-15N90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	5014
L_0~180(75)av	8789
L_0~180(85)av	26842
L_90~270(65)av	3503
L_90~270(75)av	6141
L_90~270(85)av	18821
L_45(65)av	3373
L_45(75)av	5911
L_45(85)av	18118

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.8140A P:19.53W PF:1.000 Freq:0Hz Lamp Flux:1152.46x1 lm		
NAME: AH5060-15N90下	TYPE:	WEIGHT:
SPEC.:AH5060-15N90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	13.0	12.6	12.4	12.0	13.0	12.6	12.4	12.0										
5	32.3	23.4	22.6	20.0	9.33	9.97	9.91	9.89										
10	57.4	41.7	40.4	36.1	6.65	7.48	7.46	7.72										
15	83.2	60.5	58.9	52.8	4.56	5.46	5.42	5.77										
20	109	79.6	77.6	69.6	3.07	3.84	3.80	4.20										
25	136	98.7	96.3	86.6	2.17	2.63	2.60	3.01										
30	162	118	115	103	1.72	1.75	1.69	2.08										
35	188	136	133	120	1.79	1.19	1.14	1.46										
40	213	154	150	135	2.07	1.02	1.02	1.16										
45	237	171	167	150	2.37	1.28	1.28	1.16										
50	260	186	182	164	2.63	1.91	1.89	1.50										
55	280	201	196	177	2.85	2.10	2.15	2.02										
60	299	214	209	188	3.05	2.21	2.25	2.22										
65	315	225	220	198	3.23	2.37	2.41	2.24										
70	328	234	229	207	3.36	2.46	2.49	2.34										
75	338	241	236	213	3.55	2.58	2.61	2.41										
80	344	246	241	217	3.65	2.76	2.77	2.55										
85	347	249	243	220	3.77	2.87	2.89	2.63										
90	347	249	244	220	3.81	2.98	2.88	2.73										
95	344	247	242	218	3.57	2.77	2.65	2.55										
100	334	238	234	211	3.30	2.56	2.44	2.37										
105	319	226	222	198	3.06	2.36	2.25	2.19										
110	299	208	203	180	2.85	2.25	2.24	2.20										
115	276	186	183	165	2.69	2.25	2.25	2.32										
120	250	167	166	149	2.56	2.34	2.34	2.45										
125	222	148	145	114	2.44	2.36	2.40	2.47										
130	192	105	94.1	55.5	2.31	2.42	2.48	2.57										
135	163	48.4	46.6	32.8	2.10	2.46	2.55	2.68										
140	134	28.4	27.1	18.6	1.89	2.56	2.63	2.88										
145	108	19.4	18.7	13.4	1.66	2.64	2.73	2.95										
150	85.7	15.5	14.9	10.7	1.38	2.77	2.75	3.05										
155	67.0	12.1	11.6	8.37	1.24	2.78	2.75	3.09										
160	50.7	9.21	8.88	6.46	1.04	2.71	2.66	2.95										
165	35.3	6.63	6.46	4.6	0.83	2.56	2.53	2.78										
170	21.7	4.9	4.58	3.59	0.68	2.21	2.20	2.49										
175	8.93	2.26	2.23	1.62	0.63	1.57	1.56	1.86										
180	1.05	1.19	1.58	1.70	1.02	1.36	1.39	1.80										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: