


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:1314.96x1 lm		
NAME: AH5060-15W90下	TYPE:	WEIGHT:
SPEC.:AH5060-15W90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 66.41 lm/W			
MODEL	AH5060-15W90下	I _{max} (cd)	366.8	S/MH(C0/180)	0.11
NOMINAL POWER(W)	19.8	LOR(%)	100.0	S/MH(C90/270)	0.18
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1315.0	h UP,DN(C0-180)	43.2,54.9
NOMINAL FLUX(lm)	1314.96	CIE CLASS	DIFFUSE	h UP,DN(C180-360)	1.0,0.9
LAMPS INSIDE	1	h up(%)	44.2	CIBSE SHR NOM	0.00
TEST VOLTAGE(V)	24	h down(%)	55.8	CIBSE SHR MAX	1.00

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-08

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	61.30	46.98	46.33	45.66	4.367	5.270	5.428	5.611	0- 10	2.010	2.010	0.15,0.15
20	118.1	89.04	87.25	86.30	3.626	4.450	4.588	4.764	10- 20	11.27	13.28	1.01,1.01
30	175.4	131.1	128.1	127.1	3.131	3.881	4.028	4.209	20- 30	28.57	41.85	3.18,3.18
40	230.2	171.3	166.6	165.5	2.752	3.507	3.600	3.774	30- 40	52.36	94.21	7.16,7.16
50	279.4	208.2	201.9	200.5	2.712	3.240	3.279	3.381	40- 50	80.23	174.4	13.3,13.3
60	320.6	239.5	232.0	230.2	2.799	3.093	3.133	3.173	50- 60	109.0	283.5	21.6,21.6
70	350.1	262.4	253.9	252.1	3.208	3.086	3.166	3.133	60- 70	134.9	418.3	31.8,31.8
80	365.1	273.8	264.7	262.8	4.238	3.613	3.594	3.520	70- 80	153.5	571.8	43.5,43.5
90	366.0	273.7	264.3	262.5	7.174	4.440	4.254	4.181	80- 90	161.8	733.6	55.8,55.8
100	343.0	253.1	244.2	242.9	7.568	4.262	3.967	3.995	90-100	157.9	891.5	67.8,67.8
110	296.5	209.8	201.2	200.2	7.339	3.961	3.714	3.721	100-110	134.8	1026	78.1,78.1
120	248.0	166.6	158.4	157.2	6.639	4.161	3.934	3.921	110-120	103.7	1130	85.9,85.9
130	201.5	134.4	129.0	128.4	6.466	3.821	3.573	3.581	120-130	76.26	1206	91.7,91.7
140	156.5	103.3	99.72	99.44	5.294	3.367	3.166	3.186	130-140	52.54	1259	95.7,95.7
150	115.0	74.86	72.42	72.23	4.053	3.059	2.972	3.019	140-150	32.39	1291	98.2,98.2
160	72.99	48.06	46.51	46.47	2.965	2.813	2.751	2.693	150-160	16.79	1308	99.5,99.5
170	31.06	22.30	21.73	21.79	1.723	2.171	2.077	2.038	160-170	6.055	1314	99.9,99.9
180	2.598	3.193	3.099	3.093	2.538	3.199	3.093	3.026	170-180	0.8270	1315	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:1314.96x1 lm		
NAME: AH5060-15W90下	TYPE:	WEIGHT:
SPEC.:AH5060-15W90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	56116	40600
80	28035	20321
75	18524	13438
70	13650	9900
65	10632	7704
60	8550	6186
55	7002	5060
50	5797	4188
45	4820	3484


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:1314.96x1 lm		
NAME: AH5060-15W90下	TYPE:	WEIGHT:
SPEC.:AH5060-15W90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.09	1.09	1.09	1.01	1.01	1.01	.87	.87	.87	.73	.73	.73	.61	.61	.61	.56
1.0	.86	.79	.74	.79	.73	.68	.66	.62	.58	.55	.51	.48	.44	.42	.39	.34
2.0	.71	.63	.55	.66	.58	.51	.55	.48	.43	.45	.40	.36	.35	.32	.28	.24
3.0	.61	.51	.43	.56	.47	.40	.46	.39	.33	.37	.32	.27	.29	.25	.21	.17
4.0	.52	.42	.35	.48	.39	.32	.40	.33	.27	.32	.26	.22	.25	.21	.17	.13
5.0	.46	.36	.29	.42	.33	.26	.35	.28	.22	.28	.22	.18	.22	.17	.14	.10
6.0	.41	.31	.24	.37	.28	.22	.31	.24	.18	.25	.19	.15	.19	.15	.11	.08
7.0	.36	.27	.20	.33	.25	.19	.28	.21	.16	.22	.17	.12	.17	.13	.09	.07
8.0	.33	.24	.17	.30	.22	.16	.25	.18	.13	.20	.15	.11	.16	.11	.08	.06
9.0	.29	.21	.15	.27	.19	.14	.23	.16	.12	.18	.13	.09	.14	.10	.07	.05
10.0	.27	.19	.13	.25	.17	.12	.21	.14	.10	.17	.12	.08	.13	.09	.06	.04



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:1314.96x1 lm		
NAME: AH5060-15W90下	TYPE:	WEIGHT:
SPEC.:AH5060-15W90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.456	.259	.082	.435	.248	.079	.396	.227	.073	.360	.208	.067	.327	.190	.061	
2.0	.373	.204	.063	.354	.195	.060	.318	.177	.055	.285	.160	.050	.255	.144	.045	
3.0	.321	.171	.051	.304	.163	.049	.271	.147	.045	.241	.132	.041	.213	.118	.037	
4.0	.283	.147	.043	.267	.140	.041	.238	.126	.038	.210	.113	.034	.184	.100	.030	
5.0	.254	.129	.037	.239	.123	.036	.212	.110	.032	.186	.098	.029	.162	.087	.026	
6.0	.230	.115	.033	.217	.109	.031	.191	.098	.029	.168	.087	.026	.146	.077	.023	
7.0	.210	.104	.029	.198	.099	.028	.175	.088	.025	.153	.078	.023	.132	.069	.020	
8.0	.194	.095	.027	.182	.090	.025	.161	.080	.023	.140	.071	.021	.121	.062	.018	
9.0	.179	.087	.024	.169	.082	.023	.149	.074	.021	.130	.065	.019	.112	.057	.016	
10.0	.167	.080	.022	.157	.076	.021	.139	.068	.019	.121	.060	.017	.104	.052	.015	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.527	.527	.527	.451	.451	.451	.308	.308	.308	.177	.177	.177	.056	.056	.056	
1.0	.530	.494	.462	.454	.424	.398	.310	.292	.275	.179	.169	.160	.057	.054	.052	
2.0	.525	.473	.430	.450	.408	.372	.308	.282	.259	.178	.164	.152	.057	.053	.050	
3.0	.518	.458	.411	.444	.395	.356	.305	.275	.250	.176	.160	.147	.057	.052	.048	
4.0	.511	.447	.398	.438	.386	.346	.301	.269	.244	.174	.158	.144	.056	.051	.047	
5.0	.503	.438	.390	.432	.379	.339	.297	.265	.240	.172	.155	.142	.056	.051	.047	
6.0	.495	.431	.384	.426	.373	.335	.294	.261	.237	.170	.154	.141	.055	.050	.046	
7.0	.488	.425	.380	.420	.368	.331	.290	.258	.235	.169	.152	.140	.054	.050	.046	
8.0	.481	.419	.377	.414	.364	.329	.287	.255	.233	.167	.151	.139	.054	.049	.046	
9.0	.475	.415	.374	.409	.360	.326	.283	.253	.232	.165	.149	.138	.053	.049	.046	
10.0	.469	.411	.372	.404	.357	.325	.280	.251	.231	.164	.148	.138	.053	.049	.046	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:1314.96x1 lm										
NAME: AH5060-15W90下					TYPE:			WEIGHT:		
SPEC.:AH5060-15W90下					DIM.: 1500*50*60			SERIAL No.:		
MFR.: COLORS					SUR.:1500*50			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	18.6	19.8	19.4	20.7	21.8	17.2	18.4	18.0	19.2	20.3
3H	22.5	23.6	23.3	24.5	25.6	20.8	21.9	21.7	22.8	23.9
4H	24.6	25.7	25.5	26.5	27.7	22.9	23.9	23.7	24.8	25.9
6H	26.9	27.9	27.8	28.8	29.9	25.0	26.0	25.9	26.9	28.1
8H	28.2	29.1	29.0	30.0	31.2	26.2	27.2	27.1	28.1	29.2
12H	29.6	30.5	30.5	31.4	32.6	27.6	28.5	28.5	29.4	30.6
4H 2H	19.4	20.4	20.3	21.3	22.5	18.5	19.5	19.3	20.4	21.5
3H	23.4	24.3	24.3	25.2	26.4	22.1	23.0	23.0	23.9	25.1
4H	25.6	26.5	26.5	27.4	28.6	24.2	25.0	25.1	26.0	27.2
6H	28.1	28.9	29.0	29.8	31.0	26.5	27.3	27.4	28.2	29.4
8H	29.5	30.2	30.4	31.1	32.4	27.8	28.5	28.7	29.4	30.7
12H	31.0	31.7	32.0	32.6	33.9	29.2	29.9	30.2	30.8	32.1
8H 4H	26.2	26.9	27.1	27.8	29.0	25.1	25.8	26.0	26.7	27.9
6H	28.9	29.5	29.8	30.5	31.7	27.6	28.2	28.5	29.2	30.4
8H	30.4	31.0	31.4	32.0	33.2	29.0	29.6	30.0	30.6	31.8
12H	32.2	32.7	33.2	33.7	35.0	30.7	31.1	31.6	32.1	33.4
12H 4H	26.3	27.0	27.2	27.9	29.2	25.3	26.0	26.3	27.0	28.2
6H	29.1	29.7	30.1	30.6	31.9	28.0	28.5	28.9	29.5	30.8
8H	30.8	31.2	31.7	32.2	33.5	29.5	30.0	30.5	31.0	32.3
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1				
1.5H	+ 0.2 / - 0.2					+ 0.2 / - 0.3				
2.0H	+ 0.3 / - 0.3					+ 0.3 / - 0.4				

CIE Pub.117, 1315 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 1.0)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:1314.96x1 lm		
NAME: AH5060-15W90下	TYPE:	WEIGHT:
SPEC.:AH5060-15W90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	34	21	14	33	20	13	30	19	12	5
0.80	43	28	19	40	27	18	36	24	17	8
1.00	50	35	25	47	33	24	41	32	22	11
1.25	57	42	31	53	39	30	46	35	27	14
1.50	62	47	37	58	44	35	50	39	31	16
2.00	70	56	46	65	53	43	56	46	38	21
2.50	75	62	52	70	58	49	60	51	43	24
3.00	80	68	58	74	63	54	63	55	48	27
4.00	85	75	66	79	70	62	68	60	54	32
5.00	89	80	72	82	74	67	70	64	58	35
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:1314.96x1 lm		
NAME: AH5060-15W90下	TYPE:	WEIGHT:
SPEC.:AH5060-15W90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:1314.96x1 lm		
NAME: AH5060-15W90下	TYPE:	WEIGHT:
SPEC.:AH5060-15W90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

Flux out:184.1 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:1314.96x1 lm		
NAME: AH5060-15W90下	TYPE:	WEIGHT:
SPEC.:AH5060-15W90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:1314.96x1 lm		
NAME: AH5060-15W90下	TYPE:	WEIGHT:
SPEC.:AH5060-15W90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	5362
L_0~180(75)av	9354
L_0~180(85)av	28466
L_90~270(65)av	3901
L_90~270(75)av	6804
L_90~270(85)av	20597
L_45(65)av	3950
L_45(75)av	6894
L_45(85)av	20878

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-04-08

deg Range: 0 - 180DEG
deg Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:1314.96x1 lm		
NAME: AH5060-15W90下	TYPE:	WEIGHT:
SPEC.:AH5060-15W90下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	13.6	12.3	12.7	12.4	13.6	12.3	12.7	12.4										
5	34.8	27.4	27.3	26.8	5.19	6.12	6.49	6.48										
10	61.3	47.0	46.3	45.7	4.37	5.27	5.43	5.61										
15	89.4	67.8	66.5	65.7	3.92	4.80	4.97	5.13										
20	118	89.0	87.2	86.3	3.63	4.45	4.59	4.76										
25	147	110	108	107	3.39	4.16	4.29	4.46										
30	175	131	128	127	3.13	3.88	4.03	4.21										
35	203	152	148	147	2.90	3.66	3.80	3.99										
40	230	171	167	166	2.75	3.51	3.60	3.77										
45	256	190	185	184	2.71	3.37	3.44	3.57										
50	279	208	202	201	2.71	3.24	3.28	3.38										
55	301	225	218	216	2.74	3.15	3.17	3.23										
60	321	239	232	230	2.80	3.09	3.13	3.17										
65	337	252	244	242	2.93	3.07	3.13	3.13										
70	350	262	254	252	3.21	3.09	3.17	3.13										
75	360	270	261	259	3.58	3.29	3.32	3.31										
80	365	274	265	263	4.24	3.61	3.59	3.52										
85	367	275	265	263	5.33	3.95	3.88	3.81										
90	366	274	264	263	7.17	4.44	4.25	4.18										
95	359	269	259	258	7.43	4.36	4.08	4.09										
100	343	253	244	243	7.57	4.26	3.97	3.99										
105	321	233	225	223	7.45	4.19	3.89	3.89										
110	296	210	201	200	7.34	3.96	3.71	3.72										
115	272	187	178	177	6.90	3.95	3.85	3.75										
120	248	167	158	157	6.64	4.16	3.93	3.92										
125	225	150	143	142	6.61	4.04	3.81	3.81										
130	201	134	129	128	6.47	3.82	3.57	3.58										
135	179	118	113	113	5.99	3.58	3.36	3.38										
140	156	103	99.7	99.4	5.29	3.37	3.17	3.19										
145	135	88.7	86.0	85.8	4.65	3.19	3.01	3.06										
150	115	74.9	72.4	72.2	4.05	3.06	2.97	3.02										
155	94.3	61.4	59.3	59.1	3.51	2.97	2.87	2.87										
160	73.0	48.1	46.5	46.5	2.96	2.81	2.75	2.69										
165	51.9	34.8	33.8	33.8	2.38	2.55	2.44	2.41										
170	31.1	22.3	21.7	21.8	1.72	2.17	2.08	2.04										
175	12.8	10.4	10.2	10.2	1.58	1.94	1.90	1.82										
180	2.60	3.19	3.10	3.09	2.54	3.20	3.09	3.03										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: