


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:836.976x1 lm		
NAME: AH5060-15W90上	TYPE:	WEIGHT:
SPEC.:AH5060-15W90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 42.27 lm/W			
MODEL	AH5060-15W90上	I _{max} (cd)	255.2	S/MH(C0/180)	6.28
NOMINAL POWER(W)	19.53	LOR(%)	100.0	S/MH(C90/270)	5.55
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	836.98	h UP,DN(C0-180)	1.4,1.4
NOMINAL FLUX(lm)	836.976	CIE CLASS	DIFFUSE	h UP,DN(C180-360)	38.8,58.3
LAMPS INSIDE	1	h up(%)	40.2	CIBSE SHR NOM	0.00
TEST VOLTAGE(V)	24	h down(%)	59.8	CIBSE SHR MAX	1.00

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-08

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	8.951	9.284	9.340	9.289	40.37	34.31	32.80	32.90	0- 10	1.672	1.672	0.20,0.20
20	6.985	7.868	7.966	7.971	77.95	62.68	59.99	59.83	10- 20	8.515	10.19	1.22,1.22
30	4.711	6.424	6.562	6.536	116.0	90.63	86.78	86.34	20- 30	20.33	30.52	3.65,3.65
40	2.606	4.180	4.522	4.603	153.4	117.4	112.3	111.7	30- 40	36.16	66.67	7.97,7.97
50	1.797	2.287	2.461	2.456	188.0	141.9	135.6	134.7	40- 50	54.41	121.1	14.5,14.5
60	2.023	1.496	1.497	1.469	217.5	162.5	155.2	154.1	50- 60	73.41	194.5	23.2,23.2
70	2.996	1.911	1.775	1.790	239.9	177.4	169.4	168.2	60- 70	90.80	285.3	34.1,34.1
80	5.935	4.044	3.819	3.808	252.7	184.9	176.5	175.1	70- 80	104.2	389.5	46.5,46.5
90	6.832	4.811	4.627	4.590	255.0	185.1	176.7	175.1	80- 90	110.7	500.2	59.8,59.8
100	6.221	4.321	4.183	4.107	244.1	166.4	157.5	155.3	90-100	108.2	608.4	72.7,72.7
110	5.471	3.887	3.815	3.774	186.7	112.7	105.1	103.0	100-110	84.19	692.6	82.8,82.8
120	4.830	3.861	3.820	3.841	125.7	82.55	78.27	77.08	110-120	55.29	747.9	89.4,89.4
130	4.656	3.747	3.714	3.640	92.38	64.07	61.09	60.28	120-130	37.62	785.5	93.9,93.9
140	4.196	3.279	3.240	3.186	67.80	48.52	46.51	45.92	130-140	25.03	810.5	96.8,96.8
150	3.347	2.310	2.267	2.211	46.98	34.73	33.80	33.62	140-150	15.01	825.6	98.6,98.6
160	2.274	1.435	1.497	1.442	28.79	25.05	24.57	24.42	150-160	7.945	833.5	99.6,99.6
170	0.8423	0.9350	1.049	1.015	15.35	12.50	12.35	12.32	160-170	3.006	836.5	99.9,99.9
180	1.336	1.222	1.256	1.276	1.449	1.269	1.269	1.343	170-180	0.4719	837.0	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:836.976x1 lm		
NAME: AH5060-15W90上	TYPE:	WEIGHT:
SPEC.:AH5060-15W90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:836.976x1 lm		
NAME: AH5060-15W90上	TYPE:	WEIGHT:
SPEC.:AH5060-15W90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.09	1.09	1.09	1.02	1.02	1.02	.89	.89	.89	.76	.76	.76	.65	.65	.65	.60
1.0	.86	.79	.73	.80	.74	.68	.68	.63	.59	.57	.53	.50	.47	.44	.41	.36
2.0	.71	.62	.55	.66	.58	.51	.56	.49	.44	.46	.41	.37	.37	.33	.30	.25
3.0	.61	.51	.43	.56	.47	.40	.47	.40	.34	.39	.33	.28	.31	.27	.23	.18
4.0	.52	.42	.34	.48	.39	.32	.40	.33	.27	.33	.27	.22	.27	.22	.18	.14
5.0	.46	.36	.28	.42	.33	.26	.35	.28	.22	.29	.23	.18	.23	.18	.14	.11
6.0	.40	.31	.24	.37	.28	.22	.31	.24	.18	.26	.20	.15	.21	.16	.12	.09
7.0	.36	.27	.20	.33	.25	.19	.28	.21	.16	.23	.17	.13	.19	.14	.10	.07
8.0	.32	.23	.17	.30	.22	.16	.25	.18	.13	.21	.15	.11	.17	.12	.09	.06
9.0	.29	.21	.15	.27	.19	.14	.23	.16	.12	.19	.14	.10	.15	.11	.07	.05
10.0	.27	.19	.13	.25	.17	.12	.21	.15	.10	.18	.12	.08	.14	.10	.07	.04



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2020-04-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:836.976x1 lm		
NAME: AH5060-15W90上	TYPE:	WEIGHT:
SPEC.:AH5060-15W90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.469	.267	.085	.450	.257	.082	.413	.237	.076	.379	.219	.070	.348	.202	.065	
2.0	.382	.209	.064	.364	.201	.062	.331	.184	.057	.299	.168	.053	.271	.153	.048	
3.0	.328	.175	.052	.312	.167	.050	.281	.152	.046	.252	.138	.042	.226	.125	.039	
4.0	.288	.150	.044	.274	.143	.042	.245	.130	.039	.219	.118	.036	.195	.106	.032	
5.0	.258	.131	.038	.244	.125	.037	.219	.114	.033	.194	.103	.031	.172	.092	.028	
6.0	.233	.117	.033	.221	.112	.032	.197	.101	.029	.175	.091	.027	.154	.081	.024	
7.0	.213	.105	.030	.202	.100	.029	.180	.091	.026	.159	.082	.024	.140	.073	.021	
8.0	.196	.096	.027	.186	.091	.026	.165	.083	.024	.146	.074	.021	.128	.066	.019	
9.0	.182	.088	.025	.172	.084	.023	.153	.076	.021	.135	.068	.019	.118	.060	.017	
10.0	.169	.081	.023	.160	.077	.022	.142	.070	.020	.126	.062	.018	.110	.055	.016	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.497	.497	.497	.425	.425	.425	.290	.290	.290	.167	.167	.167	.053	.053	.053	
1.0	.500	.464	.431	.428	.398	.371	.293	.274	.256	.169	.158	.149	.054	.051	.048	
2.0	.495	.443	.398	.424	.381	.344	.291	.264	.240	.168	.153	.141	.054	.050	.046	
3.0	.488	.428	.379	.419	.369	.329	.288	.256	.230	.166	.150	.136	.053	.049	.044	
4.0	.481	.416	.367	.413	.360	.319	.284	.251	.224	.164	.147	.133	.053	.048	.044	
5.0	.473	.407	.358	.406	.352	.312	.280	.246	.220	.162	.144	.131	.052	.047	.043	
6.0	.465	.400	.353	.400	.346	.307	.276	.242	.217	.160	.143	.129	.052	.047	.043	
7.0	.458	.393	.348	.394	.341	.304	.272	.239	.215	.158	.141	.128	.051	.046	.042	
8.0	.451	.388	.345	.388	.337	.301	.269	.236	.213	.156	.139	.127	.051	.046	.042	
9.0	.444	.384	.343	.383	.333	.299	.265	.234	.212	.155	.138	.127	.050	.045	.042	
10.0	.438	.380	.340	.378	.330	.297	.262	.232	.211	.153	.137	.126	.050	.045	.042	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:836.976x1 lm											
NAME: AH5060-15W90上					TYPE:			WEIGHT:			
SPEC.:AH5060-15W90上					DIM.: 1500*50*60			SERIAL No.:			
MFR.: COLORS					SUR.:1500*50			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H		-12.5	-11.2	-11.7	-10.4	-9.4	-12.6	-11.4	-11.9	-10.6	-9.6
	3H	-8.1	-6.9	-7.3	-6.1	-5.0	-10.0	-8.9	-9.2	-8.1	-7.0
	4H	-4.1	-3.0	-3.3	-2.1	-1.1	-7.4	-6.3	-6.6	-5.5	-4.4
	6H	0.0	1.1	0.9	1.9	3.0	-3.1	-2.1	-2.3	-1.2	-0.1
	8H	1.9	2.9	2.7	3.8	4.8	-0.9	0.0	-0.1	0.9	2.0
	12H	3.7	4.7	4.6	5.5	6.6	1.1	2.1	1.9	2.9	4.0
4H	2H	-11.9	-10.8	-11.1	-9.9	-8.9	-12.0	-11.0	-11.2	-10.1	-9.0
	3H	-7.1	-6.1	-6.2	-5.2	-4.1	-8.8	-7.9	-8.0	-7.0	-5.9
	4H	-3.0	-2.1	-2.1	-1.2	-0.1	-5.9	-5.0	-5.0	-4.1	-3.0
	6H	1.3	2.1	2.2	3.0	4.2	-1.4	-0.6	-0.6	0.3	1.4
	8H	3.3	4.0	4.2	4.9	6.1	0.8	1.5	1.6	2.4	3.6
	12H	5.2	5.9	6.1	6.8	8.0	2.8	3.5	3.8	4.5	5.7
8H	4H	-2.2	-1.5	-1.4	-0.6	0.6	-4.2	-3.5	-3.4	-2.6	-1.4
	6H	2.2	2.9	3.1	3.8	5.0	0.1	0.8	1.0	1.7	2.9
	8H	4.4	5.0	5.3	5.9	7.1	2.4	2.9	3.3	3.9	5.1
	12H	6.5	7.0	7.5	8.0	9.2	4.5	5.1	5.5	6.0	7.2
12H	4H	-1.9	-1.2	-1.0	-0.3	0.9	-3.4	-2.7	-2.5	-1.8	-0.6
	6H	2.5	3.1	3.5	4.1	5.3	0.8	1.4	1.7	2.3	3.5
	8H	4.8	5.3	5.7	6.2	7.5	3.0	3.6	4.0	4.5	5.7
Variations with the observer position at spacings:											
S = 1.0H		+ 0.1 / - 0.1				+ 0.1 / - 0.1					
1.5H		+ 0.3 / - 0.3				+ 0.3 / - 0.3					
2.0H		+ 0.3 / - 0.4				+ 0.4 / - 0.4					

CIE Pub.117, 837.0 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.6)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:836.976x1 lm		
NAME: AH5060-15W90上	TYPE:	WEIGHT:
SPEC.:AH5060-15W90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	35	21	14	33	21	13	31	19	13	5
0.80	43	28	19	41	27	19	37	25	17	8
1.00	50	35	25	47	33	24	42	33	22	12
1.25	57	42	31	54	40	30	47	36	28	15
1.50	62	47	37	59	45	35	51	40	32	18
2.00	70	56	46	66	53	43	57	47	39	23
2.50	76	62	52	71	59	49	62	52	44	26
3.00	80	68	58	75	64	55	65	56	49	29
4.00	86	75	66	80	70	62	69	62	55	34
5.00	89	80	72	83	75	68	72	65	59	37
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:836.976x1 lm		
NAME: AH5060-15W90上	TYPE:	WEIGHT:
SPEC.:AH5060-15W90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:836.976x1 lm		
NAME: AH5060-15W90上	TYPE:	WEIGHT:
SPEC.:AH5060-15W90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

Flux out:81.01 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:836.976x1 lm		
NAME: AH5060-15W90上	TYPE:	WEIGHT:
SPEC.:AH5060-15W90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:836.976x1 lm		
NAME: AH5060-15W90上	TYPE:	WEIGHT:
SPEC.:AH5060-15W90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	3661
L_0~180(75)av	6501
L_0~180(85)av	19977
L_90~270(65)av	2596
L_90~270(75)av	4544
L_90~270(85)av	13893
L_45(65)av	2648
L_45(75)av	4634
L_45(85)av	14159

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-04-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.8250A P:19.80W PF:1.000 Freq:0Hz Lamp Flux:836.976x1 lm		
NAME: AH5060-15W90上	TYPE:	WEIGHT:
SPEC.:AH5060-15W90上	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	10.6	10.9	10.7	10.7	10.6	10.9	10.7	10.7										
5	9.72	9.92	9.94	9.89	22.0	20.5	19.6	19.8										
10	8.95	9.28	9.34	9.29	40.4	34.3	32.8	32.9										
15	7.95	8.64	8.71	8.68	59.1	48.5	46.4	46.4										
20	6.99	7.87	7.97	7.97	78.0	62.7	60.0	59.8										
25	6.16	7.10	7.22	7.20	97.0	76.8	73.5	73.2										
30	4.71	6.42	6.56	6.54	116	90.6	86.8	86.3										
35	3.42	5.51	5.80	5.84	135	104	99.7	99.2										
40	2.61	4.18	4.52	4.60	153	117	112	112										
45	2.05	3.09	3.35	3.38	171	130	124	124										
50	1.80	2.29	2.46	2.46	188	142	136	135										
55	1.79	1.70	1.85	1.82	204	153	146	145										
60	2.02	1.50	1.50	1.47	218	162	155	154										
65	2.33	1.61	1.46	1.50	230	171	163	162										
70	3.00	1.91	1.78	1.79	240	177	169	168										
75	4.79	2.58	2.39	2.38	248	182	174	173										
80	5.94	4.04	3.82	3.81	253	185	177	175										
85	6.14	4.49	4.29	4.31	255	186	177	176										
90	6.83	4.81	4.63	4.59	255	185	177	175										
95	6.60	4.59	4.48	4.43	253	183	174	173										
100	6.22	4.32	4.18	4.11	244	166	157	155										
105	5.80	4.09	4.00	3.93	219	140	131	129										
110	5.47	3.89	3.81	3.77	187	113	105	103										
115	5.05	3.86	3.79	3.79	153	94.5	89.2	87.8										
120	4.83	3.86	3.82	3.84	126	82.6	78.3	77.1										
125	4.74	3.86	3.85	3.84	107	72.8	69.2	68.2										
130	4.66	3.75	3.71	3.64	92.4	64.1	61.1	60.3										
135	4.50	3.59	3.57	3.50	79.5	56.0	53.6	52.9										
140	4.20	3.28	3.24	3.19	67.8	48.5	46.5	45.9										
145	3.86	2.87	2.77	2.74	57.0	41.2	39.7	39.1										
150	3.35	2.31	2.27	2.21	47.0	34.7	33.8	33.6										
155	2.87	1.84	1.81	1.77	37.5	30.6	30.3	30.2										
160	2.27	1.44	1.50	1.44	28.8	25.1	24.6	24.4										
165	1.47	1.17	1.25	1.18	22.2	18.4	18.0	17.9										
170	0.84	0.93	1.05	1.01	15.4	12.5	12.4	12.3										
175	0.65	0.83	0.94	0.93	7.95	6.62	6.64	6.64										
180	1.34	1.22	1.26	1.28	1.45	1.27	1.27	1.34										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: