


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.9300A P:22.30W PF:1.000 Freq:0Hz Lamp Flux:1025.22x1 lm		
NAME: AH5060-30A45下	TYPE:	WEIGHT:
SPEC.:AH5060-30A45下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 45.97 lm/W			
MODEL	AH5060-30A45下	I _{max} (cd)	364.4	S/MH(C0/180)	1.19
NOMINAL POWER(W)	22.3	LOR(%)	100.0	S/MH(C90/270)	1.19
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1025.2	h UP,DN(C0-180)	0.7,53.5
NOMINAL FLUX(lm)	1025.22	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.5,45.2
LAMPS INSIDE	1	h up(%)	1.3	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.7	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-08

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	359.4	360.7	360.7	360.7	351.7	351.6	352.0	351.7	0- 10	34.34	34.34	3.35,3.35
20	340.9	343.0	343.0	343.1	325.9	325.6	326.1	325.8	10- 20	97.82	132.2	12.9,12.9
30	309.2	312.1	312.0	312.2	288.2	288.0	288.6	288.2	20- 30	146.7	278.8	27.2,27.2
40	267.0	270.6	270.4	270.8	241.7	241.5	242.4	241.9	30- 40	174.3	453.2	44.2,44.2
50	217.9	221.5	221.4	221.8	189.8	189.6	190.6	190.1	40- 50	178.3	631.5	61.6,61.6
60	165.0	168.2	168.0	168.4	135.3	135.2	136.1	135.7	50- 60	159.7	791.2	77.2,77.2
70	111.0	113.3	113.1	113.5	81.21	81.19	82.12	81.73	60- 70	123.0	914.2	89.2,89.2
80	57.95	59.41	59.01	59.35	29.78	29.86	30.65	30.26	70- 80	74.49	988.7	96.4,96.4
90	9.380	9.288	8.638	9.013	0.3088	0.3274	0.3278	0.3273	80- 90	23.58	1012	98.7,98.7
100	0.6406	0.8229	0.8077	0.8620	0.7487	0.6609	0.7216	0.6605	90-100	1.280	1014	98.9,98.9
110	1.176	1.304	1.255	1.324	1.196	1.035	1.063	1.001	100-110	1.004	1015	99,99
120	1.882	1.998	2.001	2.045	1.617	1.396	1.450	1.382	110-120	1.424	1016	99.1,99.1
130	2.630	2.774	2.778	2.846	2.064	1.843	1.878	1.810	120-130	1.807	1018	99.3,99.3
140	3.385	3.481	3.406	3.474	2.558	2.377	2.439	2.390	130-140	2.039	1020	99.5,99.5
150	4.061	3.881	3.841	3.861	3.027	3.051	3.140	3.085	140-150	2.015	1022	99.7,99.7
160	4.595	4.081	4.041	4.088	3.608	3.806	3.943	3.905	150-160	1.730	1024	99.8,99.8
170	4.743	4.422	4.575	4.629	4.189	4.602	4.756	4.689	160-170	1.204	1025	100,100
180	4.903	5.223	5.324	5.350	4.909	5.230	5.337	5.330	170-180	0.4592	1025	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-08

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.9300A P:22.30W PF:1.000 Freq:0Hz Lamp Flux:1025.22x1 lm		
NAME: AH5060-30A45下	TYPE:	WEIGHT:
SPEC.:AH5060-30A45下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.9300A P:22.30W PF:1.000 Freq:0Hz Lamp Flux:1025.22x1 lm		
NAME: AH5060-30A45下	TYPE:	WEIGHT:
SPEC.:AH5060-30A45下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.90	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.82	.76	.84	.79	.74	.81	.76	.72	.77	.74	.71	.68
3.0	.79	.71	.64	.77	.70	.63	.74	.68	.62	.71	.66	.61	.68	.64	.60	.57
4.0	.70	.61	.54	.69	.60	.54	.66	.59	.53	.63	.57	.52	.61	.56	.51	.49
5.0	.62	.53	.47	.61	.53	.46	.59	.52	.46	.57	.50	.45	.55	.49	.45	.42
6.0	.56	.47	.41	.55	.47	.41	.53	.46	.40	.51	.45	.40	.50	.44	.39	.37
7.0	.51	.42	.36	.50	.42	.36	.48	.41	.36	.47	.40	.35	.45	.39	.35	.33
8.0	.47	.38	.32	.46	.38	.32	.44	.37	.32	.43	.36	.31	.42	.36	.31	.29
9.0	.43	.35	.29	.42	.34	.29	.41	.34	.29	.40	.33	.28	.39	.33	.28	.26
10.0	.39	.32	.26	.39	.31	.26	.38	.31	.26	.37	.30	.26	.36	.30	.26	.24



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:24.00V I:0.9300A P:22.30W PF:1.000 Freq:0Hz Lamp Flux:1025.22x1 lm		
NAME: AH5060-30A45下	TYPE:	WEIGHT:
SPEC.:AH5060-30A45下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.314	.179	.057	.307	.175	.056	.293	.168	.054	.280	.161	.052	.268	.155	.050	
2.0	.294	.161	.049	.287	.158	.049	.275	.153	.047	.263	.148	.046	.253	.143	.045	
3.0	.271	.144	.043	.265	.142	.043	.254	.138	.042	.244	.134	.041	.234	.130	.040	
4.0	.249	.130	.038	.244	.128	.038	.234	.124	.037	.225	.121	.036	.217	.118	.036	
5.0	.230	.117	.034	.226	.116	.034	.217	.113	.033	.209	.110	.033	.201	.108	.032	
6.0	.213	.107	.031	.209	.106	.030	.201	.103	.030	.194	.101	.030	.187	.099	.029	
7.0	.198	.098	.028	.195	.097	.028	.188	.095	.027	.181	.093	.027	.175	.091	.027	
8.0	.185	.091	.025	.182	.090	.025	.176	.088	.025	.170	.086	.025	.164	.084	.025	
9.0	.174	.084	.023	.171	.083	.023	.165	.082	.023	.160	.080	.023	.155	.079	.023	
10.0	.163	.078	.022	.160	.078	.022	.155	.076	.021	.151	.075	.021	.146	.073	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.200	.200	.200	.171	.171	.171	.117	.117	.117	.067	.067	.067	.021	.021	.021	
1.0	.190	.166	.144	.163	.142	.124	.111	.098	.086	.064	.057	.050	.021	.018	.016	
2.0	.182	.142	.108	.156	.122	.093	.107	.084	.065	.062	.049	.038	.020	.016	.012	
3.0	.174	.124	.084	.150	.107	.073	.103	.074	.051	.059	.043	.030	.019	.014	.010	
4.0	.167	.111	.068	.143	.096	.059	.098	.067	.042	.057	.039	.025	.018	.013	.008	
5.0	.159	.100	.057	.137	.087	.050	.094	.061	.035	.055	.036	.021	.018	.012	.007	
6.0	.152	.092	.049	.131	.080	.043	.090	.056	.030	.052	.033	.018	.017	.011	.006	
7.0	.145	.085	.043	.125	.074	.038	.086	.052	.027	.050	.031	.016	.016	.010	.005	
8.0	.139	.079	.039	.119	.069	.034	.083	.048	.024	.048	.029	.014	.016	.009	.005	
9.0	.133	.075	.035	.114	.065	.031	.079	.045	.022	.046	.027	.013	.015	.009	.004	
10.0	.127	.070	.032	.109	.061	.028	.076	.043	.020	.044	.025	.012	.014	.008	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.9300A P:22.30W PF:1.000 Freq:0Hz Lamp Flux:1025.22x1 lm										
NAME: AH5060-30A45下						TYPE:		WEIGHT:		
SPEC.:AH5060-30A45下						DIM.: 1500*50*60		SERIAL No.:		
MFR.: COLORS						SUR.:1500*50		Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	18.2	19.7	18.5	19.9	20.1	18.2	19.7	18.5	20.0	20.2
3H	19.9	21.3	20.2	21.5	21.8	20.0	21.3	20.3	21.6	21.9
4H	20.6	22.0	21.0	22.2	22.5	20.7	22.0	21.1	22.3	22.6
6H	21.3	22.5	21.6	22.8	23.1	21.4	22.6	21.7	22.9	23.2
8H	21.6	22.8	21.9	23.1	23.4	21.7	22.9	22.0	23.2	23.5
12H	21.8	22.9	22.2	23.3	23.6	21.9	23.0	22.2	23.4	23.7
4H 2H	18.8	20.2	19.2	20.4	20.7	18.9	20.2	19.2	20.5	20.8
3H	20.7	21.9	21.1	22.2	22.6	20.8	22.0	21.2	22.3	22.6
4H	21.7	22.7	22.0	23.1	23.4	21.7	22.8	22.1	23.1	23.5
6H	22.5	23.4	22.9	23.8	24.2	22.5	23.5	23.0	23.9	24.3
8H	22.8	23.7	23.2	24.1	24.5	22.9	23.8	23.3	24.2	24.6
12H	23.1	23.9	23.6	24.3	24.8	23.2	24.0	23.6	24.4	24.8
8H 4H	22.0	22.9	22.5	23.3	23.7	22.1	23.0	22.5	23.4	23.8
6H	23.0	23.8	23.5	24.2	24.6	23.1	23.8	23.6	24.3	24.7
8H	23.5	24.1	24.0	24.6	25.1	23.6	24.2	24.0	24.7	25.1
12H	23.9	24.5	24.4	25.0	25.5	24.0	24.6	24.5	25.0	25.5
12H 4H	22.1	22.9	22.5	23.3	23.7	22.1	22.9	22.6	23.3	23.8
6H	23.1	23.8	23.6	24.2	24.7	23.2	23.9	23.7	24.3	24.8
8H	23.7	24.2	24.2	24.7	25.2	23.7	24.3	24.2	24.8	25.3
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.1 / - 0.3					+ 0.1 / - 0.3				

CIE Pub.117, 1025 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.1)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.9300A P:22.30W PF:1.000 Freq:0Hz Lamp Flux:1025.22x1 lm		
NAME: AH5060-30A45下	TYPE:	WEIGHT:
SPEC.:AH5060-30A45下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	57	46	39	57	45	39	55	45	38	32
0.80	67	56	48	66	55	48	64	54	48	41
1.00	76	64	57	74	64	57	72	65	56	49
1.25	83	72	65	81	71	64	78	70	63	56
1.50	88	78	71	86	77	70	83	75	69	61
2.00	94	86	79	92	84	78	89	82	77	69
2.50	98	90	84	96	89	83	92	86	81	73
3.00	102	95	89	99	93	88	95	90	86	77
4.00	106	100	95	103	98	94	99	94	91	82
5.00	108	103	99	106	101	97	101	97	94	85
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.9300A P:22.30W PF:1.000 Freq:0Hz Lamp Flux:1025.22x1 lm		
NAME: AH5060-30A45下	TYPE:	WEIGHT:
SPEC.:AH5060-30A45下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.9300A P:22.30W PF:1.000 Freq:0Hz Lamp Flux:1025.22x1 lm		
NAME: AH5060-30A45下	TYPE:	WEIGHT:
SPEC.:AH5060-30A45下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

Flux out:714.9 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.9300A P:22.30W PF:1.000 Freq:0Hz Lamp Flux:1025.22x1 lm		
NAME: AH5060-30A45下	TYPE:	WEIGHT:
SPEC.:AH5060-30A45下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.00V I:0.9300A P:22.30W PF:1.000 Freq:0Hz Lamp Flux:1025.22x1 lm		
NAME: AH5060-30A45下	TYPE:	WEIGHT:
SPEC.:AH5060-30A45下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	3880
L_0~180(75)av	3585
L_0~180(85)av	3029
L_90~270(65)av	3941
L_90~270(75)av	3655
L_90~270(85)av	3069
L_45(65)av	3932
L_45(75)av	3645
L_45(85)av	3072

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-04-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.9300A P:22.30W PF:1.000 Freq:0Hz Lamp Flux:1025.22x1 lm		
NAME: AH5060-30A45下	TYPE:	WEIGHT:
SPEC.:AH5060-30A45下	DIM.: 1500*50*60	SERIAL No.:
MFR.: COLORS	SUR.:1500*50	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	363	364	364	364	363	364	364	364										
5	363	364	364	364	359	359	360	359										
10	359	361	361	361	352	352	352	352										
15	352	354	354	354	340	340	341	340										
20	341	343	343	343	326	326	326	326										
25	327	329	329	329	308	308	309	308										
30	309	312	312	312	288	288	289	288										
35	289	292	292	293	266	266	266	266										
40	267	271	270	271	242	241	242	242										
45	243	247	247	247	216	216	217	217										
50	218	222	221	222	190	190	191	190										
55	192	195	195	195	163	163	163	163										
60	165	168	168	168	135	135	136	136										
65	138	141	141	141	108	108	109	108										
70	111	113	113	113	81.2	81.2	82.1	81.7										
75	84.2	86.1	85.8	86.1	55.0	55.1	56.1	55.6										
80	57.9	59.4	59.0	59.4	29.8	29.9	30.7	30.3										
85	32.6	33.4	32.8	33.2	6.98	6.78	7.29	6.97										
90	9.38	9.29	8.64	9.01	0.31	0.33	0.33	0.33										
95	0.57	0.73	0.78	0.77	0.53	0.47	0.51	0.47										
100	0.64	0.82	0.81	0.86	0.75	0.66	0.72	0.66										
105	0.93	1.04	1.02	1.06	0.98	0.84	0.89	0.82										
110	1.18	1.30	1.25	1.32	1.20	1.03	1.06	1.00										
115	1.50	1.63	1.60	1.66	1.40	1.21	1.25	1.19										
120	1.88	2.00	2.00	2.05	1.62	1.40	1.45	1.38										
125	2.23	2.39	2.40	2.43	1.84	1.60	1.65	1.59										
130	2.63	2.77	2.78	2.85	2.06	1.84	1.88	1.81										
135	2.99	3.17	3.16	3.21	2.30	2.10	2.14	2.09										
140	3.38	3.48	3.41	3.47	2.56	2.38	2.44	2.39										
145	3.71	3.70	3.62	3.67	2.80	2.72	2.77	2.72										
150	4.06	3.88	3.84	3.86	3.03	3.05	3.14	3.08										
155	4.38	3.98	3.95	3.96	3.31	3.43	3.54	3.48										
160	4.60	4.08	4.04	4.09	3.61	3.81	3.94	3.91										
165	4.79	4.19	4.18	4.24	3.89	4.22	4.35	4.29										
170	4.74	4.42	4.57	4.63	4.19	4.60	4.76	4.69										
175	4.66	4.88	5.01	5.07	4.50	4.99	5.16	5.11										
180	4.90	5.22	5.32	5.35	4.91	5.23	5.34	5.33										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: