


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.6124A P:14.70W PF:1.000 Freq:0Hz Lamp Flux:1568.55x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9NWSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 106.73 lm/W			
MODEL	D62802408NO	I _{max} (cd)	519.6	S/MH(C0/180)	1.26
NOMINAL POWER(W)	15	LOR(%)	100.0	S/MH(C90/270)	1.27
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1568.6	h UP,DN(C0-180)	1.0,49.3
NOMINAL FLUX(lm)	1568.55	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.9,48.9
LAMPS INSIDE	1	h up(%)	1.8	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.2	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	508.7	511.2	511.4	512.9	513.0	511.9	508.5	506.2	0- 10	49.11	49.11	3.13,3.13
20	482.0	486.8	489.1	492.4	491.1	488.2	482.7	478.6	10- 20	141.3	190.4	12.1,12.1
30	439.7	446.2	450.6	456.1	453.2	448.8	441.8	435.8	20- 30	215.9	406.3	25.9,25.9
40	382.1	388.2	396.9	403.9	398.9	394.7	383.9	378.5	30- 40	263.3	669.6	42.7,42.7
50	310.6	318.3	328.9	336.6	331.7	326.7	314.9	307.2	40- 50	276.0	945.6	60.3,60.3
60	227.1	235.8	247.8	258.4	253.0	247.1	234.0	224.6	50- 60	252.7	1198	76.4,76.4
70	135.2	144.3	155.3	170.1	165.5	157.4	143.9	133.2	60- 70	194.1	1392	88.8,88.8
80	53.82	58.09	62.80	81.18	79.78	71.06	54.86	50.36	70- 80	111.9	1504	95.9,95.9
90	10.97	9.616	2.579	17.71	19.50	14.48	1.376	8.496	80- 90	35.80	1540	98.2,98.2
100	2.730	2.066	1.755	2.406	2.254	1.436	1.172	1.550	90-100	5.300	1545	98.5,98.5
110	3.262	3.136	2.650	2.614	2.385	2.230	2.472	2.650	100-110	2.258	1548	98.7,98.7
120	4.548	4.403	4.054	3.715	3.589	3.336	3.521	3.860	110-120	3.255	1551	98.9,98.9
130	5.641	5.404	5.054	4.710	4.724	4.400	4.370	4.701	120-130	3.934	1555	99.1,99.1
140	6.491	6.092	5.843	5.645	5.638	5.474	5.037	5.223	130-140	4.093	1559	99.4,99.4
150	7.027	6.453	6.298	6.569	6.306	6.499	5.732	5.551	140-150	3.755	1563	99.6,99.6
160	7.621	6.814	7.225	7.415	7.015	7.387	7.036	6.272	150-160	3.086	1566	99.8,99.8
170	8.096	7.788	8.295	8.143	7.033	8.108	8.217	7.780	160-170	2.122	1568	100,100
180	7.828	9.071	9.178	9.191	7.815	9.051	9.184	9.251	170-180	0.7838	1569	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-08

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.6124A P:14.70W PF:1.000 Freq:0Hz Lamp Flux:1568.55x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	37103	35519
80	38742	45206
75	44208	52183
70	49429	56745
65	53454	59795
60	56765	61945
55	58914	63241
50	60405	63962
45	61541	64479


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.6124A P:14.70W PF:1.000 Freq:0Hz Lamp Flux:1568.55x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.00	1.00	1.00	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.78	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.78	.70	.64	.77	.69	.63	.74	.67	.62	.70	.65	.60	.68	.63	.59	.57
4.0	.69	.60	.54	.68	.60	.53	.65	.58	.52	.63	.56	.51	.60	.55	.50	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.44	.54	.48	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.42	.35	.49	.41	.35	.48	.40	.35	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.34	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.25
10.0	.39	.31	.26	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.6124A P:14.70W PF:1.000 Freq:0Hz Lamp Flux:1568.55x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9NWN5A012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.316	.180	.057	.308	.176	.056	.294	.169	.054	.281	.162	.052	.269	.156	.050	
2.0	.296	.162	.050	.289	.159	.049	.276	.154	.048	.264	.148	.046	.254	.143	.045	
3.0	.273	.145	.043	.267	.143	.043	.255	.138	.042	.245	.134	.041	.235	.130	.040	
4.0	.251	.131	.038	.246	.129	.038	.236	.125	.037	.227	.122	.037	.218	.118	.036	
5.0	.232	.118	.034	.227	.117	.034	.218	.114	.033	.210	.111	.033	.202	.108	.032	
6.0	.215	.108	.031	.211	.106	.031	.203	.104	.030	.195	.101	.030	.188	.099	.029	
7.0	.200	.099	.028	.196	.098	.028	.189	.095	.027	.182	.093	.027	.176	.091	.027	
8.0	.186	.091	.026	.183	.090	.025	.177	.088	.025	.171	.086	.025	.165	.085	.025	
9.0	.175	.084	.024	.172	.084	.023	.166	.082	.023	.160	.080	.023	.155	.079	.023	
10.0	.164	.079	.022	.161	.078	.022	.156	.076	.022	.151	.075	.021	.146	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.204	.204	.204	.175	.175	.175	.119	.119	.119	.068	.068	.068	.022	.022	.022	
1.0	.195	.170	.148	.167	.146	.127	.114	.100	.088	.066	.058	.051	.021	.019	.017	
2.0	.187	.146	.112	.160	.126	.097	.110	.087	.067	.063	.051	.039	.020	.016	.013	
3.0	.179	.128	.088	.154	.111	.076	.105	.077	.054	.061	.045	.032	.020	.015	.010	
4.0	.172	.115	.072	.147	.100	.063	.101	.069	.044	.059	.041	.026	.019	.013	.009	
5.0	.164	.105	.061	.141	.091	.053	.097	.063	.038	.056	.037	.022	.018	.012	.007	
6.0	.157	.097	.053	.135	.084	.046	.093	.059	.033	.054	.034	.020	.017	.011	.006	
7.0	.150	.090	.047	.129	.078	.041	.089	.055	.029	.052	.032	.017	.017	.011	.006	
8.0	.144	.084	.043	.124	.073	.037	.086	.051	.027	.050	.030	.016	.016	.010	.005	
9.0	.138	.079	.040	.119	.069	.034	.082	.048	.024	.048	.028	.015	.015	.009	.005	
10.0	.132	.075	.037	.114	.065	.032	.079	.046	.023	.046	.027	.014	.015	.009	.005	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.6124A P:14.70W PF:1.000 Freq:0Hz Lamp Flux:1568.55x1 lm											
NAME: D62802408NO					TYPE:			WEIGHT:			
SPEC.:D62802408NO-9NWSA012WC0100					DIM.: 1000*8*1.5mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*8mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	25.3	26.8	25.6	27.1	27.3	25.6	27.1	25.9	27.4	27.6	
	3H	26.7	28.1	27.1	28.4	28.7	27.2	28.6	27.5	28.8	29.1
	4H	27.3	28.6	27.6	28.9	29.2	27.8	29.1	28.1	29.4	29.7
	6H	27.6	28.9	28.0	29.2	29.5	28.2	29.4	28.6	29.8	30.1
	8H	27.7	28.9	28.1	29.2	29.6	28.3	29.5	28.7	29.8	30.2
	12H	27.8	28.9	28.2	29.3	29.6	28.4	29.5	28.8	29.9	30.2
4H	2H	25.9	27.3	26.3	27.6	27.9	26.2	27.5	26.5	27.8	28.1
	3H	27.5	28.7	27.9	29.0	29.4	27.9	29.1	28.3	29.4	29.7
	4H	28.2	29.2	28.6	29.6	30.0	28.6	29.7	29.0	30.0	30.4
	6H	28.6	29.6	29.1	30.0	30.4	29.2	30.1	29.6	30.5	30.9
	8H	28.8	29.7	29.2	30.1	30.5	29.3	30.2	29.8	30.6	31.0
	12H	28.9	29.7	29.4	30.1	30.6	29.4	30.2	29.9	30.7	31.1
8H	4H	28.4	29.3	28.9	29.7	30.1	28.8	29.7	29.3	30.1	30.6
	6H	29.0	29.8	29.5	30.2	30.7	29.5	30.2	30.0	30.7	31.2
	8H	29.3	29.9	29.8	30.4	30.9	29.8	30.4	30.3	30.9	31.4
	12H	29.5	30.0	30.0	30.5	31.0	29.9	30.5	30.4	31.0	31.5
12H	4H	28.4	29.3	28.9	29.7	30.1	28.8	29.7	29.3	30.1	30.5
	6H	29.1	29.7	29.6	30.2	30.7	29.6	30.2	30.0	30.7	31.2
	8H	29.4	29.9	29.9	30.4	30.9	29.8	30.4	30.3	30.9	31.4
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2				+ 0.1 / - 0.2						
1.5H	+ 0.2 / - 0.4				+ 0.2 / - 0.3						
2.0H	+ 0.2 / - 0.3				+ 0.2 / - 0.3						

CIE Pub.117, 1569 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 1.6)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.6124A P:14.70W PF:1.000 Freq:0Hz Lamp Flux:1568.55x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	45	38	56	44	37	54	44	37	31
0.80	66	55	47	65	54	47	63	53	46	39
1.00	75	63	56	73	63	56	71	64	55	48
1.25	82	71	64	80	70	63	77	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	78	92	84	78	88	81	76	68
2.50	98	90	84	96	88	83	92	85	81	72
3.00	101	94	89	99	93	87	95	89	85	76
4.00	105	99	95	103	98	93	98	94	90	81
5.00	108	103	99	105	101	97	100	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.6124A P:14.70W PF:1.000 Freq:0Hz Lamp Flux:1568.55x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.6124A P:14.70W PF:1.000 Freq:0Hz Lamp Flux:1568.55x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Flux out:1151 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.6124A P:14.70W PF:1.000 Freq:0Hz Lamp Flux:1568.55x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9NWN5A012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-01-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.6124A P:14.70W PF:1.000 Freq:0Hz Lamp Flux:1568.55x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	519	520	518	518	519	520	518	518										
5	516	518	517	517	518	518	515	514										
10	509	511	511	513	513	512	508	506										
15	498	501	502	505	504	502	498	495										
20	482	487	489	492	491	488	483	479										
25	463	468	472	476	474	470	464	459										
30	440	446	451	456	453	449	442	436										
35	413	420	426	432	429	424	416	409										
40	382	388	397	404	399	395	384	378										
45	348	355	365	371	366	362	351	345										
50	311	318	329	337	332	327	315	307										
55	270	278	290	299	294	288	276	267										
60	227	236	248	258	253	247	234	225										
65	181	191	202	215	210	203	190	179										
70	135	144	155	170	165	157	144	133										
75	91.5	98.8	108	125	121	113	98.0	88.9										
80	53.8	58.1	62.8	81.2	79.8	71.1	54.9	50.4										
85	25.9	27.0	24.8	43.9	44.1	37.0	20.0	22.5										
90	11.0	9.62	2.58	17.7	19.5	14.5	1.38	8.50										
95	5.58	4.02	1.76	6.23	7.74	5.00	0.64	3.31										
100	2.73	2.07	1.75	2.41	2.25	1.44	1.17	1.55										
105	2.64	2.53	2.00	2.16	1.80	1.68	1.82	2.04										
110	3.26	3.14	2.65	2.61	2.39	2.23	2.47	2.65										
115	3.91	3.78	3.41	3.16	2.98	2.79	3.03	3.26										
120	4.55	4.40	4.05	3.71	3.59	3.34	3.52	3.86										
125	5.12	4.93	4.57	4.23	4.19	3.87	3.97	4.38										
130	5.64	5.40	5.05	4.71	4.72	4.40	4.37	4.70										
135	6.10	5.79	5.48	5.17	5.21	4.93	4.74	5.00										
140	6.49	6.09	5.84	5.65	5.64	5.47	5.04	5.22										
145	6.81	6.30	6.06	6.13	5.96	5.99	5.31	5.37										
150	7.03	6.45	6.30	6.57	6.31	6.50	5.73	5.55										
155	7.36	6.62	6.69	7.02	6.66	6.98	6.36	5.78										
160	7.62	6.81	7.23	7.42	7.01	7.39	7.04	6.27										
165	7.95	7.16	7.79	7.75	7.27	7.77	7.66	7.01										
170	8.10	7.79	8.29	8.14	7.03	8.11	8.22	7.78										
175	7.83	8.48	8.76	8.63	7.08	8.53	8.74	8.59										
180	7.83	9.07	9.18	9.19	7.81	9.05	9.18	9.25										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: