


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.4780A P:11.40W PF:1.000 Freq:0Hz Lamp Flux:571.035x1 lm		
NAME: AS3535-15A45	TYPE:	WEIGHT:
SPEC.:AS3535-15A45	DIM.: 500*35*35	SERIAL No.:
MFR.: COLORS	SUR.:500*35	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 50.09 lm/W			
MODEL	AS3535-15A45	I _{max} (cd)	210.2	S/MH(C0/180)	1.25
NOMINAL POWER(W)	11.4	LOR(%)	100.0	S/MH(C90/270)	1.21
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	571.03	h UP,DN(C0-180)	0.8,48.9
NOMINAL FLUX(lm)	571.035	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.6,49.7
LAMPS INSIDE	1	h up(%)	1.4	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.6	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2020-04-09

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	201.7	203.4	205.4	207.1	207.9	206.0	203.5	201.1	0- 10	19.74	19.74	3.46,3.46
20	185.0	188.8	193.3	196.3	196.6	193.6	189.7	185.0	10- 20	56.05	75.80	13.3,13.3
30	161.2	167.0	173.9	177.6	177.1	173.8	169.1	162.2	20- 30	83.56	159.4	27.9,27.9
40	132.7	140.1	148.7	152.6	151.4	148.2	143.3	134.7	30- 40	98.58	257.9	45.2,45.2
50	101.7	109.8	119.8	123.5	121.8	118.8	114.2	104.4	40- 50	99.81	357.7	62.6,62.6
60	70.11	78.28	88.56	92.32	90.38	87.82	83.33	73.26	50- 60	88.26	446.0	78.1,78.1
70	39.67	47.11	56.90	60.71	59.03	56.79	52.49	42.92	60- 70	66.75	512.7	89.8,89.8
80	11.83	17.58	26.34	30.29	29.49	27.52	23.36	14.91	70- 80	39.14	551.9	96.6,96.6
90	0.3473	0.4809	0.6043	3.127	3.622	1.621	0.1203	0.1403	80- 90	11.20	563.1	98.6,98.6
100	0.5342	0.6150	0.5410	0.4677	0.2547	0.2467	0.3683	0.3941	90-100	0.4682	563.6	98.7,98.7
110	0.9071	0.9693	0.8536	0.6285	0.5420	0.5277	0.8484	0.7211	100-110	0.6040	564.2	98.8,98.8
120	1.309	1.463	1.429	0.9227	0.8619	0.8076	1.377	1.135	110-120	0.9457	565.1	99,99
130	1.762	1.965	1.910	1.230	1.196	1.149	1.603	1.575	120-130	1.216	566.3	99.2,99.2
140	2.190	2.499	2.291	1.577	1.537	1.495	1.757	1.997	130-140	1.343	567.7	99.4,99.4
150	2.531	2.859	2.465	1.957	1.877	1.930	1.877	2.137	140-150	1.300	569.0	99.6,99.6
160	2.879	2.859	2.672	2.358	2.271	2.331	2.051	2.137	150-160	1.074	570.0	99.8,99.8
170	3.079	2.852	2.765	2.699	2.699	2.744	2.712	2.204	160-170	0.7259	570.8	100,100
180	2.919	3.099	3.306	3.093	2.946	3.099	3.266	3.073	170-180	0.2714	571.0	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-09

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.4780A P:11.40W PF:1.000 Freq:0Hz Lamp Flux:571.035x1 lm		
NAME: AS3535-15A45	TYPE:	WEIGHT:
SPEC.:AS3535-15A45	DIM.: 500*35*35	SERIAL No.:
MFR.: COLORS	SUR.:500*35	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.4780A P:11.40W PF:1.000 Freq:0Hz Lamp Flux:571.035x1 lm		
NAME: AS3535-15A45	TYPE:	WEIGHT:
SPEC.:AS3535-15A45	DIM.: 500*35*35	SERIAL No.:
MFR.: COLORS	SUR.:500*35	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.04	.99	.96	1.01	.97	.94	.97	.94	.91	.93	.90	.88	.89	.87	.85	.83
2.0	.90	.84	.78	.88	.82	.77	.85	.79	.75	.81	.77	.73	.78	.74	.71	.69
3.0	.79	.71	.65	.78	.70	.64	.75	.68	.63	.72	.66	.62	.69	.64	.60	.58
4.0	.70	.62	.55	.69	.61	.55	.66	.59	.54	.64	.58	.53	.62	.56	.52	.50
5.0	.63	.54	.47	.62	.53	.47	.60	.52	.46	.57	.51	.46	.55	.50	.45	.43
6.0	.57	.48	.42	.56	.47	.41	.54	.46	.41	.52	.45	.40	.50	.44	.40	.38
7.0	.52	.43	.37	.51	.42	.37	.49	.42	.36	.47	.41	.36	.46	.40	.35	.33
8.0	.47	.39	.33	.46	.38	.33	.45	.38	.32	.44	.37	.32	.42	.36	.32	.30
9.0	.43	.35	.30	.43	.35	.29	.41	.34	.29	.40	.34	.29	.39	.33	.29	.27
10.0	.40	.32	.27	.39	.32	.27	.38	.31	.27	.37	.31	.26	.36	.30	.26	.24



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.4780A P:11.40W PF:1.000 Freq:0Hz Lamp Flux:571.035x1 lm		
NAME: AS3535-15A45	TYPE:	WEIGHT:
SPEC.:AS3535-15A45	DIM.: 500*35*35	SERIAL No.:
MFR.: COLORS	SUR.:500*35	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0														
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
rfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.307	.175	.055	.300	.171	.054	.286	.164	.052	.273	.157	.051	.261	.151	.049															
2.0	.289	.158	.049	.282	.155	.048	.270	.150	.047	.258	.145	.045	.248	.140	.044															
3.0	.267	.142	.043	.261	.140	.042	.250	.136	.041	.240	.132	.040	.231	.128	.040															
4.0	.246	.128	.038	.241	.126	.037	.232	.123	.037	.222	.119	.036	.214	.116	.035															
5.0	.228	.116	.034	.223	.115	.033	.215	.112	.033	.206	.109	.032	.199	.106	.032															
6.0	.211	.106	.030	.207	.105	.030	.200	.102	.030	.192	.100	.029	.185	.098	.029															
7.0	.197	.097	.028	.193	.096	.027	.186	.094	.027	.180	.092	.027	.174	.090	.027															
8.0	.184	.090	.025	.181	.089	.025	.174	.087	.025	.169	.085	.025	.163	.084	.024															
9.0	.172	.083	.023	.169	.083	.023	.164	.081	.023	.159	.079	.023	.154	.078	.023															
10.0	.162	.078	.022	.160	.077	.021	.154	.076	.021	.150	.074	.021	.145	.073	.021															

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.201	.201	.201	.172	.172	.172	.117	.117	.117	.067	.067	.067	.022	.022	.022	
1.0	.191	.167	.145	.163	.143	.125	.112	.099	.086	.064	.057	.050	.021	.018	.016	
2.0	.183	.143	.109	.156	.123	.094	.107	.085	.066	.062	.049	.039	.020	.016	.013	
3.0	.175	.125	.086	.150	.108	.074	.103	.075	.052	.059	.044	.031	.019	.014	.010	
4.0	.167	.112	.070	.143	.097	.060	.099	.067	.043	.057	.039	.025	.018	.013	.008	
5.0	.160	.101	.058	.137	.088	.051	.094	.061	.036	.055	.036	.021	.018	.012	.007	
6.0	.152	.093	.050	.131	.081	.044	.090	.056	.031	.052	.033	.018	.017	.011	.006	
7.0	.146	.086	.044	.125	.075	.039	.087	.052	.027	.050	.031	.016	.016	.010	.005	
8.0	.139	.080	.040	.120	.070	.035	.083	.049	.025	.048	.029	.015	.016	.009	.005	
9.0	.133	.075	.036	.115	.065	.032	.079	.046	.023	.046	.027	.013	.015	.009	.004	
10.0	.128	.071	.034	.110	.062	.029	.076	.043	.021	.044	.026	.012	.014	.008	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.4780A P:11.40W PF:1.000 Freq:0Hz Lamp Flux:571.035x1 lm										
NAME: AS3535-15A45					TYPE:			WEIGHT:		
SPEC.:AS3535-15A45					DIM.: 500*35*35			SERIAL No.:		
MFR.: COLORS					SUR.:500*35			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	21.9	23.4	22.2	23.6	23.8	22.7	24.2	23.0	24.4	24.6
3H	23.1	24.5	23.4	24.7	25.0	24.3	25.7	24.6	25.9	26.2
4H	23.5	24.8	23.9	25.1	25.4	25.0	26.3	25.3	26.5	26.8
6H	23.7	25.0	24.1	25.3	25.6	25.5	26.7	25.8	27.0	27.3
8H	23.7	24.9	24.1	25.2	25.6	25.7	26.8	26.0	27.2	27.5
12H	23.7	24.8	24.1	25.2	25.5	25.8	26.9	26.1	27.2	27.6
4H 2H	22.5	23.8	22.9	24.1	24.4	23.2	24.5	23.5	24.8	25.0
3H	23.9	25.1	24.3	25.4	25.7	24.9	26.1	25.3	26.4	26.7
4H	24.5	25.5	24.9	25.9	26.2	25.7	26.8	26.1	27.1	27.5
6H	24.8	25.7	25.2	26.1	26.5	26.4	27.3	26.8	27.7	28.1
8H	24.8	25.7	25.2	26.1	26.5	26.6	27.5	27.0	27.9	28.3
12H	24.8	25.6	25.2	26.0	26.4	26.8	27.6	27.2	28.0	28.4
8H 4H	24.8	25.6	25.2	26.0	26.4	25.9	26.8	26.3	27.1	27.6
6H	25.2	25.9	25.7	26.3	26.8	26.7	27.4	27.1	27.8	28.3
8H	25.3	25.9	25.7	26.3	26.8	27.0	27.6	27.5	28.1	28.5
12H	25.3	25.8	25.8	26.3	26.8	27.2	27.7	27.7	28.2	28.7
12H 4H	24.8	25.6	25.2	26.0	26.4	25.9	26.7	26.3	27.1	27.5
6H	25.2	25.9	25.7	26.3	26.8	26.7	27.3	27.2	27.8	28.2
8H	25.3	25.9	25.8	26.4	26.9	27.0	27.6	27.5	28.0	28.5
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.3					+ 0.1 / - 0.2				
1.5H	+ 0.2 / - 0.4					+ 0.1 / - 0.2				
2.0H	+ 0.2 / - 0.5					+ 0.2 / - 0.3				

CIE Pub.117, 571.0 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -1.9)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.4780A P:11.40W PF:1.000 Freq:0Hz Lamp Flux:571.035x1 lm		
NAME: AS3535-15A45	TYPE:	WEIGHT:
SPEC.:AS3535-15A45	DIM.: 500*35*35	SERIAL No.:
MFR.: COLORS	SUR.:500*35	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	58	46	39	57	46	39	56	46	39	33
0.80	68	56	49	67	56	49	65	55	48	41
1.00	76	65	58	75	64	58	72	66	57	50
1.25	83	73	66	82	72	65	79	70	64	57
1.50	88	78	71	86	77	71	83	75	70	62
2.00	95	86	80	93	85	79	89	83	77	69
2.50	99	91	85	97	89	84	92	87	82	73
3.00	102	95	90	100	94	88	95	90	86	77
4.00	106	100	96	103	98	94	99	95	91	82
5.00	108	104	100	106	101	98	101	98	95	85
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.4780A P:11.40W PF:1.000 Freq:0Hz Lamp Flux:571.035x1 lm		
NAME: AS3535-15A45	TYPE:	WEIGHT:
SPEC.:AS3535-15A45	DIM.: 500*35*35	SERIAL No.:
MFR.: COLORS	SUR.:500*35	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-09

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

AAI Figure

Test:U:24.00V I:0.4780A P:11.40W PF:1.000 Freq:0Hz Lamp Flux:571.035x1 lm		
NAME: AS3535-15A45	TYPE:	WEIGHT:
SPEC.:AS3535-15A45	DIM.: 500*35*35	SERIAL No.:
MFR.: COLORS	SUR.:500*35	Shielding Angle:

Flux out:385.9 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.4780A P:11.40W PF:1.000 Freq:0Hz Lamp Flux:571.035x1 lm		
NAME: AS3535-15A45	TYPE:	WEIGHT:
SPEC.:AS3535-15A45	DIM.: 500*35*35	SERIAL No.:
MFR.: COLORS	SUR.:500*35	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.00V I:0.4780A P:11.40W PF:1.000 Freq:0Hz Lamp Flux:571.035x1 lm		
NAME: AS3535-15A45	TYPE:	WEIGHT:
SPEC.:AS3535-15A45	DIM.: 500*35*35	SERIAL No.:
MFR.: COLORS	SUR.:500*35	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	8740
L_0~180(75)av	7646
L_0~180(85)av	5542
L_90~270(65)av	9595
L_90~270(75)av	8732
L_90~270(85)av	6981
L_45(65)av	9093
L_45(75)av	8153
L_45(85)av	6036

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.4780A P:11.40W PF:1.000 Freq:0Hz Lamp Flux:571.035x1 lm		
NAME: AS3535-15A45	TYPE:	WEIGHT:
SPEC.:AS3535-15A45	DIM.: 500*35*35	SERIAL No.:
MFR.: COLORS	SUR.:500*35	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	210	209	209	209	210	209	209	209										
5	207	208	208	209	210	209	207	206										
10	202	203	205	207	208	206	203	201										
15	194	197	200	203	203	201	198	194										
20	185	189	193	196	197	194	190	185										
25	174	179	184	188	188	185	180	174										
30	161	167	174	178	177	174	169	162										
35	147	154	162	166	165	162	157	149										
40	133	140	149	153	151	148	143	135										
45	117	125	135	138	137	134	129	120										
50	102	110	120	123	122	119	114	104										
55	85.9	94.1	104	108	106	103	98.8	88.8										
60	70.1	78.3	88.6	92.3	90.4	87.8	83.3	73.3										
65	54.7	62.5	74.1	76.4	74.6	72.2	67.8	57.8										
70	39.7	47.1	56.9	60.7	59.0	56.8	52.5	42.9										
75	25.3	32.0	41.4	45.3	44.0	41.8	37.7	28.5										
80	11.8	17.6	26.3	30.3	29.5	27.5	23.4	14.9										
85	1.03	4.30	11.7	16.0	15.9	13.8	9.59	2.73										
90	0.35	0.48	0.60	3.13	3.62	1.62	0.12	0.14										
95	0.41	0.52	0.54	0.43	0.15	0.15	0.25	0.23										
100	0.53	0.62	0.54	0.47	0.25	0.25	0.37	0.39										
105	0.70	0.76	0.62	0.53	0.39	0.37	0.57	0.57										
110	0.91	0.97	0.85	0.63	0.54	0.53	0.85	0.72										
115	1.11	1.21	1.16	0.78	0.69	0.62	1.14	0.93										
120	1.31	1.46	1.43	0.92	0.86	0.81	1.38	1.14										
125	1.54	1.74	1.68	1.08	1.02	0.94	1.52	1.36										
130	1.76	1.96	1.91	1.23	1.20	1.15	1.60	1.58										
135	2.00	2.23	2.10	1.42	1.36	1.30	1.68	1.81										
140	2.19	2.50	2.29	1.58	1.54	1.50	1.76	2.00										
145	2.38	2.73	2.45	1.76	1.71	1.71	1.83	2.14										
150	2.53	2.86	2.46	1.96	1.88	1.93	1.88	2.14										
155	2.74	2.86	2.56	2.16	2.07	2.15	1.94	2.14										
160	2.88	2.86	2.67	2.36	2.27	2.33	2.05	2.14										
165	3.03	2.84	2.67	2.54	2.49	2.55	2.32	2.14										
170	3.08	2.85	2.77	2.70	2.70	2.74	2.71	2.20										
175	2.91	2.97	3.07	2.89	2.76	2.88	3.07	2.66										
180	2.92	3.10	3.31	3.09	2.95	3.10	3.27	3.07										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: