


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.8360A P:20.00W PF:1.000 Freq:0Hz Lamp Flux:1242.8lx1 lm		
NAME: AS3535-30A45	TYPE:	WEIGHT:
SPEC.:AS3535-30A45	DIM.: 1000*35*35	SERIAL No.:
MFR.: COLORS	SUR.:1000*35	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 62.14 lm/W			
MODEL	AS3535-30A45	I _{max} (cd)	441.7	S/MH(C0/180)	1.18
NOMINAL POWER(W)	20	LOR(%)	100.0	S/MH(C90/270)	1.23
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1242.8	h UP,DN(C0-180)	0.7,50.6
NOMINAL FLUX(lm)	1242.81	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,48.0
LAMPS INSIDE	1	h up(%)	1.4	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.6	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-09

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	437.2	434.8	429.1	425.8	426.7	425.9	429.5	433.5	0~ 10	41.50	41.50	3.34,3.34
20	415.7	413.4	403.4	394.0	392.9	395.6	403.4	411.4	10~ 20	118.3	159.8	12.9,12.9
30	378.5	373.9	363.9	350.4	346.9	351.5	362.0	373.8	20~ 30	177.2	337.0	27.1,27.1
40	328.3	324.7	312.2	295.7	290.2	296.2	310.6	323.8	30~ 40	211.2	548.1	44.1,44.1
50	269.7	266.5	252.9	233.5	226.4	233.0	251.0	265.4	40~ 50	216.6	764.7	61.5,61.5
60	204.3	202.8	187.1	167.5	159.3	165.1	186.3	199.6	50~ 60	194.3	959.0	77.2,77.2
70	137.9	136.9	121.0	101.0	92.60	98.74	119.9	133.5	60~ 70	149.2	1108	89.2,89.2
80	72.90	71.71	55.98	36.27	28.88	34.98	55.62	69.23	70~ 80	89.88	1198	96.4,96.4
90	12.39	9.899	1.375	1.069	0.4159	0.4000	0.4396	9.088	80~ 90	27.26	1225	98.6,98.6
100	0.8611	1.183	1.202	1.277	1.063	0.9206	0.8425	0.6407	90~100	1.388	1227	98.7,98.7
110	1.596	1.787	1.674	1.738	1.698	1.466	1.838	1.401	100~110	1.369	1228	98.8,98.8
120	2.577	2.819	2.416	2.338	2.365	2.108	2.572	2.370	110~120	2.029	1230	99,99
130	3.592	3.662	3.157	3.026	3.026	2.838	3.167	3.199	120~130	2.529	1233	99.2,99.2
140	4.561	4.248	3.825	3.869	3.661	3.820	3.675	3.854	130~140	2.760	1235	99.4,99.4
150	5.350	4.629	4.607	4.837	4.162	4.895	4.469	4.262	140~150	2.680	1238	99.6,99.6
160	6.083	5.110	5.857	5.800	4.743	5.864	5.799	4.661	150~160	2.336	1240	99.8,99.8
170	6.232	6.528	6.872	6.646	5.377	6.806	6.874	6.037	160~170	1.674	1242	99.9,99.9
180	6.292	7.474	7.374	7.247	6.285	7.468	7.441	7.261	170~180	0.6363	1243	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-09

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.8360A P:20.00W PF:1.000 Freq:0Hz Lamp Flux:1242.81x1 lm		
NAME: AS3535-30A45	TYPE:	WEIGHT:
SPEC.:AS3535-30A45	DIM.: 1000*35*35	SERIAL No.:
MFR.: COLORS	SUR.:1000*35	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	13612	7865
80	11995	9211
75	11598	9750
70	11519	10111
65	11559	10421
60	11673	10691
55	11852	11011
50	11990	11239
45	12113	11459


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.8360A P:20.00W PF:1.000 Freq:0Hz Lamp Flux:1242.8lx1 lm		
NAME: AS3535-30A45	TYPE:	WEIGHT:
SPEC.:AS3535-30A45	DIM.: 1000*35*35	SERIAL No.:
MFR.: COLORS	SUR.:1000*35	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.90	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.82	.76	.84	.79	.74	.81	.76	.72	.77	.74	.71	.68
3.0	.79	.71	.64	.77	.70	.63	.74	.68	.62	.71	.66	.61	.68	.64	.60	.57
4.0	.70	.61	.54	.69	.60	.54	.66	.59	.53	.63	.57	.52	.61	.56	.51	.49
5.0	.62	.53	.47	.61	.53	.46	.59	.52	.46	.57	.50	.45	.55	.49	.45	.42
6.0	.56	.47	.41	.55	.47	.41	.53	.46	.40	.51	.45	.40	.50	.44	.39	.37
7.0	.51	.42	.36	.50	.42	.36	.48	.41	.36	.47	.40	.35	.45	.39	.35	.33
8.0	.47	.38	.32	.46	.38	.32	.44	.37	.32	.43	.36	.31	.42	.36	.31	.29
9.0	.43	.35	.29	.42	.34	.29	.41	.34	.29	.40	.33	.28	.39	.33	.28	.26
10.0	.39	.32	.26	.39	.31	.26	.38	.31	.26	.37	.30	.26	.36	.30	.26	.24



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.8360A P:20.00W PF:1.000 Freq:0Hz Lamp Flux:1242.81x1 lm		
NAME: AS3535-30A45	TYPE:	WEIGHT:
SPEC.:AS3535-30A45	DIM.: 1000*35*35	SERIAL No.:
MFR.: COLORS	SUR.:1000*35	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0														
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
rfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.313	.178	.056	.306	.174	.055	.292	.167	.053	.279	.161	.052	.267	.155	.050															
2.0	.293	.161	.049	.286	.158	.049	.274	.152	.047	.262	.147	.046	.252	.142	.045															
3.0	.270	.144	.043	.265	.142	.043	.253	.137	.042	.243	.133	.041	.234	.129	.040															
4.0	.249	.129	.038	.244	.128	.038	.234	.124	.037	.225	.121	.036	.217	.118	.036															
5.0	.230	.117	.034	.225	.116	.034	.217	.113	.033	.209	.110	.033	.201	.107	.032															
6.0	.213	.107	.031	.209	.106	.030	.201	.103	.030	.194	.101	.030	.187	.099	.029															
7.0	.198	.098	.028	.195	.097	.028	.188	.095	.027	.181	.093	.027	.175	.091	.027															
8.0	.185	.090	.025	.182	.090	.025	.176	.088	.025	.170	.086	.025	.164	.084	.025															
9.0	.174	.084	.023	.171	.083	.023	.165	.082	.023	.160	.080	.023	.155	.078	.023															
10.0	.163	.078	.022	.160	.077	.022	.155	.076	.021	.150	.075	.021	.146	.073	.021															

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.201	.201	.201	.172	.172	.172	.117	.117	.117	.067	.067	.067	.022	.022	.022	
1.0	.191	.167	.145	.164	.143	.125	.112	.099	.086	.064	.057	.050	.021	.018	.016	
2.0	.183	.143	.109	.157	.123	.094	.108	.085	.066	.062	.049	.038	.020	.016	.013	
3.0	.175	.125	.085	.150	.108	.074	.103	.075	.052	.060	.044	.031	.019	.014	.010	
4.0	.168	.112	.069	.144	.097	.060	.099	.067	.042	.057	.039	.025	.018	.013	.008	
5.0	.160	.102	.058	.138	.088	.051	.095	.061	.036	.055	.036	.021	.018	.012	.007	
6.0	.153	.093	.050	.132	.081	.044	.091	.056	.031	.053	.033	.018	.017	.011	.006	
7.0	.146	.086	.044	.126	.075	.039	.087	.052	.027	.051	.031	.016	.016	.010	.005	
8.0	.140	.081	.040	.120	.070	.035	.083	.049	.025	.048	.029	.015	.016	.009	.005	
9.0	.134	.076	.036	.115	.066	.032	.080	.046	.022	.046	.027	.013	.015	.009	.004	
10.0	.128	.071	.034	.110	.062	.029	.077	.044	.021	.045	.026	.012	.014	.008	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.8360A P:20.00W PF:1.000 Freq:0Hz Lamp Flux:1242.8lx1 lm											
NAME: AS3535-30A45					TYPE:			WEIGHT:			
SPEC.:AS3535-30A45					DIM.: 1000*35*35			SERIAL No.:			
MFR.: COLORS					SUR.:1000*35			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	20.9	22.4	21.2	22.6	22.8	20.6	22.1	20.9	22.3	22.5	
	3H	22.6	24.0	22.9	24.2	24.5	22.2	23.5	22.5	23.8	24.1
	4H	23.4	24.7	23.7	25.0	25.3	22.8	24.2	23.2	24.4	24.7
	6H	24.1	25.3	24.4	25.6	25.9	23.4	24.6	23.7	24.9	25.2
	8H	24.3	25.5	24.7	25.8	26.2	23.5	24.7	23.9	25.0	25.4
	12H	24.6	25.7	24.9	26.1	26.4	23.6	24.8	24.0	25.1	25.5
4H	2H	21.5	22.8	21.9	23.1	23.4	21.3	22.6	21.6	22.9	23.2
	3H	23.4	24.6	23.8	24.9	25.3	23.1	24.2	23.5	24.6	24.9
	4H	24.4	25.4	24.8	25.8	26.1	23.9	25.0	24.3	25.3	25.7
	6H	25.2	26.1	25.6	26.5	26.9	24.6	25.5	25.0	25.9	26.3
	8H	25.6	26.4	26.0	26.8	27.2	24.8	25.7	25.3	26.1	26.5
	12H	25.9	26.7	26.3	27.1	27.5	25.0	25.8	25.4	26.2	26.6
8H	4H	24.7	25.6	25.2	26.0	26.4	24.3	25.2	24.8	25.6	26.0
	6H	25.7	26.5	26.2	26.9	27.4	25.2	25.9	25.7	26.4	26.8
	8H	26.2	26.9	26.7	27.3	27.8	25.6	26.2	26.0	26.6	27.1
	12H	26.7	27.2	27.2	27.7	28.2	25.8	26.4	26.3	26.8	27.4
12H	4H	24.7	25.6	25.2	26.0	26.4	24.4	25.2	24.8	25.6	26.0
	6H	25.8	26.5	26.3	26.9	27.4	25.3	26.0	25.8	26.4	26.9
	8H	26.4	26.9	26.9	27.4	27.9	25.7	26.3	26.2	26.8	27.3
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2				+ 0.1 / - 0.2						
1.5H	+ 0.2 / - 0.3				+ 0.2 / - 0.3						
2.0H	+ 0.1 / - 0.3				+ 0.1 / - 0.4						

CIE Pub.117, 1243 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.8)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.8360A P:20.00W PF:1.000 Freq:0Hz Lamp Flux:1242.81x1 lm		
NAME: AS3535-30A45	TYPE:	WEIGHT:
SPEC.:AS3535-30A45	DIM.: 1000*35*35	SERIAL No.:
MFR.: COLORS	SUR.:1000*35	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	57	46	39	56	45	39	55	45	38	32
0.80	67	56	48	66	55	48	64	54	48	41
1.00	76	64	57	74	64	57	72	65	56	49
1.25	83	72	65	81	71	64	78	70	63	56
1.50	88	78	71	86	77	70	83	75	69	61
2.00	94	86	79	92	84	78	89	82	77	69
2.50	98	90	84	96	89	83	92	86	81	73
3.00	102	95	89	99	93	88	95	90	86	77
4.00	106	100	95	103	98	94	99	94	91	81
5.00	108	103	99	106	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.8360A P:20.00W PF:1.000 Freq:0Hz Lamp Flux:1242.8lx1 lm		
NAME: AS3535-30A45	TYPE:	WEIGHT:
SPEC.:AS3535-30A45	DIM.: 1000*35*35	SERIAL No.:
MFR.: COLORS	SUR.:1000*35	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-04-09

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.8360A P:20.00W PF:1.000 Freq:0Hz Lamp Flux:1242.81x1 lm		
NAME: AS3535-30A45	TYPE:	WEIGHT:
SPEC.:AS3535-30A45	DIM.: 1000*35*35	SERIAL No.:
MFR.: COLORS	SUR.:1000*35	Shielding Angle:

Flux out:866.3 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.8360A P:20.00W PF:1.000 Freq:0Hz Lamp Flux:1242.8lx1 lm		
NAME: AS3535-30A45	TYPE:	WEIGHT:
SPEC.:AS3535-30A45	DIM.: 1000*35*35	SERIAL No.:
MFR.: COLORS	SUR.:1000*35	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-04-09

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:24.00V I:0.8360A P:20.00W PF:1.000 Freq:0Hz Lamp Flux:1242.81x1 lm		
NAME: AS3535-30A45	TYPE:	WEIGHT:
SPEC.:AS3535-30A45	DIM.: 1000*35*35	SERIAL No.:
MFR.: COLORS	SUR.:1000*35	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	10027
L_0~180(75)av	9126
L_0~180(85)av	7267
L_90~270(65)av	10385
L_90~270(75)av	9703
L_90~270(85)av	7902
L_45(65)av	10180
L_45(75)av	9373
L_45(85)av	7480

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-04-09

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.8360A P:20.00W PF:1.000 Freq:0Hz Lamp Flux:1242.81x1 lm		
NAME: AS3535-30A45	TYPE:	WEIGHT:
SPEC.:AS3535-30A45	DIM.: 1000*35*35	SERIAL No.:
MFR.: COLORS	SUR.:1000*35	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	441	440	439	438	441	440	439	438										
5	441	440	436	434	436	435	436	438										
10	437	435	429	426	427	426	429	433										
15	429	426	418	413	413	413	419	425										
20	416	413	403	394	393	396	403	411										
25	399	394	385	374	372	375	384	394										
30	379	374	364	350	347	352	362	374										
35	355	351	339	324	320	325	338	350										
40	328	325	312	296	290	296	311	324										
45	300	297	284	265	259	265	282	296										
50	270	267	253	233	226	233	251	265										
55	238	235	221	201	193	198	219	234										
60	204	203	187	168	159	165	186	200										
65	171	170	154	134	126	132	153	167										
70	138	137	121	101	92.6	98.7	120	133										
75	105	104	88.3	68.2	60.3	66.6	87.5	101										
80	72.9	71.7	56.0	36.3	28.9	35.0	55.6	69.2										
85	41.5	39.9	24.0	7.25	2.81	6.00	24.2	38.1										
90	12.4	9.90	1.37	1.07	0.42	0.40	0.44	9.09										
95	0.64	1.04	1.20	1.14	0.73	0.61	0.59	0.42										
100	0.86	1.18	1.20	1.28	1.06	0.92	0.84	0.64										
105	1.21	1.42	1.29	1.46	1.38	1.14	1.32	1.02										
110	1.60	1.79	1.67	1.74	1.70	1.47	1.84	1.40										
115	2.06	2.29	2.08	2.02	2.00	1.76	2.27	1.90										
120	2.58	2.82	2.42	2.34	2.36	2.11	2.57	2.37										
125	3.08	3.28	2.78	2.63	2.69	2.44	2.85	2.85										
130	3.59	3.66	3.16	3.03	3.03	2.84	3.17	3.20										
135	4.07	4.00	3.49	3.40	3.36	3.29	3.44	3.57										
140	4.56	4.25	3.83	3.87	3.66	3.82	3.67	3.85										
145	4.99	4.44	4.10	4.33	3.95	4.35	3.94	4.07										
150	5.35	4.63	4.61	4.84	4.16	4.89	4.47	4.26										
155	5.74	4.84	5.25	5.34	4.43	5.42	5.17	4.47										
160	6.08	5.11	5.86	5.80	4.74	5.86	5.80	4.66										
165	6.31	5.75	6.44	6.23	5.06	6.35	6.38	5.13										
170	6.23	6.53	6.87	6.65	5.38	6.81	6.87	6.04										
175	6.04	7.07	7.17	7.05	5.73	7.23	7.25	6.71										
180	6.29	7.47	7.37	7.25	6.29	7.47	7.44	7.26										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-04-09

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: