


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.2714A P:6.513W PF:1.000 Freq:0Hz Lamp Flux:365.49lx1 lm		
NAME: ALS-LE2409FDXSH1000	TYPE:	WEIGHT:
SPEC.:ALS-LE2409FDXSH1000-F7NW9X-BC	DIM.: 1000*24*09mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*24	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 56.12 lm/W			
MODEL	ALS-LE2409FDXSH1000	I _{max} (cd)	153.3	S/MH(C0/180)	0.80
NOMINAL POWER(W)	6.6	LOR(%)	100.0	S/MH(C90/270)	1.22
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	365.49	h UP,DN(C0-180)	0.9,40.9
NOMINAL FLUX(lm)	365.491	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.5,57.6
LAMPS INSIDE	1	h up(%)	1.5	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.5	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	104.9	110.7	122.5	134.5	139.1	134.5	121.8	109.3	0- 10	11.78	11.78	3.22,3.22
20	81.61	91.64	115.4	139.4	148.7	138.7	114.0	89.69	10- 20	33.59	45.37	12.4,12.4
30	53.88	68.51	104.0	139.0	153.2	137.8	102.2	66.42	20- 30	50.47	95.85	26.2,26.2
40	22.52	43.60	89.29	133.6	151.4	131.9	87.03	41.60	30- 40	59.80	155.6	42.6,42.6
50	9.159	20.88	71.75	123.3	143.0	120.9	69.32	19.41	40- 50	61.66	217.3	59.5,59.5
60	4.854	8.448	52.26	107.9	127.3	104.8	49.69	7.830	50- 60	58.18	275.5	75.4,75.4
70	2.169	3.840	31.47	85.76	86.09	81.96	29.50	3.501	60- 70	49.44	324.9	88.9,88.9
80	0.6911	1.135	12.42	34.32	26.68	31.12	11.23	1.045	70- 80	29.52	354.4	97,97
90	0.1070	0.1404	0.3822	0.6276	0.0134	0.0470	0.0602	0.1136	80- 90	5.647	360.1	98.5,98.5
100	0.6192	0.7177	0.3139	0.1666	0.0200	0.0200	0.2273	0.5398	90-100	0.2514	360.3	98.6,98.6
110	1.474	1.317	0.4867	0.0804	0.0334	0.0201	0.5155	1.041	100-110	0.4985	360.8	98.7,98.7
120	1.923	1.644	0.8010	0.1671	0.0937	0.1002	0.7619	1.362	110-120	0.7411	361.6	98.9,98.9
130	2.151	1.837	1.048	0.3546	0.1606	0.2864	0.9624	1.510	120-130	0.8496	362.4	99.2,99.2
140	2.330	1.857	1.276	0.6414	0.3882	0.5744	1.115	1.596	130-140	0.8703	363.3	99.4,99.4
150	2.345	1.857	1.376	0.9954	0.7291	0.9552	1.296	1.676	140-150	0.8208	364.1	99.6,99.6
160	2.351	1.864	1.716	1.363	1.109	1.282	1.617	1.683	150-160	0.6960	364.8	99.8,99.8
170	2.112	1.991	1.904	1.730	1.429	1.683	1.924	1.910	160-170	0.4872	365.3	100,100
180	1.790	2.131	2.131	2.117	1.777	2.131	2.137	2.104	170-180	0.1816	365.5	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-11

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.2714A P:6.513W PF:1.000 Freq:0Hz Lamp Flux:365.49lx1 lm		
NAME: ALS-LE2409FDXSH1000	TYPE:	WEIGHT:
SPEC.:ALS-LE2409FDXSH1000-F7NW9X-BC	DIM.: 1000*24*09mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*24	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	122	2423
80	166	2981
75	212	3447
70	264	3834
65	329	4140
60	404	4355
55	496	4516
50	594	4651
45	796	4762


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-11

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.2714A P:6.513W PF:1.000 Freq:0Hz Lamp Flux:365.49lx1 lm		
NAME: ALS-LE2409FDXSH1000	TYPE:	WEIGHT:
SPEC.:ALS-LE2409FDXSH1000-F7NW9X-BC	DIM.: 1000*24*09mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*24	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.87	.81	.76	.84	.78	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.78	.70	.63	.77	.69	.63	.73	.67	.61	.70	.65	.60	.68	.63	.59	.56
4.0	.69	.60	.53	.68	.59	.53	.65	.58	.52	.62	.56	.51	.60	.55	.50	.48
5.0	.62	.53	.46	.60	.52	.45	.58	.51	.45	.56	.49	.44	.54	.48	.44	.41
6.0	.55	.46	.40	.54	.46	.40	.52	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.35	.46	.39	.34	.45	.38	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.35	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.25
10.0	.39	.31	.26	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.2714A P:6.513W PF:1.000 Freq:0Hz Lamp Flux:365.491x1 lm		
NAME: ALS-LE2409FDXSH1000	TYPE:	WEIGHT:
SPEC.:ALS-LE2409FDXSH1000-F7NW9X-BC	DIM.: 1000*24*09mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*24	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.315	.179	.057	.307	.175	.056	.293	.168	.054	.280	.162	.052	.268	.155	.050	
2.0	.297	.163	.050	.290	.160	.049	.278	.155	.048	.266	.149	.047	.256	.145	.046	
3.0	.275	.146	.044	.269	.144	.043	.257	.140	.042	.247	.135	.042	.238	.132	.041	
4.0	.253	.131	.039	.247	.130	.038	.238	.126	.038	.228	.123	.037	.220	.119	.036	
5.0	.233	.119	.034	.228	.117	.034	.220	.114	.034	.211	.112	.033	.204	.109	.033	
6.0	.216	.108	.031	.212	.107	.031	.204	.104	.030	.196	.102	.030	.189	.100	.030	
7.0	.200	.099	.028	.197	.098	.028	.190	.096	.028	.183	.094	.027	.177	.092	.027	
8.0	.187	.091	.026	.184	.090	.026	.177	.089	.025	.171	.087	.025	.166	.085	.025	
9.0	.175	.085	.024	.172	.084	.024	.166	.082	.023	.161	.081	.023	.156	.079	.023	
10.0	.164	.079	.022	.162	.078	.022	.156	.077	.022	.152	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.202	.202	.202	.172	.172	.172	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.192	.167	.145	.164	.144	.125	.112	.099	.086	.065	.057	.050	.021	.018	.016	
2.0	.184	.143	.109	.158	.123	.094	.108	.085	.066	.062	.050	.038	.020	.016	.013	
3.0	.177	.126	.085	.152	.109	.074	.104	.075	.052	.060	.044	.031	.019	.014	.010	
4.0	.169	.113	.069	.145	.097	.060	.100	.068	.042	.058	.040	.025	.019	.013	.008	
5.0	.162	.102	.058	.139	.088	.051	.096	.062	.036	.055	.036	.021	.018	.012	.007	
6.0	.155	.094	.050	.133	.081	.044	.092	.057	.031	.053	.033	.018	.017	.011	.006	
7.0	.148	.087	.045	.127	.075	.039	.088	.053	.028	.051	.031	.016	.016	.010	.005	
8.0	.141	.081	.040	.121	.071	.035	.084	.050	.025	.049	.029	.015	.016	.010	.005	
9.0	.135	.076	.037	.116	.066	.032	.081	.047	.023	.047	.028	.014	.015	.009	.004	
10.0	.129	.072	.034	.111	.063	.030	.077	.044	.021	.045	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.2714A P:6.513W PF:1.000 Freq:0Hz Lamp Flux:365.49lx1 lm										
NAME: ALS-LE2409FDXSH1000					TYPE:			WEIGHT:		
SPEC.:ALS-LE2409FDXSH1000-F7NW9X-BC					DIM.: 1000*24*09mm			SERIAL No.:		
MFR.: COLORS					SUR.:1000*24			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	10.3	11.8	10.6	12.0	12.3	19.0	20.5	19.3	20.7	21.0
3H	10.4	11.8	10.8	12.1	12.4	20.7	22.1	21.0	22.4	22.7
4H	10.4	11.8	10.8	12.1	12.3	21.4	22.8	21.8	23.0	23.3
6H	10.4	11.7	10.8	12.0	12.3	21.9	23.2	22.3	23.5	23.8
8H	10.4	11.6	10.7	11.9	12.2	22.1	23.3	22.5	23.6	23.9
12H	10.3	11.5	10.7	11.8	12.2	22.2	23.4	22.6	23.7	24.0
4H 2H	11.2	12.6	11.6	12.9	13.2	18.8	20.1	19.1	20.4	20.7
3H	11.4	12.6	11.8	12.9	13.3	20.7	21.8	21.0	22.2	22.5
4H	11.5	12.6	11.9	12.9	13.3	21.5	22.6	21.9	22.9	23.3
6H	11.5	12.4	11.9	12.8	13.2	22.2	23.1	22.6	23.5	23.9
8H	11.5	12.4	11.9	12.8	13.2	22.4	23.3	22.8	23.7	24.1
12H	11.4	12.3	11.9	12.7	13.1	22.6	23.4	23.0	23.8	24.2
8H 4H	12.1	13.0	12.6	13.4	13.8	21.4	22.3	21.8	22.7	23.1
6H	12.2	12.9	12.6	13.3	13.8	22.1	22.9	22.6	23.3	23.7
8H	12.2	12.8	12.7	13.3	13.8	22.4	23.1	22.9	23.5	24.0
12H	12.2	12.7	12.7	13.2	13.7	22.7	23.2	23.2	23.7	24.2
12H 4H	12.3	13.1	12.8	13.6	14.0	21.3	22.1	21.8	22.6	23.0
6H	12.4	13.0	12.9	13.5	14.0	22.1	22.7	22.6	23.2	23.7
8H	12.4	13.0	12.9	13.4	13.9	22.4	23.0	22.9	23.4	23.9
Variations with the observer position at spacings:										
S = 1.0H	+ 1.2 / - 1.6					+ 0.3 / - 0.2				
1.5H	+ 1.1 / - 1.5					+ 0.9 / - 0.8				
2.0H	+ 1.6 / - 1.8					+ 1.6 / - 1.8				

CIE Pub.117, 365.5 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -3.5)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.2714A P:6.513W PF:1.000 Freq:0Hz Lamp Flux:365.49lx1 lm		
NAME: ALS-LE2409FDXSH1000	TYPE:	WEIGHT:
SPEC.:ALS-LE2409FDXSH1000-F7NW9X-BC	DIM.: 1000*24*09mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*24	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	57	45	38	56	45	38	54	44	37	31
0.80	66	55	47	65	54	47	63	53	46	39
1.00	75	63	56	73	63	56	71	64	55	47
1.25	82	71	64	80	70	63	77	69	62	55
1.50	87	77	69	85	76	69	82	74	68	60
2.00	94	85	78	92	84	77	88	81	76	68
2.50	98	90	84	96	88	83	92	86	81	72
3.00	101	94	89	99	93	87	95	89	85	76
4.00	106	100	95	103	98	93	99	94	91	81
5.00	108	103	99	106	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.2714A P:6.513W PF:1.000 Freq:0Hz Lamp Flux:365.49lx1 lm		
NAME: ALS-LE2409FDXSH1000	TYPE:	WEIGHT:
SPEC.:ALS-LE2409FDXSH1000-F7NW9X-BC	DIM.: 1000*24*09mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*24	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.2714A P:6.513W PF:1.000 Freq:0Hz Lamp Flux:365.49lx1 lm		
NAME: ALS-LE2409FDXSH1000	TYPE:	WEIGHT:
SPEC.:ALS-LE2409FDXSH1000-F7NW9X-BC	DIM.: 1000*24*09mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*24	Shielding Angle:

Flux out:199.0 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2021-03-11

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.2714A P:6.513W PF:1.000 Freq:0Hz Lamp Flux:365.49lx1 lm		
NAME: ALS-LE2409FDXSH1000	TYPE:	WEIGHT:
SPEC.:ALS-LE2409FDXSH1000-F7NW9X-BC	DIM.: 1000*24*09mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*24	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:24.00V I:0.2714A P:6.513W PF:1.000 Freq:0Hz Lamp Flux:365.49lx1 lm		
NAME: ALS-LE2409FDXSH1000	TYPE:	WEIGHT:
SPEC.:ALS-LE2409FDXSH1000-F7NW9X-BC	DIM.: 1000*24*09mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*24	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	5656
L_0~180(75)av	4570
L_0~180(85)av	1419
L_90~270(65)av	4021
L_90~270(75)av	3324
L_90~270(85)av	2248
L_45(65)av	5087
L_45(75)av	5124
L_45(85)av	1962

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-03-11

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.2714A P:6.513W PF:1.000 Freq:0Hz Lamp Flux:365.491x1 lm		
NAME: ALS-LE2409FDXSH1000	TYPE:	WEIGHT:
SPEC.:ALS-LE2409FDXSH1000-F7NW9X-BC	DIM.: 1000*24*09mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*24	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	124	125	125	124	124	125	125	124										
5	115	118	124	130	133	130	124	117										
10	105	111	122	134	139	135	122	109										
15	93.6	102	120	138	145	137	118	100										
20	81.6	91.6	115	139	149	139	114	89.7										
25	68.9	80.5	110	140	152	139	109	78.4										
30	53.9	68.5	104	139	153	138	102	66.4										
35	37.2	56.1	97.1	137	153	135	95.0	53.9										
40	22.5	43.6	89.3	134	151	132	87.0	41.6										
45	13.5	31.6	80.8	129	148	127	78.5	29.8										
50	9.16	20.9	71.8	123	143	121	69.3	19.4										
55	6.83	12.8	62.2	116	136	114	59.7	11.8										
60	4.85	8.45	52.3	108	127	105	49.7	7.83										
65	3.34	5.92	42.0	99.3	111	95.8	39.6	5.44										
70	2.17	3.84	31.5	85.8	86.1	82.0	29.5	3.50										
75	1.31	2.26	21.4	63.4	55.5	59.6	19.9	2.03										
80	0.69	1.13	12.4	34.3	26.7	31.1	11.2	1.05										
85	0.26	0.41	5.07	8.84	5.68	6.79	4.34	0.38										
90	0.11	0.14	0.38	0.63	0.01	0.05	0.06	0.11										
95	0.26	0.36	0.33	0.39	0.03	0.02	0.12	0.23										
100	0.62	0.72	0.31	0.17	0.02	0.02	0.23	0.54										
105	1.05	1.07	0.34	0.07	0.03	0.02	0.37	0.81										
110	1.47	1.32	0.49	0.08	0.03	0.02	0.52	1.04										
115	1.74	1.50	0.63	0.11	0.05	0.10	0.64	1.23										
120	1.92	1.64	0.80	0.17	0.09	0.10	0.76	1.36										
125	2.04	1.76	0.93	0.23	0.13	0.19	0.87	1.45										
130	2.15	1.84	1.05	0.35	0.16	0.29	0.96	1.51										
135	2.20	1.86	1.15	0.49	0.25	0.41	1.05	1.57										
140	2.33	1.86	1.28	0.64	0.39	0.57	1.12	1.60										
145	2.35	1.86	1.30	0.81	0.55	0.74	1.19	1.64										
150	2.34	1.86	1.38	1.00	0.73	0.96	1.30	1.68										
155	2.34	1.86	1.50	1.18	0.92	1.11	1.46	1.68										
160	2.35	1.86	1.72	1.36	1.11	1.28	1.62	1.68										
165	2.26	1.90	1.79	1.54	1.31	1.47	1.78	1.81										
170	2.11	1.99	1.90	1.73	1.43	1.68	1.92	1.91										
175	1.89	2.08	2.02	1.94	1.54	1.89	2.06	2.02										
180	1.79	2.13	2.13	2.12	1.78	2.13	2.14	2.10										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: