


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.6047A P:14.51W PF:1.000 Freq:0Hz Lamp Flux:1522.92x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9SWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 104.94 lm/W			
MODEL	D62802408NO	I _{max} (cd)	501.5	S/MH(C0/180)	1.24
NOMINAL POWER(W)	15	LOR(%)	100.0	S/MH(C90/270)	1.28
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1522.9	h UP,DN(C0-180)	0.9,46.8
NOMINAL FLUX(lm)	1522.92	CIE CLASS	DIRECT	h UP,DN(C180-360)	1.2,51.1
LAMPS INSIDE	1	h up(%)	2.2	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	97.8	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	488.2	488.9	492.1	481.4	498.0	495.3	491.6	484.3	0- 10	47.13	47.13	3.09,3.09
20	460.1	462.7	469.2	458.1	479.5	475.7	468.4	463.1	10- 20	135.7	182.8	12,12
30	416.9	421.4	431.4	420.4	446.6	440.9	430.6	427.0	20- 30	207.5	390.3	25.6,25.6
40	358.9	362.9	378.6	367.7	397.2	392.1	376.2	376.5	30- 40	253.1	643.4	42.2,42.2
50	287.8	293.6	312.0	305.7	335.1	329.8	310.9	312.8	40- 50	266.2	909.6	59.7,59.7
60	204.3	213.2	232.0	233.2	261.6	255.5	233.7	236.9	50- 60	244.6	1154	75.8,75.8
70	115.3	125.3	142.8	152.1	177.6	169.8	147.7	150.8	60- 70	189.2	1343	88.2,88.2
80	36.83	43.68	55.18	70.31	90.10	82.99	61.91	69.74	70- 80	110.5	1454	95.5,95.5
90	3.494	4.414	3.193	12.18	21.29	18.93	3.688	27.20	80- 90	36.36	1490	97.8,97.8
100	2.225	2.178	1.951	2.164	3.322	5.257	1.171	16.94	90-100	7.592	1498	98.3,98.3
110	3.426	3.287	2.748	2.807	2.064	3.687	2.488	11.99	100-110	4.023	1502	98.6,98.6
120	4.655	4.485	4.132	3.816	3.226	3.186	3.454	3.607	110-120	3.978	1506	98.9,98.9
130	5.697	5.445	5.049	4.723	4.351	4.048	4.222	4.468	120-130	3.844	1510	99.1,99.1
140	6.484	6.053	5.862	5.532	5.304	5.115	4.803	4.982	130-140	3.978	1514	99.4,99.4
150	6.960	6.393	6.277	6.400	5.932	6.091	5.439	5.310	140-150	3.640	1517	99.6,99.6
160	7.553	6.701	7.093	7.187	6.686	6.973	6.742	5.750	150-160	2.979	1520	99.8,99.8
170	7.849	7.528	8.042	7.856	6.993	7.713	7.876	7.139	160-170	2.040	1522	100,100
180	7.595	8.717	8.797	8.790	7.588	8.690	8.837	8.643	170-180	0.7515	1523	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.6047A P:14.51W PF:1.000 Freq:0Hz Lamp Flux:1522.92x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9SWWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	17116	30520
80	26512	39723
75	35331	47110
70	42143	52185
65	47184	55533
60	51076	57997
55	53928	59725
50	55966	60673
45	57432	61345


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.6047A P:14.51W PF:1.000 Freq:0Hz Lamp Flux:1522.92x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9SWWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.00	1.00	1.00	.98
1.0	1.03	.99	.95	1.00	.96	.93	.96	.92	.89	.91	.89	.86	.88	.85	.83	.81
2.0	.89	.82	.77	.87	.81	.75	.83	.78	.73	.80	.75	.71	.76	.73	.69	.67
3.0	.78	.70	.63	.77	.69	.63	.73	.67	.61	.70	.65	.60	.67	.63	.59	.56
4.0	.69	.60	.53	.68	.59	.53	.65	.58	.52	.62	.56	.51	.60	.54	.50	.48
5.0	.62	.53	.46	.60	.52	.45	.58	.51	.45	.56	.49	.44	.54	.48	.43	.41
6.0	.55	.46	.40	.54	.46	.40	.52	.45	.39	.50	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.34	.46	.39	.34	.44	.38	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.31	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.27	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.6047A P:14.51W PF:1.000 Freq:0Hz Lamp Flux:1522.92x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9SWWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0	
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
rfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.318	.181	.057	.310	.177	.056	.296	.170	.054	.282	.163	.052	.270	.157	.050		
2.0	.297	.163	.050	.290	.160	.049	.277	.154	.048	.265	.149	.047	.254	.144	.045		
3.0	.274	.146	.044	.268	.143	.043	.256	.139	.042	.245	.135	.041	.236	.130	.040		
4.0	.252	.131	.038	.246	.129	.038	.236	.125	.037	.227	.122	.037	.218	.118	.036		
5.0	.232	.118	.034	.228	.117	.034	.219	.114	.033	.210	.111	.033	.202	.108	.032		
6.0	.215	.108	.031	.211	.107	.031	.203	.104	.030	.195	.101	.030	.188	.099	.029		
7.0	.200	.099	.028	.196	.098	.028	.189	.096	.028	.182	.093	.027	.176	.091	.027		
8.0	.187	.091	.026	.183	.090	.026	.177	.088	.025	.171	.086	.025	.165	.085	.025		
9.0	.175	.085	.024	.172	.084	.023	.166	.082	.023	.160	.080	.023	.155	.079	.023		
10.0	.164	.079	.022	.161	.078	.022	.156	.076	.022	.151	.075	.021	.146	.074	.021		

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.207	.207	.207	.177	.177	.177	.121	.121	.121	.069	.069	.069	.022	.022	.022	
1.0	.197	.173	.150	.169	.148	.129	.116	.102	.089	.067	.059	.052	.021	.019	.017	
2.0	.190	.149	.114	.162	.128	.099	.111	.088	.069	.064	.051	.040	.021	.017	.013	
3.0	.182	.131	.091	.156	.113	.079	.107	.079	.055	.062	.046	.032	.020	.015	.011	
4.0	.174	.118	.075	.150	.102	.065	.103	.071	.046	.060	.042	.027	.019	.014	.009	
5.0	.167	.108	.064	.143	.093	.055	.099	.065	.039	.057	.038	.023	.018	.012	.008	
6.0	.160	.099	.056	.137	.086	.049	.095	.060	.034	.055	.035	.020	.018	.012	.007	
7.0	.153	.092	.050	.132	.080	.044	.091	.056	.031	.053	.033	.018	.017	.011	.006	
8.0	.146	.087	.046	.126	.075	.040	.087	.053	.028	.051	.031	.017	.016	.010	.006	
9.0	.140	.082	.042	.121	.071	.037	.084	.050	.026	.049	.029	.016	.016	.010	.005	
10.0	.135	.077	.039	.116	.067	.034	.080	.047	.024	.047	.028	.015	.015	.009	.005	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.6047A P:14.51W PF:1.000 Freq:0Hz Lamp Flux:1522.92x1 lm											
NAME: D62802408NO					TYPE:			WEIGHT:			
SPEC.:D62802408NO-9SWWNSA012WC0100					DIM.: 1000*8*1.5mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*8mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	24.9	26.4	25.2	26.6	26.9	25.3	26.8	25.6	27.1	27.3	
	3H	26.2	27.6	26.5	27.8	28.1	26.8	28.2	27.1	28.5	28.8
	4H	26.6	27.9	26.9	28.2	28.5	27.4	28.7	27.7	29.0	29.3
	6H	26.8	28.1	27.2	28.4	28.7	27.8	29.0	28.1	29.3	29.6
	8H	26.8	28.0	27.2	28.4	28.7	27.8	29.1	28.2	29.4	29.7
	12H	26.8	28.0	27.2	28.3	28.7	27.9	29.0	28.3	29.4	29.7
4H	2H	25.5	26.8	25.8	27.1	27.4	25.8	27.1	26.2	27.4	27.7
	3H	26.9	28.1	27.3	28.4	28.8	27.5	28.6	27.9	29.0	29.3
	4H	27.5	28.5	27.9	28.9	29.3	28.2	29.2	28.6	29.6	30.0
	6H	27.8	28.7	28.2	29.1	29.5	28.6	29.6	29.1	30.0	30.4
	8H	27.8	28.7	28.3	29.1	29.5	28.8	29.7	29.2	30.1	30.5
	12H	27.8	28.7	28.3	29.1	29.5	28.9	29.7	29.3	30.1	30.5
8H	4H	27.7	28.6	28.1	29.0	29.4	28.3	29.2	28.8	29.6	30.0
	6H	28.1	28.8	28.6	29.3	29.7	28.9	29.6	29.4	30.1	30.5
	8H	28.2	28.9	28.7	29.3	29.8	29.1	29.8	29.6	30.2	30.7
	12H	28.3	28.8	28.8	29.3	29.8	29.2	29.8	29.8	30.3	30.8
12H	4H	27.7	28.5	28.1	28.9	29.4	28.3	29.1	28.8	29.5	30.0
	6H	28.1	28.8	28.6	29.2	29.7	28.9	29.6	29.4	30.0	30.5
	8H	28.3	28.8	28.8	29.3	29.8	29.1	29.7	29.7	30.2	30.7
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2				+ 0.2 / - 0.2						
1.5H	+ 0.2 / - 0.4				+ 0.2 / - 0.3						
2.0H	+ 0.2 / - 0.3				+ 0.2 / - 0.3						

CIE Pub.117, 1523 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 1.5)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.6047A P:14.51W PF:1.000 Freq:0Hz Lamp Flux:1522.92x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9SWWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	44	37	55	44	37	54	43	37	30
0.80	66	54	47	65	54	47	63	53	46	39
1.00	74	63	56	73	62	55	71	64	55	47
1.25	82	71	63	80	70	63	77	68	62	54
1.50	87	76	69	85	75	69	82	74	67	60
2.00	94	85	78	92	83	77	88	81	76	67
2.50	98	90	83	95	88	82	91	85	80	71
3.00	101	94	88	99	92	87	94	89	85	75
4.00	105	99	94	103	97	93	98	94	90	80
5.00	108	103	98	105	100	97	100	96	93	83
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.6047A P:14.51W PF:1.000 Freq:0Hz Lamp Flux:1522.92x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9SWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-08

deg Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

AAI Figure

Test:U:24.00V I:0.6047A P:14.51W PF:1.000 Freq:0Hz Lamp Flux:1522.92x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9SWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Flux out:1109 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.6047A P:14.51W PF:1.000 Freq:0Hz Lamp Flux:1522.92x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9SWWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-01-08

deg Range: 0 - 180DEG
deg Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.6047A P:14.51W PF:1.000 Freq:0Hz Lamp Flux:1522.92x1 lm		
NAME: D62802408NO	TYPE:	WEIGHT:
SPEC.:D62802408NO-9SWWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	501	500	499	490	501	500	499	490										
5	496	496	498	488	501	499	497	489										
10	488	489	492	481	498	495	492	484										
15	476	478	483	471	491	487	482	476										
20	460	463	469	458	480	476	468	463										
25	440	444	452	441	465	460	451	447										
30	417	421	431	420	447	441	431	427										
35	390	393	407	395	425	418	406	403										
40	359	363	379	368	397	392	376	377										
45	325	330	347	338	367	363	345	346										
50	288	294	312	306	335	330	311	313										
55	247	255	274	271	300	294	274	276										
60	204	213	232	233	262	255	234	237										
65	160	170	188	194	221	214	191	194										
70	115	125	143	152	178	170	148	151										
75	73.2	82.1	97.5	110	134	126	103	108										
80	36.8	43.7	55.2	70.3	90.1	83.0	61.9	69.7										
85	11.9	15.9	21.3	35.9	50.5	45.3	27.5	40.9										
90	3.49	4.41	3.19	12.2	21.3	18.9	3.69	27.2										
95	2.93	2.61	2.44	3.96	8.56	8.48	0.61	22.6										
100	2.22	2.18	1.95	2.16	3.32	5.26	1.17	16.9										
105	2.76	2.70	2.10	2.40	1.64	4.54	1.85	10.9										
110	3.43	3.29	2.75	2.81	2.06	3.69	2.49	12.0										
115	4.06	3.91	3.47	3.31	2.64	3.30	3.01	7.78										
120	4.65	4.48	4.13	3.82	3.23	3.19	3.45	3.61										
125	5.20	4.99	4.60	4.30	3.80	3.51	3.87	4.09										
130	5.70	5.44	5.05	4.72	4.35	4.05	4.22	4.47										
135	6.12	5.79	5.52	5.11	4.86	4.55	4.55	4.76										
140	6.48	6.05	5.86	5.53	5.30	5.12	4.80	4.98										
145	6.72	6.24	6.06	5.97	5.65	5.62	5.05	5.12										
150	6.96	6.39	6.28	6.40	5.93	6.09	5.44	5.31										
155	7.25	6.54	6.59	6.81	6.32	6.58	6.08	5.50										
160	7.55	6.70	7.09	7.19	6.69	6.97	6.74	5.75										
165	7.82	7.01	7.59	7.50	7.03	7.33	7.33	6.35										
170	7.85	7.53	8.04	7.86	6.99	7.71	7.88	7.14										
175	7.49	8.14	8.48	8.30	6.99	8.15	8.40	7.97										
180	7.59	8.72	8.80	8.79	7.59	8.69	8.84	8.64										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: