


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:1.115A P:26.76W PF:1.000 Freq:0Hz Lamp Flux:1570.5lx1 lm		
NAME: LLS-LE9435FDXSS1000	TYPE:	WEIGHT:
SPEC.:LLS-LE9435FDXSS1000-F30WWHX-DC	DIM.: 1000*94*35mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*94	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 58.68 lm/W			
MODEL	LLS-LE9435FDXSS1000	I <sub>max</sub> (cd)	583.6	S/MH(C0/180)	1.21
NOMINAL POWER(W)	30	LOR(%)	100.0	S/MH(C90/270)	1.23
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1570.5	h UP,DN(C0-180)	0.5,49.5
NOMINAL FLUX(lm)	1570.51	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.5,49.5
LAMPS INSIDE	1	h up(%)	1.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	99.0	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-03-03

Range: 0 - 180DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	569.1	572.3	570.5	564.4	572.3	570.7	569.8	564.0	0- 10	54.91	54.91	3.5,3.5
20	530.6	537.0	535.9	529.4	536.8	534.1	534.2	527.9	10- 20	156.2	211.1	13.4,13.4
30	472.4	481.8	481.2	473.6	480.6	477.5	479.2	472.0	20- 30	233.8	444.9	28.3,28.3
40	399.7	411.4	412.0	402.2	408.6	405.3	408.3	401.3	30- 40	277.3	722.3	46,46
50	316.2	326.3	330.9	320.0	324.6	322.3	325.3	319.3	40- 50	281.8	1004	63.9,63.9
60	225.1	236.2	241.1	230.9	234.2	231.4	235.5	229.9	50- 60	249.2	1253	79.8,79.8
70	128.5	141.1	144.8	137.1	139.0	135.1	140.7	135.0	60- 70	183.3	1437	91.5,91.5
80	41.68	51.40	54.42	48.83	50.35	47.08	51.78	47.86	70- 80	96.99	1534	97.6,97.6
90	0.6948	1.035	1.308	0.9610	0.2139	0.2926	0.2485	0.3295	80- 90	20.82	1554	99,99
100	1.075	1.156	1.082	1.083	0.7820	0.7415	0.8088	0.8335	90-100	0.7963	1555	99,99
110	1.922	1.778	1.749	1.598	1.571	1.361	1.760	1.449	100-110	1.347	1557	99.1,99.1
120	2.745	2.533	2.656	2.191	2.352	2.017	2.692	2.304	110-120	2.027	1559	99.2,99.2
130	3.426	3.228	3.371	2.840	3.047	2.770	3.341	2.965	120-130	2.498	1561	99.4,99.4
140	4.027	3.781	3.933	3.568	3.709	3.631	3.814	3.627	130-140	2.666	1564	99.6,99.6
150	4.594	4.242	4.261	4.437	4.302	4.649	4.242	4.267	140-150	2.545	1566	99.7,99.7
160	5.316	4.830	4.881	5.204	5.072	5.437	4.924	4.781	150-160	2.174	1568	99.9,99.9
170	5.998	5.517	5.437	5.631	5.664	5.925	5.538	5.403	160-170	1.512	1570	100,100
180	6.579	6.272	5.998	6.098	6.593	6.299	6.025	6.092	170-180	0.5562	1571	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-03-03

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### LUMINANCE LIMITATION CURVES

Test:U:24.00V I:1.115A P:26.76W PF:1.000 Freq:0Hz Lamp Flux:1570.51x1 lm		
NAME: LLS-LE9435FDXSS1000	TYPE:	WEIGHT:
SPEC.:LLS-LE9435FDXSS1000-F30WWHX-DC	DIM.: 1000*94*35mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*94	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	1402	2437
80	2553	3334
75	3392	4021
70	3996	4504
65	4433	4845
60	4789	5130
55	5040	5323
50	5233	5476
45	5403	5607


C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-03-03

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:1.115A P:26.76W PF:1.000 Freq:0Hz Lamp Flux:1570.51x1 lm		
NAME: LLS-LE9435FDXSS1000	TYPE:	WEIGHT:
SPEC.:LLS-LE9435FDXSS1000-F30WWHX-DC	DIM.: 1000*94*35mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*94	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-03-03

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

WEC AND CCEC

Test:U:24.00V I:1.115A P:26.76W PF:1.000 Freq:0Hz Lamp Flux:1570.5lx1 lm		
NAME: LLS-LE9435FDXSS1000	TYPE:	WEIGHT:
SPEC.:LLS-LE9435FDXSS1000-F30WWHX-DC	DIM.: 1000*94*35mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*94	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0	
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
rfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.298	.169	.054	.290	.166	.053	.276	.159	.051	.264	.152	.049	.252	.146	.047		
2.0	.283	.155	.048	.276	.152	.047	.264	.147	.046	.253	.142	.044	.243	.137	.043		
3.0	.263	.140	.042	.257	.138	.042	.247	.134	.041	.237	.130	.040	.228	.126	.039		
4.0	.244	.127	.037	.239	.125	.037	.229	.122	.036	.220	.118	.036	.212	.115	.035		
5.0	.226	.115	.033	.222	.114	.033	.213	.111	.033	.205	.108	.032	.198	.106	.032		
6.0	.210	.105	.030	.206	.104	.030	.198	.102	.030	.191	.099	.029	.185	.097	.029		
7.0	.196	.097	.027	.192	.096	.027	.185	.094	.027	.179	.092	.027	.173	.090	.026		
8.0	.183	.090	.025	.180	.089	.025	.174	.087	.025	.168	.085	.025	.163	.084	.024		
9.0	.172	.083	.023	.169	.082	.023	.163	.081	.023	.158	.079	.023	.153	.078	.023		
10.0	.162	.078	.022	.159	.077	.021	.154	.076	.021	.149	.074	.021	.145	.073	.021		

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.198	.198	.198	.169	.169	.169	.116	.116	.116	.066	.066	.066	.021	.021	.021	
1.0	.187	.164	.143	.160	.141	.123	.110	.097	.085	.063	.056	.050	.020	.018	.016	
2.0	.179	.140	.107	.153	.120	.093	.105	.083	.065	.061	.048	.038	.019	.016	.012	
3.0	.171	.122	.083	.147	.105	.072	.101	.073	.051	.058	.043	.030	.019	.014	.010	
4.0	.164	.109	.067	.140	.094	.058	.097	.066	.041	.056	.038	.024	.018	.013	.008	
5.0	.156	.098	.056	.134	.085	.049	.092	.060	.034	.054	.035	.020	.017	.011	.007	
6.0	.149	.090	.048	.128	.078	.042	.088	.055	.029	.051	.032	.017	.017	.011	.006	
7.0	.142	.083	.042	.122	.072	.036	.085	.051	.026	.049	.030	.015	.016	.010	.005	
8.0	.136	.077	.037	.117	.067	.032	.081	.047	.023	.047	.028	.014	.015	.009	.005	
9.0	.130	.072	.034	.112	.063	.029	.078	.044	.021	.045	.026	.012	.015	.009	.004	
10.0	.124	.068	.031	.107	.059	.027	.074	.042	.019	.043	.025	.011	.014	.008	.004	

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-03-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:1.115A P:26.76W PF:1.000 Freq:0Hz Lamp Flux:1570.51x1 lm											
NAME: LLS-LE9435FDXSS1000					TYPE:			WEIGHT:			
SPEC.:LLS-LE9435FDXSS1000-F30WWHX-DC					DIM.: 1000*94*35mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*94			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	16.8	18.3	17.1	18.5	18.8	17.1	18.6	17.4	18.8	19.0	
	3H	18.1	19.5	18.4	19.8	20.0	18.5	19.9	18.8	20.1	20.4
	4H	18.6	19.9	18.9	20.2	20.4	19.0	20.3	19.4	20.6	20.9
	6H	18.8	20.0	19.2	20.3	20.6	19.4	20.6	19.7	20.9	21.2
	8H	18.9	20.0	19.2	20.3	20.6	19.4	20.6	19.8	20.9	21.2
	12H	18.8	20.0	19.2	20.3	20.6	19.5	20.6	19.8	20.9	21.2
4H	2H	17.4	18.7	17.8	19.0	19.3	17.6	18.9	18.0	19.2	19.5
	3H	18.9	20.1	19.3	20.4	20.7	19.2	20.4	19.6	20.7	21.0
	4H	19.5	20.5	19.9	20.9	21.2	19.9	20.9	20.3	21.2	21.6
	6H	19.8	20.7	20.2	21.1	21.5	20.3	21.2	20.7	21.6	22.0
	8H	19.9	20.7	20.3	21.1	21.5	20.4	21.3	20.9	21.7	22.1
	12H	19.9	20.7	20.3	21.1	21.5	20.5	21.3	20.9	21.7	22.1
8H	4H	19.7	20.6	20.2	21.0	21.4	20.1	20.9	20.5	21.3	21.7
	6H	20.2	20.9	20.6	21.3	21.8	20.6	21.3	21.1	21.8	22.2
	8H	20.3	20.9	20.8	21.4	21.8	20.8	21.4	21.3	21.9	22.4
	12H	20.3	20.9	20.8	21.3	21.8	20.9	21.5	21.4	21.9	22.4
12H	4H	19.7	20.5	20.2	20.9	21.3	20.1	20.8	20.5	21.2	21.7
	6H	20.2	20.8	20.7	21.3	21.8	20.7	21.3	21.1	21.7	22.2
	8H	20.4	20.9	20.9	21.4	21.9	20.9	21.4	21.4	21.9	22.4
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2				+ 0.2 / - 0.2						
1.5H	+ 0.2 / - 0.4				+ 0.2 / - 0.3						
2.0H	+ 0.2 / - 0.3				+ 0.2 / - 0.3						

CIE Pub.117, 1571 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 1.6)

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-03-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:24.00V I:1.115A P:26.76W PF:1.000 Freq:0Hz Lamp Flux:1570.51x1 lm		
NAME: LLS-LE9435FDXSS1000	TYPE:	WEIGHT:
SPEC.:LLS-LE9435FDXSS1000-F30WWHX-DC	DIM.: 1000*94*35mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*94	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	58	47	40	57	47	40	56	46	40	33
0.80	68	57	50	67	56	49	65	56	49	42
1.00	77	66	59	75	65	58	73	66	58	51
1.25	84	74	67	82	73	66	80	71	65	58
1.50	89	79	72	87	78	72	84	76	71	63
2.00	95	87	81	94	86	80	90	84	78	71
2.50	99	92	86	97	90	85	93	88	83	75
3.00	103	96	91	100	94	89	96	91	87	79
4.00	106	101	96	104	99	95	100	96	92	83
5.00	109	104	100	106	102	99	102	98	95	86
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-03-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### ISOCANDELA DIAGRAM

Test:U:24.00V I:1.115A P:26.76W PF:1.000 Freq:0Hz Lamp Flux:1570.5lx1 lm		
NAME: LLS-LE9435FDXSS1000	TYPE:	WEIGHT:
SPEC.:LLS-LE9435FDXSS1000-F30WWHX-DC	DIM.: 1000*94*35mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*94	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-03-03


Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:24.00V I:1.115A P:26.76W PF:1.000 Freq:0Hz Lamp Flux:1570.51x1 lm		
NAME: LLS-LE9435FDXSS1000	TYPE:	WEIGHT:
SPEC.:LLS-LE9435FDXSS1000-F30WWHX-DC	DIM.: 1000*94*35mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*94	Shielding Angle:

Flux out:1110 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-03-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM

Test:U:24.00V I:1.115A P:26.76W PF:1.000 Freq:0Hz Lamp Flux:1570.5lx1 lm		
NAME: LLS-LE9435FDXSS1000	TYPE:	WEIGHT:
SPEC.:LLS-LE9435FDXSS1000-F30WWHX-DC	DIM.: 1000*94*35mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*94	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-03-03

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### LED Avg.L Report

Test:U:24.00V I:1.115A P:26.76W PF:1.000 Freq:0Hz Lamp Flux:1570.51x1 lm		
NAME: LLS-LE9435FDXSS1000	TYPE:	WEIGHT:
SPEC.:LLS-LE9435FDXSS1000-F30WWHX-DC	DIM.: 1000*94*35mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*94	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	4567
L_0~180(75)av	3600
L_0~180(85)av	1732
L_90~270(65)av	4792
L_90~270(75)av	3950
L_90~270(85)av	2347
L_45(65)av	4641
L_45(75)av	3735
L_45(85)av	1971

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-03-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2021-03-03

deg Range: 0 - 180DEG  
deg Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:1.115A P:26.76W PF:1.000 Freq:0Hz Lamp Flux:1570.51x1 lm		
NAME: LLS-LE9435FDXSS1000	TYPE:	WEIGHT:
SPEC.:LLS-LE9435FDXSS1000-F30WWHX-DC	DIM.: 1000*94*35mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*94	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	583	584	582	576	583	584	582	576										
5	579	581	580	573	581	580	579	573										
10	569	572	571	564	572	571	570	564										
15	553	557	556	549	557	555	555	549										
20	531	537	536	529	537	534	534	528										
25	504	512	511	504	511	508	509	502										
30	472	482	481	474	481	478	479	472										
35	438	448	448	440	447	443	446	438										
40	400	411	412	402	409	405	408	401										
45	359	369	373	362	367	365	367	362										
50	316	326	331	320	325	322	325	319										
55	272	282	287	276	280	278	281	276										
60	225	236	241	231	234	231	235	230										
65	176	189	192	184	187	183	188	182										
70	128	141	145	137	139	135	141	135										
75	82.5	94.5	97.8	90.9	92.7	88.8	94.4	89.3										
80	41.7	51.4	54.4	48.8	50.4	47.1	51.8	47.9										
85	11.5	17.8	20.0	16.1	16.9	14.9	18.5	15.8										
90	0.69	1.03	1.31	0.96	0.21	0.29	0.25	0.33										
95	0.77	1.01	1.11	0.95	0.42	0.42	0.48	0.43										
100	1.07	1.16	1.08	1.08	0.78	0.74	0.81	0.83										
105	1.48	1.42	1.30	1.31	1.18	1.05	1.25	1.17										
110	1.92	1.78	1.75	1.60	1.57	1.36	1.76	1.45										
115	2.34	2.16	2.20	1.90	1.95	1.67	2.25	1.88										
120	2.74	2.53	2.66	2.19	2.35	2.02	2.69	2.30										
125	3.09	2.89	3.05	2.51	2.70	2.44	3.02	2.66										
130	3.43	3.23	3.37	2.84	3.05	2.77	3.34	2.97										
135	3.74	3.53	3.73	3.19	3.38	3.18	3.61	3.31										
140	4.03	3.78	3.93	3.57	3.71	3.63	3.81	3.63										
145	4.29	4.01	4.13	3.99	4.00	4.14	4.01	3.96										
150	4.59	4.24	4.26	4.44	4.30	4.65	4.24	4.27										
155	4.94	4.52	4.59	4.87	4.68	5.08	4.61	4.59										
160	5.32	4.83	4.88	5.20	5.07	5.44	4.92	4.78										
165	5.76	5.14	5.21	5.48	5.38	5.73	5.24	5.09										
170	6.00	5.52	5.44	5.63	5.66	5.92	5.54	5.40										
175	6.29	5.89	5.74	5.83	5.93	6.07	5.81	5.72										
180	6.58	6.27	6.00	6.10	6.59	6.30	6.02	6.09										

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-03-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks: