


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.2716A P:6.518W PF:1.000 Freq:0Hz Lamp Flux:737.483x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-40D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 113.15 lm/W			
MODEL	DLS-LS1612LTFSS1000	I _{max} (cd)	584.7	S/MH(C0/180)	0.58
NOMINAL POWER(W)	7	LOR(%)	100.0	S/MH(C90/270)	1.62
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	737.48	h UP,DN(C0-180)	1.9,49.9
NOMINAL FLUX(lm)	737.483	CIE CLASS	DIRECT	h UP,DN(C180-360)	1.7,46.6
LAMPS INSIDE	1	h up(%)	3.5	CIBSE SHR NOM	0.50
TEST VOLTAGE(V)	24	h down(%)	96.5	CIBSE SHR MAX	0.65



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	450.1	464.3	482.5	468.5	441.4	460.0	483.7	461.3	0- 10	45.03	45.03	6.11,6.11
20	228.5	392.7	489.9	331.6	151.7	288.9	492.1	406.5	10- 20	118.0	163.0	22.1,22.1
30	61.15	109.9	510.2	91.59	58.88	75.80	509.1	115.0	20- 30	116.0	279.0	37.8,37.8
40	62.92	53.30	565.6	58.58	76.83	58.22	540.1	50.09	30- 40	114.3	393.3	53.3,53.3
50	61.47	49.54	484.6	52.98	57.83	53.72	394.0	46.40	40- 50	135.2	528.5	71.7,71.7
60	56.69	39.56	189.1	38.28	48.74	36.30	166.2	36.94	50- 60	98.21	626.7	85,85
70	16.33	30.89	58.60	24.53	13.61	26.77	52.36	28.09	60- 70	51.50	678.2	92,92
80	10.56	12.92	14.58	12.76	10.19	11.31	12.97	14.61	70- 80	23.79	702.0	95.2,95.2
90	7.935	8.175	0.9826	7.904	8.128	7.486	0.9465	8.332	80- 90	9.341	711.3	96.5,96.5
100	7.518	6.691	0.5723	6.251	6.699	6.461	0.2813	5.812	90-100	6.000	717.3	97.3,97.3
110	6.386	5.664	1.020	4.647	5.450	4.993	0.8576	4.968	100-110	4.918	722.3	97.9,97.9
120	5.432	3.522	2.755	2.878	4.801	3.221	2.053	3.081	110-120	3.775	726.0	98.4,98.4
130	4.703	2.670	5.633	1.638	3.824	2.626	4.090	2.231	120-130	3.093	729.1	98.9,98.9
140	3.708	2.056	6.853	1.204	2.458	1.242	5.477	1.824	130-140	2.498	731.6	99.2,99.2
150	2.754	1.827	6.439	2.514	1.258	2.323	5.625	1.700	140-150	1.821	733.4	99.5,99.5
160	3.579	4.252	6.765	5.473	3.647	5.279	6.327	3.890	150-160	1.747	735.2	99.7,99.7
170	6.484	6.333	7.347	6.920	5.537	6.785	7.128	6.263	160-170	1.636	736.8	99.9,99.9
180	6.613	7.802	7.915	7.909	6.599	7.795	7.942	7.895	170-180	0.6602	737.5	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-28

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.2716A P:6.518W PF:1.000 Freq:0Hz Lamp Flux:737.483x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-40D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	6259	3526
80	3801	5249
75	2798	7417
70	2984	10709
65	7770	15679
60	7086	23642
55	5875	34817
50	5977	47120
45	5907	51426


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-28

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.2716A P:6.518W PF:1.000 Freq:0Hz Lamp Flux:737.483x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-40D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.04	1.04	1.04	.99	.99	.99	.96
1.0	1.06	1.02	.99	1.03	.90	.97	.98	.95	.93	.94	.92	.90	.90	.88	.86	.84
2.0	.94	.88	.83	.92	.87	.82	.88	.83	.80	.84	.81	.77	.81	.78	.75	.73
3.0	.84	.77	.71	.82	.76	.71	.79	.74	.69	.76	.71	.67	.73	.69	.66	.64
4.0	.76	.68	.62	.74	.67	.62	.72	.65	.61	.69	.64	.59	.66	.62	.58	.56
5.0	.69	.61	.55	.68	.60	.55	.65	.59	.54	.63	.57	.53	.61	.56	.52	.50
6.0	.63	.55	.49	.62	.54	.49	.60	.53	.48	.58	.52	.47	.56	.51	.47	.45
7.0	.58	.50	.44	.57	.49	.44	.55	.48	.43	.53	.47	.43	.52	.46	.42	.41
8.0	.53	.46	.40	.52	.45	.40	.51	.44	.40	.49	.43	.39	.48	.43	.39	.37
9.0	.49	.42	.37	.49	.42	.37	.47	.41	.36	.46	.40	.36	.45	.40	.36	.34
10.0	.46	.39	.34	.45	.38	.34	.44	.38	.33	.43	.37	.33	.42	.37	.33	.31



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.2716A P:6.518W PF:1.000 Freq:0Hz Lamp Flux:737.483x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-40D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.262	.149	.047	.254	.145	.046	.239	.137	.044	.225	.130	.042	.212	.123	.040	
2.0	.249	.136	.042	.242	.133	.041	.229	.127	.039	.216	.121	.038	.205	.116	.037	
3.0	.233	.124	.037	.227	.122	.037	.215	.117	.035	.205	.112	.034	.195	.108	.033	
4.0	.218	.113	.033	.212	.111	.033	.202	.107	.032	.192	.103	.031	.183	.100	.030	
5.0	.203	.104	.030	.198	.102	.030	.189	.099	.029	.181	.095	.028	.173	.092	.028	
6.0	.190	.095	.027	.186	.094	.027	.178	.091	.026	.170	.088	.026	.163	.086	.025	
7.0	.178	.088	.025	.175	.087	.025	.167	.084	.024	.160	.082	.024	.154	.080	.023	
8.0	.168	.082	.023	.164	.081	.023	.157	.079	.022	.151	.077	.022	.145	.075	.022	
9.0	.158	.076	.021	.155	.075	.021	.149	.074	.021	.143	.072	.021	.138	.070	.020	
10.0	.149	.072	.020	.146	.071	.020	.141	.069	.019	.136	.067	.019	.131	.066	.019	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.217	.217	.217	.186	.186	.186	.127	.127	.127	.073	.073	.073	.023	.023	.023	
1.0	.204	.184	.165	.175	.158	.142	.120	.109	.098	.069	.063	.057	.022	.020	.019	
2.0	.194	.160	.131	.166	.137	.113	.114	.095	.079	.066	.055	.046	.021	.018	.015	
3.0	.185	.142	.107	.159	.122	.093	.109	.085	.065	.063	.050	.038	.020	.016	.013	
4.0	.177	.128	.091	.152	.111	.079	.104	.077	.055	.060	.045	.033	.019	.015	.011	
5.0	.169	.117	.079	.145	.101	.069	.100	.071	.049	.058	.042	.029	.019	.014	.009	
6.0	.162	.109	.070	.139	.094	.061	.096	.066	.043	.056	.039	.026	.018	.013	.009	
7.0	.156	.102	.064	.134	.088	.056	.093	.062	.039	.054	.036	.023	.017	.012	.008	
8.0	.150	.096	.059	.129	.083	.051	.089	.058	.036	.052	.034	.022	.017	.011	.007	
9.0	.144	.091	.055	.124	.079	.048	.086	.055	.034	.050	.033	.020	.016	.011	.007	
10.0	.139	.087	.052	.119	.075	.045	.083	.053	.032	.048	.031	.019	.016	.010	.006	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.2716A P:6.518W PF:1.000 Freq:0Hz Lamp Flux:737.483x1 lm											
NAME: DLS-LS1612LTFSS1000						TYPE:		WEIGHT:			
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-40D						DIM.: 1000*16*12mm		SERIAL No.:			
MFR.: COLORS						SUR.:1000*16		Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	17.4	18.7	17.7	18.9	19.2	26.2	27.5	26.5	27.8	28.0	
	3H	18.5	19.7	18.8	20.0	20.3	26.6	27.8	26.9	28.1	28.4
	4H	18.8	19.9	19.1	20.2	20.5	26.7	27.8	27.0	28.1	28.4
	6H	19.0	20.1	19.4	20.4	20.8	26.7	27.7	27.0	28.0	28.4
	8H	19.2	20.3	19.6	20.6	21.0	26.6	27.7	27.0	28.0	28.4
	12H	19.5	20.5	19.9	20.8	21.2	26.6	27.6	27.0	27.9	28.3
4H	2H	18.4	19.5	18.7	19.8	20.1	26.0	27.1	26.3	27.4	27.7
	3H	19.5	20.5	19.9	20.9	21.2	26.5	27.5	26.9	27.8	28.2
	4H	20.0	20.9	20.5	21.3	21.7	26.6	27.5	27.1	27.9	28.3
	6H	20.4	21.2	20.8	21.6	22.0	26.7	27.5	27.1	27.9	28.3
	8H	20.6	21.4	21.1	21.8	22.3	26.7	27.4	27.2	27.8	28.3
	12H	21.0	21.6	21.4	22.1	22.5	26.7	27.3	27.2	27.8	28.3
8H	4H	20.5	21.3	21.0	21.7	22.2	26.6	27.3	27.0	27.7	28.2
	6H	21.0	21.6	21.5	22.1	22.6	26.7	27.3	27.2	27.8	28.3
	8H	21.4	21.9	21.9	22.4	22.9	26.7	27.2	27.2	27.7	28.3
	12H	21.8	22.3	22.4	22.8	23.3	26.7	27.2	27.3	27.7	28.2
12H	4H	20.6	21.2	21.0	21.7	22.1	26.5	27.2	27.0	27.7	28.1
	6H	21.1	21.6	21.6	22.1	22.7	26.7	27.2	27.2	27.7	28.2
	8H	21.5	22.0	22.1	22.5	23.0	26.7	27.2	27.2	27.7	28.2
Variations with the observer position at spacings:											
S = 1.0H	+ 0.5 / - 0.5					+ 0.8 / - 0.7					
1.5H	+ 0.4 / - 0.3					+ 2.7 / - 3.7					
2.0H	+ 0.5 / - 0.8					+ 4.0 / - 5.1					

CIE Pub.117, 737.5 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -1.1)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.2716A P:6.518W PF:1.000 Freq:0Hz Lamp Flux:737.483x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-40D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	62	52	45	61	51	45	60	51	45	39
0.80	72	62	55	71	61	55	69	60	54	48
1.00	80	71	64	79	70	64	77	71	63	57
1.25	87	78	72	86	77	71	83	76	70	63
1.50	92	83	77	90	82	76	87	80	75	68
2.00	98	90	85	96	89	84	92	86	82	74
2.50	101	94	89	99	93	88	95	90	86	77
3.00	104	98	93	102	96	92	97	93	89	81
4.00	107	102	98	105	100	97	100	96	93	84
5.00	109	105	101	107	103	100	102	99	96	86
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-28

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.2716A P:6.518W PF:1.000 Freq:0Hz Lamp Flux:737.483x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-40D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-28

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

AAI Figure

Test:U:24.00V I:0.2716A P:6.518W PF:1.000 Freq:0Hz Lamp Flux:737.483x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-40D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

Flux out:368.2 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-03-28

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.2716A P:6.518W PF:1.000 Freq:0Hz Lamp Flux:737.483x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-40D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2021-03-28

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-03-28

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.2716A P:6.518W PF:1.000 Freq:0Hz Lamp Flux:737.483x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-40D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	477	479	481	479	477	479	481	479										
5	467	473	482	481	472	476	482	471										
10	450	464	482	469	441	460	484	461										
15	406	450	485	434	329	414	487	448										
20	228	393	490	332	152	289	492	407										
25	94.1	242	498	178	75.7	139	498	256										
30	61.1	110	510	91.6	58.9	75.8	509	115										
35	59.0	66.2	532	60.3	69.9	53.4	527	65.9										
40	62.9	53.3	566	58.6	76.8	58.2	540	50.1										
45	66.8	50.5	582	56.1	74.7	56.3	504	46.9										
50	61.5	49.5	485	53.0	57.8	53.7	394	46.4										
55	53.9	44.1	320	47.2	45.9	46.4	269	41.7										
60	56.7	39.6	189	38.3	48.7	36.3	166	36.9										
65	52.5	34.1	106	29.3	32.5	28.6	95.4	32.3										
70	16.3	30.9	58.6	24.5	13.6	26.8	52.4	28.1										
75	11.6	31.3	30.7	26.8	11.2	22.0	27.4	29.4										
80	10.6	12.9	14.6	12.8	10.2	11.3	13.0	14.6										
85	8.73	9.91	4.92	9.77	8.41	9.05	4.54	10.4										
90	7.94	8.17	0.98	7.90	8.13	7.49	0.95	8.33										
95	7.15	7.22	0.74	6.90	7.35	6.73	0.55	7.13										
100	7.52	6.69	0.57	6.25	6.70	6.46	0.28	5.81										
105	7.43	6.27	0.62	5.51	5.96	5.81	0.52	5.08										
110	6.39	5.66	1.02	4.65	5.45	4.99	0.86	4.97										
115	5.93	4.57	1.71	3.46	5.21	3.92	1.35	4.02										
120	5.43	3.52	2.76	2.88	4.80	3.22	2.05	3.08										
125	5.11	3.06	4.10	2.52	4.29	2.88	2.99	2.59										
130	4.70	2.67	5.63	1.64	3.82	2.63	4.09	2.23										
135	4.30	2.31	6.69	1.02	3.26	1.22	5.05	1.97										
140	3.71	2.06	6.85	1.20	2.46	1.24	5.48	1.82										
145	3.18	1.80	6.63	1.63	1.00	1.54	5.50	1.35										
150	2.75	1.83	6.44	2.51	1.26	2.32	5.63	1.70										
155	1.99	2.90	6.49	3.98	2.06	3.74	5.97	2.67										
160	3.58	4.25	6.77	5.47	3.65	5.28	6.33	3.89										
165	5.52	5.35	7.02	6.37	5.07	6.21	6.70	5.15										
170	6.48	6.33	7.35	6.92	5.54	6.79	7.13	6.26										
175	6.46	7.14	7.65	7.41	5.83	7.28	7.57	7.19										
180	6.61	7.80	7.92	7.91	6.60	7.79	7.94	7.90										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: