


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.2724A P:6.537W PF:1.000 Freq:0Hz Lamp Flux:746.022x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-60D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 114.12 lm/W			
MODEL	DLS-LS1612LTFSS1000	I _{max} (cd)	418.6	S/MH(C0/180)	0.83
NOMINAL POWER(W)	7	LOR(%)	100.0	S/MH(C90/270)	1.50
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	746.02	h UP,DN(C0-180)	1.5,49.9
NOMINAL FLUX(lm)	746.022	CIE CLASS	DIRECT	h UP,DN(C180-360)	1.4,47.2
LAMPS INSIDE	1	h up(%)	2.9	CIBSE SHR NOM	0.75
TEST VOLTAGE(V)	24	h down(%)	97.1	CIBSE SHR MAX	0.95



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	389.4	392.9	402.0	394.1	383.5	392.8	398.3	392.2	0- 10	37.90	37.90	5.08,5.08
20	354.0	372.0	398.2	368.8	335.3	362.4	394.6	369.9	10- 20	108.1	146.0	19.6,19.6
30	174.0	319.3	393.9	276.8	108.7	242.4	391.5	320.6	20- 30	154.1	300.1	40.2,40.2
40	43.91	80.06	397.0	66.62	46.46	54.07	391.1	85.46	30- 40	124.3	424.3	56.9,56.9
50	40.18	36.56	417.7	39.04	48.29	37.24	394.4	33.88	40- 50	104.8	529.1	70.9,70.9
60	35.03	28.27	271.4	30.29	36.59	29.59	229.8	26.44	50- 60	101.5	630.6	84.5,84.5
70	39.73	22.57	80.01	21.49	37.73	21.30	71.72	20.94	60- 70	58.18	688.8	92.3,92.3
80	8.820	23.44	18.39	18.70	7.994	14.74	16.00	20.51	70- 80	26.40	715.2	95.9,95.9
90	6.352	6.234	1.042	6.092	5.963	5.726	0.5593	6.467	80- 90	9.186	724.4	97.1,97.1
100	6.668	4.900	0.6547	4.355	5.614	4.472	0.3345	3.821	90-100	4.528	728.9	97.7,97.7
110	4.651	4.062	1.355	3.218	3.705	3.378	1.078	3.525	100-110	3.711	732.6	98.2,98.2
120	3.342	2.290	3.659	1.983	2.992	2.152	2.661	2.025	110-120	2.768	735.4	98.6,98.6
130	2.819	1.817	5.469	1.365	2.438	1.844	4.336	1.637	120-130	2.430	737.8	98.9,98.9
140	2.418	2.052	5.444	1.952	1.936	1.678	4.470	1.882	130-140	2.023	739.9	99.2,99.2
150	3.479	3.562	5.286	4.276	2.786	4.057	4.624	3.163	140-150	1.980	741.8	99.4,99.4
160	5.087	4.644	5.690	5.378	4.523	5.334	5.358	4.255	150-160	2.076	743.9	99.7,99.7
170	5.918	5.651	6.278	6.059	5.070	5.985	6.125	5.623	160-170	1.534	745.4	99.9,99.9
180	5.764	6.720	6.840	6.833	5.771	6.706	6.840	6.820	170-180	0.5787	746.0	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-28

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.2724A P:6.537W PF:1.000 Freq:0Hz Lamp Flux:746.022x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-60D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	5054	4198
80	3175	6618
75	4715	9713
70	7260	14620
65	5140	22686
60	4378	33929
55	4060	42239
50	3907	40611
45	3669	35738


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.2724A P:6.537W PF:1.000 Freq:0Hz Lamp Flux:746.022x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-60D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.10	1.10	1.10	1.04	1.04	1.04	.99	.99	.99	.97
1.0	1.06	1.02	.99	1.03	.90	.97	.98	.96	.93	.94	.92	.90	.90	.88	.87	.85
2.0	.94	.88	.83	.92	.87	.82	.88	.84	.80	.84	.81	.77	.81	.78	.75	.73
3.0	.84	.77	.71	.82	.76	.71	.79	.74	.69	.76	.71	.67	.73	.69	.66	.64
4.0	.76	.68	.62	.74	.67	.62	.72	.65	.60	.69	.64	.59	.67	.62	.58	.56
5.0	.69	.61	.55	.68	.60	.54	.65	.59	.54	.63	.57	.53	.61	.56	.52	.50
6.0	.63	.55	.49	.62	.54	.49	.60	.53	.48	.58	.52	.47	.56	.51	.47	.45
7.0	.58	.50	.44	.57	.49	.44	.55	.48	.43	.53	.47	.43	.52	.47	.42	.41
8.0	.53	.45	.40	.52	.45	.40	.51	.44	.40	.49	.43	.39	.48	.43	.39	.37
9.0	.49	.42	.37	.49	.41	.37	.47	.41	.36	.46	.40	.36	.45	.40	.36	.34
10.0	.46	.39	.34	.45	.38	.34	.44	.38	.33	.43	.37	.33	.42	.37	.33	.31



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-28

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:24.00V I:0.2724A P:6.537W PF:1.000 Freq:0Hz Lamp Flux:746.022x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-60D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.264	.150	.047	.256	.146	.046	.241	.138	.044	.228	.131	.042	.215	.125	.040	
2.0	.250	.137	.042	.244	.134	.041	.231	.128	.040	.219	.123	.038	.208	.118	.037	
3.0	.234	.125	.037	.228	.122	.037	.217	.118	.036	.207	.113	.035	.197	.109	.034	
4.0	.219	.114	.033	.213	.112	.033	.203	.108	.032	.194	.104	.031	.185	.101	.031	
5.0	.204	.104	.030	.199	.102	.030	.190	.099	.029	.182	.096	.029	.174	.093	.028	
6.0	.191	.096	.027	.187	.094	.027	.179	.092	.027	.171	.089	.026	.164	.086	.026	
7.0	.179	.089	.025	.175	.087	.025	.168	.085	.024	.161	.083	.024	.155	.080	.024	
8.0	.168	.082	.023	.165	.081	.023	.158	.079	.023	.152	.077	.022	.146	.075	.022	
9.0	.159	.077	.021	.156	.076	.021	.150	.074	.021	.144	.072	.021	.139	.071	.020	
10.0	.150	.072	.020	.147	.071	.020	.142	.069	.020	.137	.068	.019	.132	.066	.019	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.213	.213	.213	.182	.182	.182	.124	.124	.124	.071	.071	.071	.023	.023	.023	
1.0	.199	.179	.160	.171	.153	.138	.117	.106	.095	.067	.061	.055	.022	.020	.018	
2.0	.189	.155	.125	.162	.133	.108	.111	.092	.076	.064	.054	.044	.021	.017	.014	
3.0	.180	.137	.102	.154	.118	.088	.106	.082	.062	.061	.048	.037	.020	.016	.012	
4.0	.172	.123	.085	.148	.106	.074	.101	.074	.052	.059	.043	.031	.019	.014	.010	
5.0	.164	.112	.074	.141	.097	.064	.097	.068	.045	.056	.040	.027	.018	.013	.009	
6.0	.157	.104	.065	.135	.090	.057	.093	.063	.040	.054	.037	.024	.017	.012	.008	
7.0	.151	.097	.059	.130	.084	.051	.090	.059	.036	.052	.035	.022	.017	.011	.007	
8.0	.145	.091	.054	.125	.079	.047	.086	.055	.033	.050	.033	.020	.016	.011	.007	
9.0	.139	.086	.050	.120	.074	.044	.083	.052	.031	.048	.031	.018	.016	.010	.006	
10.0	.134	.082	.047	.115	.071	.041	.080	.050	.029	.047	.029	.017	.015	.010	.006	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.2724A P:6.537W PF:1.000 Freq:0Hz Lamp Flux:746.022x1 lm											
NAME: DLS-LS1612LTFSS1000						TYPE:		WEIGHT:			
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-60D						DIM.: 1000*16*12mm		SERIAL No.:			
MFR.: COLORS						SUR.:1000*16		Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	15.0	16.3	15.3	16.5	16.8	26.6	27.9	26.9	28.2	28.4	
	3H	17.8	19.0	18.2	19.3	19.6	27.3	28.5	27.6	28.7	29.0
	4H	19.0	20.2	19.4	20.4	20.8	27.4	28.5	27.7	28.8	29.1
	6H	19.3	20.3	19.6	20.7	21.0	27.4	28.5	27.8	28.8	29.1
	8H	19.4	20.4	19.8	20.7	21.1	27.4	28.4	27.8	28.8	29.1
	12H	19.5	20.5	19.9	20.9	21.2	27.4	28.4	27.8	28.7	29.1
4H	2H	16.8	17.9	17.1	18.2	18.5	26.4	27.5	26.7	27.8	28.1
	3H	19.2	20.2	19.6	20.5	20.9	27.1	28.1	27.5	28.4	28.8
	4H	20.2	21.1	20.6	21.5	21.9	27.3	28.2	27.7	28.6	29.0
	6H	20.6	21.4	21.1	21.8	22.3	27.4	28.2	27.9	28.6	29.0
	8H	20.8	21.6	21.3	22.0	22.4	27.4	28.2	27.9	28.6	29.0
	12H	21.0	21.7	21.5	22.1	22.6	27.4	28.1	27.9	28.5	29.0
8H	4H	20.6	21.4	21.1	21.8	22.2	27.2	28.0	27.7	28.4	28.8
	6H	21.4	22.0	21.9	22.5	22.9	27.4	28.0	27.9	28.5	29.0
	8H	21.7	22.2	22.2	22.7	23.2	27.5	28.0	28.0	28.5	29.0
	12H	22.0	22.4	22.5	22.9	23.4	27.5	28.0	28.0	28.5	29.0
12H	4H	20.7	21.4	21.2	21.9	22.3	27.2	27.9	27.7	28.3	28.8
	6H	21.6	22.1	22.1	22.6	23.1	27.4	28.0	27.9	28.4	29.0
	8H	21.9	22.4	22.4	22.9	23.4	27.5	28.0	28.0	28.5	29.0
Variations with the observer position at spacings:											
S = 1.0H	+ 0.4 / - 0.5					+ 0.7 / - 0.7					
1.5H	+ 0.2 / - 0.5					+ 2.6 / - 2.2					
2.0H	+ 0.9 / - 0.8					+ 3.2 / - 4.8					

CIE Pub.117, 746.0 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -1.0)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.2724A P:6.537W PF:1.000 Freq:0Hz Lamp Flux:746.022x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-60D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	64	54	48	64	54	48	63	53	48	42
0.80	74	64	58	73	64	57	71	63	57	51
1.00	82	72	66	81	72	66	78	72	65	59
1.25	88	79	73	87	78	73	84	77	72	65
1.50	93	84	78	91	83	78	88	81	76	69
2.00	98	91	86	96	90	85	93	87	83	75
2.50	102	95	90	99	93	89	95	91	87	78
3.00	104	99	94	102	97	93	98	94	90	82
4.00	108	103	99	105	101	97	101	97	94	85
5.00	110	106	102	107	104	100	102	99	97	87
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.2724A P:6.537W PF:1.000 Freq:0Hz Lamp Flux:746.022x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-60D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.2724A P:6.537W PF:1.000 Freq:0Hz Lamp Flux:746.022x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-60D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

Flux out:486.0 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.2724A P:6.537W PF:1.000 Freq:0Hz Lamp Flux:746.022x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-60D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-03-28

deg Range: 0 - 180DEG
deg Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.2724A P:6.537W PF:1.000 Freq:0Hz Lamp Flux:746.022x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-60D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	402	401	399	401	402	401	399	401										
5	397	397	403	401	397	401	399	397										
10	389	393	402	394	383	393	398	392										
15	374	385	400	383	365	379	396	383										
20	354	372	398	369	335	362	395	370										
25	314	354	396	345	249	332	393	353										
30	174	319	394	277	109	242	392	321										
35	70.0	187	394	146	53.8	111	390	203										
40	43.9	80.1	397	66.6	46.5	54.1	391	85.5										
45	41.5	46.7	404	45.2	52.7	40.2	396	46.2										
50	40.2	36.6	418	39.0	48.3	37.2	394	33.9										
55	37.3	31.8	388	34.8	42.1	34.4	334	29.5										
60	35.0	28.3	271	30.3	36.6	29.6	230	26.4										
65	34.8	25.2	153	25.9	30.7	26.1	135	23.6										
70	39.7	22.6	80.0	21.5	37.7	21.3	71.7	20.9										
75	19.5	21.4	40.2	17.6	10.9	18.7	35.6	19.4										
80	8.82	23.4	18.4	18.7	7.99	14.7	16.0	20.5										
85	7.05	8.62	5.85	8.31	6.29	7.44	5.03	9.41										
90	6.35	6.23	1.04	6.09	5.96	5.73	0.56	6.47										
95	5.64	5.32	0.75	4.97	5.39	4.87	0.44	5.17										
100	6.67	4.90	0.65	4.35	5.61	4.47	0.33	3.82										
105	6.16	4.48	0.79	3.81	4.58	3.98	0.62	3.54										
110	4.65	4.06	1.35	3.22	3.70	3.38	1.08	3.53										
115	3.75	3.15	2.36	2.38	3.25	2.58	1.74	2.74										
120	3.34	2.29	3.66	1.98	2.99	2.15	2.66	2.03										
125	3.11	1.98	4.87	1.80	2.67	1.94	3.66	1.74										
130	2.82	1.82	5.47	1.36	2.44	1.84	4.34	1.64										
135	2.61	1.83	5.54	1.24	2.18	1.05	4.48	1.61										
140	2.42	2.05	5.44	1.95	1.94	1.68	4.47	1.88										
145	2.51	2.68	5.32	3.18	1.54	2.87	4.47	2.33										
150	3.48	3.56	5.29	4.28	2.79	4.06	4.62	3.16										
155	4.23	4.25	5.42	4.97	3.82	4.91	4.99	3.72										
160	5.09	4.64	5.69	5.38	4.52	5.33	5.36	4.25										
165	5.60	5.06	5.97	5.71	5.04	5.64	5.72	4.91										
170	5.92	5.65	6.28	6.06	5.07	5.98	6.13	5.62										
175	5.73	6.23	6.62	6.44	5.21	6.39	6.51	6.29										
180	5.76	6.72	6.84	6.83	5.77	6.71	6.84	6.82										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: