


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.2731A P:6.554W PF:1.000 Freq:0Hz Lamp Flux:726.865x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-80D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 110.91 lm/W			
MODEL	DLS-LS1612LTFSS1000	I _{max} (cd)	356.6	S/MH(C0/180)	1.11
NOMINAL POWER(W)	7	LOR(%)	100.0	S/MH(C90/270)	1.40
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	726.86	h UP,DN(C0-180)	1.2,51.1
NOMINAL FLUX(lm)	726.865	CIE CLASS	DIRECT	h UP,DN(C180-360)	1.1,46.6
LAMPS INSIDE	1	h up(%)	2.3	CIBSE SHR NOM	1.00
TEST VOLTAGE(V)	24	h down(%)	97.7	CIBSE SHR MAX	1.15



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	350.0	353.2	355.0	348.7	341.3	345.6	352.7	350.9	0- 10	33.69	33.69	4.64,4.64
20	331.8	340.3	346.9	327.9	310.7	321.0	343.1	336.7	10- 20	96.64	130.3	17.9,17.9
30	285.9	313.1	335.6	294.3	245.5	282.6	329.9	307.2	20- 30	146.8	277.1	38.1,38.1
40	134.1	246.8	321.1	158.5	60.29	127.4	310.7	244.7	30- 40	160.8	437.8	60.2,60.2
50	31.57	59.52	302.7	37.64	28.24	30.99	283.5	57.16	40- 50	109.1	546.9	75.2,75.2
60	19.73	22.86	254.2	21.81	25.00	19.78	197.4	20.27	50- 60	79.32	626.2	86.2,86.2
70	16.12	15.38	104.6	14.75	18.62	13.79	74.55	13.74	60- 70	51.80	678.0	93.3,93.3
80	19.90	10.57	24.17	10.72	6.952	11.10	17.80	10.05	70- 80	23.93	702.0	96.6,96.6
90	4.095	4.809	1.401	4.287	3.375	3.687	0.3466	4.931	80- 90	8.419	710.4	97.7,97.7
100	3.317	3.025	0.7086	2.589	2.629	2.454	0.4090	2.327	90-100	2.853	713.2	98.1,98.1
110	2.293	2.404	1.515	1.794	1.554	1.779	1.361	1.999	100-110	2.111	715.4	98.4,98.4
120	1.657	1.282	3.297	1.276	1.262	1.256	2.868	1.209	110-120	1.739	717.1	98.7,98.7
130	1.490	1.384	4.253	1.623	1.383	1.669	3.588	1.241	120-130	1.706	718.8	98.9,98.9
140	2.102	2.656	4.488	3.309	2.625	3.063	3.767	2.551	130-140	1.906	720.7	99.2,99.2
150	4.134	3.727	4.489	4.357	3.668	4.259	4.048	3.300	140-150	2.237	722.9	99.5,99.5
160	4.782	4.236	5.049	4.990	4.456	5.022	4.783	3.940	150-160	1.995	724.9	99.7,99.7
170	5.337	5.084	5.630	5.524	4.742	5.530	5.525	5.069	160-170	1.403	726.3	99.9,99.9
180	5.217	6.072	6.172	6.165	5.217	6.092	6.172	6.165	170-180	0.5241	726.9	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-28

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.2731A P:6.554W PF:1.000 Freq:0Hz Lamp Flux:726.865x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-80D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	3857	5597
80	7164	8700
75	3702	12784
70	2945	19119
65	2522	26950
60	2466	31778
55	2430	31496
50	3070	29431
45	5113	27644


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-28

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.2731A P:6.554W PF:1.000 Freq:0Hz Lamp Flux:726.865x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-80D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.15	1.15	1.15	1.10	1.10	1.10	1.05	1.05	1.05	.00	.00	.00	.98
1.0	1.06	1.02	.99	1.04	1.00	.97	.99	.96	.94	.95	.93	.91	.91	.89	.88	.85
2.0	.95	.89	.84	.93	.87	.83	.89	.84	.81	.85	.82	.78	.82	.79	.76	.74
3.0	.85	.78	.72	.83	.77	.71	.80	.74	.70	.77	.72	.68	.74	.70	.67	.65
4.0	.77	.69	.63	.75	.68	.62	.72	.66	.61	.70	.65	.60	.68	.63	.59	.57
5.0	.69	.61	.56	.68	.61	.55	.66	.59	.54	.64	.58	.54	.62	.57	.53	.51
6.0	.63	.55	.50	.62	.55	.49	.60	.54	.49	.59	.53	.48	.57	.52	.48	.46
7.0	.58	.50	.45	.57	.50	.44	.55	.49	.44	.54	.48	.43	.52	.47	.43	.41
8.0	.53	.46	.40	.53	.45	.40	.51	.45	.40	.50	.44	.39	.49	.43	.39	.37
9.0	.49	.42	.37	.49	.42	.37	.47	.41	.36	.46	.40	.36	.45	.40	.36	.34
10.0	.46	.39	.34	.45	.38	.34	.44	.38	.33	.43	.37	.33	.42	.37	.33	.31



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-28

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:24.00V I:0.2731A P:6.554W PF:1.000 Freq:0Hz Lamp Flux:726.865x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-80D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.259	.147	.047	.251	.143	.046	.237	.136	.043	.224	.129	.041	.212	.123	.040	
2.0	.246	.135	.041	.240	.132	.041	.227	.126	.039	.216	.121	.038	.205	.116	.037	
3.0	.231	.123	.037	.225	.121	.036	.214	.116	.035	.204	.112	.034	.195	.108	.033	
4.0	.216	.112	.033	.211	.111	.033	.201	.107	.032	.192	.103	.031	.184	.100	.030	
5.0	.202	.103	.030	.198	.102	.030	.189	.099	.029	.181	.096	.028	.174	.093	.028	
6.0	.190	.095	.027	.186	.094	.027	.178	.091	.027	.171	.089	.026	.164	.086	.026	
7.0	.178	.088	.025	.175	.087	.025	.168	.085	.024	.161	.083	.024	.155	.081	.024	
8.0	.168	.082	.023	.165	.081	.023	.159	.079	.023	.153	.077	.022	.147	.076	.022	
9.0	.159	.077	.021	.156	.076	.021	.150	.074	.021	.145	.073	.021	.140	.071	.021	
10.0	.150	.072	.020	.148	.071	.020	.142	.070	.020	.138	.068	.019	.133	.067	.019	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.208	.208	.208	.178	.178	.178	.121	.121	.121	.070	.070	.070	.022	.022	.022	
1.0	.194	.174	.156	.166	.149	.134	.114	.103	.093	.065	.059	.054	.021	.019	.017	
2.0	.184	.150	.121	.157	.129	.105	.108	.089	.073	.062	.052	.043	.020	.017	.014	
3.0	.175	.132	.097	.150	.114	.084	.103	.079	.059	.059	.046	.035	.019	.015	.011	
4.0	.166	.118	.081	.143	.102	.070	.098	.071	.049	.057	.042	.029	.018	.014	.010	
5.0	.159	.107	.069	.137	.093	.060	.094	.065	.042	.054	.038	.025	.018	.012	.008	
6.0	.152	.099	.060	.131	.085	.053	.090	.060	.037	.052	.035	.022	.017	.012	.007	
7.0	.146	.092	.054	.125	.079	.047	.087	.056	.033	.050	.033	.020	.016	.011	.007	
8.0	.140	.086	.049	.120	.074	.043	.083	.052	.030	.048	.031	.018	.016	.010	.006	
9.0	.134	.081	.045	.115	.070	.039	.080	.049	.028	.047	.029	.017	.015	.010	.005	
10.0	.129	.077	.042	.111	.067	.036	.077	.047	.026	.045	.028	.015	.015	.009	.005	

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-28

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.2731A P:6.554W PF:1.000 Freq:0Hz Lamp Flux:726.865x1 lm											
NAME: DLS-LS1612LTFSS1000						TYPE:		WEIGHT:			
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-80D						DIM.: 1000*16*12mm		SERIAL No.:			
MFR.: COLORS						SUR.:1000*16		Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	17.2	18.5	17.5	18.7	19.0	25.9	27.2	26.2	27.5	27.7	
	3H	17.5	18.7	17.8	19.0	19.3	27.2	28.4	27.6	28.7	29.0
	4H	17.9	19.0	18.2	19.3	19.6	27.5	28.6	27.8	28.9	29.2
	6H	18.9	20.0	19.3	20.3	20.6	27.6	28.7	28.0	29.0	29.3
	8H	19.2	20.2	19.5	20.5	20.8	27.6	28.6	28.0	28.9	29.3
	12H	19.3	20.3	19.7	20.6	20.9	27.6	28.6	28.0	28.9	29.2
4H	2H	18.0	19.1	18.3	19.4	19.7	25.7	26.8	26.0	27.1	27.4
	3H	18.4	19.3	18.7	19.7	20.0	27.1	28.1	27.5	28.4	28.8
	4H	18.8	19.7	19.2	20.1	20.4	27.4	28.3	27.8	28.7	29.1
	6H	20.0	20.8	20.4	21.2	21.6	27.6	28.4	28.1	28.8	29.2
	8H	20.3	21.1	20.8	21.5	21.9	27.7	28.4	28.1	28.8	29.2
	12H	20.5	21.2	21.0	21.6	22.0	27.7	28.4	28.1	28.8	29.2
8H	4H	19.2	20.0	19.7	20.4	20.8	27.3	28.1	27.8	28.5	28.9
	6H	20.6	21.2	21.0	21.6	22.1	27.6	28.2	28.0	28.6	29.1
	8H	21.0	21.5	21.5	22.0	22.5	27.7	28.2	28.1	28.6	29.1
	12H	21.3	21.7	21.8	22.2	22.8	27.7	28.2	28.2	28.7	29.2
12H	4H	19.3	20.0	19.8	20.4	20.8	27.3	28.0	27.7	28.4	28.8
	6H	20.7	21.2	21.2	21.7	22.2	27.5	28.1	28.0	28.5	29.0
	8H	21.1	21.6	21.7	22.1	22.6	27.6	28.1	28.2	28.6	29.1
Variations with the observer position at spacings:											
S = 1.0H	+ 1.1 / - 1.3					+ 0.4 / - 0.4					
1.5H	+ 1.7 / - 1.2					+ 1.3 / - 1.4					
2.0H	+ 1.1 / - 0.6					+ 2.5 / - 3.5					

CIE Pub.117, 726.9 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -1.1)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.2731A P:6.554W PF:1.000 Freq:0Hz Lamp Flux:726.865x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-80D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	67	57	51	66	57	51	65	56	51	45
0.80	76	67	60	75	66	60	73	65	60	54
1.00	84	74	68	82	74	68	80	74	67	61
1.25	90	81	75	88	80	75	86	79	74	67
1.50	94	86	80	92	85	80	89	83	78	72
2.00	99	92	87	98	91	86	94	89	85	77
2.50	103	96	91	100	95	90	97	92	88	80
3.00	105	100	95	103	98	94	99	95	91	83
4.00	108	104	100	106	102	98	102	98	95	87
5.00	110	106	103	108	104	101	103	100	98	89
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.2731A P:6.554W PF:1.000 Freq:0Hz Lamp Flux:726.865x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-80D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-28

deg Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

AAI Figure

Test:U:24.00V I:0.2731A P:6.554W PF:1.000 Freq:0Hz Lamp Flux:726.865x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-80D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

Flux out:546.9 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.2731A P:6.554W PF:1.000 Freq:0Hz Lamp Flux:726.865x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-80D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-03-28

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.2731A P:6.554W PF:1.000 Freq:0Hz Lamp Flux:726.865x1 lm		
NAME: DLS-LS1612LTFSS1000	TYPE:	WEIGHT:
SPEC.:DLS-LS1612LTFSS1000-F7NW9X-DC-80D	DIM.: 1000*16*12mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*16	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	356	356	356	356	356	356	356	356										
5	355	356	356	354	352	353	355	355										
10	350	353	355	349	341	346	353	351										
15	343	348	352	340	327	335	349	345										
20	332	340	347	328	311	321	343	337										
25	313	330	341	313	290	304	337	325										
30	286	313	336	294	246	283	330	307										
35	247	288	329	257	137	235	322	284										
40	134	247	321	159	60.3	127	311	245										
45	57.8	130	313	71.3	32.9	56.9	298	130										
50	31.6	59.5	303	37.6	28.2	31.0	284	57.2										
55	22.3	32.9	289	26.7	31.2	23.3	257	30.4										
60	19.7	22.9	254	21.8	25.0	19.8	197	20.3										
65	17.1	18.0	182	17.1	21.1	16.1	127	16.0										
70	16.1	15.4	105	14.8	18.6	13.8	74.5	13.7										
75	15.3	12.6	52.9	12.1	25.6	11.5	39.2	11.7										
80	19.9	10.6	24.2	10.7	6.95	11.1	17.8	10.1										
85	5.38	11.5	7.81	9.35	3.97	6.98	5.25	10.3										
90	4.09	4.81	1.40	4.29	3.38	3.69	0.35	4.93										
95	3.23	3.59	0.98	3.12	2.73	2.82	0.33	3.48										
100	3.32	3.03	0.71	2.59	2.63	2.45	0.41	2.33										
105	3.13	2.75	0.87	2.17	2.01	2.10	0.78	2.02										
110	2.29	2.40	1.52	1.79	1.55	1.78	1.36	2.00										
115	1.85	1.77	2.43	1.34	1.37	1.39	2.10	1.56										
120	1.66	1.28	3.30	1.28	1.26	1.26	2.87	1.21										
125	1.58	1.28	3.95	1.40	1.28	1.26	3.35	1.13										
130	1.49	1.38	4.25	1.62	1.38	1.67	3.59	1.24										
135	1.57	1.79	4.36	2.39	1.77	2.16	3.71	1.68										
140	2.10	2.66	4.49	3.31	2.63	3.06	3.77	2.55										
145	3.26	3.41	4.49	3.96	3.12	3.76	3.87	3.00										
150	4.13	3.73	4.49	4.36	3.67	4.26	4.05	3.30										
155	4.39	4.00	4.73	4.70	4.07	4.67	4.41	3.61										
160	4.78	4.24	5.05	4.99	4.46	5.02	4.78	3.94										
165	5.14	4.57	5.34	5.24	4.78	5.22	5.16	4.47										
170	5.34	5.08	5.63	5.52	4.74	5.53	5.52	5.07										
175	5.16	5.61	5.94	5.85	4.76	5.76	5.86	5.64										
180	5.22	6.07	6.17	6.17	5.22	6.09	6.17	6.17										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: