


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.2715A P:6.515W PF:1.000 Freq:0Hz Lamp Flux:186.361x1 lm		
NAME: ALS-LS2126FDXSS1000	TYPE:	WEIGHT:
SPEC.:ALS-LS2126FDXSS1000-F7NW9X-DC	DIM.: 1000*21*26mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*21	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 28.60 lm/W			
MODEL	ALS-LS2126FDXSS1000	I _{max} (cd)	63.82	S/MH(C0/180)	1.27
NOMINAL POWER(W)	7	LOR(%)	100.0	S/MH(C90/270)	1.26
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	186.36	h UP,DN(C0-180)	0.9,50.1
NOMINAL FLUX(lm)	186.361	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,48.2
LAMPS INSIDE	1	h up(%)	1.7	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.3	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	62.84	62.95	62.95	62.78	62.41	62.43	62.57	62.77	0- 10	6.037	6.037	3.24,3.24
20	59.74	60.11	60.16	59.71	59.00	58.96	59.33	59.57	10- 20	17.33	23.37	12.5,12.5
30	54.49	55.16	55.03	54.54	53.32	53.57	54.12	54.40	20- 30	26.36	49.73	26.7,26.7
40	47.44	48.23	48.33	47.41	45.84	46.29	47.08	47.36	30- 40	31.90	81.63	43.8,43.8
50	38.71	39.71	39.88	38.64	36.73	37.37	38.51	38.61	40- 50	33.21	114.8	61.6,61.6
60	28.63	29.74	29.99	28.48	26.53	27.13	28.52	28.50	50- 60	30.04	144.9	77.7,77.7
70	17.61	18.67	19.19	17.32	15.65	16.09	17.60	17.48	60- 70	22.75	167.6	89.9,89.9
80	6.709	7.452	7.702	6.432	5.187	5.580	6.930	6.729	70- 80	12.53	180.2	96.7,96.7
90	0.1547	0.3192	1.162	0.6411	0.2338	0.4411	0.6210	0.4486	80- 90	3.010	183.2	98.3,98.3
100	0.0935	0.4080	0.4213	0.5936	0.2805	0.4275	0.1336	0.4275	90-100	0.4688	183.6	98.5,98.5
110	0.2135	0.5076	0.2872	0.5002	0.3609	0.4473	0.2546	0.4943	100-110	0.3818	184.0	98.7,98.7
120	0.3873	0.5010	0.4137	0.4542	0.4546	0.3542	0.3941	0.3683	110-120	0.4014	184.4	99.99
130	0.5277	0.5611	0.5277	0.5080	0.5546	0.4999	0.5012	0.4274	120-130	0.4117	184.8	99.2,99.2
140	0.6145	0.6613	0.6212	0.6412	0.6280	0.6077	0.5745	0.5344	130-140	0.4403	185.3	99.4,99.4
150	0.7212	0.7281	0.7147	0.7550	0.7082	0.7211	0.6680	0.6271	140-150	0.4081	185.7	99.6,99.6
160	0.8348	0.7816	0.8280	0.8884	0.8085	0.8350	0.8216	0.6609	150-160	0.3465	186.0	99.8,99.8
170	0.9485	0.8953	0.9418	0.9819	0.8149	0.9483	0.9687	0.8349	160-170	0.2427	186.3	100,100
180	0.8884	1.049	1.049	1.049	0.8550	1.055	1.055	1.049	170-180	0.0903	186.4	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-28

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.2715A P:6.515W PF:1.000 Freq:0Hz Lamp Flux:186.361x1 lm		
NAME: ALS-LS2126FDXSS1000	TYPE:	WEIGHT:
SPEC.:ALS-LS2126FDXSS1000-F7NW9X-DC	DIM.: 1000*21*26mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*21	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	1306	1745
80	1840	2112
75	2203	2419
70	2451	2672
65	2615	2771
60	2726	2856
55	2809	2915
50	2868	2955
45	2914	2984


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.2715A P:6.515W PF:1.000 Freq:0Hz Lamp Flux:186.36lx1 lm		
NAME: ALS-LS2126FDXSS1000	TYPE:	WEIGHT:
SPEC.:ALS-LS2126FDXSS1000-F7NW9X-DC	DIM.: 1000*21*26mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*21	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.00	1.00	1.00	.98
1.0	1.04	.99	.96	1.01	.97	.94	.97	.93	.91	.92	.90	.87	.89	.87	.85	.82
2.0	.90	.83	.78	.88	.82	.77	.84	.79	.75	.81	.76	.73	.78	.74	.71	.69
3.0	.79	.71	.64	.77	.70	.64	.74	.68	.62	.71	.66	.61	.68	.64	.60	.58
4.0	.70	.61	.55	.69	.60	.54	.66	.59	.53	.63	.57	.52	.61	.56	.51	.49
5.0	.63	.54	.47	.61	.53	.47	.59	.52	.46	.57	.50	.45	.55	.49	.45	.42
6.0	.56	.47	.41	.55	.47	.41	.53	.46	.40	.51	.45	.40	.50	.44	.39	.37
7.0	.51	.42	.36	.50	.42	.36	.48	.41	.35	.47	.40	.35	.45	.39	.35	.33
8.0	.46	.38	.32	.46	.38	.32	.44	.37	.32	.43	.36	.31	.42	.36	.31	.29
9.0	.43	.34	.29	.42	.34	.29	.41	.33	.28	.39	.33	.28	.38	.32	.28	.26
10.0	.39	.31	.26	.39	.31	.26	.38	.31	.26	.37	.30	.26	.36	.30	.25	.24



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.2715A P:6.515W PF:1.000 Freq:0Hz Lamp Flux:186.361x1 lm		
NAME: ALS-LS2126FDXSS1000	TYPE:	WEIGHT:
SPEC.:ALS-LS2126FDXSS1000-F7NW9X-DC	DIM.: 1000*21*26mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*21	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.306	.174	.055	.299	.170	.054	.284	.163	.052	.271	.156	.050	.259	.150	.048	
2.0	.289	.159	.049	.283	.156	.048	.270	.150	.047	.259	.145	.045	.248	.140	.044	
3.0	.268	.143	.043	.262	.141	.042	.251	.136	.041	.241	.132	.041	.231	.128	.040	
4.0	.248	.129	.038	.243	.127	.038	.233	.123	.037	.224	.120	.036	.215	.117	.036	
5.0	.229	.117	.034	.225	.115	.034	.216	.112	.033	.208	.110	.033	.200	.107	.032	
6.0	.213	.107	.031	.209	.105	.030	.201	.103	.030	.193	.101	.030	.186	.098	.029	
7.0	.198	.098	.028	.194	.097	.028	.187	.095	.027	.181	.093	.027	.174	.091	.027	
8.0	.185	.090	.025	.182	.090	.025	.175	.088	.025	.169	.086	.025	.164	.084	.024	
9.0	.174	.084	.023	.171	.083	.023	.165	.081	.023	.159	.080	.023	.154	.078	.023	
10.0	.163	.078	.022	.160	.078	.022	.155	.076	.021	.150	.075	.021	.146	.073	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.204	.204	.204	.174	.174	.174	.119	.119	.119	.068	.068	.068	.022	.022	.022	
1.0	.193	.169	.148	.165	.145	.127	.113	.100	.088	.065	.058	.051	.021	.019	.017	
2.0	.185	.145	.112	.159	.125	.096	.109	.086	.067	.063	.050	.039	.020	.016	.013	
3.0	.177	.128	.088	.152	.110	.076	.104	.076	.053	.060	.045	.031	.019	.014	.010	
4.0	.170	.114	.072	.146	.099	.062	.100	.069	.044	.058	.040	.026	.019	.013	.009	
5.0	.163	.104	.061	.140	.090	.053	.096	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.155	.096	.053	.134	.083	.046	.092	.058	.032	.053	.034	.019	.017	.011	.006	
7.0	.149	.089	.047	.128	.077	.041	.088	.054	.029	.051	.032	.017	.017	.010	.006	
8.0	.142	.083	.042	.122	.072	.037	.085	.051	.026	.049	.030	.016	.016	.010	.005	
9.0	.136	.078	.039	.117	.068	.034	.081	.048	.024	.047	.028	.014	.015	.009	.005	
10.0	.131	.074	.036	.113	.064	.031	.078	.045	.022	.046	.027	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.2715A P:6.515W PF:1.000 Freq:0Hz Lamp Flux:186.361x1 lm											
NAME: ALS-LS2126FDXSS1000					TYPE:			WEIGHT:			
SPEC.:ALS-LS2126FDXSS1000-F7NW9X-DC					DIM.: 1000*21*26mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*21			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	22.4	23.8	22.6	24.1	24.3	22.5	24.0	22.8	24.2	24.5	
	3H	23.8	25.2	24.2	25.5	25.8	24.1	25.5	24.4	25.7	26.0
	4H	24.4	25.7	24.7	26.0	26.3	24.7	26.0	25.0	26.3	26.6
	6H	24.8	26.0	25.1	26.3	26.6	25.1	26.4	25.5	26.7	27.0
	8H	24.8	26.0	25.2	26.4	26.7	25.2	26.4	25.6	26.7	27.1
	12H	24.9	26.0	25.3	26.3	26.7	25.3	26.4	25.7	26.8	27.1
4H	2H	23.0	24.3	23.3	24.6	24.9	23.1	24.4	23.5	24.7	25.0
	3H	24.7	25.8	25.0	26.1	26.5	24.9	26.0	25.3	26.4	26.7
	4H	25.3	26.4	25.7	26.7	27.1	25.6	26.7	26.0	27.0	27.4
	6H	25.8	26.7	26.2	27.1	27.5	26.1	27.1	26.6	27.4	27.9
	8H	25.9	26.8	26.4	27.2	27.6	26.3	27.2	26.7	27.6	28.0
	12H	26.0	26.8	26.5	27.2	27.7	26.4	27.2	26.9	27.6	28.1
8H	4H	25.6	26.5	26.1	26.9	27.3	25.9	26.7	26.3	27.1	27.5
	6H	26.2	26.9	26.7	27.4	27.8	26.5	27.2	27.0	27.7	28.1
	8H	26.4	27.1	26.9	27.5	28.0	26.8	27.4	27.2	27.8	28.3
	12H	26.5	27.1	27.1	27.6	28.1	26.9	27.5	27.4	27.9	28.5
12H	4H	25.6	26.4	26.1	26.8	27.3	25.9	26.6	26.3	27.1	27.5
	6H	26.3	26.9	26.8	27.4	27.9	26.6	27.2	27.0	27.6	28.1
	8H	26.5	27.1	27.0	27.5	28.0	26.8	27.4	27.3	27.9	28.4
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 186.4 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -5.8)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.2715A P:6.515W PF:1.000 Freq:0Hz Lamp Flux:186.361x1 lm		
NAME: ALS-LS2126FDXSS1000	TYPE:	WEIGHT:
SPEC.:ALS-LS2126FDXSS1000-F7NW9X-DC	DIM.: 1000*21*26mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*21	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	57	45	38	56	45	38	55	45	38	32
0.80	67	55	48	66	55	48	64	54	47	40
1.00	75	64	57	74	64	57	72	65	56	49
1.25	83	72	65	81	71	64	78	70	64	56
1.50	88	78	71	86	77	70	83	75	69	61
2.00	95	86	79	93	85	79	89	82	77	69
2.50	98	91	85	96	89	84	92	86	82	73
3.00	102	95	89	100	93	88	95	90	86	77
4.00	106	100	95	103	98	94	99	95	91	82
5.00	108	103	99	106	101	98	101	97	94	85
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.2715A P:6.515W PF:1.000 Freq:0Hz Lamp Flux:186.36lx1 lm		
NAME: ALS-LS2126FDXSS1000	TYPE:	WEIGHT:
SPEC.:ALS-LS2126FDXSS1000-F7NW9X-DC	DIM.: 1000*21*26mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*21	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.2715A P:6.515W PF:1.000 Freq:0Hz Lamp Flux:186.36lx1 lm		
NAME: ALS-LS2126FDXSS1000	TYPE:	WEIGHT:
SPEC.:ALS-LS2126FDXSS1000-F7NW9X-DC	DIM.: 1000*21*26mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*21	Shielding Angle:

Flux out:133.5 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.2715A P:6.515W PF:1.000 Freq:0Hz Lamp Flux:186.361x1 lm		
NAME: ALS-LS2126FDXSS1000	TYPE:	WEIGHT:
SPEC.:ALS-LS2126FDXSS1000-F7NW9X-DC	DIM.: 1000*21*26mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*21	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-28

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-03-28

deg Range: 0 - 180DEG
deg Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.2715A P:6.515W PF:1.000 Freq:0Hz Lamp Flux:186.361x1 lm		
NAME: ALS-LS2126FDXSS1000	TYPE:	WEIGHT:
SPEC.:ALS-LS2126FDXSS1000-F7NW9X-DC	DIM.: 1000*21*26mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*21	Shielding Angle:

Table--1

UNIT: cd

C(DEC) g (DEC)	0	45	90	135	180	225	270	315										
0	63.7	63.7	63.8	63.8	63.7	63.7	63.8	63.8										
5	63.6	63.6	63.6	63.6	63.3	63.4	63.4	63.6										
10	62.8	63.0	62.9	62.8	62.4	62.4	62.6	62.8										
15	61.5	61.8	61.7	61.5	61.0	61.0	61.2	61.4										
20	59.7	60.1	60.2	59.7	59.0	59.0	59.3	59.6										
25	57.4	57.9	57.8	57.5	56.4	56.5	57.0	57.2										
30	54.5	55.2	55.0	54.5	53.3	53.6	54.1	54.4										
35	51.2	52.0	51.9	51.2	49.8	50.1	50.8	51.1										
40	47.4	48.2	48.3	47.4	45.8	46.3	47.1	47.4										
45	43.3	44.2	44.3	43.2	41.4	42.0	43.0	43.2										
50	38.7	39.7	39.9	38.6	36.7	37.4	38.5	38.6										
55	33.8	34.9	35.1	33.7	31.8	32.4	33.7	33.7										
60	28.6	29.7	30.0	28.5	26.5	27.1	28.5	28.5										
65	23.2	24.3	24.6	23.0	21.2	21.7	23.1	23.1										
70	17.6	18.7	19.2	17.3	15.6	16.1	17.6	17.5										
75	12.0	12.9	13.1	11.8	10.2	10.6	12.1	11.9										
80	6.71	7.45	7.70	6.43	5.19	5.58	6.93	6.73										
85	2.39	2.87	3.19	2.32	1.43	1.70	2.62	2.49										
90	0.15	0.32	1.16	0.64	0.23	0.44	0.62	0.45										
95	0.10	0.27	0.98	0.61	0.24	0.42	0.53	0.43										
100	0.09	0.41	0.42	0.59	0.28	0.43	0.13	0.43										
105	0.19	0.51	0.28	0.51	0.33	0.43	0.18	0.48										
110	0.21	0.51	0.29	0.50	0.36	0.45	0.25	0.49										
115	0.28	0.51	0.36	0.45	0.41	0.45	0.33	0.48										
120	0.39	0.50	0.41	0.45	0.45	0.35	0.39	0.37										
125	0.43	0.50	0.53	0.47	0.49	0.39	0.45	0.39										
130	0.53	0.56	0.53	0.51	0.55	0.50	0.50	0.43										
135	0.58	0.62	0.61	0.57	0.58	0.53	0.55	0.53										
140	0.61	0.66	0.62	0.64	0.63	0.61	0.57	0.53										
145	0.70	0.69	0.65	0.70	0.67	0.62	0.61	0.55										
150	0.72	0.73	0.71	0.76	0.71	0.72	0.67	0.63										
155	0.80	0.75	0.73	0.84	0.76	0.74	0.75	0.62										
160	0.83	0.78	0.83	0.89	0.81	0.84	0.82	0.66										
165	0.93	0.84	0.87	0.92	0.83	0.85	0.89	0.75										
170	0.95	0.90	0.94	0.98	0.81	0.95	0.97	0.83										
175	0.90	0.99	1.00	1.02	0.83	0.95	1.04	0.94										
180	0.89	1.05	1.05	1.05	0.85	1.06	1.06	1.05										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: