


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.8V I:0.0946A P:19.38W PF:0.9277 Freq:49.99Hz Lamp Flux:1361.6x1 lm		
NAME: LLS-M60BDXBX0600	TYPE:	WEIGHT:
SPEC.:LLS-M60BDXBX0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 70.26 lm/W			
MODEL	LLS-M60BDXBX0600	I _{max} (cd)	827.3	S/MH(C0/180)	1.00
NOMINAL POWER(W)	17	LOR(%)	100.0	S/MH(C90/270)	0.87
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	1361.6	h UP,DN(C0-180)	1.4,46.4
NOMINAL FLUX(lm)	1361.6	CIE CLASS	DIRECT	h UP,DN(C180-360)	1.5,50.7
LAMPS INSIDE	1	h up(%)	2.9	CIBSE SHR NOM	1.00
TEST VOLTAGE(V)	220	h down(%)	97.1	CIBSE SHR MAX	1.05



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	764.6	728.3	724.3	755.8	814.5	765.9	734.0	738.7	0- 10	74.68	74.68	5.48,5.48
20	660.8	592.3	579.1	633.5	741.0	645.1	589.6	604.9	10- 20	195.2	269.8	19.8,19.8
30	525.7	443.5	421.3	490.0	627.9	497.1	424.3	450.7	20- 30	256.6	526.4	38.7,38.7
40	378.6	293.4	261.2	343.3	487.1	346.0	263.0	301.7	30- 40	255.1	781.6	57.4,57.4
50	229.2	172.5	168.8	213.5	334.6	218.8	170.2	178.1	40- 50	206.4	988.0	72.6,72.6
60	100.5	110.0	127.5	132.3	185.9	132.2	126.8	108.9	50- 60	147.9	1136	83.4,83.4
70	49.79	62.87	91.36	83.59	76.12	84.84	91.99	61.57	60- 70	99.04	1235	90.7,90.7
80	8.579	27.17	60.66	43.49	41.58	42.39	65.34	27.31	70- 80	60.29	1295	95.1,95.1
90	0.8556	10.59	7.451	12.56	4.388	12.02	10.74	10.09	80- 90	26.75	1322	97.1,97.1
100	1.055	5.783	2.091	8.755	0.3951	8.257	7.934	9.486	90-100	10.11	1332	97.8,97.8
110	1.700	6.253	1.782	7.908	0.9909	7.716	1.524	8.897	100-110	5.040	1337	98.2,98.2
120	3.158	7.467	2.317	7.674	1.758	7.429	5.771	6.723	110-120	4.941	1342	98.6,98.6
130	4.753	7.051	2.833	7.030	3.046	6.928	5.181	6.707	120-130	4.849	1347	98.9,98.9
140	6.262	6.720	4.031	6.279	4.289	6.885	6.073	6.453	130-140	4.339	1351	99.2,99.2
150	7.447	6.948	5.422	6.459	5.473	7.053	7.196	7.046	140-150	3.906	1355	99.5,99.5
160	8.662	7.341	6.638	7.335	6.749	7.647	8.170	8.182	150-160	3.271	1358	99.8,99.8
170	9.719	8.190	8.728	8.844	8.024	8.515	8.952	9.477	160-170	2.298	1361	99.9,99.9
180	9.111	10.13	10.99	10.95	9.138	10.12	10.99	10.93	170-180	0.8848	1362	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.8V I:0.0946A P:19.38W PF:0.9277 Freq:49.99Hz Lamp Flux:1361.6x1 lm		
NAME: LLS-M60BDXBX0600	TYPE:	WEIGHT:
SPEC.:LLS-M60BDXBX0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	462	18225
80	1647	11644
75	3386	9753
70	4853	8904
65	6097	8515
60	6702	8502
55	9154	8598
50	11886	8751
45	14399	9249


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.8V I:0.0946A P:19.38W PF:0.9277 Freq:49.99Hz Lamp Flux:1361.6x1 lm		
NAME: LLS-M60BDXB0600	TYPE:	WEIGHT:
SPEC.:LLS-M60BDXB0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.04	1.04	1.04	.99	.99	.99	.97
1.0	1.05	1.01	.98	1.03	.99	.96	.98	.95	.93	.94	.91	.89	.90	.88	.86	.84
2.0	.94	.88	.83	.92	.86	.81	.88	.83	.79	.84	.80	.77	.81	.78	.75	.73
3.0	.84	.77	.71	.82	.76	.70	.79	.73	.69	.76	.71	.67	.73	.69	.66	.64
4.0	.76	.68	.62	.74	.67	.61	.71	.65	.60	.69	.64	.59	.67	.62	.58	.56
5.0	.69	.61	.55	.68	.60	.54	.65	.59	.54	.63	.57	.53	.61	.56	.52	.50
6.0	.63	.55	.49	.62	.54	.49	.60	.53	.48	.58	.52	.47	.56	.51	.47	.45
7.0	.58	.50	.44	.57	.49	.44	.55	.48	.43	.53	.47	.43	.52	.47	.43	.41
8.0	.53	.46	.40	.52	.45	.40	.51	.44	.40	.50	.44	.39	.48	.43	.39	.37
9.0	.49	.42	.37	.49	.42	.37	.47	.41	.36	.46	.40	.36	.45	.40	.36	.34
10.0	.46	.39	.34	.45	.38	.34	.44	.38	.33	.43	.37	.33	.42	.37	.33	.31



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.8V I:0.0946A P:19.38W PF:0.9277 Freq:49.99Hz Lamp Flux:1361.6x1 lm		
NAME: LLS-M60BDXBX0600	TYPE:	WEIGHT:
SPEC.:LLS-M60BDXBX0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.272	.155	.049	.265	.151	.048	.250	.143	.046	.236	.136	.044	.224	.130	.042	
2.0	.254	.139	.043	.248	.136	.042	.235	.131	.041	.223	.125	.039	.212	.120	.038	
3.0	.236	.126	.038	.230	.123	.037	.219	.119	.036	.208	.114	.035	.199	.110	.034	
4.0	.219	.114	.034	.214	.112	.033	.204	.108	.032	.195	.105	.032	.186	.101	.031	
5.0	.204	.104	.030	.200	.102	.030	.191	.099	.029	.182	.096	.029	.174	.093	.028	
6.0	.191	.096	.027	.187	.094	.027	.179	.092	.027	.171	.089	.026	.164	.086	.026	
7.0	.179	.088	.025	.175	.087	.025	.168	.085	.024	.161	.083	.024	.155	.080	.024	
8.0	.168	.082	.023	.165	.081	.023	.158	.079	.023	.152	.077	.022	.146	.075	.022	
9.0	.158	.077	.021	.155	.076	.021	.149	.074	.021	.144	.072	.021	.139	.070	.020	
10.0	.150	.072	.020	.147	.071	.020	.142	.069	.020	.137	.068	.019	.132	.066	.019	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.213	.213	.213	.182	.182	.182	.124	.124	.124	.071	.071	.071	.023	.023	.023	
1.0	.200	.179	.160	.171	.153	.137	.117	.106	.095	.067	.061	.055	.022	.020	.018	
2.0	.190	.155	.125	.163	.133	.108	.111	.092	.075	.064	.054	.044	.021	.017	.014	
3.0	.181	.137	.102	.155	.118	.088	.106	.082	.062	.061	.048	.036	.020	.016	.012	
4.0	.172	.123	.085	.148	.106	.074	.102	.074	.052	.059	.043	.031	.019	.014	.010	
5.0	.165	.112	.074	.141	.097	.064	.097	.068	.045	.056	.040	.027	.018	.013	.009	
6.0	.157	.104	.065	.135	.090	.057	.093	.063	.040	.054	.037	.024	.017	.012	.008	
7.0	.151	.097	.059	.130	.084	.051	.090	.059	.036	.052	.035	.022	.017	.011	.007	
8.0	.145	.091	.054	.125	.079	.047	.086	.055	.033	.050	.033	.020	.016	.011	.007	
9.0	.139	.086	.050	.120	.075	.044	.083	.052	.031	.048	.031	.018	.016	.010	.006	
10.0	.134	.082	.047	.115	.071	.041	.080	.050	.029	.047	.029	.017	.015	.010	.006	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.8V I:0.0946A P:19.38W PF:0.9277 Freq:49.99Hz Lamp Flux:1361.6x1 lm											
NAME: LLS-M60BDXBX0600						TYPE:		WEIGHT:			
SPEC.:LLS-M60BDXBX0600-T19NW8B-DC						DIM.: 600*50*45mm		SERIAL No.:			
MFR.: COLORS						SUR.:600*50mm		Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	18.0	19.3	18.3	19.5	19.8	17.7	19.0	18.0	19.2	19.5	
	3H	18.6	19.9	19.0	20.1	20.4	19.3	20.5	19.6	20.7	21.0
	4H	18.8	20.0	19.2	20.2	20.5	20.1	21.3	20.5	21.6	21.9
	6H	18.8	19.9	19.2	20.2	20.5	21.0	22.1	21.4	22.4	22.8
	8H	18.8	19.8	19.2	20.1	20.5	21.5	22.6	21.9	22.9	23.2
	12H	18.7	19.7	19.1	20.1	20.4	22.1	23.1	22.5	23.5	23.8
4H	2H	18.3	19.4	18.6	19.7	20.0	18.0	19.2	18.4	19.5	19.8
	3H	19.2	20.1	19.5	20.5	20.8	19.8	20.8	20.2	21.1	21.5
	4H	19.4	20.3	19.8	20.7	21.1	20.8	21.7	21.2	22.1	22.5
	6H	19.5	20.3	20.0	20.7	21.1	21.9	22.7	22.4	23.1	23.5
	8H	19.5	20.2	19.9	20.7	21.1	22.5	23.3	23.0	23.7	24.1
	12H	19.5	20.1	19.9	20.6	21.0	23.3	23.9	23.7	24.4	24.8
8H	4H	19.7	20.4	20.1	20.8	21.3	20.9	21.7	21.4	22.1	22.5
	6H	19.9	20.5	20.3	20.9	21.4	22.2	22.8	22.7	23.3	23.7
	8H	19.9	20.4	20.4	20.9	21.4	22.9	23.5	23.4	23.9	24.5
	12H	19.9	20.3	20.4	20.8	21.4	23.9	24.3	24.4	24.8	25.4
12H	4H	19.7	20.4	20.2	20.8	21.3	20.9	21.6	21.4	22.0	22.5
	6H	20.0	20.5	20.5	21.0	21.5	22.2	22.7	22.7	23.2	23.7
	8H	20.0	20.5	20.5	21.0	21.5	23.0	23.4	23.5	23.9	24.5
Variations with the observer position at spacings:											
S = 1.0H	+ 0.4 / - 0.5					+ 0.2 / - 0.2					
1.5H	+ 0.5 / - 0.6					+ 0.1 / - 0.1					
2.0H	+ 1.5 / - 1.1					+ 0.2 / - 0.3					

CIE Pub.117, 1362 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 1.1$)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.8V I:0.0946A P:19.38W PF:0.9277 Freq:49.99Hz Lamp Flux:1361.6x1 lm		
NAME: LLS-M60BDXBX0600	TYPE:	WEIGHT:
SPEC.:LLS-M60BDXBX0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	65	55	49	64	55	49	63	54	49	43
0.80	75	65	58	74	64	58	72	63	58	51
1.00	82	72	66	81	72	66	78	72	65	59
1.25	88	79	73	87	78	73	84	77	72	65
1.50	92	84	78	91	83	77	88	81	76	69
2.00	98	91	85	96	89	84	93	87	83	75
2.50	101	95	89	99	93	88	95	90	86	78
3.00	104	98	93	102	96	92	98	93	90	81
4.00	107	102	98	105	100	97	100	97	94	85
5.00	109	105	102	107	103	100	102	99	96	87
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.8V I:0.0946A P:19.38W PF:0.9277 Freq:49.99Hz Lamp Flux:1361.6x1 lm		
NAME: LLS-M60BDXB0600	TYPE:	WEIGHT:
SPEC.:LLS-M60BDXB0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.8V I:0.0946A P:19.38W PF:0.9277 Freq:49.99Hz Lamp Flux:1361.6x1 lm		
NAME: LLS-M60BDXB0600	TYPE:	WEIGHT:
SPEC.:LLS-M60BDXB0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

Flux out:553.0 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:220.8V I:0.0946A P:19.38W PF:0.9277 Freq:49.99Hz Lamp Flux:1361.6x1 lm		
NAME: LLS-M60BDXB0600	TYPE:	WEIGHT:
SPEC.:LLS-M60BDXB0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.8V I:0.0946A P:19.38W PF:0.9277 Freq:49.99Hz Lamp Flux:1361.6x1 lm		
NAME: LLS-M60BDXB0600	TYPE:	WEIGHT:
SPEC.:LLS-M60BDXB0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	822	821	823	821	822	821	823	821										
5	800	782	780	797	827	806	789	791										
10	765	728	724	756	814	766	734	739										
15	718	664	655	699	784	711	666	676										
20	661	592	579	633	741	645	590	605										
25	596	516	505	561	689	573	508	529										
30	526	443	421	490	628	497	424	451										
35	453	367	336	419	560	421	345	373										
40	379	293	261	343	487	346	263	302										
45	305	227	196	273	412	281	191	240										
50	229	172	169	214	335	219	170	178										
55	158	136	148	164	261	161	145	136										
60	101	110	128	132	186	132	127	109										
65	77.3	84.7	108	108	120	107	109	83.5										
70	49.8	62.9	91.4	83.6	76.1	84.8	92.0	61.6										
75	26.3	43.8	75.7	62.3	67.5	61.8	77.8	43.3										
80	8.58	27.2	60.7	43.5	41.6	42.4	65.3	27.3										
85	1.21	13.3	47.7	26.8	20.5	26.4	48.6	13.4										
90	0.86	10.6	7.45	12.6	4.39	12.0	10.7	10.1										
95	0.90	6.85	24.6	9.03	0.66	8.28	25.8	9.79										
100	1.05	5.78	2.09	8.76	0.40	8.26	7.93	9.49										
105	1.35	3.84	1.77	8.33	0.66	7.98	3.70	9.21										
110	1.70	6.25	1.78	7.91	0.99	7.72	1.52	8.90										
115	2.42	7.48	2.31	7.77	1.31	7.59	2.48	8.63										
120	3.16	7.47	2.32	7.67	1.76	7.43	5.77	6.72										
125	3.95	7.27	2.56	7.46	2.39	7.17	5.53	7.26										
130	4.75	7.05	2.83	7.03	3.05	6.93	5.18	6.71										
135	5.54	6.77	3.35	6.62	3.67	6.88	5.30	6.50										
140	6.26	6.72	4.03	6.28	4.29	6.89	6.07	6.45										
145	6.91	6.80	4.69	6.29	4.91	6.92	6.65	6.61										
150	7.45	6.95	5.42	6.46	5.47	7.05	7.20	7.05										
155	8.09	7.19	6.04	6.77	6.11	7.27	7.72	7.53										
160	8.66	7.34	6.64	7.34	6.75	7.65	8.17	8.18										
165	9.26	7.65	7.49	8.04	7.35	8.06	8.52	8.86										
170	9.72	8.19	8.73	8.84	8.02	8.51	8.95	9.48										
175	8.97	9.06	10.0	9.89	8.56	9.26	10.0	10.1										
180	9.11	10.1	11.0	11.0	9.14	10.1	11.0	10.9										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: