


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.8V I:0.0902A P:19.19W PF:0.9637 Freq:49.99Hz Lamp Flux:1906.24x1 lm		
NAME: LLS-M60FDXBS0600	TYPE:	WEIGHT:
SPEC.:LLS-M60FDXBS0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 99.36 lm/W			
MODEL	LLS-M60FDXBS0600	I _{max} (cd)	842.8	S/MH(C0/180)	1.04
NOMINAL POWER(W)	17	LOR(%)	100.0	S/MH(C90/270)	1.17
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	1906.2	h UP,DN(C0-180)	0.7,48.1
NOMINAL FLUX(lm)	1906.24	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.6,50.7
LAMPS INSIDE	1	h up(%)	1.3	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	220	h down(%)	98.7	CIBSE SHR MAX	1.25



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	793.5	805.0	815.3	819.9	826.7	823.0	818.8	806.0	0- 10	78.92	78.92	4.14,4.14
20	694.1	721.7	747.9	749.7	754.5	754.6	754.0	723.8	10- 20	219.7	298.6	15.7,15.7
30	566.2	604.9	645.6	641.0	639.7	646.4	653.4	607.2	20- 30	314.9	613.5	32.2,32.2
40	433.6	474.7	522.0	512.4	507.4	517.2	529.5	476.9	30- 40	351.2	964.7	50.6,50.6
50	311.1	344.3	391.5	379.5	376.0	385.6	396.0	348.3	40- 50	332.7	1297	68.1,68.1
60	201.2	227.8	266.2	259.6	260.5	263.9	268.0	231.0	50- 60	273.4	1571	82.4,82.4
70	104.0	123.7	150.0	152.1	157.5	153.1	152.3	125.0	60- 70	190.2	1761	92.4,92.4
80	27.48	38.73	53.41	60.40	68.23	60.80	54.67	39.70	70- 80	98.08	1859	97.5,97.5
90	1.055	1.496	1.493	3.489	7.225	3.200	0.5745	0.5615	80- 90	23.12	1882	98.7,98.7
100	1.467	1.472	1.365	1.236	0.6625	0.9613	0.9824	1.180	90-100	1.195	1883	98.8,98.8
110	2.503	2.494	2.495	1.867	1.483	1.808	2.347	2.111	100-110	1.684	1885	98.9,98.9
120	3.672	3.804	4.506	2.800	2.439	2.523	4.153	2.897	110-120	2.705	1888	99,99
130	4.927	5.268	6.307	3.764	3.449	3.518	5.578	4.246	120-130	3.570	1891	99.2,99.2
140	6.250	6.822	7.665	4.858	4.605	4.487	6.540	5.683	130-140	4.047	1895	99.4,99.4
150	7.459	8.159	8.514	6.128	5.671	5.884	7.141	6.846	140-150	4.031	1899	99.6,99.6
160	8.855	8.911	8.883	7.596	7.088	7.446	7.589	7.666	150-160	3.455	1903	99.8,99.8
170	10.45	9.445	9.502	9.113	8.858	8.935	8.900	8.646	160-170	2.413	1905	100,100
180	10.08	10.57	10.99	10.67	10.11	10.56	11.02	10.66	170-180	0.9262	1906	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.8V I:0.0902A P:19.19W PF:0.9637 Freq:49.99Hz Lamp Flux:1906.24x1 lm		
NAME: LLS-M60FDXBS0600	TYPE:	WEIGHT:
SPEC.:LLS-M60FDXBS0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	1943	7334
80	5274	10253
75	7991	12681
70	10137	14618
65	11876	16305
60	13414	17744
55	14832	19037
50	16134	20302
45	17485	21525


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.8V I:0.0902A P:19.19W PF:0.9637 Freq:49.99Hz Lamp Flux:1906.24x1 lm		
NAME: LLS-M60FDXBS0600	TYPE:	WEIGHT:
SPEC.:LLS-M60FDXBS0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.05	1.01	.97	1.03	.99	.96	.98	.95	.93	.94	.92	.89	.90	.88	.87	.85
2.0	.92	.86	.81	.90	.85	.80	.87	.82	.78	.83	.79	.76	.80	.77	.74	.72
3.0	.82	.74	.68	.80	.73	.67	.77	.71	.66	.74	.69	.65	.72	.67	.64	.61
4.0	.73	.65	.59	.72	.64	.58	.69	.62	.57	.67	.61	.56	.64	.59	.55	.53
5.0	.66	.57	.51	.65	.57	.51	.62	.55	.50	.60	.54	.49	.58	.53	.49	.47
6.0	.60	.51	.45	.59	.51	.45	.57	.50	.44	.55	.49	.44	.53	.48	.43	.41
7.0	.54	.46	.40	.53	.45	.40	.52	.45	.39	.50	.44	.39	.49	.43	.39	.37
8.0	.50	.42	.36	.49	.41	.36	.48	.41	.36	.46	.40	.35	.45	.39	.35	.33
9.0	.46	.38	.33	.45	.38	.32	.44	.37	.32	.43	.37	.32	.42	.36	.32	.30
10.0	.42	.35	.30	.42	.35	.30	.41	.34	.29	.40	.34	.29	.39	.33	.29	.27



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.8V I:0.0902A P:19.19W PF:0.9637 Freq:49.99Hz Lamp Flux:1906.24x1 lm		
NAME: LLS-M60FDXBS0600	TYPE:	WEIGHT:
SPEC.:LLS-M60FDXBS0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.283	.161	.051	.276	.157	.050	.262	.150	.048	.249	.144	.046	.237	.138	.044	
2.0	.269	.148	.045	.263	.145	.045	.251	.139	.043	.240	.134	.042	.229	.130	.041	
3.0	.251	.134	.040	.246	.132	.040	.235	.127	.039	.225	.123	.038	.216	.120	.037	
4.0	.234	.121	.036	.229	.120	.035	.219	.116	.035	.210	.113	.034	.202	.110	.033	
5.0	.217	.111	.032	.213	.109	.032	.204	.106	.031	.197	.104	.031	.189	.101	.030	
6.0	.203	.102	.029	.199	.100	.029	.191	.098	.028	.184	.096	.028	.177	.093	.028	
7.0	.189	.094	.027	.186	.093	.026	.179	.091	.026	.173	.089	.026	.167	.087	.025	
8.0	.178	.087	.024	.174	.086	.024	.168	.084	.024	.163	.082	.024	.157	.081	.023	
9.0	.167	.081	.023	.164	.080	.022	.159	.078	.022	.153	.077	.022	.148	.075	.022	
10.0	.157	.075	.021	.155	.075	.021	.150	.073	.021	.145	.072	.020	.141	.071	.020	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.200	.200	.200	.171	.171	.171	.117	.117	.117	.067	.067	.067	.021	.021	.021	
1.0	.188	.166	.146	.161	.143	.126	.110	.098	.087	.063	.057	.051	.020	.018	.016	
2.0	.179	.142	.110	.153	.122	.095	.105	.084	.067	.061	.049	.039	.019	.016	.013	
3.0	.171	.124	.087	.146	.107	.075	.100	.074	.053	.058	.043	.031	.019	.014	.010	
4.0	.163	.110	.070	.140	.095	.061	.096	.067	.043	.056	.039	.026	.018	.013	.008	
5.0	.155	.100	.059	.134	.086	.051	.092	.060	.036	.053	.035	.021	.017	.012	.007	
6.0	.148	.091	.051	.128	.079	.044	.088	.055	.031	.051	.033	.019	.016	.011	.006	
7.0	.142	.085	.044	.122	.073	.039	.084	.051	.027	.049	.030	.016	.016	.010	.005	
8.0	.136	.079	.040	.117	.068	.035	.081	.048	.025	.047	.028	.015	.015	.009	.005	
9.0	.130	.074	.036	.112	.064	.031	.077	.045	.022	.045	.027	.013	.015	.009	.004	
10.0	.124	.069	.033	.107	.060	.029	.074	.042	.021	.043	.025	.012	.014	.008	.004	

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.8V I:0.0902A P:19.19W PF:0.9637 Freq:49.99Hz Lamp Flux:1906.24x1 lm											
NAME: LLS-M60FDXBS0600					TYPE:			WEIGHT:			
SPEC.:LLS-M60FDXBS0600-T19NW8B-DC					DIM.: 600*50*45mm			SERIAL No.:			
MFR.: COLORS					SUR.:600*50mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	19.3	20.7	19.6	21.0	21.2	20.3	21.7	20.6	22.0	22.2	
	3H	20.3	21.6	20.6	21.9	22.1	21.6	22.9	21.9	23.1	23.4
	4H	20.6	21.8	20.9	22.1	22.4	22.0	23.2	22.3	23.5	23.8
	6H	20.7	21.9	21.0	22.1	22.4	22.3	23.4	22.6	23.7	24.0
	8H	20.7	21.8	21.0	22.1	22.4	22.3	23.5	22.7	23.8	24.1
	12H	20.6	21.7	21.0	22.0	22.4	22.3	23.4	22.7	23.7	24.1
4H	2H	19.9	21.1	20.2	21.4	21.7	20.7	21.9	21.0	22.2	22.5
	3H	21.0	22.1	21.4	22.4	22.7	22.1	23.2	22.5	23.5	23.8
	4H	21.4	22.4	21.8	22.7	23.1	22.6	23.6	23.0	24.0	24.3
	6H	21.6	22.5	22.0	22.8	23.2	23.0	23.9	23.4	24.2	24.6
	8H	21.6	22.4	22.0	22.8	23.2	23.1	23.9	23.5	24.3	24.7
	12H	21.6	22.3	22.0	22.7	23.2	23.1	23.9	23.6	24.3	24.7
8H	4H	21.6	22.4	22.0	22.8	23.2	22.7	23.5	23.2	23.9	24.3
	6H	21.9	22.5	22.3	23.0	23.4	23.2	23.9	23.6	24.3	24.7
	8H	21.9	22.5	22.4	22.9	23.4	23.3	23.9	23.8	24.4	24.8
	12H	21.9	22.4	22.4	22.9	23.4	23.4	23.9	23.9	24.4	24.9
12H	4H	21.6	22.3	22.0	22.7	23.2	22.7	23.4	23.1	23.8	24.3
	6H	21.9	22.5	22.4	22.9	23.4	23.2	23.8	23.7	24.2	24.7
	8H	21.9	22.5	22.4	22.9	23.4	23.3	23.8	23.8	24.3	24.8
Variations with the observer position at spacings:											
S = 1.0H	+ 0.3 / - 0.4					+ 0.2 / - 0.3					
1.5H	+ 0.2 / - 0.4					+ 0.2 / - 0.2					
2.0H	+ 0.4 / - 0.7					+ 0.5 / - 0.5					

CIE Pub.117, 1906 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 2.2$)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.8V I:0.0902A P:19.19W PF:0.9637 Freq:49.99Hz Lamp Flux:1906.24x1 lm		
NAME: LLS-M60FDXBS0600	TYPE:	WEIGHT:
SPEC.:LLS-M60FDXBS0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	61	50	43	60	50	43	59	49	43	37
0.80	71	60	53	70	60	53	68	59	53	46
1.00	79	69	62	78	68	62	76	69	61	54
1.25	86	76	70	84	75	69	82	74	68	61
1.50	91	81	75	89	81	75	86	79	73	66
2.00	97	89	83	95	88	82	92	85	81	73
2.50	100	93	88	98	92	87	94	89	85	77
3.00	104	97	92	101	96	91	97	93	89	80
4.00	107	102	98	105	100	96	100	97	93	84
5.00	109	105	101	107	103	100	102	99	96	87
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.8V I:0.0902A P:19.19W PF:0.9637 Freq:49.99Hz Lamp Flux:1906.24x1 lm		
NAME: LLS-M60FDXBS0600	TYPE:	WEIGHT:
SPEC.:LLS-M60FDXBS0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.8V I:0.0902A P:19.19W PF:0.9637 Freq:49.99Hz Lamp Flux:1906.24x1 lm		
NAME: LLS-M60FDXBS0600	TYPE:	WEIGHT:
SPEC.:LLS-M60FDXBS0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

Flux out:1170 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:220.8V I:0.0902A P:19.19W PF:0.9637 Freq:49.99Hz Lamp Flux:1906.24x1 lm		
NAME: LLS-M60FDXBS0600	TYPE:	WEIGHT:
SPEC.:LLS-M60FDXBS0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

deg Range: 0 - 180DEG
deg Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.8V I:0.0902A P:19.19W PF:0.9637 Freq:49.99Hz Lamp Flux:1906.24x1 lm		
NAME: LLS-M60FDXBS0600	TYPE:	WEIGHT:
SPEC.:LLS-M60FDXBS0600-T19NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	841	841	840	839	841	841	840	839										
5	824	829	833	836	841	838	835	829										
10	794	805	815	820	827	823	819	806										
15	749	768	787	791	797	795	792	770										
20	694	722	748	750	754	755	754	724										
25	632	666	700	699	701	704	708	669										
30	566	605	646	641	640	646	653	607										
35	499	540	586	578	574	583	593	543										
40	434	475	522	512	507	517	529	477										
45	371	409	457	446	442	451	464	411										
50	311	344	391	380	376	386	396	348										
55	255	285	328	318	317	323	330	288										
60	201	228	266	260	260	264	268	231										
65	151	174	207	204	207	207	209	175										
70	104	124	150	152	157	153	152	125										
75	62.0	77.8	98.5	104	111	104	100	79.0										
80	27.5	38.7	53.4	60.4	68.2	60.8	54.7	39.7										
85	5.08	11.0	19.2	25.4	32.2	25.5	19.7	11.2										
90	1.06	1.50	1.49	3.49	7.23	3.20	0.57	0.56										
95	1.13	1.21	1.36	1.13	0.35	0.59	0.82	0.79										
100	1.47	1.47	1.37	1.24	0.66	0.96	0.98	1.18										
105	1.91	1.89	1.67	1.49	1.04	1.34	1.51	1.67										
110	2.50	2.49	2.49	1.87	1.48	1.81	2.35	2.11										
115	3.06	3.13	3.50	2.33	1.94	2.14	3.27	2.40										
120	3.67	3.80	4.51	2.80	2.44	2.52	4.15	2.90										
125	4.34	4.53	5.46	3.27	2.91	2.98	4.93	3.55										
130	4.93	5.27	6.31	3.76	3.45	3.52	5.58	4.25										
135	5.61	6.03	7.04	4.29	4.00	3.92	6.12	4.89										
140	6.25	6.82	7.67	4.86	4.60	4.49	6.54	5.68										
145	6.92	7.56	8.15	5.46	5.18	5.16	6.87	6.37										
150	7.46	8.16	8.51	6.13	5.67	5.88	7.14	6.85										
155	8.13	8.60	8.73	6.84	6.33	6.69	7.38	7.27										
160	8.85	8.91	8.88	7.60	7.09	7.45	7.59	7.67										
165	9.67	9.18	9.08	8.39	7.93	8.21	8.04	7.97										
170	10.5	9.44	9.50	9.11	8.86	8.93	8.90	8.65										
175	10.1	9.93	10.2	9.91	9.53	9.78	10.1	9.60										
180	10.1	10.6	11.0	10.7	10.1	10.6	11.0	10.7										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: