


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.7V I:0.0713A P:14.85W PF:0.9436 Freq:49.99Hz Lamp Flux:1432.04x1 lm		
NAME: LLS-M60GFXBX0600	TYPE:	WEIGHT:
SPEC.: LLS-M60GFXBX0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.: 600*50mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 96.46 lm/W			
MODEL	LLS-M60GFXBX0600	I _{max} (cd)	14490	S/MH (C0/180)	0.14
NOMINAL POWER (W)	12.5	LOR (%)	100.0	S/MH (C90/270)	0.18
RATED VOLTAGE (V)	220	TOTAL FLUX (lm)	1432.0	h UP, DN (C0-180)	0.7, 49.4
NOMINAL FLUX (lm)	1432.04	CIE CLASS	DIRECT	h UP, DN (C180-360)	0.5, 49.4
LAMPS INSIDE	1	h up (%)	1.2	CIBSE SHR NOM	0.00
TEST VOLTAGE (V)	220	h down (%)	98.8	CIBSE SHR MAX	1.00



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	227.6	311.1	346.1	364.2	476.4	293.9	261.4	249.3	0~ 10	621.8	621.8	43.4,43.4
20	88.06	108.3	111.2	113.7	112.4	95.12	88.12	85.69	10~ 20	465.9	1088	76,76
30	10.42	17.11	22.55	24.42	30.82	17.78	13.40	13.85	20~ 30	259.3	1347	94.1,94.1
40	2.754	4.012	4.313	4.441	3.110	3.461	3.128	3.014	30~ 40	47.30	1394	97.4,97.4
50	0.4325	0.7400	0.8848	0.9223	1.025	0.8259	0.7489	0.7177	40~ 50	14.66	1409	98.4,98.4
60	0.1299	0.2549	0.2907	0.2901	0.2666	0.2731	0.2478	0.2480	50~ 60	3.981	1413	98.7,98.7
70	0.0174	0.0301	0.0628	0.0607	0.0200	0.0770	0.0392	0.0428	60~ 70	1.351	1414	98.8,98.8
80	0.0080	0.0140	0.0414	0.0353	0.0080	0.0167	0.0260	0.0342	70~ 80	0.3269	1415	98.8,98.8
90	0.0027	0.0027	0.0127	0.0080	0.0027	0.0074	0.0073	0.0107	80~ 90	0.1621	1415	98.8,98.8
100	0.0027	0.0033	0.0053	0.0033	0.0027	0.0047	0.0047	0.0060	90~100	0.0536	1415	98.8,98.8
110	0.0027	0.0047	0.0040	0.0053	0.0040	0.0040	0.0060	0.0053	100~110	0.0436	1415	98.8,98.8
120	0.0080	0.0134	0.0073	0.0120	0.0061	0.0080	0.0114	0.0073	110~120	0.0623	1415	98.8,98.8
130	0.0393	0.0355	0.0280	0.0314	0.0200	0.0233	0.0315	0.0280	120~130	0.1453	1415	98.8,98.8
140	0.1585	0.1284	0.1095	0.1110	0.0684	0.0920	0.1065	0.1060	130~140	0.4704	1416	98.8,98.8
150	0.6593	0.4851	0.4046	0.3866	0.2822	0.3665	0.3688	0.3895	140~150	1.377	1417	98.9,98.9
160	1.835	1.442	1.258	1.244	0.9536	1.148	1.060	1.089	150~160	3.550	1420	99.2,99.2
170	7.368	3.823	3.158	3.095	3.044	3.722	3.252	3.334	160~170	5.944	1426	99.6,99.6
180	8.583	9.976	10.20	10.24	8.719	10.07	10.02	10.32	170~180	5.639	1432	100,100
DEG	LUMINOUS INTENSITY:×10cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.7V I:0.0713A P:14.85W PF:0.9436 Freq:49.99Hz Lamp Flux:1432.04x1 lm		
NAME: LLS-M60GFXBX0600	TYPE:	WEIGHT:
SPEC.: LLS-M60GFXBX0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.: 600*50mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(°)	C0/180	C90/270
85	15	115
80	15	80
75	17	68
70	17	61
65	20	129
60	87	194
55	132	266
50	224	459
45	463	1002


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.7V I:0.0713A P:14.85W PF:0.9436 Freq:49.99Hz Lamp Flux:1432.04x1 lm		
NAME: LLS-M60GFXBX0600	TYPE:	WEIGHT:
SPEC.: LLS-M60GFXBX0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.13	1.11	1.09	1.10	1.09	1.07	1.06	1.05	1.04	1.02	1.01	1.01	.99	.98	.97	.96
2.0	1.08	1.05	1.02	1.06	1.03	1.01	1.03	1.00	.99	.99	.98	.96	.97	.95	.94	.93
3.0	1.03	.90	.97	1.02	.99	.96	.99	.96	.94	.97	.95	.93	.94	.93	.91	.90
4.0	.99	.95	.92	.98	.95	.92	.96	.93	.91	.94	.92	.90	.92	.90	.88	.87
5.0	.96	.92	.89	.95	.91	.88	.93	.90	.88	.92	.89	.87	.90	.88	.86	.85
6.0	.93	.89	.86	.92	.88	.85	.90	.87	.85	.89	.86	.84	.88	.85	.84	.82
7.0	.90	.86	.83	.89	.85	.83	.88	.85	.82	.87	.84	.82	.86	.83	.81	.80
8.0	.87	.83	.81	.87	.83	.80	.86	.82	.80	.85	.82	.80	.84	.81	.79	.78
9.0	.85	.81	.78	.84	.81	.78	.84	.80	.78	.83	.80	.78	.82	.79	.77	.76
10.0	.83	.79	.76	.82	.79	.76	.82	.78	.76	.81	.78	.76	.80	.78	.76	.75



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.7V I:0.0713A P:14.85W PF:0.9436 Freq:49.99Hz Lamp Flux:1432.04x1 lm		
NAME: LLS-M60GFXBX0600	TYPE:	WEIGHT:
SPEC.: LLS-M60GFXBX0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)									
0.0																
1.0	.135	.077	.024	.128	.073	.023	.115	.066	.021	.103	.059	.019	.091	.053	.017	
2.0	.124	.068	.021	.119	.065	.020	.108	.060	.019	.098	.055	.017	.089	.050	.016	
3.0	.116	.062	.018	.111	.059	.018	.102	.055	.017	.094	.051	.016	.086	.047	.015	
4.0	.108	.056	.017	.104	.055	.016	.097	.051	.015	.089	.048	.014	.083	.045	.014	
5.0	.102	.052	.015	.098	.050	.015	.092	.048	.014	.086	.045	.013	.080	.043	.013	
6.0	.096	.048	.014	.093	.047	.014	.087	.045	.013	.082	.043	.013	.077	.041	.012	
7.0	.091	.045	.013	.089	.044	.013	.084	.042	.012	.079	.040	.012	.074	.039	.011	
8.0	.087	.042	.012	.084	.042	.012	.080	.040	.011	.076	.038	.011	.072	.037	.011	
9.0	.083	.040	.011	.081	.039	.011	.077	.038	.011	.073	.037	.010	.070	.035	.010	
10.0	.079	.038	.011	.077	.037	.010	.074	.036	.010	.070	.035	.010	.067	.034	.010	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.200	.200	.200	.171	.171	.171	.116	.116	.116	.067	.067	.067	.021	.021	.021	
1.0	.177	.167	.158	.152	.143	.136	.104	.099	.094	.060	.057	.055	.019	.018	.018	
2.0	.159	.142	.128	.136	.122	.110	.093	.085	.077	.054	.049	.045	.017	.016	.015	
3.0	.144	.123	.105	.124	.106	.091	.085	.074	.064	.049	.043	.038	.016	.014	.012	
4.0	.132	.107	.089	.113	.093	.077	.078	.065	.054	.045	.038	.032	.014	.012	.011	
5.0	.121	.095	.076	.104	.082	.066	.072	.057	.047	.041	.034	.028	.013	.011	.009	
6.0	.112	.085	.066	.096	.074	.057	.066	.051	.040	.039	.030	.024	.012	.010	.008	
7.0	.104	.077	.057	.090	.066	.050	.062	.047	.035	.036	.027	.021	.012	.009	.007	
8.0	.098	.070	.051	.084	.061	.044	.058	.043	.031	.034	.025	.019	.011	.008	.006	
9.0	.092	.064	.046	.079	.056	.040	.055	.039	.028	.032	.023	.017	.010	.008	.006	
10.0	.087	.059	.041	.075	.052	.036	.052	.036	.026	.030	.021	.015	.010	.007	.005	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.7V I:0.0713A P:14.85W PF:0.9436 Freq:49.99Hz Lamp Flux:1432.04x1 lm											
NAME: LLS-M60GFXBX0600					TYPE:			WEIGHT:			
SPEC.:LLS-M60GFXBX0600-T15NW8B-DC					DIM.: 600*50*45mm			SERIAL No.:			
MFR.: COLORS					SUR.: 600*50mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions											
Viewed crosswise					Viewed endwise						
x = 2H y = 2H	-1.8	-1.1	-1.5	-1.0	-0.8	0.8	1.4	1.0	1.6	1.8	
	3H	-1.9	-1.3	-1.7	-1.1	-0.9	0.7	1.3	0.9	1.5	1.7
	4H	-2.0	-1.4	-1.7	-1.2	-1.0	0.6	1.2	0.9	1.4	1.6
	6H	-2.1	-1.5	-1.8	-1.3	-1.0	0.5	1.1	0.8	1.3	1.6
	8H	-2.1	-1.6	-1.8	-1.3	-1.1	0.5	1.0	0.8	1.3	1.5
	12H	-2.2	-1.7	-1.8	-1.4	-1.1	0.5	0.9	0.8	1.2	1.5
4H	2H	-1.9	-1.4	-1.6	-1.1	-0.9	0.6	1.2	0.9	1.4	1.6
	3H	-2.1	-1.6	-1.8	-1.3	-1.0	0.5	0.9	0.8	1.2	1.5
	4H	-2.2	-1.7	-1.8	-1.4	-1.1	0.4	0.8	0.7	1.1	1.4
	6H	-2.3	-1.9	-1.9	-1.5	-1.2	0.3	0.7	0.7	1.0	1.4
	8H	-2.3	-2.0	-1.9	-1.6	-1.2	0.2	0.6	0.6	1.0	1.4
	12H	-2.4	-2.1	-2.0	-1.7	-1.3	0.2	0.5	0.6	0.9	1.3
8H	4H	-2.3	-2.0	-1.9	-1.6	-1.2	0.2	0.6	0.6	0.9	1.3
	6H	-2.5	-2.1	-2.0	-1.7	-1.3	0.1	0.4	0.6	0.8	1.3
	8H	-2.5	-2.2	-2.1	-1.8	-1.3	0.1	0.3	0.5	0.8	1.2
	12H	-2.6	-2.3	-2.1	-1.9	-1.4	0.0	0.3	0.5	0.7	1.2
12H	4H	-2.4	-2.1	-2.0	-1.7	-1.3	0.1	0.5	0.6	0.9	1.3
	6H	-2.5	-2.2	-2.1	-1.8	-1.3	0.1	0.3	0.5	0.8	1.2
	8H	-2.6	-2.3	-2.1	-1.9	-1.4	0.0	0.2	0.5	0.7	1.2
Variations with the observer position at spacings:											
S = 1.0H	+ 2.6 / - 9.3					+ 2.8 / - 7.7					
1.5H	+ 4.5 / - 7.3					+ 4.7 / - 6.7					
2.0H	+ 4.8 / - 6.1					+ 6.0 / - 4.3					

CIE Pub.117, 1432 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 1.2)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.7V I:0.0713A P:14.85W PF:0.9436 Freq:49.99Hz Lamp Flux:1432.04x1 lm		
NAME: LLS-M60GFXBX0600	TYPE:	WEIGHT:
SPEC.: LLS-M60GFXBX0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.: 600*50mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	90	84	81	89	84	81	89	84	80	77
0.80	97	92	88	96	91	88	95	91	88	84
1.00	101	96	92	100	95	92	98	95	91	88
1.25	104	100	97	103	99	96	101	98	95	91
1.50	107	103	100	106	102	99	103	100	98	93
2.00	109	105	102	108	104	102	105	102	100	95
2.50	111	107	104	109	106	103	106	103	101	95
3.00	112	109	106	110	107	105	107	105	103	96
4.00	114	112	109	112	110	108	108	106	105	98
5.00	115	113	112	113	111	110	109	108	107	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:220.7V I:0.0713A P:14.85W PF:0.9436 Freq:49.99Hz Lamp Flux:1432.04x1 lm		
NAME: LLS-M60GFXBX0600	TYPE:	WEIGHT:
SPEC.: LLS-M60GFXBX0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.: 600*50mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.7V I:0.0713A P:14.85W PF:0.9436 Freq:49.99Hz Lamp Flux:1432.04x1 lm		
NAME: LLS-M60GFXBX0600	TYPE:	WEIGHT:
SPEC.: LLS-M60GFXBX0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.: 600*50mm	Shielding Angle:

Flux out:336.8 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:220.7V I:0.0713A P:14.85W PF:0.9436 Freq:49.99Hz Lamp Flux:1432.04x1 lm		
NAME: LLS-M60GFXBX0600	TYPE:	WEIGHT:
SPEC.: LLS-M60GFXBX0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.: 600*50mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2020-09-15

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

deg Range: 0 - 180DEG
deg Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.7V I:0.0713A P:14.85W PF:0.9436 Freq:49.99Hz Lamp Flux:1432.04x1 lm		
NAME: LLS-M60GFXBX0600	TYPE:	WEIGHT:
SPEC.: LLS-M60GFXBX0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.: 600*50mm	Shielding Angle:

Table--1

UNIT: x10cd

C (DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	1195	1400	1438	1436	1195	1400	1438	1436										
5	490	755	905	958	1276	857	739	691										
10	228	311	346	364	476	294	261	249										
15	140	172	179	180	186	148	138	134										
20	88.1	108	111	114	112	95.1	88.1	85.7										
25	36.4	65.1	71.7	74.0	70.8	56.7	49.7	47.1										
30	10.4	17.1	22.5	24.4	30.8	17.8	13.4	13.9										
35	4.51	6.75	7.56	7.91	8.39	5.82	4.99	4.79										
40	2.75	4.01	4.31	4.44	3.11	3.46	3.13	3.01										
45	0.98	1.84	2.13	2.21	2.24	1.83	1.61	1.54										
50	0.43	0.74	0.88	0.92	1.03	0.83	0.75	0.72										
55	0.23	0.40	0.46	0.47	0.51	0.44	0.42	0.41										
60	0.13	0.25	0.29	0.29	0.27	0.27	0.25	0.25										
65	0.02	0.14	0.16	0.17	0.15	0.20	0.13	0.12										
70	0.02	0.03	0.06	0.06	0.02	0.08	0.04	0.04										
75	0.01	0.02	0.05	0.05	0.01	0.02	0.04	0.04										
80	0.01	0.01	0.04	0.04	0.01	0.02	0.03	0.03										
85	0.00	0.01	0.03	0.02	0.00	0.01	0.02	0.02										
90	0.00	0.00	0.01	0.01	0.00	0.01	0.01	0.01										
95	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.01										
100	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.01										
105	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01										
110	0.00	0.00	0.00	0.01	0.00	0.00	0.01	0.01										
115	0.00	0.01	0.00	0.01	0.00	0.00	0.01	0.01										
120	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.01										
125	0.02	0.02	0.01	0.02	0.01	0.01	0.02	0.01										
130	0.04	0.04	0.03	0.03	0.02	0.02	0.03	0.03										
135	0.08	0.07	0.06	0.06	0.04	0.05	0.06	0.05										
140	0.16	0.13	0.11	0.11	0.07	0.09	0.11	0.11										
145	0.32	0.24	0.20	0.19	0.13	0.18	0.19	0.19										
150	0.66	0.49	0.40	0.39	0.28	0.37	0.37	0.39										
155	1.09	0.90	0.79	0.77	0.58	0.68	0.68	0.70										
160	1.83	1.44	1.26	1.24	0.95	1.15	1.06	1.09										
165	3.33	2.28	1.94	1.91	1.62	1.96	1.74	1.79										
170	7.37	3.82	3.16	3.09	3.04	3.72	3.25	3.33										
175	9.81	6.91	6.14	6.05	6.10	7.15	6.67	6.96										
180	8.58	9.98	10.2	10.2	8.72	10.1	10.0	10.3										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks: