


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.8V I:0.0772A P:15.30W PF:0.8972 Freq:49.99Hz Lamp Flux:1256.78x1 lm		
NAME: LLS-M60GHXB0600	TYPE:	WEIGHT:
SPEC.:LLS-M60GHXB0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 82.14 lm/W			
MODEL	LLS-M60GHXB0600	I _{max} (cd)	3081	S/MH(C0/180)	0.60
NOMINAL POWER(W)	12.5	LOR(%)	100.0	S/MH(C90/270)	0.61
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	1256.8	h UP,DN(C0-180)	0.7,48.8
NOMINAL FLUX(lm)	1256.78	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.5,50.1
LAMPS INSIDE	1	h up(%)	1.2	CIBSE SHR NOM	0.50
TEST VOLTAGE(V)	220	h down(%)	98.8	CIBSE SHR MAX	0.60



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	2722	2752	2677	2602	2659	2598	2680	2745	0- 10	274.1	274.1	21.8,21.8
20	1406	1463	1308	1186	1344	1284	1471	1618	10- 20	575.3	849.4	67.6,67.6
30	209.3	215.1	181.3	151.2	165.1	155.9	209.9	269.6	20- 30	317.9	1167	92.9,92.9
40	38.60	46.86	42.61	37.37	23.63	27.63	29.73	34.31	30- 40	50.14	1218	96.9,96.9
50	9.543	13.00	12.10	9.819	7.045	8.741	9.919	12.17	40- 50	15.83	1233	98.1,98.1
60	2.601	3.868	4.371	3.068	2.082	3.021	4.058	3.870	50- 60	5.353	1239	98.6,98.6
70	0.2742	1.009	1.684	0.6145	0.1602	0.6540	1.369	1.365	60- 70	1.930	1241	98.7,98.7
80	0.1337	0.2527	1.183	0.3940	0.0734	0.3407	0.8345	0.7956	70- 80	0.6763	1241	98.8,98.8
90	0.0335	0.0468	0.3212	0.0534	0.0267	0.0807	0.6627	0.2748	80- 90	0.4921	1242	98.8,98.8
100	0.0200	0.0468	0.0534	0.0534	0.0267	0.0534	0.0468	0.0468	90-100	0.0700	1242	98.8,98.8
110	0.0200	0.0534	0.0468	0.0733	0.0467	0.0534	0.0601	0.0401	100-110	0.0467	1242	98.8,98.8
120	0.0596	0.1270	0.0802	0.1472	0.0938	0.0804	0.1340	0.0664	110-120	0.0634	1242	98.8,98.8
130	0.2863	0.3808	0.3869	0.4688	0.3215	0.3000	0.3877	0.2270	120-130	0.1739	1242	98.8,98.8
140	1.192	1.238	1.328	1.451	1.026	1.039	1.049	0.8870	130-140	0.5161	1243	98.9,98.9
150	5.288	4.799	5.129	5.601	4.523	4.200	3.452	3.468	140-150	1.457	1244	99.99
160	16.65	15.37	16.60	17.47	14.73	14.97	11.97	11.77	150-160	4.157	1248	99.3,99.3
170	29.58	25.52	26.92	28.19	27.03	26.59	24.24	21.88	160-170	5.747	1254	99.8,99.8
180	33.06	34.09	34.65	33.86	33.11	34.03	34.84	33.85	170-180	2.777	1257	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.8V I:0.0772A P:15.30W PF:0.8972 Freq:49.99Hz Lamp Flux:1256.78x1 lm		
NAME: LLS-M60GHXBX0600	TYPE:	WEIGHT:
SPEC.:LLS-M60GHXBX0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	26	676
80	26	227
75	23	178
70	27	164
65	93	206
60	173	291
55	277	400
50	495	628
45	976	1115


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.8V I:0.0772A P:15.30W PF:0.8972 Freq:49.99Hz Lamp Flux:1256.78x1 lm		
NAME: LLS-M60GHXB0600	TYPE:	WEIGHT:
SPEC.:LLS-M60GHXB0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.12	1.10	1.08	1.10	1.08	1.06	1.05	1.04	1.03	1.02	1.00	.99	.98	.97	.96	.95
2.0	1.06	1.03	.00	1.04	1.01	.99	1.01	.98	.96	.98	.96	.94	.95	.93	.92	.90
3.0	1.01	.97	.93	.99	.96	.93	.96	.93	.91	.94	.92	.89	.92	.90	.88	.87
4.0	.96	.91	.88	.95	.91	.87	.93	.89	.86	.91	.88	.85	.89	.86	.84	.83
5.0	.92	.87	.84	.91	.86	.83	.89	.85	.82	.87	.84	.82	.86	.83	.81	.79
6.0	.88	.83	.80	.87	.82	.79	.85	.82	.79	.84	.81	.78	.83	.80	.77	.76
7.0	.84	.79	.76	.83	.79	.76	.82	.78	.75	.81	.78	.75	.80	.77	.74	.73
8.0	.81	.76	.73	.80	.76	.73	.79	.75	.72	.78	.75	.72	.77	.74	.72	.71
9.0	.78	.73	.70	.77	.73	.70	.76	.72	.70	.76	.72	.69	.75	.71	.69	.68
10.0	.75	.70	.67	.75	.70	.67	.74	.70	.67	.73	.69	.67	.72	.69	.67	.66



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.8V I:0.0772A P:15.30W PF:0.8972 Freq:49.99Hz Lamp Flux:1256.78x1 lm		
NAME: LLS-M60GHXB0600	TYPE:	WEIGHT:
SPEC.:LLS-M60GHXB0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0														
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
rfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.150	.086	.027	.143	.082	.026	.130	.075	.024	.118	.068	.022	.107	.062	.020															
2.0	.141	.077	.024	.135	.074	.023	.124	.069	.021	.114	.064	.020	.104	.059	.019															
3.0	.132	.070	.021	.127	.068	.020	.118	.064	.019	.109	.060	.018	.101	.056	.017															
4.0	.125	.065	.019	.120	.063	.019	.112	.060	.018	.105	.056	.017	.098	.053	.016															
5.0	.118	.060	.017	.114	.059	.017	.107	.056	.016	.101	.053	.016	.095	.051	.015															
6.0	.112	.056	.016	.109	.055	.016	.103	.053	.015	.097	.051	.015	.092	.049	.014															
7.0	.107	.053	.015	.104	.052	.015	.099	.050	.014	.094	.048	.014	.089	.046	.014															
8.0	.102	.050	.014	.100	.049	.014	.095	.048	.014	.091	.046	.013	.087	.044	.013															
9.0	.098	.047	.013	.096	.047	.013	.092	.045	.013	.088	.044	.013	.084	.043	.012															
10.0	.094	.045	.013	.092	.045	.012	.088	.043	.012	.085	.042	.012	.082	.041	.012															

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.200	.200	.200	.171	.171	.171	.116	.116	.116	.067	.067	.067	.021	.021	.021	
1.0	.178	.167	.156	.153	.143	.134	.104	.098	.093	.060	.057	.054	.019	.018	.017	
2.0	.161	.142	.126	.138	.122	.109	.095	.084	.076	.055	.049	.044	.018	.016	.014	
3.0	.147	.123	.103	.126	.106	.089	.087	.074	.063	.050	.043	.037	.016	.014	.012	
4.0	.135	.108	.086	.116	.093	.075	.080	.065	.053	.046	.038	.031	.015	.012	.010	
5.0	.126	.095	.073	.108	.083	.064	.074	.058	.045	.043	.034	.027	.014	.011	.009	
6.0	.117	.086	.063	.101	.074	.055	.070	.052	.039	.040	.031	.023	.013	.010	.008	
7.0	.110	.078	.055	.095	.067	.048	.065	.047	.034	.038	.028	.020	.012	.009	.007	
8.0	.104	.071	.049	.090	.062	.043	.062	.043	.030	.036	.026	.018	.012	.008	.006	
9.0	.099	.066	.044	.085	.057	.038	.059	.040	.027	.034	.024	.016	.011	.008	.005	
10.0	.094	.061	.039	.081	.053	.034	.056	.037	.024	.033	.022	.015	.011	.007	.005	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.8V I:0.0772A P:15.30W PF:0.8972 Freq:49.99Hz Lamp Flux:1256.78x1 lm											
NAME: LLS-M60GHXB0600						TYPE:		WEIGHT:			
SPEC.:LLS-M60GHXB0600-T15NW8B-DC						DIM.: 600*50*45mm		SERIAL No.:			
MFR.: COLORS						SUR.:600*50mm		Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	2.4	3.2	2.7	3.3	3.5	2.5	3.3	2.7	3.4	3.6
	3H	2.3	3.0	2.5	3.2	3.4	2.4	3.1	2.7	3.3	3.5
	4H	2.2	2.8	2.5	3.1	3.3	2.4	3.1	2.7	3.3	3.5
	6H	2.1	2.7	2.4	3.0	3.2	2.4	3.0	2.7	3.3	3.5
	8H	2.1	2.7	2.4	2.9	3.2	2.4	3.0	2.7	3.3	3.5
	12H	2.0	2.6	2.3	2.9	3.2	2.6	3.2	2.9	3.4	3.7
4H	2H	2.3	2.9	2.5	3.1	3.4	2.3	3.0	2.6	3.2	3.5
	3H	2.1	2.7	2.4	2.9	3.2	2.3	2.8	2.6	3.1	3.4
	4H	2.0	2.5	2.4	2.8	3.2	2.2	2.7	2.6	3.1	3.4
	6H	1.9	2.4	2.3	2.7	3.1	2.2	2.7	2.6	3.1	3.4
	8H	1.8	2.3	2.3	2.6	3.0	2.3	2.7	2.7	3.1	3.5
	12H	1.8	2.2	2.2	2.6	3.0	2.6	3.0	3.0	3.4	3.8
8H	4H	1.9	2.3	2.3	2.6	3.0	2.1	2.5	2.5	2.9	3.3
	6H	1.7	2.1	2.2	2.5	2.9	2.1	2.5	2.6	2.9	3.3
	8H	1.7	2.0	2.2	2.4	2.9	2.2	2.5	2.6	2.9	3.4
	12H	1.6	1.9	2.1	2.4	2.8	2.7	2.9	3.1	3.4	3.9
12H	4H	1.8	2.2	2.2	2.6	3.0	2.0	2.4	2.5	2.8	3.2
	6H	1.7	2.0	2.2	2.4	2.9	2.0	2.4	2.5	2.8	3.3
	8H	1.6	1.9	2.1	2.4	2.9	2.1	2.4	2.6	2.8	3.3
Variations with the observer position at spacings:											
S = 1.0H		+ 2.3 / - 7.4					+ 2.1 / - 4.6				
1.5H		+ 3.5 / - 5.1					+ 3.5 / - 4.1				
2.0H		+ 4.8 / - 5.2					+ 4.1 / - 2.8				

CIE Pub.117, 1257 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.8)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.8V I:0.0772A P:15.30W PF:0.8972 Freq:49.99Hz Lamp Flux:1256.78x1 lm		
NAME: LLS-M60GHXB0600	TYPE:	WEIGHT:
SPEC.:LLS-M60GHXB0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	90	84	80	89	84	80	88	83	80	77
0.80	97	91	88	96	91	88	95	90	87	84
1.00	101	95	92	100	95	92	98	95	91	87
1.25	104	99	96	103	99	96	101	98	95	91
1.50	107	102	99	105	102	99	103	100	98	93
2.00	109	105	102	108	104	101	105	102	100	94
2.50	111	107	104	109	106	103	106	103	101	95
3.00	112	109	106	110	107	105	107	105	103	96
4.00	114	111	109	112	110	108	108	106	105	98
5.00	115	113	111	113	111	110	109	108	106	99
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.8V I:0.0772A P:15.30W PF:0.8972 Freq:49.99Hz Lamp Flux:1256.78x1 lm		
NAME: LLS-M60GHXB0600	TYPE:	WEIGHT:
SPEC.:LLS-M60GHXB0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.8V I:0.0772A P:15.30W PF:0.8972 Freq:49.99Hz Lamp Flux:1256.78x1 lm		
NAME: LLS-M60GHXB0600	TYPE:	WEIGHT:
SPEC.:LLS-M60GHXB0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

Flux out:796.0 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:220.8V I:0.0772A P:15.30W PF:0.8972 Freq:49.99Hz Lamp Flux:1256.78x1 lm		
NAME: LLS-M60GHXBX0600	TYPE:	WEIGHT:
SPEC.:LLS-M60GHXBX0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

deg Range: 0 - 180DEG
deg Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.8V I:0.0772A P:15.30W PF:0.8972 Freq:49.99Hz Lamp Flux:1256.78x1 lm		
NAME: LLS-M60GHXB0600	TYPE:	WEIGHT:
SPEC.:LLS-M60GHXB0600-T15NW8B-DC	DIM.: 600*50*45mm	SERIAL No.:
MFR.: COLORS	SUR.:600*50mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	3081	3073	3066	3069	3081	3073	3066	3069										
5	2971	2997	2966	2944	2983	2936	2949	2984										
10	2722	2752	2677	2602	2659	2598	2680	2745										
15	2171	2238	2092	1969	2088	2033	2206	2310										
20	1406	1463	1308	1186	1344	1284	1471	1618										
25	730	781	620	528	698	642	781	882										
30	209	215	181	151	165	156	210	270										
35	75.9	85.6	75.3	64.9	47.6	52.9	65.6	75.1										
40	38.6	46.9	42.6	37.4	23.6	27.6	29.7	34.3										
45	20.7	26.6	23.7	19.8	13.5	16.0	17.4	20.9										
50	9.54	13.0	12.1	9.82	7.04	8.74	9.92	12.2										
55	4.77	6.71	6.88	5.23	3.79	4.93	6.17	6.63										
60	2.60	3.87	4.37	3.07	2.08	3.02	4.06	3.87										
65	1.18	2.29	2.61	1.72	0.82	1.81	2.66	2.41										
70	0.27	1.01	1.68	0.61	0.16	0.65	1.37	1.36										
75	0.18	0.39	1.38	0.53	0.08	0.48	1.11	0.83										
80	0.13	0.25	1.18	0.39	0.07	0.34	0.83	0.80										
85	0.07	0.11	1.77	0.23	0.03	0.21	0.78	0.72										
90	0.03	0.05	0.32	0.05	0.03	0.08	0.66	0.27										
95	0.02	0.05	0.12	0.05	0.03	0.06	0.07	0.05										
100	0.02	0.05	0.05	0.05	0.03	0.05	0.05	0.05										
105	0.02	0.05	0.05	0.05	0.03	0.05	0.06	0.04										
110	0.02	0.05	0.05	0.07	0.05	0.05	0.06	0.04										
115	0.02	0.08	0.05	0.09	0.06	0.05	0.08	0.04										
120	0.06	0.13	0.08	0.15	0.09	0.08	0.13	0.07										
125	0.13	0.21	0.19	0.27	0.16	0.17	0.23	0.10										
130	0.29	0.38	0.39	0.47	0.32	0.30	0.39	0.23										
135	0.61	0.69	0.73	0.81	0.58	0.59	0.64	0.51										
140	1.19	1.24	1.33	1.45	1.03	1.04	1.05	0.89										
145	2.40	2.27	2.49	2.71	1.98	1.96	1.79	1.66										
150	5.29	4.80	5.13	5.60	4.52	4.20	3.45	3.47										
155	10.3	9.66	10.5	10.7	8.81	8.62	6.98	7.02										
160	16.7	15.4	16.6	17.5	14.7	15.0	12.0	11.8										
165	23.6	21.1	22.4	24.1	21.1	21.4	17.7	17.0										
170	29.6	25.5	26.9	28.2	27.0	26.6	24.2	21.9										
175	31.7	29.8	31.5	31.6	30.0	30.6	30.3	27.6										
180	33.1	34.1	34.6	33.9	33.1	34.0	34.8	33.9										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: