


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.8V I:0.1234A P:26.62W PF:0.9773 Freq:49.99Hz Lamp Flux:3122.83x1 lm		
NAME: LLS-M60LAXBX1200	TYPE:	WEIGHT:
SPEC.:LLS-M60LAXBX1200-T27NW8B-DC	DIM.: 1200*30*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1200*30mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 117.33 lm/W			
MODEL	LLS-M60LAXBX1200	I _{max} (cd)	1755	S/MH(C0/180)	1.20
NOMINAL POWER(W)	26.6	LOR(%)	100.0	S/MH(C90/270)	1.15
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	3122.8	h UP,DN(C0-180)	0.7,52.6
NOMINAL FLUX(lm)	3122.83	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,46.0
LAMPS INSIDE	1	h up(%)	1.4	CIBSE SHR NOM	1.00
TEST VOLTAGE(V)	220	h down(%)	98.6	CIBSE SHR MAX	1.05



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	1751	1719	1610	1456	1414	1478	1644	1739	0- 10	157.3	157.3	5.04,5.04
20	1608	1605	1446	1016	834.8	1061	1506	1637	10- 20	416.0	573.3	18.4,18.4
30	1376	1365	1220	591.2	450.1	624.5	1283	1398	20- 30	544.0	1117	35.8,35.8
40	1126	1096	933.8	364.9	296.2	385.8	1007	1121	30- 40	569.3	1687	54,54
50	766.2	859.6	644.8	250.3	235.1	261.3	716.3	881.0	40- 50	526.1	2213	70.9,70.9
60	421.5	584.7	407.4	179.8	178.9	185.9	463.3	597.9	50- 60	425.3	2638	84.5,84.5
70	128.7	320.7	224.2	107.8	120.9	112.2	263.5	321.3	60- 70	283.2	2921	93.5,93.5
80	6.112	61.01	90.62	37.27	42.18	44.90	117.1	65.16	70- 80	134.8	3056	97.9,97.9
90	1.112	4.330	7.846	3.393	1.007	3.060	11.62	2.392	80- 90	22.96	3079	98.6,98.6
100	1.214	2.358	5.922	4.579	1.098	4.070	5.140	2.962	90-100	3.677	3083	98.7,98.7
110	1.981	3.150	4.464	6.660	2.829	5.979	3.688	3.565	100-110	3.562	3086	98.8,98.8
120	2.677	4.549	6.539	8.707	5.282	7.834	5.672	3.713	110-120	4.766	3091	99,99
130	3.472	5.037	8.811	10.49	8.264	9.748	8.045	4.187	120-130	5.750	3097	99.2,99.2
140	4.575	6.182	11.38	12.53	11.32	11.82	10.60	5.147	130-140	6.323	3103	99.4,99.4
150	7.099	8.278	14.29	15.32	13.66	14.85	13.41	7.396	140-150	6.499	3110	99.6,99.6
160	12.54	12.04	18.10	18.64	16.48	18.30	17.24	11.64	150-160	6.241	3116	99.8,99.8
170	18.99	18.29	21.02	21.99	19.33	21.55	20.49	18.33	160-170	4.993	3121	99.9,99.9
180	20.61	23.42	23.10	23.79	20.67	23.28	23.23	23.77	170-180	2.009	3123	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-15

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.8V I:0.1234A P:26.62W PF:0.9773 Freq:49.99Hz Lamp Flux:3122.83x1 lm		
NAME: LLS-M60LAXBX1200	TYPE:	WEIGHT:
SPEC.:LLS-M60LAXBX1200-T27NW8B-DC	DIM.: 1200*30*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1200*30mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	778	12767
80	978	14496
75	4135	16212
70	10449	18209
65	18032	20323
60	23418	22635
55	28433	25179
50	33111	27864
45	37319	30856


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.8V I:0.1234A P:26.62W PF:0.9773 Freq:49.99Hz Lamp Flux:3122.83x1 lm		
NAME: LLS-M60LAXBX1200	TYPE:	WEIGHT:
SPEC.:LLS-M60LAXBX1200-T27NW8B-DC	DIM.: 1200*30*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1200*30mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.99
1.0	1.06	1.02	.99	1.03	.90	.97	.99	.96	.94	.95	.93	.91	.91	.89	.88	.86
2.0	.94	.88	.83	.92	.86	.81	.88	.83	.79	.85	.81	.77	.81	.78	.76	.73
3.0	.84	.76	.70	.82	.75	.70	.79	.73	.68	.76	.71	.67	.73	.69	.66	.64
4.0	.75	.67	.61	.74	.66	.60	.71	.64	.59	.69	.63	.58	.66	.62	.58	.56
5.0	.68	.59	.53	.67	.59	.53	.64	.58	.52	.62	.56	.52	.60	.55	.51	.49
6.0	.62	.53	.47	.61	.53	.47	.59	.52	.47	.57	.51	.46	.55	.50	.46	.44
7.0	.56	.48	.42	.55	.48	.42	.54	.47	.42	.52	.46	.41	.51	.45	.41	.39
8.0	.52	.44	.38	.51	.43	.38	.50	.43	.38	.48	.42	.38	.47	.42	.37	.36
9.0	.48	.40	.35	.47	.40	.35	.46	.39	.35	.45	.39	.34	.44	.38	.34	.32
10.0	.44	.37	.32	.44	.37	.32	.43	.36	.32	.42	.36	.32	.41	.35	.31	.30



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.8V I:0.1234A P:26.62W PF:0.9773 Freq:49.99Hz Lamp Flux:3122.83x1 lm		
NAME: LLS-M60LAXBX1200	TYPE:	WEIGHT:
SPEC.:LLS-M60LAXBX1200-T27NW8B-DC	DIM.: 1200*30*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1200*30mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.268	.152	.048	.261	.149	.047	.247	.142	.045	.234	.135	.043	.222	.129	.042	
2.0	.257	.141	.043	.251	.138	.043	.239	.133	.041	.227	.128	.040	.217	.123	.039	
3.0	.241	.128	.038	.236	.126	.038	.225	.122	.037	.215	.118	.036	.206	.114	.035	
4.0	.225	.117	.034	.220	.115	.034	.211	.112	.033	.202	.108	.033	.194	.105	.032	
5.0	.210	.107	.031	.206	.105	.031	.197	.103	.030	.189	.100	.030	.182	.097	.029	
6.0	.196	.098	.028	.192	.097	.028	.185	.095	.028	.178	.092	.027	.171	.090	.027	
7.0	.184	.091	.026	.180	.090	.026	.173	.088	.025	.167	.086	.025	.161	.084	.025	
8.0	.173	.084	.024	.169	.083	.024	.163	.082	.023	.158	.080	.023	.152	.078	.023	
9.0	.162	.079	.022	.160	.078	.022	.154	.076	.022	.149	.075	.021	.144	.073	.021	
10.0	.153	.074	.020	.151	.073	.020	.146	.071	.020	.141	.070	.020	.137	.069	.020	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.201	.201	.201	.172	.172	.172	.117	.117	.117	.067	.067	.067	.022	.022	.022	
1.0	.188	.167	.148	.161	.144	.128	.110	.099	.088	.063	.057	.051	.020	.018	.017	
2.0	.178	.143	.113	.153	.123	.098	.105	.085	.068	.060	.050	.040	.019	.016	.013	
3.0	.170	.125	.089	.146	.108	.077	.100	.075	.054	.058	.044	.032	.019	.014	.010	
4.0	.162	.111	.073	.139	.096	.063	.096	.067	.045	.055	.039	.026	.018	.013	.009	
5.0	.154	.101	.061	.133	.087	.053	.091	.061	.038	.053	.036	.022	.017	.012	.007	
6.0	.147	.092	.053	.127	.080	.046	.087	.056	.032	.051	.033	.019	.016	.011	.006	
7.0	.141	.085	.046	.121	.074	.040	.084	.052	.029	.049	.031	.017	.016	.010	.006	
8.0	.135	.079	.041	.116	.069	.036	.080	.048	.026	.047	.029	.015	.015	.009	.005	
9.0	.129	.074	.038	.111	.065	.033	.077	.045	.023	.045	.027	.014	.015	.009	.005	
10.0	.123	.070	.035	.106	.061	.030	.074	.043	.021	.043	.025	.013	.014	.008	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.8V I:0.1234A P:26.62W PF:0.9773 Freq:49.99Hz Lamp Flux:3122.83x1 lm											
NAME: LLS-M60LAXBX1200					TYPE:			WEIGHT:			
SPEC.:LLS-M60LAXBX1200-T27NW8B-DC					DIM.: 1200*30*25mm			SERIAL No.:			
MFR.: COLORS					SUR.:1200*30mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions											
					Viewed crosswise			Viewed endwise			
x = 2H y = 2H	21.3	22.6	21.6	22.9	23.1	20.9	22.3	21.2	22.5	22.7	
	3H	21.8	23.1	22.1	23.3	23.6	21.9	23.2	22.2	23.4	23.7
	4H	21.8	23.0	22.1	23.3	23.5	22.2	23.4	22.6	23.7	24.0
	6H	21.7	22.8	22.1	23.1	23.4	22.5	23.6	22.8	23.9	24.2
	8H	21.7	22.8	22.0	23.1	23.4	22.5	23.6	22.9	23.9	24.2
	12H	21.6	22.7	22.0	23.0	23.3	22.5	23.6	22.9	23.9	24.2
4H	2H	21.9	23.1	22.2	23.3	23.6	21.6	22.8	21.9	23.1	23.4
	3H	22.6	23.6	23.0	24.0	24.3	22.8	23.8	23.2	24.1	24.5
	4H	22.7	23.7	23.1	24.0	24.4	23.2	24.2	23.6	24.5	24.9
	6H	22.7	23.5	23.1	23.9	24.3	23.5	24.3	23.9	24.7	25.1
	8H	22.6	23.4	23.1	23.8	24.2	23.6	24.3	24.0	24.7	25.1
	12H	22.6	23.3	23.0	23.7	24.1	23.6	24.3	24.1	24.7	25.2
8H	4H	22.9	23.7	23.4	24.1	24.5	23.4	24.2	23.8	24.6	25.0
	6H	22.9	23.6	23.4	24.0	24.5	23.7	24.4	24.2	24.8	25.3
	8H	22.9	23.5	23.4	23.9	24.4	23.8	24.4	24.3	24.8	25.3
	12H	22.9	23.3	23.4	23.8	24.3	23.9	24.4	24.4	24.9	25.4
12H	4H	22.9	23.6	23.4	24.0	24.5	23.4	24.1	23.8	24.5	24.9
	6H	22.9	23.5	23.4	23.9	24.4	23.7	24.3	24.2	24.7	25.2
	8H	22.9	23.4	23.4	23.8	24.3	23.8	24.3	24.3	24.8	25.3
Variations with the observer position at spacings:											
S = 1.0H	+ 0.4 / - 0.5					+ 0.3 / - 0.4					
1.5H	+ 0.3 / - 0.5					+ 0.3 / - 0.6					
2.0H	+ 0.5 / - 1.2					+ 0.4 / - 1.0					

CIE Pub.117, 3123 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 4.0)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.8V I:0.1234A P:26.62W PF:0.9773 Freq:49.99Hz Lamp Flux:3122.83x1 lm		
NAME: LLS-M60LAXBX1200	TYPE:	WEIGHT:
SPEC.:LLS-M60LAXBX1200-T27NW8B-DC	DIM.: 1200*30*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1200*30mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	63	52	46	62	52	46	61	52	46	40
0.80	73	62	56	72	62	56	70	61	55	49
1.00	81	71	64	80	70	64	77	71	63	57
1.25	87	78	72	86	77	71	83	76	70	64
1.50	92	83	77	90	82	77	87	81	75	68
2.00	98	91	85	96	89	84	93	87	82	75
2.50	101	95	89	99	93	88	96	90	86	78
3.00	104	98	94	102	97	92	98	94	90	82
4.00	108	103	99	105	101	97	101	98	95	86
5.00	110	106	102	108	104	101	103	100	97	88
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:220.8V I:0.1234A P:26.62W PF:0.9773 Freq:49.99Hz Lamp Flux:3122.83x1 lm		
NAME: LLS-M60LAXBX1200	TYPE:	WEIGHT:
SPEC.:LLS-M60LAXBX1200-T27NW8B-DC	DIM.: 1200*30*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1200*30mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.8V I:0.1234A P:26.62W PF:0.9773 Freq:49.99Hz Lamp Flux:3122.83x1 lm		
NAME: LLS-M60LAXBX1200	TYPE:	WEIGHT:
SPEC.:LLS-M60LAXBX1200-T27NW8B-DC	DIM.: 1200*30*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1200*30mm	Shielding Angle:

Flux out:1346 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:220.8V I:0.1234A P:26.62W PF:0.9773 Freq:49.99Hz Lamp Flux:3122.83x1 lm		
NAME: LLS-M60LAXBX1200	TYPE:	WEIGHT:
SPEC.:LLS-M60LAXBX1200-T27NW8B-DC	DIM.: 1200*30*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1200*30mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-15

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.8V I:0.1234A P:26.62W PF:0.9773 Freq:49.99Hz Lamp Flux:3122.83x1 lm		
NAME: LLS-M60LAXBX1200	TYPE:	WEIGHT:
SPEC.:LLS-M60LAXBX1200-T27NW8B-DC	DIM.: 1200*30*25mm	SERIAL No.:
MFR.: COLORS	SUR.:1200*30mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	1711	1695	1680	1700	1711	1695	1680	1700										
5	1751	1725	1657	1605	1603	1614	1676	1739										
10	1751	1719	1610	1456	1414	1478	1644	1739										
15	1703	1678	1539	1256	1142	1291	1585	1708										
20	1608	1605	1446	1016	835	1061	1506	1637										
25	1478	1498	1342	779	601	824	1403	1534										
30	1376	1365	1220	591	450	625	1283	1398										
35	1273	1221	1082	462	351	485	1150	1252										
40	1126	1096	934	365	296	386	1007	1121										
45	950	982	785	298	261	313	859	1004										
50	766	860	645	250	235	261	716	881										
55	587	724	520	214	208	222	584	745										
60	422	585	407	180	179	186	463	598										
65	274	449	309	144	150	149	354	452										
70	129	321	224	108	121	112	264	321										
75	38.5	203	151	72.6	86.0	77.9	186	203										
80	6.11	61.0	90.6	37.3	42.2	44.9	117	65.2										
85	2.44	8.43	40.1	5.92	2.51	9.03	58.2	6.27										
90	1.11	4.33	7.85	3.39	1.01	3.06	11.6	2.39										
95	0.78	3.43	5.97	3.53	0.92	2.68	5.96	2.03										
100	1.21	2.36	5.92	4.58	1.10	4.07	5.14	2.96										
105	1.60	2.54	3.81	5.67	1.72	5.19	2.73	3.37										
110	1.98	3.15	4.46	6.66	2.83	5.98	3.69	3.57										
115	2.32	3.95	5.51	7.72	3.98	6.89	4.67	3.64										
120	2.68	4.55	6.54	8.71	5.28	7.83	5.67	3.71										
125	3.06	4.73	7.63	9.63	6.72	8.76	6.83	3.95										
130	3.47	5.04	8.81	10.5	8.26	9.75	8.04	4.19										
135	3.93	5.51	10.1	11.4	9.85	10.7	9.35	4.54										
140	4.58	6.18	11.4	12.5	11.3	11.8	10.6	5.15										
145	5.56	7.08	12.6	13.8	12.6	13.2	11.9	6.07										
150	7.10	8.28	14.3	15.3	13.7	14.8	13.4	7.40										
155	9.37	9.85	16.1	17.0	15.0	16.6	15.3	9.24										
160	12.5	12.0	18.1	18.6	16.5	18.3	17.2	11.6										
165	16.2	15.0	19.8	20.4	17.9	19.9	18.9	14.8										
170	19.0	18.3	21.0	22.0	19.3	21.6	20.5	18.3										
175	19.0	21.1	22.2	23.5	20.3	22.9	22.0	21.3										
180	20.6	23.4	23.1	23.8	20.7	23.3	23.2	23.8										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-15

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: