


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.2973A P:7.135W PF:1.000 Freq:0Hz Lamp Flux:357.84lx1 lm		
NAME: ALS-SK6013FDXWX1000(B)	TYPE:	WEIGHT:
SPEC.:ALS-SK6013FDXWX1000(B)-F7NW9X-BC	DIM.: 1000*60*13mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*60	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 50.16 lm/W			
MODELS-SK6013FDXWX1000(B)		I _{max} (cd)	163.7	S/MH(C0/180)	3.36
NOMINAL POWER(W)	6.6	LOR(%)	100.0	S/MH(C90/270)	1.30
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	357.84	h UP,DN(C0-180)	10.0,57.4
NOMINAL FLUX(lm)	357.841	CIE CLASS	SEMI-D.	h UP,DN(C180-360)	3.7,29.0
LAMPS INSIDE	1	h up(%)	13.7	CIBSE SHR NOM	0.00
TEST VOLTAGE(V)	24	h down(%)	86.3	CIBSE SHR MAX	1.30



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	51.19	43.82	36.96	31.51	29.06	31.12	36.99	45.02	0- 10	3.600	3.600	1.01,1.01
20	75.17	58.99	35.26	24.93	21.14	24.66	35.41	60.79	10- 20	11.42	15.02	4.2,4.2
30	98.48	74.17	32.53	18.50	14.27	18.32	32.83	76.23	20- 30	20.37	35.40	9.89,9.89
40	119.7	87.90	28.73	12.46	8.447	12.35	29.16	90.15	30- 40	29.69	65.09	18.2,18.2
50	138.0	99.74	24.00	7.162	3.963	7.142	24.57	102.1	40- 50	38.58	103.7	29,29
60	152.8	109.2	18.37	3.069	0.9192	3.181	19.08	111.4	50- 60	46.32	150.0	41.9,41.9
70	162.3	115.1	12.10	0.5179	0.4227	0.7467	12.92	117.2	60- 70	52.19	202.2	56.5,56.5
80	161.8	113.3	5.868	0.9650	1.276	1.121	6.783	114.0	70- 80	54.97	257.1	71.9,71.9
90	144.9	97.29	1.018	1.717	2.044	1.643	1.294	96.99	80- 90	51.79	308.9	86.3,86.3
100	83.82	38.40	0.2405	1.677	2.097	1.683	0.1605	23.73	90-100	35.97	344.9	96.4,96.4
110	13.85	1.173	0.2338	1.435	1.930	1.590	0.2341	1.283	100-110	10.02	354.9	99.2,99.2
120	0.4554	0.1869	0.3139	1.249	1.810	1.209	0.2872	0.0601	110-120	1.137	356.1	99.5,99.5
130	0.1336	0.1336	0.3139	1.068	1.555	1.116	0.3272	0.0802	120-130	0.5699	356.6	99.7,99.7
140	0.1069	0.1871	0.3273	0.9418	1.302	1.035	0.3341	0.1131	130-140	0.4375	357.1	99.8,99.8
150	0.1803	0.2538	0.3870	0.8349	1.035	0.9356	0.3941	0.1803	140-150	0.3367	357.4	99.9,99.9
160	0.3005	0.3273	0.4275	0.7279	0.8149	0.8085	0.4676	0.2805	150-160	0.2417	357.6	99.9,99.9
170	0.4008	0.4475	0.5277	0.6077	0.5944	0.6413	0.5210	0.3606	160-170	0.1464	357.8	100,100
180	0.5344	0.5477	0.5344	0.5477	0.5210	0.5477	0.5544	0.5277	170-180	0.0489	357.8	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-11

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.2973A P:7.135W PF:1.000 Freq:0Hz Lamp Flux:357.84lx1 lm		
NAME: ALS-SK6013FDXWX1000(B)	TYPE:	WEIGHT:
SPEC.:ALS-SK6013FDXWX1000(B)-F7NW9X-BC	DIM.: 1000*60*13mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*60	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	29746	571
80	15525	563
75	10541	573
70	7911	590
65	6248	602
60	5094	612
55	4240	618
50	3579	622
45	3047	624


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-11

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.2973A P:7.135W PF:1.000 Freq:0Hz Lamp Flux:357.84lx1 lm		
NAME: ALS-SK6013FDXWX1000(B)	TYPE:	WEIGHT:
SPEC.:ALS-SK6013FDXWX1000(B)-F7NW9X-BC	DIM.: 1000*60*13mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*60	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.2973A P:7.135W PF:1.000 Freq:0Hz Lamp Flux:357.84lx1 lm		
NAME: ALS-SK6013FDXWX1000(B)	TYPE:	WEIGHT:
SPEC.:ALS-SK6013FDXWX1000(B)-F7NW9X-BC	DIM.: 1000*60*13mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*60	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.498	.283	.090	.486	.277	.088	.464	.266	.085	.444	.256	.082	.425	.247	.079	
2.0	.406	.223	.068	.396	.218	.067	.376	.209	.065	.357	.201	.063	.340	.193	.061	
3.0	.349	.186	.056	.339	.182	.055	.321	.174	.053	.304	.167	.051	.289	.160	.050	
4.0	.306	.159	.047	.297	.156	.046	.281	.149	.045	.266	.143	.043	.252	.137	.042	
5.0	.273	.139	.040	.265	.136	.040	.251	.131	.038	.237	.125	.037	.224	.120	.036	
6.0	.247	.124	.035	.240	.121	.035	.226	.116	.034	.214	.111	.033	.202	.107	.032	
7.0	.225	.111	.032	.219	.109	.031	.206	.104	.030	.195	.100	.029	.184	.096	.028	
8.0	.207	.101	.028	.201	.099	.028	.190	.095	.027	.179	.091	.026	.170	.087	.025	
9.0	.191	.092	.026	.186	.091	.025	.176	.087	.025	.166	.083	.024	.157	.080	.023	
10.0	.178	.085	.024	.173	.084	.023	.164	.080	.023	.155	.077	.022	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.295	.295	.295	.252	.252	.252	.172	.172	.172	.099	.099	.099	.032	.032	.032	
1.0	.298	.259	.224	.255	.223	.193	.175	.153	.134	.100	.089	.078	.032	.029	.025	
2.0	.293	.237	.190	.251	.204	.164	.172	.141	.114	.099	.082	.067	.032	.027	.022	
3.0	.286	.221	.169	.245	.191	.147	.168	.132	.103	.097	.077	.061	.031	.025	.020	
4.0	.278	.209	.157	.238	.181	.136	.164	.126	.096	.095	.074	.057	.030	.024	.019	
5.0	.269	.199	.148	.231	.173	.129	.159	.121	.091	.092	.071	.054	.030	.023	.018	
6.0	.261	.192	.142	.224	.166	.123	.155	.116	.087	.090	.068	.052	.029	.022	.017	
7.0	.253	.185	.137	.218	.160	.120	.150	.112	.085	.087	.066	.050	.028	.022	.017	
8.0	.246	.179	.134	.211	.156	.117	.146	.109	.083	.085	.064	.049	.028	.021	.016	
9.0	.239	.175	.131	.206	.151	.114	.142	.106	.081	.083	.063	.048	.027	.021	.016	
10.0	.232	.170	.129	.200	.148	.113	.139	.104	.080	.081	.062	.048	.026	.020	.016	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.2973A P:7.135W PF:1.000 Freq:0Hz Lamp Flux:357.84lx1 lm											
NAME.: ALS-SK6013FDXWX1000(B)						TYPE:		WEIGHT:			
SPEC.:ALS-SK6013FDXWX1000(B)-F7NW9X-BC						DIM.: 1000*60*13mm		SERIAL No.:			
MFR.: COLORS						SUR.:1000*60		Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	23.8	25.4	24.2	25.8	26.3	18.0	19.6	18.5	20.1	20.6	
	3H	27.5	29.0	28.0	29.5	30.1	19.8	21.3	20.3	21.8	22.4
	4H	29.6	31.0	30.1	31.6	32.1	20.6	22.1	21.1	22.6	23.2
	6H	31.8	33.2	32.4	33.7	34.3	21.3	22.6	21.8	23.2	23.8
	8H	33.0	34.3	33.6	34.9	35.5	21.5	22.8	22.1	23.4	24.0
	12H	34.3	35.6	34.9	36.2	36.8	21.7	23.0	22.2	23.5	24.1
4H	2H	24.4	25.9	24.9	26.4	27.0	21.2	22.6	21.7	23.1	23.7
	3H	28.4	29.7	29.0	30.2	30.9	23.4	24.7	24.0	25.2	25.9
	4H	30.6	31.8	31.2	32.4	33.1	24.5	25.7	25.1	26.2	26.9
	6H	33.1	34.2	33.7	34.7	35.4	25.4	26.5	26.0	27.1	27.8
	8H	34.4	35.4	35.0	36.0	36.7	25.7	26.8	26.4	27.4	28.1
	12H	35.8	36.8	36.5	37.4	38.1	26.0	27.0	26.6	27.6	28.3
8H	4H	31.1	32.1	31.7	32.7	33.4	26.9	27.9	27.5	28.6	29.3
	6H	33.8	34.7	34.4	35.3	36.1	28.4	29.3	29.0	29.9	30.7
	8H	35.3	36.1	36.0	36.8	37.5	29.1	29.9	29.7	30.5	31.3
	12H	37.0	37.7	37.7	38.4	39.2	29.6	30.3	30.3	31.0	31.8
12H	4H	31.1	32.1	31.8	32.7	33.4	27.6	28.6	28.3	29.2	29.9
	6H	34.0	34.8	34.6	35.4	36.2	29.5	30.3	30.1	31.0	31.7
	8H	35.6	36.3	36.3	37.0	37.8	30.4	31.1	31.1	31.8	32.6
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.2					+ 0.2 / - 0.2					
2.0H	+ 0.3 / - 0.3					+ 0.3 / - 0.4					

CIE Pub.117, 357.8 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -3.6)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.2973A P:7.135W PF:1.000 Freq:0Hz Lamp Flux:357.84lx1 lm		
NAME: ALS-SK6013FDXWX1000(B)	TYPE:	WEIGHT:
SPEC.:ALS-SK6013FDXWX1000(B)-F7NW9X-BC	DIM.: 1000*60*13mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*60	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	42	29	20	41	28	20	40	28	20	13
0.80	51	36	27	49	35	27	47	34	26	18
1.00	58	43	33	56	42	33	53	44	32	23
1.25	65	50	40	63	49	39	59	47	38	28
1.50	70	56	45	68	54	45	63	52	43	33
2.00	78	64	54	75	63	53	70	59	51	40
2.50	83	70	60	80	68	59	74	65	57	44
3.00	87	75	66	84	73	65	78	69	62	49
4.00	93	82	74	89	80	72	83	75	68	55
5.00	96	87	79	93	84	77	86	79	73	59
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-11

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.2973A P:7.135W PF:1.000 Freq:0Hz Lamp Flux:357.84lx1 lm		
NAME: ALS-SK6013FDXWX1000(B)	TYPE:	WEIGHT:
SPEC.:ALS-SK6013FDXWX1000(B)-F7NW9X-BC	DIM.: 1000*60*13mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*60	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-11

deg Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

AAI Figure

Test:U:24.00V I:0.2973A P:7.135W PF:1.000 Freq:0Hz Lamp Flux:357.84lx1 lm		
NAME: ALS-SK6013FDXWX1000(B)	TYPE:	WEIGHT:
SPEC.:ALS-SK6013FDXWX1000(B)-F7NW9X-BC	DIM.: 1000*60*13mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*60	Shielding Angle:

Flux out:103.7 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2021-03-11

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.2973A P:7.135W PF:1.000 Freq:0Hz Lamp Flux:357.84lx1 lm		
NAME: ALS-SK6013FDXWX1000(B)	TYPE:	WEIGHT:
SPEC.:ALS-SK6013FDXWX1000(B)-F7NW9X-BC	DIM.: 1000*60*13mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*60	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-03-11

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:24.00V I:0.2973A P:7.135W PF:1.000 Freq:0Hz Lamp Flux:357.84lx1 lm		
NAME: ALS-SK6013FDXWX1000(B)	TYPE:	WEIGHT:
SPEC.:ALS-SK6013FDXWX1000(B)-F7NW9X-BC	DIM.: 1000*60*13mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*60	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	3128
L_0~180(75)av	5297
L_0~180(85)av	15036
L_90~270(65)av	618
L_90~270(75)av	601
L_90~270(85)av	654
L_45(65)av	2278
L_45(75)av	3767
L_45(85)av	10413

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-03-11

deg Range: 0 - 180DEG
deg Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.2973A P:7.135W PF:1.000 Freq:0Hz Lamp Flux:357.84lx1 lm		
NAME: ALS-SK6013FDXWX1000(B)	TYPE:	WEIGHT:
SPEC.:ALS-SK6013FDXWX1000(B)-F7NW9X-BC	DIM.: 1000*60*13mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*60	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	37.6	37.4	37.5	38.0	37.6	37.4	37.5	38.0										
5	41.7	40.3	37.4	34.8	33.3	34.3	37.4	41.0										
10	51.2	43.8	37.0	31.5	29.1	31.1	37.0	45.0										
15	63.1	51.2	36.2	28.2	25.0	27.9	36.3	52.7										
20	75.2	59.0	35.3	24.9	21.1	24.7	35.4	60.8										
25	87.0	66.7	34.0	21.7	17.6	21.5	34.3	68.7										
30	98.5	74.2	32.5	18.5	14.3	18.3	32.8	76.2										
35	109	81.3	30.8	15.4	11.2	15.2	31.1	83.4										
40	120	87.9	28.7	12.5	8.45	12.4	29.2	90.1										
45	129	94.1	26.5	9.69	6.04	9.64	27.0	96.4										
50	138	99.7	24.0	7.16	3.96	7.14	24.6	102										
55	146	105	21.3	4.94	2.27	5.00	21.9	107										
60	153	109	18.4	3.07	0.92	3.18	19.1	111										
65	158	113	15.3	1.56	0.19	1.74	16.1	115										
70	162	115	12.1	0.52	0.42	0.75	12.9	117										
75	164	116	8.90	0.56	0.81	0.74	9.75	117										
80	162	113	5.87	0.96	1.28	1.12	6.78	114										
85	156	107	2.98	1.50	1.70	1.45	3.85	107										
90	145	97.3	1.02	1.72	2.04	1.64	1.29	97.0										
95	121	73.1	0.59	1.72	2.11	1.68	0.94	70.4										
100	83.8	38.4	0.24	1.68	2.10	1.68	0.16	23.7										
105	45.3	9.21	0.23	1.56	2.00	1.66	0.20	7.61										
110	13.8	1.17	0.23	1.44	1.93	1.59	0.23	1.28										
115	0.76	0.60	0.25	1.37	1.85	1.27	0.26	0.26										
120	0.46	0.19	0.31	1.25	1.81	1.21	0.29	0.06										
125	0.25	0.11	0.32	1.14	1.68	1.17	0.29	0.07										
130	0.13	0.13	0.31	1.07	1.55	1.12	0.33	0.08										
135	0.11	0.15	0.31	1.03	1.43	1.07	0.33	0.09										
140	0.11	0.19	0.33	0.94	1.30	1.04	0.33	0.11										
145	0.12	0.23	0.35	0.95	1.15	1.00	0.35	0.18										
150	0.18	0.25	0.39	0.83	1.03	0.94	0.39	0.18										
155	0.24	0.29	0.39	0.83	0.96	0.89	0.43	0.20										
160	0.30	0.33	0.43	0.73	0.81	0.81	0.47	0.28										
165	0.33	0.37	0.53	0.65	0.71	0.73	0.50	0.31										
170	0.40	0.45	0.53	0.61	0.59	0.64	0.52	0.36										
175	0.43	0.50	0.53	0.55	0.51	0.59	0.53	0.43										
180	0.53	0.55	0.53	0.55	0.52	0.55	0.55	0.53										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-03-11

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: