


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.2980A P:7.150W PF:1.000 Freq:0Hz Lamp Flux:1447.09x1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 202.39 lm/W			
MODEL	D81442410NO	I _{max} (cd)	475.6	S/MH(C0/180)	1.27
NOMINAL POWER(W)	7.2	LOR(%)	100.0	S/MH(C90/270)	1.27
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1447.1	h UP,DN(C0-180)	0.9,49.5
NOMINAL FLUX(lm)	1447.09	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,48.8
LAMPS INSIDE	1	h up(%)	1.7	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.3	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	465.3	467.5	469.0	471.8	469.4	468.4	465.9	464.2	0- 10	44.98	44.98	3.11,3.11
20	441.9	445.6	449.3	454.3	450.1	447.7	443.2	439.0	10- 20	129.6	174.5	12.1,12.1
30	404.5	410.2	415.5	422.6	416.6	412.7	406.2	400.2	20- 30	198.5	373.0	25.8,25.8
40	354.0	358.0	367.8	374.3	366.8	364.4	354.9	348.9	30- 40	242.4	615.4	42.5,42.5
50	290.9	295.5	306.6	315.1	306.6	303.2	293.1	284.9	40- 50	255.9	871.3	60.2,60.2
60	215.9	221.0	232.5	242.9	233.9	230.1	219.6	209.1	50- 60	235.8	1107	76.5,76.5
70	130.2	136.3	146.4	159.7	150.9	146.0	136.8	124.9	60- 70	182.0	1289	89.1,89.1
80	48.43	52.58	59.89	73.02	65.58	62.06	54.01	45.23	70- 80	104.0	1393	96.3,96.3
90	4.954	5.148	3.697	11.42	8.343	7.836	1.972	4.416	80- 90	29.54	1423	98.3,98.3
100	1.837	1.910	1.683	1.818	1.184	1.139	1.266	1.442	90-100	2.550	1425	98.5,98.5
110	2.985	2.880	2.337	2.542	2.413	2.176	2.546	2.565	100-110	2.112	1427	98.6,98.6
120	4.233	4.095	3.607	3.655	3.561	3.165	3.460	3.780	110-120	3.109	1430	98.8,98.8
130	5.302	5.064	4.589	4.576	4.598	4.141	4.142	4.542	120-130	3.738	1434	99.1,99.1
140	6.065	5.712	5.376	5.332	5.452	5.076	4.656	4.988	130-140	3.858	1438	99.4,99.4
150	6.618	6.052	5.871	6.087	5.972	5.944	5.265	5.230	140-150	3.510	1442	99.6,99.6
160	7.160	6.387	6.685	6.888	6.553	6.691	6.454	5.669	150-160	2.861	1444	99.8,99.8
170	7.268	7.268	7.628	7.535	6.926	7.361	7.515	7.079	160-170	1.958	1446	100,100
180	7.241	8.316	8.409	8.423	7.261	8.303	8.436	8.430	170-180	0.7208	1447	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-29

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.2980A P:7.150W PF:1.000 Freq:0Hz Lamp Flux:1447.09x1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	21602	28854
80	27889	34492
75	33854	39491
70	38080	42813
65	40922	44896
60	43171	46495
55	44376	47297
50	45261	47694
45	45799	47927


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-29

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.2980A P:7.150W PF:1.000 Freq:0Hz Lamp Flux:1447.09x1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.00	1.00	1.00	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.78	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.60	.68	.63	.59	.57
4.0	.69	.60	.54	.68	.60	.53	.65	.58	.52	.63	.56	.51	.60	.55	.50	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.44	.54	.48	.44	.41
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.35	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.35	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.2980A P:7.150W PF:1.000 Freq:0Hz Lamp Flux:1447.09x1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.315	.179	.057	.307	.175	.056	.293	.168	.054	.280	.161	.052	.268	.155	.050	
2.0	.295	.162	.050	.289	.159	.049	.276	.153	.048	.264	.148	.046	.254	.143	.045	
3.0	.273	.145	.043	.267	.143	.043	.256	.139	.042	.245	.134	.041	.236	.130	.040	
4.0	.251	.131	.038	.246	.129	.038	.236	.125	.037	.227	.122	.037	.218	.119	.036	
5.0	.232	.118	.034	.228	.117	.034	.219	.114	.034	.210	.111	.033	.203	.108	.033	
6.0	.215	.108	.031	.211	.107	.031	.203	.104	.030	.196	.102	.030	.189	.099	.029	
7.0	.200	.099	.028	.196	.098	.028	.189	.096	.028	.183	.094	.027	.176	.092	.027	
8.0	.187	.091	.026	.183	.090	.026	.177	.088	.025	.171	.087	.025	.165	.085	.025	
9.0	.175	.085	.024	.172	.084	.024	.166	.082	.023	.161	.081	.023	.155	.079	.023	
10.0	.164	.079	.022	.162	.078	.022	.156	.077	.022	.151	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.203	.203	.203	.174	.174	.174	.119	.119	.119	.068	.068	.068	.022	.022	.022	
1.0	.194	.169	.147	.166	.145	.126	.113	.100	.087	.065	.058	.051	.021	.019	.016	
2.0	.186	.145	.111	.159	.125	.096	.109	.086	.067	.063	.050	.039	.020	.016	.013	
3.0	.178	.127	.087	.153	.110	.075	.105	.076	.053	.061	.045	.031	.019	.014	.010	
4.0	.171	.114	.071	.146	.099	.062	.101	.069	.044	.058	.040	.026	.019	.013	.008	
5.0	.163	.104	.060	.140	.090	.052	.097	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.156	.096	.052	.134	.083	.045	.093	.058	.032	.054	.034	.019	.017	.011	.006	
7.0	.149	.089	.046	.128	.077	.040	.089	.054	.029	.052	.032	.017	.017	.010	.006	
8.0	.143	.083	.042	.123	.072	.037	.085	.051	.026	.049	.030	.015	.016	.010	.005	
9.0	.137	.078	.038	.118	.068	.034	.082	.048	.024	.047	.028	.014	.015	.009	.005	
10.0	.131	.074	.036	.113	.064	.031	.078	.045	.022	.046	.027	.013	.015	.009	.004	

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-29

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.2980A P:7.150W PF:1.000 Freq:0Hz Lamp Flux:1447.09x1 lm											
NAME: D81442410NO					TYPE:			WEIGHT:			
SPEC.:D81442410NO-8WWNSA012WC0100					DIM.: 1000*10*1.5mm			SERIAL No.:01			
MFR.: COLORS					SUR.:1000*10			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	24.7	26.2	25.0	26.4	26.6	24.9	26.4	25.2	26.7	26.9	
	3H	26.1	27.5	26.4	27.8	28.1	26.5	27.9	26.8	28.2	28.5
	4H	26.7	28.0	27.0	28.3	28.6	27.1	28.5	27.5	28.7	29.0
	6H	27.0	28.2	27.4	28.5	28.9	27.6	28.8	27.9	29.1	29.4
	8H	27.1	28.3	27.4	28.6	28.9	27.7	28.9	28.0	29.2	29.5
	12H	27.1	28.3	27.5	28.6	28.9	27.7	28.9	28.1	29.2	29.6
4H	2H	25.3	26.6	25.6	26.9	27.2	25.5	26.8	25.8	27.1	27.4
	3H	26.9	28.1	27.3	28.4	28.8	27.3	28.4	27.6	28.7	29.1
	4H	27.6	28.6	28.0	29.0	29.4	28.0	29.1	28.4	29.4	29.8
	6H	28.0	29.0	28.4	29.4	29.8	28.5	29.5	29.0	29.9	30.3
	8H	28.1	29.0	28.6	29.4	29.8	28.7	29.6	29.1	30.0	30.4
	12H	28.2	29.0	28.7	29.4	29.9	28.8	29.6	29.3	30.0	30.5
8H	4H	27.8	28.7	28.3	29.1	29.5	28.2	29.1	28.6	29.5	29.9
	6H	28.4	29.1	28.9	29.6	30.0	28.9	29.6	29.3	30.0	30.5
	8H	28.6	29.2	29.1	29.7	30.2	29.1	29.8	29.6	30.2	30.7
	12H	28.7	29.3	29.2	29.8	30.3	29.3	29.9	29.8	30.3	30.8
12H	4H	27.8	28.7	28.3	29.1	29.5	28.2	29.0	28.7	29.4	29.9
	6H	28.5	29.1	28.9	29.6	30.0	28.9	29.6	29.4	30.0	30.5
	8H	28.7	29.2	29.2	29.7	30.2	29.2	29.7	29.7	30.2	30.7
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 1447 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 1.3)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.2980A P:7.150W PF:1.000 Freq:0Hz Lamp Flux:1447.09x1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	45	37	55	44	37	54	44	37	31
0.80	66	54	47	65	54	47	63	53	46	39
1.00	75	63	56	73	63	56	71	64	55	48
1.25	82	71	64	80	70	63	77	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	81	76	68
2.50	98	90	84	96	88	83	92	86	81	72
3.00	101	94	89	99	93	87	95	89	85	76
4.00	105	100	95	103	98	93	98	94	90	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.2980A P:7.150W PF:1.000 Freq:0Hz Lamp Flux:1447.09x1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.2980A P:7.150W PF:1.000 Freq:0Hz Lamp Flux:1447.09x1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Flux out:1085 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.2980A P:7.150W PF:1.000 Freq:0Hz Lamp Flux:1447.09x1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.2980A P:7.150W PF:1.000 Freq:0Hz Lamp Flux:1447.09x1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8WWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	475	475	475	475	475	475	475	475										
5	472	473	474	475	474	474	472	471										
10	465	467	469	472	469	468	466	464										
15	455	458	461	465	462	460	456	453										
20	442	446	449	454	450	448	443	439										
25	425	430	434	440	435	432	427	421										
30	405	410	416	423	417	413	406	400										
35	381	384	393	400	392	390	381	376										
40	354	358	368	374	367	364	355	349										
45	324	328	339	346	338	335	325	318										
50	291	295	307	315	307	303	293	285										
55	255	260	271	281	272	268	258	248										
60	216	221	232	243	234	230	220	209										
65	173	179	190	203	193	188	179	167										
70	130	136	146	160	151	146	137	125										
75	87.6	92.8	102	116	107	103	94.3	83.0										
80	48.4	52.6	59.9	73.0	65.6	62.1	54.0	45.2										
85	18.8	21.1	25.1	36.1	30.1	27.9	21.4	17.4										
90	4.95	5.15	3.70	11.4	8.34	7.84	1.97	4.42										
95	1.94	1.93	1.78	2.92	1.46	1.64	0.70	1.39										
100	1.84	1.91	1.68	1.82	1.18	1.14	1.27	1.44										
105	2.35	2.32	1.81	2.09	1.76	1.64	1.95	1.92										
110	2.98	2.88	2.34	2.54	2.41	2.18	2.55	2.56										
115	3.62	3.52	3.00	3.11	2.98	2.68	3.05	3.18										
120	4.23	4.10	3.61	3.65	3.56	3.17	3.46	3.78										
125	4.79	4.61	4.12	4.14	4.10	3.63	3.82	4.25										
130	5.30	5.06	4.59	4.58	4.60	4.14	4.14	4.54										
135	5.75	5.44	5.00	4.94	5.05	4.60	4.42	4.80										
140	6.06	5.71	5.38	5.33	5.45	5.08	4.66	4.99										
145	6.30	5.90	5.64	5.70	5.77	5.51	4.87	5.11										
150	6.62	6.05	5.87	6.09	5.97	5.94	5.26	5.23										
155	6.86	6.21	6.18	6.50	6.25	6.32	5.82	5.34										
160	7.16	6.39	6.69	6.89	6.55	6.69	6.45	5.67										
165	7.44	6.72	7.17	7.20	6.82	7.00	6.98	6.28										
170	7.27	7.27	7.63	7.53	6.93	7.36	7.52	7.08										
175	7.05	7.82	8.06	7.95	6.84	7.78	8.02	7.79										
180	7.24	8.32	8.41	8.42	7.26	8.30	8.44	8.43										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: