


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.3000A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:1398.4lx1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 194.22 lm/W			
MODEL	D81442410NO	I <sub>max</sub> (cd)	459.6	S/MH(C0/180)	1.28
NOMINAL POWER(W)	7.2	LOR(%)	100.0	S/MH(C90/270)	1.27
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1398.4	h UP,DN(C0-180)	0.9,49.5
NOMINAL FLUX(lm)	1398.41	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,48.9
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.4	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-29

Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	450.4	452.7	453.5	454.9	453.2	452.6	451.2	450.2	0- 10	43.51	43.51	3.11,3.11
20	428.5	432.4	434.1	436.7	434.0	431.8	429.4	427.6	10- 20	125.3	168.8	12.1,12.1
30	393.2	395.2	401.1	404.1	399.4	397.7	392.2	391.4	20- 30	192.0	360.8	25.8,25.8
40	345.4	349.1	355.2	356.9	352.7	351.1	344.9	343.1	30- 40	234.5	595.3	42.6,42.6
50	284.9	289.5	296.0	298.4	294.2	291.6	285.5	282.5	40- 50	247.9	843.2	60.3,60.3
60	212.5	218.2	224.2	227.6	223.5	220.6	214.7	210.3	50- 60	228.7	1072	76.7,76.7
70	130.7	136.7	140.9	146.1	142.7	138.8	134.8	129.1	60- 70	176.8	1249	89.3,89.3
80	49.26	53.75	56.65	61.04	59.19	56.64	53.53	48.60	70- 80	100.8	1349	96.5,96.5
90	3.089	4.174	2.884	5.004	3.743	3.758	1.445	2.340	80- 90	26.05	1376	98.4,98.4
100	1.710	1.824	1.623	1.731	1.133	1.133	1.205	1.188	90-100	1.685	1377	98.5,98.5
110	2.809	2.726	2.335	2.552	2.395	2.168	2.474	2.420	100-110	2.033	1379	98.6,98.6
120	4.027	3.877	3.533	3.682	3.521	3.118	3.388	3.592	110-120	3.021	1382	98.8,98.8
130	5.028	4.757	4.462	4.556	4.524	4.027	4.076	4.381	120-130	3.628	1386	99.1,99.1
140	5.736	5.357	5.228	5.271	5.337	4.936	4.609	4.836	130-140	3.740	1390	99.4,99.4
150	6.244	5.672	5.736	5.972	5.812	5.764	5.160	5.116	140-150	3.400	1393	99.6,99.6
160	6.798	6.033	6.499	6.701	6.359	6.491	6.335	5.516	150-160	2.768	1396	99.8,99.8
170	6.881	6.994	7.454	7.321	6.666	7.153	7.362	6.811	160-170	1.895	1398	100,100
180	6.940	8.102	8.209	8.209	6.940	8.042	8.209	8.209	170-180	0.6989	1398	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-01-29

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.3000A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:1398.4lx1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	20098	25348
80	28368	32622
75	34355	37835
70	38226	41199
65	40709	43274
60	42498	44844
55	43616	45637
50	44317	46051
45	44739	46241


C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-01-29

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.3000A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:1398.4lx1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.79	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.60	.68	.63	.59	.57
4.0	.69	.61	.54	.68	.60	.53	.65	.58	.52	.63	.56	.51	.60	.55	.51	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.44	.54	.48	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.35	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-29

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.3000A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:1398.41x1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.313	.178	.056	.305	.174	.055	.291	.167	.053	.278	.160	.051	.266	.154	.050	
2.0	.295	.161	.050	.288	.159	.049	.275	.153	.048	.264	.148	.046	.253	.143	.045	
3.0	.272	.145	.043	.267	.143	.043	.255	.138	.042	.245	.134	.041	.235	.130	.040	
4.0	.251	.131	.038	.246	.129	.038	.236	.125	.037	.227	.122	.037	.218	.119	.036	
5.0	.232	.118	.034	.227	.117	.034	.219	.114	.033	.210	.111	.033	.203	.108	.033	
6.0	.215	.108	.031	.211	.107	.031	.203	.104	.030	.196	.102	.030	.189	.099	.029	
7.0	.200	.099	.028	.196	.098	.028	.189	.096	.028	.183	.094	.027	.176	.092	.027	
8.0	.187	.091	.026	.183	.090	.026	.177	.088	.025	.171	.087	.025	.165	.085	.025	
9.0	.175	.085	.024	.172	.084	.024	.166	.082	.023	.161	.081	.023	.156	.079	.023	
10.0	.164	.079	.022	.162	.078	.022	.156	.077	.022	.151	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.203	.203	.203	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.193	.169	.147	.165	.145	.126	.113	.100	.087	.065	.058	.051	.021	.019	.016	
2.0	.185	.145	.110	.159	.124	.095	.109	.086	.067	.063	.050	.039	.020	.016	.013	
3.0	.178	.127	.087	.152	.110	.075	.105	.076	.053	.060	.044	.031	.019	.014	.010	
4.0	.170	.114	.071	.146	.098	.061	.100	.069	.043	.058	.040	.026	.019	.013	.008	
5.0	.163	.103	.060	.140	.090	.052	.096	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.156	.095	.052	.134	.082	.045	.092	.058	.032	.054	.034	.019	.017	.011	.006	
7.0	.149	.088	.046	.128	.077	.040	.088	.054	.028	.051	.032	.017	.017	.010	.006	
8.0	.142	.083	.041	.122	.072	.036	.085	.050	.026	.049	.030	.015	.016	.010	.005	
9.0	.136	.078	.038	.117	.067	.033	.081	.047	.024	.047	.028	.014	.015	.009	.005	
10.0	.130	.073	.035	.112	.064	.031	.078	.045	.022	.046	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-29

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.3000A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:1398.4lx1 lm											
NAME: D81442410NO					TYPE:			WEIGHT:			
SPEC.:D81442410NO-8SWNSA012WC0100					DIM.: 1000*10*1.5mm			SERIAL No.:01			
MFR.: COLORS					SUR.:1000*10			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	24.8	26.3	25.1	26.5	26.8	25.0	26.5	25.3	26.7	27.0	
	3H	26.3	27.7	26.6	28.0	28.2	26.6	28.0	26.9	28.2	28.5
	4H	26.9	28.2	27.2	28.5	28.8	27.2	28.5	27.5	28.8	29.1
	6H	27.2	28.5	27.6	28.8	29.1	27.6	28.8	27.9	29.1	29.4
	8H	27.3	28.5	27.7	28.8	29.1	27.7	28.9	28.1	29.2	29.5
	12H	27.3	28.5	27.7	28.8	29.2	27.7	28.9	28.1	29.2	29.6
4H	2H	25.4	26.8	25.8	27.0	27.3	25.6	26.9	25.9	27.2	27.5
	3H	27.1	28.3	27.5	28.6	28.9	27.3	28.5	27.7	28.8	29.2
	4H	27.8	28.9	28.2	29.2	29.6	28.1	29.1	28.5	29.5	29.8
	6H	28.3	29.2	28.7	29.6	30.0	28.6	29.5	29.0	29.9	30.3
	8H	28.4	29.3	28.8	29.7	30.1	28.8	29.6	29.2	30.0	30.4
	12H	28.4	29.3	28.9	29.7	30.1	28.8	29.6	29.3	30.1	30.5
8H	4H	28.1	28.9	28.5	29.3	29.8	28.3	29.2	28.7	29.6	30.0
	6H	28.7	29.4	29.1	29.8	30.3	29.0	29.7	29.4	30.1	30.6
	8H	28.9	29.5	29.3	30.0	30.4	29.2	29.8	29.7	30.3	30.8
	12H	29.0	29.5	29.5	30.0	30.5	29.3	29.9	29.9	30.4	30.9
12H	4H	28.1	28.9	28.5	29.3	29.7	28.3	29.1	28.8	29.5	30.0
	6H	28.7	29.4	29.2	29.8	30.3	29.0	29.6	29.5	30.1	30.6
	8H	28.9	29.5	29.4	30.0	30.5	29.3	29.8	29.8	30.3	30.8
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 1398 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 1.2)

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-29

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.3000A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:1398.4lx1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	45	37	55	44	37	54	44	37	31
0.80	66	55	47	65	54	47	63	53	46	39
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	80	70	64	78	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	82	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	101	94	89	99	93	88	95	90	85	76
4.00	106	100	95	103	98	93	98	94	91	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-29

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### ISOCANDELA DIAGRAM

Test:U:24.00V I:0.3000A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:1398.4lx1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-01-29


deg Range: 0 - 180DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:



### AAI Figure

Test:U:24.00V I:0.3000A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:1398.4lx1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Flux out:1051 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-29

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM


Test:U:24.00V I:0.3000A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:1398.4lx1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-01-29

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2021-01-29

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.3000A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:1398.41x1 lm		
NAME: D81442410NO	TYPE:	WEIGHT:
SPEC.:D81442410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	459	460	459	459	459	460	459	459										
5	456	458	458	459	458	458	457	457										
10	450	453	453	455	453	453	451	450										
15	441	444	445	448	446	444	442	441										
20	429	432	434	437	434	432	429	428										
25	413	417	419	422	419	417	414	411										
30	393	395	401	404	399	398	392	391										
35	371	374	380	381	377	376	370	369										
40	345	349	355	357	353	351	345	343										
45	316	321	327	329	325	323	317	314										
50	285	290	296	298	294	292	286	283										
55	250	255	262	265	260	257	251	248										
60	212	218	224	228	223	221	215	210										
65	172	178	183	188	184	180	176	170										
70	131	137	141	146	143	139	135	129										
75	88.9	94.3	97.9	103	100	96.9	93.3	87.7										
80	49.3	53.8	56.6	61.0	59.2	56.6	53.5	48.6										
85	17.5	20.6	22.1	25.3	24.1	22.8	20.7	17.2										
90	3.09	4.17	2.88	5.00	3.74	3.76	1.45	2.34										
95	1.70	1.80	1.70	1.77	0.80	0.86	0.65	0.95										
100	1.71	1.82	1.62	1.73	1.13	1.13	1.21	1.19										
105	2.19	2.17	1.78	2.05	1.76	1.67	1.88	1.77										
110	2.81	2.73	2.33	2.55	2.39	2.17	2.47	2.42										
115	3.42	3.33	2.96	3.14	2.95	2.64	2.98	3.00										
120	4.03	3.88	3.53	3.68	3.52	3.12	3.39	3.59										
125	4.55	4.33	4.03	4.14	4.03	3.59	3.75	4.05										
130	5.03	4.76	4.46	4.56	4.52	4.03	4.08	4.38										
135	5.42	5.10	4.87	4.91	4.95	4.48	4.36	4.67										
140	5.74	5.36	5.23	5.27	5.34	4.94	4.61	4.84										
145	5.98	5.53	5.46	5.61	5.64	5.36	4.81	4.99										
150	6.24	5.67	5.74	5.97	5.81	5.76	5.16	5.12										
155	6.50	5.83	6.08	6.35	6.09	6.17	5.73	5.23										
160	6.80	6.03	6.50	6.70	6.36	6.49	6.33	5.52										
165	7.04	6.43	6.99	7.01	6.61	6.80	6.85	6.07										
170	6.88	6.99	7.45	7.32	6.67	7.15	7.36	6.81										
175	6.67	7.58	7.88	7.75	6.57	7.56	7.85	7.58										
180	6.94	8.10	8.21	8.21	6.94	8.04	8.21	8.21										

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-01-29

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks: