


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.6480A P:15.50W PF:1.000 Freq:0Hz Lamp Flux:1453.43x1 lm		
NAME: D8168M2410NO	TYPE:	WEIGHT:
SPEC.:D8168M2410NO-9NWDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 93.77 lm/W			
MODEL	D8168M2410NO	I _{max} (cd)	480.9	S/MH(C0/180)	1.29
NOMINAL POWER(W)	16.2	LOR(%)	100.0	S/MH(C90/270)	1.28
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1453.4	h UP,DN(C0-180)	0.9,49.4
NOMINAL FLUX(lm)	1453.43	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,49.0
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.4	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-03-31

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	473.8	475.0	473.7	473.4	472.0	471.3	472.3	473.6	0~ 10	45.51	45.51	3.13,3.13
20	452.5	454.8	452.6	451.4	449.1	447.8	449.8	451.8	10~ 20	131.0	176.5	12.1,12.1
30	416.8	419.8	416.9	415.3	412.4	410.3	413.6	415.7	20~ 30	200.5	377.1	25.9,25.9
40	366.7	368.1	366.9	362.8	359.3	359.4	361.1	365.7	30~ 40	244.4	621.5	42.8,42.8
50	303.4	305.0	303.3	299.4	296.1	296.0	298.5	302.7	40~ 50	257.3	878.8	60.5,60.5
60	227.6	229.3	226.8	224.1	221.7	221.1	224.2	227.9	50~ 60	236.1	1115	76.7,76.7
70	141.5	144.5	139.4	139.3	139.3	137.6	141.0	142.4	60~ 70	181.4	1296	89.2,89.2
80	57.58	60.15	52.95	55.56	59.30	58.48	58.12	58.48	70~ 80	103.6	1400	96.3,96.3
90	10.19	9.807	2.344	5.066	6.909	8.234	2.382	7.775	80~ 90	29.81	1430	98.4,98.4
100	2.988	2.651	1.376	1.618	1.116	2.285	0.9649	1.456	90~100	3.265	1433	98.6,98.6
110	2.622	2.601	2.322	2.448	2.173	2.090	2.179	2.108	100~110	2.052	1435	98.7,98.7
120	3.798	3.789	3.537	3.387	3.160	2.952	3.135	3.072	110~120	2.819	1438	98.9,98.9
130	4.841	4.737	4.507	4.249	4.095	3.913	3.869	3.753	120~130	3.414	1441	99.2,99.2
140	5.689	5.372	5.203	5.058	4.885	4.855	4.403	4.340	130~140	3.574	1445	99.4,99.4
150	6.385	5.804	5.637	5.845	5.438	5.737	5.117	4.768	140~150	3.308	1448	99.6,99.6
160	7.098	6.220	6.459	6.600	6.059	6.498	6.320	5.442	150~160	2.746	1451	99.8,99.8
170	7.114	7.135	7.414	7.202	6.666	7.160	7.362	6.905	160~170	1.895	1453	100,100
180	7.120	8.122	8.136	8.222	7.140	8.116	8.162	8.216	170~180	0.7033	1453	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.6480A P:15.50W PF:1.000 Freq:0Hz Lamp Flux:1453.43x1 lm		
NAME: D8168M2410NO	TYPE:	WEIGHT:
SPEC.:D8168M2410NO-9NWDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	29950	22275
80	33161	30495
75	37874	36803
70	41364	40770
65	43684	43399
60	45516	45366
55	46551	46531
50	47203	47190
45	47622	47650


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.6480A P:15.50W PF:1.000 Freq:0Hz Lamp Flux:1453.43x1 lm		
NAME: D8168M2410NO	TYPE:	WEIGHT:
SPEC.:D8168M2410NO-9NWDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.79	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.60	.68	.63	.59	.57
4.0	.69	.61	.54	.68	.60	.53	.65	.58	.52	.63	.57	.51	.60	.55	.51	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.44	.54	.48	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.42	.35	.50	.41	.35	.48	.40	.35	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.34	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.26
10.0	.39	.31	.26	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-03-31

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:24.00V I:0.6480A P:15.50W PF:1.000 Freq:0Hz Lamp Flux:1453.43x1 lm		
NAME: D8168M2410NO	TYPE:	WEIGHT:
SPEC.:D8168M2410NO-9NWDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.314	.179	.057	.306	.175	.056	.292	.168	.054	.279	.161	.052	.267	.155	.050	
2.0	.295	.161	.050	.288	.159	.049	.275	.153	.048	.264	.148	.046	.253	.143	.045	
3.0	.272	.145	.043	.266	.143	.043	.255	.138	.042	.245	.134	.041	.235	.130	.040	
4.0	.251	.130	.038	.246	.129	.038	.236	.125	.037	.227	.122	.037	.218	.118	.036	
5.0	.232	.118	.034	.227	.117	.034	.218	.114	.033	.210	.111	.033	.202	.108	.032	
6.0	.215	.108	.031	.211	.106	.031	.203	.104	.030	.195	.101	.030	.188	.099	.029	
7.0	.200	.099	.028	.196	.098	.028	.189	.096	.028	.182	.093	.027	.176	.091	.027	
8.0	.187	.091	.026	.183	.090	.025	.177	.088	.025	.171	.087	.025	.165	.085	.025	
9.0	.175	.085	.024	.172	.084	.023	.166	.082	.023	.160	.080	.023	.155	.079	.023	
10.0	.164	.079	.022	.161	.078	.022	.156	.077	.022	.151	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.203	.203	.203	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.193	.169	.147	.165	.145	.126	.113	.100	.087	.065	.058	.051	.021	.019	.016	
2.0	.185	.145	.110	.159	.124	.095	.109	.086	.067	.063	.050	.039	.020	.016	.013	
3.0	.178	.127	.087	.152	.110	.075	.105	.076	.053	.060	.044	.031	.019	.014	.010	
4.0	.170	.114	.071	.146	.098	.062	.100	.069	.043	.058	.040	.026	.019	.013	.008	
5.0	.163	.103	.060	.140	.090	.052	.096	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.156	.095	.052	.134	.082	.045	.092	.058	.032	.054	.034	.019	.017	.011	.006	
7.0	.149	.088	.046	.128	.077	.040	.088	.054	.028	.051	.032	.017	.017	.010	.006	
8.0	.142	.083	.042	.122	.072	.036	.085	.050	.026	.049	.030	.015	.016	.010	.005	
9.0	.136	.078	.038	.117	.067	.033	.081	.047	.024	.047	.028	.014	.015	.009	.005	
10.0	.130	.073	.035	.112	.064	.031	.078	.045	.022	.045	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.6480A P:15.50W PF:1.000 Freq:0Hz Lamp Flux:1453.43x1 lm											
NAME: D8168M2410NO					TYPE:			WEIGHT:			
SPEC.:D8168M2410NO-9NWDA012WC0100					DIM.: 1000*10*1.5			SERIAL No.:01			
MFR.: COLORS					SUR.:1000*10			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	24.9	26.4	25.2	26.7	26.9	24.9	26.4	25.2	26.7	26.9	
	3H	26.5	27.9	26.8	28.1	28.4	26.4	27.8	26.8	28.1	28.4
	4H	27.1	28.4	27.4	28.7	29.0	27.0	28.3	27.4	28.6	28.9
	6H	27.5	28.7	27.8	29.0	29.3	27.4	28.6	27.7	28.9	29.2
	8H	27.6	28.8	28.0	29.1	29.4	27.5	28.7	27.8	29.0	29.3
	12H	27.7	28.8	28.0	29.2	29.5	27.5	28.7	27.9	29.0	29.3
4H	2H	25.6	26.9	25.9	27.2	27.5	25.6	26.9	25.9	27.2	27.5
	3H	27.3	28.4	27.7	28.8	29.1	27.3	28.4	27.6	28.7	29.1
	4H	28.0	29.1	28.4	29.4	29.8	28.0	29.0	28.4	29.4	29.7
	6H	28.5	29.5	28.9	29.8	30.3	28.4	29.4	28.9	29.8	30.2
	8H	28.7	29.6	29.1	30.0	30.4	28.6	29.4	29.0	29.8	30.3
	12H	28.8	29.6	29.3	30.0	30.5	28.6	29.4	29.1	29.9	30.3
8H	4H	28.3	29.1	28.7	29.5	30.0	28.2	29.1	28.7	29.5	29.9
	6H	28.9	29.7	29.4	30.1	30.6	28.8	29.6	29.3	30.0	30.5
	8H	29.2	29.8	29.7	30.3	30.8	29.1	29.7	29.5	30.2	30.6
	12H	29.4	29.9	29.9	30.4	30.9	29.2	29.8	29.7	30.2	30.7
12H	4H	28.3	29.1	28.7	29.5	29.9	28.2	29.0	28.7	29.5	29.9
	6H	29.0	29.6	29.5	30.1	30.6	28.9	29.6	29.4	30.0	30.5
	8H	29.3	29.8	29.8	30.3	30.8	29.2	29.7	29.7	30.2	30.7
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 1453 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 1.3$)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.6480A P:15.50W PF:1.000 Freq:0Hz Lamp Flux:1453.43x1 lm		
NAME: D8168M2410NO	TYPE:	WEIGHT:
SPEC.:D8168M2410NO-9NWDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	45	38	56	44	38	54	44	37	31
0.80	66	55	47	65	54	47	63	53	47	39
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	80	71	64	78	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	82	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	101	94	89	99	93	88	95	90	85	76
4.00	106	100	95	103	98	93	98	94	91	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.6480A P:15.50W PF:1.000 Freq:0Hz Lamp Flux:1453.43x1 lm		
NAME: D8168M2410NO	TYPE:	WEIGHT:
SPEC.:D8168M2410NO-9NWDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-31

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.6480A P:15.50W PF:1.000 Freq:0Hz Lamp Flux:1453.43x1 lm		
NAME: D8168M2410NO	TYPE:	WEIGHT:
SPEC.:D8168M2410NO-9NWDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Flux out:1071 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.6480A P:15.50W PF:1.000 Freq:0Hz Lamp Flux:1453.43x1 lm		
NAME: D8168M2410NO	TYPE:	WEIGHT:
SPEC.:D8168M2410NO-9NWDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-03-31

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-03-31

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.6480A P:15.50W PF:1.000 Freq:0Hz Lamp Flux:1453.43x1 lm		
NAME: D8168M2410NO	TYPE:	WEIGHT:
SPEC.:D8168M2410NO-9NWDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	481	480	480	481	481	480	480	481										
5	479	480	479	479	478	478	478	479										
10	474	475	474	473	472	471	472	474										
15	465	467	465	464	462	461	463	464										
20	453	455	453	451	449	448	450	452										
25	436	439	437	435	432	431	433	436										
30	417	420	417	415	412	410	414	416										
35	393	395	394	389	386	386	388	392										
40	367	368	367	363	359	359	361	366										
45	337	338	337	333	329	329	331	336										
50	303	305	303	299	296	296	298	303										
55	267	269	267	263	260	260	263	267										
60	228	229	227	224	222	221	224	228										
65	185	188	183	182	181	179	183	185										
70	141	144	139	139	139	138	141	142										
75	98.0	101	95.3	96.0	98.1	96.7	98.5	99.3										
80	57.6	60.1	53.0	55.6	59.3	58.5	58.1	58.5										
85	26.1	27.4	19.4	23.0	26.6	26.6	24.7	25.2										
90	10.2	9.81	2.34	5.07	6.91	8.23	2.38	7.78										
95	5.20	4.67	1.44	1.61	1.30	3.00	0.56	2.12										
100	2.99	2.65	1.38	1.62	1.12	2.28	0.96	1.46										
105	2.20	2.21	1.70	1.98	1.65	2.07	1.56	1.70										
110	2.62	2.60	2.32	2.45	2.17	2.09	2.18	2.11										
115	3.19	3.21	2.96	2.92	2.69	2.48	2.70	2.64										
120	3.80	3.79	3.54	3.39	3.16	2.95	3.14	3.07										
125	4.34	4.30	4.03	3.82	3.64	3.46	3.53	3.41										
130	4.84	4.74	4.51	4.25	4.09	3.91	3.87	3.75										
135	5.31	5.10	4.88	4.66	4.52	4.37	4.18	4.07										
140	5.69	5.37	5.20	5.06	4.88	4.85	4.40	4.34										
145	6.04	5.60	5.41	5.47	5.20	5.33	4.66	4.53										
150	6.38	5.80	5.64	5.84	5.44	5.74	5.12	4.77										
155	6.75	5.99	6.01	6.24	5.73	6.12	5.71	5.04										
160	7.10	6.22	6.46	6.60	6.06	6.50	6.32	5.44										
165	7.26	6.57	6.93	6.87	6.40	6.80	6.86	6.08										
170	7.11	7.13	7.41	7.20	6.67	7.16	7.36	6.90										
175	6.91	7.71	7.85	7.66	6.73	7.59	7.82	7.65										
180	7.12	8.12	8.14	8.22	7.14	8.12	8.16	8.22										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: