


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.3833A P:9.198W PF:1.000 Freq:0Hz Lamp Flux:1969.45x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 214.11 lm/W			
MODEL	D81802410NO	I _{max} (cd)	635.3	S/MH(C0/180)	1.28
NOMINAL POWER(W)	8.7	LOR(%)	100.0	S/MH(C90/270)	1.29
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1969.4	h UP,DN(C0-180)	0.9,48.9
NOMINAL FLUX(lm)	1969.45	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,49.3
LAMPS INSIDE	1	h up(%)	1.8	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	h down(%)	98.2	CIBSE SHR MAX	1.50



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-20

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	621.9	623.4	625.1	628.5	626.8	626.8	624.9	622.8	0- 10	60.10	60.10	3.05,3.05
20	592.8	594.8	598.3	604.1	602.4	600.7	597.1	592.6	10- 20	173.3	233.4	11.9,11.9
30	545.6	548.3	554.0	562.0	560.0	556.6	551.3	544.3	20- 30	266.4	499.8	25.4,25.4
40	480.8	484.4	491.4	501.3	499.3	494.7	488.0	478.7	30- 40	327.6	827.4	42,42
50	398.2	400.9	410.2	422.5	420.6	414.7	406.5	396.0	40- 50	348.2	1176	59.7,59.7
60	298.8	301.2	311.4	322.6	321.1	317.6	307.8	297.3	50- 60	322.3	1498	76.1,76.1
70	184.1	188.1	196.7	209.5	208.9	205.2	196.0	183.5	60- 70	251.7	1750	88.8,88.8
80	70.57	73.57	79.01	91.41	90.95	87.79	80.70	70.60	70- 80	145.1	1895	96.2,96.2
90	5.557	5.987	3.545	10.16	9.754	8.699	3.844	4.900	80- 90	40.12	1935	98.2,98.2
100	2.819	2.880	2.611	2.854	1.820	1.801	1.712	2.076	90-100	3.118	1938	98.4,98.4
110	4.249	4.094	3.478	3.992	3.781	3.502	3.661	3.874	100-110	3.195	1941	98.6,98.6
120	5.989	5.796	5.200	5.587	5.539	4.996	4.952	5.629	110-120	4.625	1946	98.8,98.8
130	7.492	6.982	6.476	6.930	7.035	6.163	5.926	6.739	120-130	5.484	1951	99.1,99.1
140	8.610	7.736	7.340	7.883	8.124	7.246	6.688	7.313	130-140	5.564	1957	99.4,99.4
150	9.137	8.170	8.041	8.678	8.798	8.329	7.363	7.540	140-150	4.983	1962	99.6,99.6
160	9.705	8.557	9.157	9.552	9.439	9.304	8.845	7.987	150-160	3.989	1966	99.8,99.8
170	9.894	9.847	10.49	10.31	9.363	10.10	10.35	9.762	160-170	2.695	1968	100,100
180	9.692	11.31	11.54	11.64	9.699	11.32	11.53	11.63	170-180	0.9837	1969	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-20

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.3833A P:9.198W PF:1.000 Freq:0Hz Lamp Flux:1969.45x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	31337	34458
80	40638	45502
75	48479	52765
70	53821	57498
65	57591	60610
60	59754	62288
55	61152	63285
50	61955	63814
45	62474	64038


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-20

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.3833A P:9.198W PF:1.000 Freq:0Hz Lamp Flux:1969.45x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.00	1.00	1.00	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.89	.82	.77	.87	.81	.76	.84	.78	.74	.80	.76	.72	.77	.73	.70	.67
3.0	.78	.70	.63	.77	.69	.63	.73	.67	.61	.70	.65	.60	.67	.63	.59	.56
4.0	.69	.60	.53	.68	.59	.53	.65	.58	.52	.62	.56	.51	.60	.55	.50	.48
5.0	.62	.52	.46	.60	.52	.45	.58	.50	.45	.56	.49	.44	.54	.48	.43	.41
6.0	.55	.46	.40	.54	.46	.39	.52	.45	.39	.50	.44	.38	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.47	.40	.34	.46	.39	.34	.44	.38	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.31	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.33	.28	.41	.33	.28	.40	.33	.27	.39	.32	.27	.37	.31	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.24	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-20

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.3833A P:9.198W PF:1.000 Freq:0Hz Lamp Flux:1969.45x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.316	.180	.057	.309	.176	.056	.294	.169	.054	.281	.162	.052	.269	.156	.050	
2.0	.297	.163	.050	.290	.160	.049	.277	.154	.048	.266	.149	.047	.255	.144	.045	
3.0	.274	.146	.044	.268	.144	.043	.257	.139	.042	.246	.135	.041	.237	.131	.041	
4.0	.253	.131	.039	.247	.129	.038	.237	.126	.038	.228	.122	.037	.219	.119	.036	
5.0	.233	.119	.034	.228	.117	.034	.219	.114	.034	.211	.111	.033	.203	.109	.033	
6.0	.216	.108	.031	.212	.107	.031	.204	.104	.030	.196	.102	.030	.189	.100	.030	
7.0	.201	.099	.028	.197	.098	.028	.190	.096	.028	.183	.094	.027	.177	.092	.027	
8.0	.187	.092	.026	.184	.091	.026	.177	.089	.025	.171	.087	.025	.166	.085	.025	
9.0	.175	.085	.024	.172	.084	.024	.167	.082	.023	.161	.081	.023	.156	.079	.023	
10.0	.165	.079	.022	.162	.078	.022	.157	.077	.022	.152	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.204	.204	.204	.174	.174	.174	.119	.119	.119	.068	.068	.068	.022	.022	.022	
1.0	.194	.170	.147	.166	.146	.127	.114	.100	.088	.065	.058	.051	.021	.019	.016	
2.0	.187	.145	.111	.160	.125	.096	.109	.087	.067	.063	.050	.039	.020	.016	.013	
3.0	.179	.128	.087	.153	.110	.076	.105	.077	.053	.061	.045	.031	.020	.015	.010	
4.0	.171	.115	.072	.147	.099	.062	.101	.069	.044	.059	.040	.026	.019	.013	.009	
5.0	.164	.104	.061	.141	.090	.053	.097	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.157	.096	.053	.135	.083	.046	.093	.058	.032	.054	.034	.019	.017	.011	.006	
7.0	.150	.089	.047	.129	.077	.041	.089	.054	.029	.052	.032	.017	.017	.010	.006	
8.0	.143	.084	.042	.124	.072	.037	.085	.051	.026	.050	.030	.016	.016	.010	.005	
9.0	.137	.079	.039	.118	.068	.034	.082	.048	.024	.048	.028	.014	.015	.009	.005	
10.0	.132	.074	.036	.113	.065	.032	.079	.045	.022	.046	.027	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-20

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.3833A P:9.198W PF:1.000 Freq:0Hz Lamp Flux:1969.45x1 lm											
NAME: D81802410NO					TYPE:			WEIGHT:			
SPEC.:D81802410NO-8NWN5A012WC0100					DIM.: 1000*10*1.5mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*10mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	24.7	26.2	25.0	26.5	26.7	24.9	26.4	25.2	26.6	26.9	
	3H	26.2	27.6	26.6	27.9	28.2	26.5	27.9	26.8	28.1	28.4
	4H	26.8	28.1	27.2	28.4	28.7	27.1	28.4	27.4	28.7	29.0
	6H	27.2	28.4	27.5	28.7	29.1	27.5	28.7	27.8	29.0	29.4
	8H	27.3	28.5	27.6	28.8	29.1	27.6	28.8	28.0	29.1	29.5
	12H	27.3	28.5	27.7	28.8	29.1	27.6	28.8	28.0	29.1	29.5
4H	2H	25.3	26.7	25.7	27.0	27.3	25.5	26.8	25.8	27.1	27.4
	3H	27.0	28.2	27.4	28.5	28.9	27.2	28.4	27.6	28.7	29.1
	4H	27.7	28.8	28.1	29.1	29.5	28.0	29.0	28.4	29.4	29.7
	6H	28.2	29.1	28.6	29.5	29.9	28.5	29.4	28.9	29.8	30.2
	8H	28.3	29.2	28.8	29.6	30.0	28.6	29.5	29.1	29.9	30.3
	12H	28.4	29.2	28.9	29.6	30.1	28.7	29.5	29.2	30.0	30.4
8H	4H	28.0	28.9	28.4	29.3	29.7	28.2	29.1	28.6	29.5	29.9
	6H	28.6	29.3	29.1	29.8	30.2	28.8	29.6	29.3	30.0	30.5
	8H	28.8	29.4	29.3	29.9	30.4	29.1	29.7	29.6	30.2	30.7
	12H	28.9	29.5	29.4	30.0	30.5	29.2	29.8	29.7	30.3	30.8
12H	4H	28.0	28.8	28.4	29.2	29.7	28.2	29.0	28.6	29.4	29.9
	6H	28.6	29.3	29.1	29.7	30.2	28.9	29.5	29.4	30.0	30.5
	8H	28.9	29.4	29.4	29.9	30.4	29.1	29.7	29.6	30.2	30.7
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 1969 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 2.4$)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-20

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.3833A P:9.198W PF:1.000 Freq:0Hz Lamp Flux:1969.45x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	44	37	55	44	37	54	43	37	30
0.80	66	54	47	65	54	46	63	53	46	39
1.00	74	63	56	73	62	55	71	64	55	47
1.25	82	71	64	80	70	63	77	68	62	54
1.50	87	77	69	85	76	69	82	74	68	60
2.00	94	85	78	92	84	77	88	81	76	67
2.50	98	90	84	96	88	83	91	85	80	72
3.00	101	94	88	99	92	87	95	89	85	76
4.00	105	99	95	103	98	93	98	94	90	81
5.00	108	103	99	105	101	97	100	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-20

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.3833A P:9.198W PF:1.000 Freq:0Hz Lamp Flux:1969.45x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-01-20

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.3833A P:9.198W PF:1.000 Freq:0Hz Lamp Flux:1969.45x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:

Flux out:1498 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-20

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.3833A P:9.198W PF:1.000 Freq:0Hz Lamp Flux:1969.45x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-20

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-01-20

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.3833A P:9.198W PF:1.000 Freq:0Hz Lamp Flux:1969.45x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8NWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*10mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	634	634	634	635	634	634	634	635										
5	630	631	632	634	633	633	632	631										
10	622	623	625	628	627	627	625	623										
15	610	611	614	618	617	616	613	610										
20	593	595	598	604	602	601	597	593										
25	572	574	579	585	584	581	577	571										
30	546	548	554	562	560	557	551	544										
35	516	519	525	534	532	528	522	514										
40	481	484	491	501	499	495	488	479										
45	442	446	453	464	462	457	450	440										
50	398	401	410	422	421	415	407	396										
55	351	353	363	373	372	368	358	349										
60	299	301	311	323	321	318	308	297										
65	243	246	256	268	267	263	253	242										
70	184	188	197	210	209	205	196	184										
75	125	129	137	150	149	145	137	125										
80	70.6	73.6	79.0	91.4	90.9	87.8	80.7	70.6										
85	27.3	29.0	30.0	41.3	40.8	38.8	33.1	26.8										
90	5.56	5.99	3.55	10.2	9.75	8.70	3.84	4.90										
95	2.79	2.94	2.70	3.10	1.82	1.83	0.96	2.00										
100	2.82	2.88	2.61	2.85	1.82	1.80	1.71	2.08										
105	3.42	3.36	2.84	3.31	2.81	2.69	2.75	2.87										
110	4.25	4.09	3.48	3.99	3.78	3.50	3.66	3.87										
115	5.15	4.98	4.39	4.82	4.70	4.26	4.32	4.83										
120	5.99	5.80	5.20	5.59	5.54	5.00	4.95	5.63										
125	6.78	6.47	5.90	6.29	6.33	5.61	5.47	6.26										
130	7.49	6.98	6.48	6.93	7.03	6.16	5.93	6.74										
135	8.10	7.41	6.93	7.46	7.66	6.70	6.33	7.12										
140	8.61	7.74	7.34	7.88	8.12	7.25	6.69	7.31										
145	8.88	7.99	7.77	8.28	8.52	7.80	6.99	7.45										
150	9.14	8.17	8.04	8.68	8.80	8.33	7.36	7.54										
155	9.48	8.33	8.50	9.11	9.15	8.84	8.02	7.65										
160	9.70	8.56	9.16	9.55	9.44	9.30	8.84	7.99										
165	9.98	9.00	9.86	9.91	9.63	9.72	9.65	8.73										
170	9.89	9.85	10.5	10.3	9.36	10.1	10.3	9.76										
175	9.53	10.7	11.1	10.9	9.00	10.6	11.0	10.8										
180	9.69	11.3	11.5	11.6	9.70	11.3	11.5	11.6										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-20

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: