


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.4277A P:10.26W PF:1.000 Freq:0Hz Lamp Flux:1972.04x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 192.13 lm/W			
MODEL	D81802410NO	I _{max} (cd)	646.8	S/MH(C0/180)	1.27
NOMINAL POWER(W)	9.6	LOR(%)	100.0	S/MH(C90/270)	1.28
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1972.0	h UP,DN(C0-180)	0.9,49.7
NOMINAL FLUX(lm)	1972.04	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,48.7
LAMPS INSIDE	1	h up(%)	1.7	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.3	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	632.1	634.8	636.8	639.6	636.7	636.3	635.2	634.3	0- 10	61.15	61.15	3.1,3.1
20	601.2	605.4	609.0	613.1	609.8	607.9	605.3	602.7	10- 20	176.1	237.2	12,12
30	551.6	557.3	562.6	568.1	564.3	560.1	556.7	551.9	20- 30	269.9	507.1	25.7,25.7
40	484.2	492.1	497.8	504.5	499.5	494.2	489.1	483.2	30- 40	330.5	837.7	42.5,42.5
50	399.0	408.1	416.1	423.5	417.3	408.9	401.2	396.4	40- 50	349.5	1187	60.2,60.2
60	298.0	308.1	317.3	322.7	315.2	307.1	298.5	293.9	50- 60	321.2	1508	76.5,76.5
70	183.0	195.3	203.3	210.0	201.8	190.4	184.0	177.3	60- 70	248.8	1757	89.1,89.1
80	69.33	81.73	87.24	93.43	85.31	77.16	70.82	64.33	70- 80	142.2	1899	96.3,96.3
90	6.793	11.88	11.01	13.34	8.054	6.575	1.469	4.613	80- 90	39.83	1939	98.3,98.3
100	2.410	3.184	2.183	2.592	1.604	1.711	1.787	1.970	90-100	3.447	1943	98.5,98.5
110	4.007	3.749	3.058	3.583	3.284	3.186	3.489	3.532	100-110	2.926	1946	98.7,98.7
120	5.741	4.957	4.466	5.079	4.826	4.473	4.864	5.140	110-120	4.191	1950	98.9,98.9
130	7.072	5.793	5.516	6.355	6.132	5.729	5.947	6.352	120-130	4.968	1955	99.1,99.1
140	8.015	6.460	6.506	7.382	7.196	6.918	6.740	7.126	130-140	5.099	1960	99.4,99.4
150	8.643	6.947	7.972	8.431	7.802	8.101	7.684	7.661	140-150	4.676	1965	99.6,99.6
160	9.383	8.159	9.288	9.599	8.377	9.150	9.267	8.502	150-160	3.879	1968	99.8,99.8
170	9.239	9.787	10.47	10.68	8.770	10.13	10.45	10.16	160-170	2.675	1971	100,100
180	9.184	11.33	11.43	11.86	9.178	11.31	11.43	11.92	170-180	0.9788	1972	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-29

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.4277A P:10.26W PF:1.000 Freq:0Hz Lamp Flux:1972.04x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	30535	47639
80	39927	50238
75	48145	55387
70	53516	59430
65	57358	62213
60	59595	63466
55	61103	64296
50	62072	64733
45	62742	64922


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-29

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.4277A P:10.26W PF:1.000 Freq:0Hz Lamp Flux:1972.04x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.78	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.78	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.60	.68	.63	.59	.57
4.0	.69	.60	.54	.68	.60	.53	.65	.58	.52	.63	.56	.51	.60	.55	.50	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.49	.44	.54	.48	.44	.41
6.0	.56	.46	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.35	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.35	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.27	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.4277A P:10.26W PF:1.000 Freq:0Hz Lamp Flux:1972.04x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0														
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
rfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.315	.179	.057	.307	.175	.056	.293	.168	.054	.280	.161	.052	.268	.155	.050															
2.0	.295	.162	.050	.289	.159	.049	.276	.153	.048	.264	.148	.046	.254	.143	.045															
3.0	.273	.145	.044	.267	.143	.043	.256	.139	.042	.245	.134	.041	.236	.131	.040															
4.0	.252	.131	.038	.246	.129	.038	.236	.125	.037	.227	.122	.037	.218	.119	.036															
5.0	.232	.118	.034	.228	.117	.034	.219	.114	.034	.210	.111	.033	.203	.108	.033															
6.0	.215	.108	.031	.211	.107	.031	.203	.104	.030	.196	.102	.030	.189	.099	.030															
7.0	.200	.099	.028	.196	.098	.028	.189	.096	.028	.183	.094	.027	.176	.092	.027															
8.0	.187	.091	.026	.183	.090	.026	.177	.088	.025	.171	.087	.025	.165	.085	.025															
9.0	.175	.085	.024	.172	.084	.024	.166	.082	.023	.161	.081	.023	.156	.079	.023															
10.0	.164	.079	.022	.162	.078	.022	.156	.077	.022	.152	.075	.021	.147	.074	.021															

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.203	.203	.203	.174	.174	.174	.119	.119	.119	.068	.068	.068	.022	.022	.022	
1.0	.193	.169	.147	.166	.145	.126	.113	.100	.087	.065	.058	.051	.021	.019	.016	
2.0	.186	.145	.110	.159	.125	.095	.109	.086	.067	.063	.050	.039	.020	.016	.013	
3.0	.178	.127	.087	.153	.110	.075	.105	.076	.053	.061	.045	.031	.019	.014	.010	
4.0	.170	.114	.071	.146	.099	.062	.101	.069	.043	.058	.040	.026	.019	.013	.008	
5.0	.163	.104	.060	.140	.090	.052	.096	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.156	.095	.052	.134	.083	.045	.092	.058	.032	.054	.034	.019	.017	.011	.006	
7.0	.149	.089	.046	.128	.077	.040	.089	.054	.028	.051	.032	.017	.017	.010	.006	
8.0	.143	.083	.042	.123	.072	.036	.085	.050	.026	.049	.030	.015	.016	.010	.005	
9.0	.136	.078	.038	.118	.068	.033	.081	.047	.024	.047	.028	.014	.015	.009	.005	
10.0	.131	.074	.036	.113	.064	.031	.078	.045	.022	.046	.027	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.4277A P:10.26W PF:1.000 Freq:0Hz Lamp Flux:1972.04x1 lm											
NAME: D81802410NO					TYPE:			WEIGHT:			
SPEC.:D81802410NO-8SWNSA012WC0100					DIM.: 1000*10*1.5mm			SERIAL No.:01			
MFR.: COLORS					SUR.:1000*10			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	24.8	26.3	25.1	26.5	26.8	25.0	26.5	25.3	26.7	27.0	
	3H	26.3	27.7	26.6	27.9	28.2	26.6	28.0	26.9	28.3	28.6
	4H	26.8	28.2	27.2	28.5	28.8	27.3	28.6	27.6	28.9	29.2
	6H	27.2	28.5	27.6	28.8	29.1	27.7	29.0	28.1	29.3	29.6
	8H	27.3	28.5	27.7	28.8	29.1	27.9	29.1	28.2	29.4	29.7
	12H	27.3	28.5	27.7	28.8	29.2	28.0	29.1	28.4	29.5	29.8
4H	2H	25.4	26.8	25.8	27.0	27.3	25.6	26.9	25.9	27.2	27.5
	3H	27.1	28.3	27.5	28.6	28.9	27.4	28.6	27.8	28.9	29.2
	4H	27.8	28.9	28.2	29.2	29.6	28.2	29.2	28.6	29.6	29.9
	6H	28.3	29.2	28.7	29.6	30.0	28.8	29.7	29.2	30.1	30.5
	8H	28.4	29.3	28.9	29.7	30.1	29.0	29.8	29.4	30.2	30.7
	12H	28.5	29.3	28.9	29.7	30.2	29.1	29.9	29.6	30.3	30.8
8H	4H	28.1	29.0	28.5	29.4	29.8	28.4	29.3	28.9	29.7	30.1
	6H	28.7	29.4	29.2	29.9	30.3	29.1	29.9	29.6	30.3	30.8
	8H	28.9	29.6	29.4	30.0	30.5	29.4	30.1	29.9	30.5	31.0
	12H	29.1	29.6	29.6	30.1	30.6	29.7	30.2	30.2	30.7	31.2
12H	4H	28.1	28.9	28.6	29.3	29.8	28.4	29.2	28.9	29.6	30.1
	6H	28.8	29.4	29.3	29.9	30.4	29.2	29.8	29.7	30.3	30.8
	8H	29.0	29.6	29.5	30.1	30.6	29.5	30.1	30.0	30.6	31.1
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2				+ 0.1 / - 0.2						
1.5H	+ 0.2 / - 0.3				+ 0.2 / - 0.3						
2.0H	+ 0.2 / - 0.4				+ 0.2 / - 0.3						

CIE Pub.117, 1972 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 2.4)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.4277A P:10.26W PF:1.000 Freq:0Hz Lamp Flux:1972.04x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	44	37	55	44	37	54	44	37	31
0.80	66	54	47	65	54	47	63	53	46	39
1.00	75	63	56	73	63	56	71	64	55	48
1.25	82	71	64	80	70	63	77	69	62	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	81	76	68
2.50	98	90	84	96	88	83	92	86	81	72
3.00	101	94	89	99	93	87	95	89	85	76
4.00	105	100	95	103	98	93	98	94	90	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-29

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.4277A P:10.26W PF:1.000 Freq:0Hz Lamp Flux:1972.04x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-01-29

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.4277A P:10.26W PF:1.000 Freq:0Hz Lamp Flux:1972.04x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Flux out:1479 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:24.00V I:0.4277A P:10.26W PF:1.000 Freq:0Hz Lamp Flux:1972.04x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-29

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:24.00V I:0.4277A P:10.26W PF:1.000 Freq:0Hz Lamp Flux:1972.04x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	59430
L_0~180(75)av	51607
L_0~180(85)av	35841
L_90~270(65)av	59775
L_90~270(75)av	52021
L_90~270(85)av	37867
L_45(65)av	59710
L_45(75)av	51948
L_45(85)av	38761

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.4277A P:10.26W PF:1.000 Freq:0Hz Lamp Flux:1972.04x1 lm		
NAME: D81802410NO	TYPE:	WEIGHT:
SPEC.:D81802410NO-8SWNSA012WC0100	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	644	645	646	647	644	645	646	647										
5	641	642	644	645	643	643	643	643										
10	632	635	637	640	637	636	635	634										
15	619	622	625	629	626	624	623	621										
20	601	605	609	613	610	608	605	603										
25	579	584	588	593	589	586	584	580										
30	552	557	563	568	564	560	557	552										
35	520	527	532	539	534	529	525	520										
40	484	492	498	505	500	494	489	483										
45	444	452	459	466	460	454	448	442										
50	399	408	416	423	417	409	401	396										
55	350	359	369	374	367	360	351	347										
60	298	308	317	323	315	307	299	294										
65	242	253	263	268	260	251	242	237										
70	183	195	203	210	202	190	184	177										
75	125	137	143	151	143	131	126	119										
80	69.3	81.7	87.2	93.4	85.3	77.2	70.8	64.3										
85	26.6	35.8	41.5	44.1	35.9	32.3	24.5	23.0										
90	6.79	11.9	11.0	13.3	8.05	6.58	1.47	4.61										
95	2.39	5.35	2.17	4.23	1.26	1.56	1.08	1.48										
100	2.41	3.18	2.18	2.59	1.60	1.71	1.79	1.97										
105	3.14	3.09	2.52	2.92	2.44	2.51	2.70	2.66										
110	4.01	3.75	3.06	3.58	3.28	3.19	3.49	3.53										
115	4.90	4.47	3.76	4.36	4.06	3.82	4.22	4.36										
120	5.74	4.96	4.47	5.08	4.83	4.47	4.86	5.14										
125	6.46	5.36	5.00	5.75	5.51	5.12	5.45	5.86										
130	7.07	5.79	5.52	6.35	6.13	5.73	5.95	6.35										
135	7.60	6.17	6.00	6.87	6.70	6.32	6.39	6.79										
140	8.02	6.46	6.51	7.38	7.20	6.92	6.74	7.13										
145	8.31	6.70	7.15	7.88	7.58	7.55	7.06	7.43										
150	8.64	6.95	7.97	8.43	7.80	8.10	7.68	7.66										
155	9.02	7.41	8.64	9.01	8.06	8.64	8.48	7.99										
160	9.38	8.16	9.29	9.60	8.38	9.15	9.27	8.50										
165	9.62	8.94	9.92	10.1	8.68	9.58	9.87	9.29										
170	9.24	9.79	10.5	10.7	8.77	10.1	10.4	10.2										
175	8.84	10.6	11.0	11.3	8.64	10.7	11.0	11.1										
180	9.18	11.3	11.4	11.9	9.18	11.3	11.4	11.9										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-29

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: