


## LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.6530A P:15.67W PF:1.000 Freq:0Hz Lamp Flux:531.01x1 lm		
NAME: DA1682410NO	TYPE:	WEIGHT:
SPEC.:DA1682410NO-0RGBNDA012WC0500	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: Colors	SUR.:1000*10mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 33.88 lm/W			
MODEL	DA1682410NO	I <sub>max</sub> (cd)	141.8	S/MH(C0/180)	1.41
NOMINAL POWER(W)	16W/M	LOR(%)	100.0	S/MH(C90/270)	1.42
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	531.01	h UP,DN(C0-180)	0.3,49.9
NOMINAL FLUX(lm)	531.01	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.4,49.4
LAMPS INSIDE	1	h up(%)	0.7	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	h down(%)	99.3	CIBSE SHR MAX	1.55

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:COLORS  
 Test Date:2018-12-12

g Range: 0 - 180DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:7.500m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C90	C180	C270					g	F zone	F total	%lum,lamp
10	140.5	141.3	140.3	141.1					0~ 10	13.48	13.48	2.54,2.54
20	137.6	138.2	137.1	138.1					10~ 20	39.49	52.97	9.98,9.98
30	133.2	133.9	132.6	133.6					20~ 30	62.70	115.7	21.8,21.8
40	126.7	126.7	125.3	126.7					30~ 40	81.75	197.4	37.2,37.2
50	114.6	111.9	112.2	112.6					40~ 50	92.92	290.3	54.7,54.7
60	95.42	90.34	91.79	91.49					50~ 60	92.34	382.7	72.1,72.1
70	67.11	62.40	62.15	64.22					60~ 70	77.97	460.6	86.7,86.7
80	32.92	28.31	27.84	31.81					70~ 80	49.89	510.5	96.1,96.1
90	5.951	0.2371	4.018	4.009					80~ 90	16.71	527.3	99.3,99.3
100	0.2475	0.2729	0.2822	0.2568					90~100	0.9974	528.3	99.5,99.5
110	0.3416	0.3886	0.3981	0.3974					100~110	0.3396	528.6	99.5,99.5
120	0.4418	0.4983	0.5046	0.4857					110~120	0.4292	529.0	99.6,99.6
130	0.5389	0.5891	0.5985	0.5826					120~130	0.4791	529.5	99.7,99.7
140	0.6141	0.6580	0.6612	0.6361					130~140	0.4741	530.0	99.8,99.8
150	0.6891	0.7114	0.7114	0.6862					140~150	0.4213	530.4	99.9,99.9
160	0.7205	0.7397	0.7521	0.7270					150~160	0.3315	530.7	99.9,99.9
170	0.7489	0.7552	0.7740	0.7458					160~170	0.2128	530.9	100,100
180	0.7583	0.7583	0.7771	0.7458					170~180	0.0723	531.0	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2018-12-12

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.6530A P:15.67W PF:1.000 Freq:0Hz Lamp Flux:531.01x1 lm		
NAME: DA1682410NO	TYPE:	WEIGHT:
SPEC.:DA1682410NO-0RGBNDA012WC0500	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: Colors	SUR.:1000*10mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	19822	13361
80	18960	16303
75	19390	17817
70	19622	18245
65	19498	18253
60	19083	18068
55	18475	17757
50	17824	17403
45	17167	17009


C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2018-12-12

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.6530A P:15.67W PF:1.000 Freq:0Hz Lamp Flux:531.01x1 lm		
NAME: DA1682410NO	TYPE:	WEIGHT:
SPEC.:DA1682410NO-0RGBNDA012WC0500	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: Colors	SUR.:1000*10mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.01	1.01	1.01	.99
1.0	1.02	.97	.93	.99	.95	.91	.95	.91	.88	.91	.88	.85	.87	.85	.83	.80
2.0	.87	.80	.74	.85	.79	.73	.82	.76	.71	.78	.73	.69	.75	.71	.67	.65
3.0	.76	.67	.60	.74	.66	.59	.71	.64	.58	.68	.62	.57	.65	.60	.56	.53
4.0	.67	.57	.50	.65	.56	.49	.62	.55	.49	.60	.53	.48	.58	.52	.47	.45
5.0	.59	.49	.42	.58	.49	.42	.55	.48	.41	.53	.46	.41	.51	.45	.40	.38
6.0	.53	.43	.36	.52	.43	.36	.50	.42	.36	.48	.41	.35	.46	.40	.35	.33
7.0	.47	.38	.32	.47	.38	.32	.45	.37	.31	.43	.36	.31	.42	.36	.31	.29
8.0	.43	.34	.28	.42	.34	.28	.41	.33	.28	.40	.33	.27	.38	.32	.27	.25
9.0	.39	.31	.25	.39	.31	.25	.38	.30	.25	.36	.29	.25	.35	.29	.24	.22
10.0	.36	.28	.23	.36	.28	.22	.35	.27	.22	.34	.27	.22	.33	.26	.22	.20



C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2018-12-12

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

## WEC AND CCEC

Test:U:24.00V I:0.6530A P:15.67W PF:1.000 Freq:0Hz Lamp Flux:531.01x1 lm		
NAME: DA1682410NO	TYPE:	WEIGHT:
SPEC.:DA1682410NO-0RGBNDA012WC0500	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: Colors	SUR.:1000*10mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.345	.196	.062	.338	.193	.061	.324	.186	.059	.311	.180	.058	.300	.174	.056	
2.0	.319	.175	.054	.312	.172	.053	.300	.167	.052	.289	.162	.051	.278	.157	.050	
3.0	.291	.155	.046	.286	.153	.046	.275	.149	.045	.264	.145	.044	.255	.141	.044	
4.0	.266	.138	.041	.261	.137	.040	.251	.133	.040	.242	.130	.039	.234	.127	.039	
5.0	.244	.125	.036	.240	.123	.036	.231	.120	.035	.223	.118	.035	.215	.115	.035	
6.0	.225	.113	.032	.221	.112	.032	.213	.109	.032	.206	.107	.031	.199	.105	.031	
7.0	.209	.103	.029	.205	.102	.029	.198	.100	.029	.191	.098	.029	.185	.096	.028	
8.0	.194	.095	.027	.191	.094	.027	.184	.092	.026	.179	.090	.026	.173	.089	.026	
9.0	.181	.088	.024	.178	.087	.024	.173	.085	.024	.167	.084	.024	.162	.082	.024	
10.0	.170	.081	.023	.167	.081	.023	.162	.079	.022	.157	.078	.022	.153	.077	.022	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.196	.196	.196	.167	.167	.167	.114	.114	.114	.066	.066	.066	.021	.021	.021	
1.0	.188	.161	.137	.161	.138	.118	.110	.095	.082	.063	.055	.047	.020	.018	.015	
2.0	.181	.137	.100	.155	.118	.087	.106	.082	.060	.061	.048	.035	.020	.015	.012	
3.0	.174	.120	.077	.149	.103	.067	.102	.072	.047	.059	.042	.028	.019	.014	.009	
4.0	.167	.107	.061	.143	.092	.053	.098	.064	.037	.057	.038	.022	.018	.012	.007	
5.0	.159	.097	.051	.137	.084	.044	.094	.058	.031	.055	.034	.018	.018	.011	.006	
6.0	.152	.088	.043	.130	.077	.037	.090	.054	.027	.052	.032	.016	.017	.010	.005	
7.0	.145	.082	.037	.124	.071	.033	.086	.050	.023	.050	.029	.014	.016	.010	.005	
8.0	.138	.076	.033	.119	.066	.029	.082	.046	.021	.048	.027	.012	.015	.009	.004	
9.0	.132	.071	.030	.113	.062	.026	.079	.043	.019	.046	.026	.011	.015	.008	.004	
10.0	.126	.067	.027	.108	.058	.024	.075	.041	.017	.044	.024	.010	.014	.008	.003	

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2018-12-12

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

## UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.6530A P:15.67W PF:1.000 Freq:0Hz Lamp Flux:531.01lx1 lm										
NAME: DA1682410NO					TYPE:			WEIGHT:		
SPEC.:DA1682410NO-0RGBNDA012WC0500					DIM.: 1000*10*1.5mm			SERIAL No.:01		
MFR.: Colors					SUR.:1000*10mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.5	27.1	25.8	27.3	27.6	25.3	26.9	25.6	27.2	27.4
3H	27.5	29.0	27.8	29.2	29.5	27.2	28.7	27.5	29.0	29.2
4H	28.3	29.7	28.6	30.0	30.3	28.0	29.4	28.3	29.7	30.0
6H	29.0	30.3	29.3	30.6	30.9	28.6	29.9	28.9	30.2	30.5
8H	29.2	30.5	29.6	30.8	31.1	28.8	30.0	29.1	30.4	30.7
12H	29.4	30.6	29.8	31.0	31.3	28.8	30.1	29.2	30.4	30.7
4H 2H	26.2	27.7	26.6	27.9	28.2	26.1	27.5	26.4	27.8	28.1
3H	28.4	29.6	28.7	29.9	30.3	28.2	29.4	28.5	29.7	30.0
4H	29.3	30.5	29.7	30.8	31.2	29.1	30.2	29.5	30.6	30.9
6H	30.1	31.1	30.5	31.5	31.9	29.8	30.8	30.2	31.2	31.6
8H	30.4	31.4	30.9	31.8	32.2	30.0	31.0	30.4	31.4	31.8
12H	30.7	31.6	31.1	32.0	32.4	30.2	31.0	30.6	31.4	31.9
8H 4H	29.7	30.6	30.1	31.0	31.4	29.4	30.4	29.9	30.8	31.2
6H	30.6	31.4	31.1	31.9	32.3	30.3	31.1	30.8	31.5	32.0
8H	31.0	31.8	31.5	32.2	32.7	30.6	31.4	31.1	31.8	32.3
12H	31.4	32.0	31.9	32.5	33.0	30.9	31.5	31.4	32.0	32.5
12H 4H	29.7	30.6	30.1	31.0	31.4	29.5	30.4	29.9	30.8	31.2
6H	30.7	31.4	31.2	31.9	32.3	30.4	31.1	30.9	31.6	32.0
8H	31.2	31.8	31.7	32.3	32.7	30.8	31.4	31.3	31.9	32.4
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.2 / - 0.4					+ 0.1 / - 0.4				

CIE Pub.117, 531.0 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.2)

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2018-12-12

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.6530A P:15.67W PF:1.000 Freq:0Hz Lamp Flux:531.01x1 lm		
NAME: DA1682410NO	TYPE:	WEIGHT:
SPEC.:DA1682410NO-0RGBNDA012WC0500	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: Colors	SUR.:1000*10mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	53	41	34	53	41	33	51	40	33	26
0.80	63	51	43	62	50	43	60	49	42	35
1.00	72	60	52	71	59	52	68	61	51	43
1.25	79	68	60	78	67	59	75	65	59	51
1.50	84	73	66	83	73	65	79	71	64	56
2.00	92	82	75	90	81	74	86	79	73	64
2.50	96	87	81	94	86	80	90	83	78	69
3.00	100	92	86	98	91	85	93	87	83	73
4.00	104	98	93	102	96	91	97	93	88	79
5.00	107	102	97	104	100	95	100	96	92	82
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2018-12-12

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

## ISOCANDELA DIAGRAM

Test:U:24.00V I:0.6530A P:15.67W PF:1.000 Freq:0Hz Lamp Flux:531.01x1 lm		
NAME: DA1682410NO	TYPE:	WEIGHT:
SPEC.:DA1682410NO-0RGBNDA012WC0500	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: Colors	SUR.:1000*10mm	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2018-12-12

Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

## AAI Figure

Test:U:24.00V I:0.6530A P:15.67W PF:1.000 Freq:0Hz Lamp Flux:531.01x1 lm		
NAME: DA1682410NO	TYPE:	WEIGHT:
SPEC.:DA1682410NO-0RGBNDA012WC0500	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: Colors	SUR.:1000*10mm	Shielding Angle:

Flux out:446.9 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 90.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:COLORS  
 Test Date:2018-12-12

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:7.500m [K=1.0000]  
 Remarks:

### ISOLUX DIAGRAM

Test:U:24.00V I:0.6530A P:15.67W PF:1.000 Freq:0Hz Lamp Flux:531.01x1 lm		
NAME: DA1682410NO	TYPE:	WEIGHT:
SPEC.:DA1682410NO-0RGBNDA012WC0500	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: Colors	SUR.:1000*10mm	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2018-12-12

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

### LED Avg.L Report

Test:U:24.00V I:0.6530A P:15.67W PF:1.000 Freq:0Hz Lamp Flux:531.01x1 lm		
NAME: DA1682410NO	TYPE:	WEIGHT:
SPEC.:DA1682410NO-0RGBNDA012WC0500	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: Colors	SUR.:1000*10mm	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	18983
L_0~180(75)av	18385
L_0~180(85)av	17405
L_90~270(65)av	18431
L_90~270(75)av	18248
L_90~270(85)av	16004
L_45(65)av	18606
L_45(75)av	18236
L_45(85)av	16378

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2018-12-12

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: COLORS  
Test Date: 2018-12-12

Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 7.500m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.6530A P:15.67W PF:1.000 Freq:0Hz Lamp Flux:531.01x1 lm		
NAME: DA1682410NO	TYPE:	WEIGHT:
SPEC.:DA1682410NO-0RGBNDA012WC0500	DIM.: 1000*10*1.5mm	SERIAL No.:01
MFR.: Colors	SUR.:1000*10mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	90	180	270														
0	141	142	141	142														
5	141	142	141	142														
10	141	141	140	141														
15	139	140	139	140														
20	138	138	137	138														
25	136	136	135	136														
30	133	134	133	134														
35	130	131	130	131														
40	127	127	125	127														
45	121	120	120	121														
50	115	112	112	113														
55	106	102	103	103														
60	95.4	90.3	91.8	91.5														
65	82.4	77.1	78.1	78.6														
70	67.1	62.4	62.1	64.2														
75	50.2	46.1	45.0	48.3														
80	32.9	28.3	27.8	31.8														
85	17.3	11.6	13.1	16.3														
90	5.95	0.24	4.02	4.01														
95	0.61	0.22	0.86	0.20														
100	0.25	0.27	0.28	0.26														
105	0.29	0.33	0.34	0.34														
110	0.34	0.39	0.40	0.40														
115	0.40	0.45	0.45	0.45														
120	0.44	0.50	0.50	0.49														
125	0.50	0.55	0.55	0.54														
130	0.54	0.59	0.60	0.58														
135	0.60	0.62	0.63	0.61														
140	0.61	0.66	0.66	0.64														
145	0.64	0.68	0.69	0.68														
150	0.69	0.71	0.71	0.69														
155	0.70	0.73	0.73	0.70														
160	0.72	0.74	0.75	0.73														
165	0.75	0.75	0.76	0.75														
170	0.75	0.76	0.77	0.75														
175	0.75	0.76	0.77	0.75														
180	0.76	0.76	0.78	0.75														

C Range: 0 - 360DEG  
C Interval: 90.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:COLORS  
Test Date:2018-12-12

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:7.500m [K=1.0000]  
Remarks: