


## LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.3435A P:8.243W PF:1.000 Freq:0Hz Lamp Flux:688.63x1 lm		
NAME: DF62408NO	TYPE:	WEIGHT:
SPEC.:DF62408NO-9NWN5A012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 83.54 lm/W			
MODEL	DF62408NO	I <sub>max</sub> (cd)	181.3	S/MH(C0/180)	1.31
NOMINAL POWER(W)	8	LOR(%)	100.0	S/MH(C90/270)	1.27
RATED VOLTAGE(V)	48	TOTAL FLUX(lm)	688.63	h UP,DN(C0-180)	2.1,47.6
NOMINAL FLUX(lm)	688.63	CIE CLASS	DIRECT	h UP,DN(C180-360)	2.4,47.9
LAMPS INSIDE	1	h up(%)	4.5	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	48	h down(%)	95.5	CIBSE SHR MAX	1.55

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-16

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	176.7	177.8	178.7	180.2	180.2	179.2	177.6	176.6	0- 10	17.15	17.15	2.49,2.49
20	168.7	169.7	171.0	174.2	175.0	172.4	168.7	167.4	10- 20	49.50	66.65	9.68,9.68
30	157.8	157.4	157.7	163.3	166.0	160.8	154.5	154.0	20- 30	76.32	143.0	20.8,20.8
40	144.5	141.8	139.1	148.2	154.1	145.4	135.0	137.2	30- 40	94.87	237.8	34.5,34.5
50	129.5	123.1	115.3	129.6	139.9	126.8	110.9	117.6	40- 50	103.5	341.3	49.6,49.6
60	113.7	103.1	86.83	108.8	124.3	106.6	82.41	96.85	50- 60	101.7	443.0	64.3,64.3
70	96.26	83.01	54.51	87.59	108.4	86.46	50.73	76.38	60- 70	90.86	533.9	77.5,77.5
80	76.05	61.33	21.61	68.75	94.41	68.97	19.20	54.93	70- 80	73.08	607.0	88.1,88.1
90	45.85	32.86	1.204	46.48	69.70	47.02	0.8269	27.61	80- 90	50.66	657.6	95.5,95.5
100	3.831	1.924	0.6746	1.946	14.94	1.060	0.4415	1.110	90-100	21.40	679.0	98.6,98.6
110	2.305	1.790	0.9213	1.696	1.570	1.176	0.8559	1.262	100-110	1.701	680.7	98.9,98.9
120	2.124	1.817	1.389	1.537	1.744	1.349	1.190	1.596	110-120	1.497	682.2	99.1,99.1
130	2.304	2.038	1.762	1.737	1.957	1.603	1.476	1.703	120-130	1.532	683.8	99.3,99.3
140	2.418	2.205	2.017	1.971	2.131	1.856	1.683	1.790	130-140	1.486	685.2	99.5,99.5
150	2.518	2.271	2.238	2.258	2.251	2.244	1.951	1.843	140-150	1.313	686.6	99.7,99.7
160	2.665	2.405	2.537	2.558	2.478	2.484	2.432	2.103	150-160	1.070	687.6	99.9,99.9
170	2.772	2.692	2.859	2.819	2.431	2.752	2.846	2.644	160-170	0.7322	688.4	100,100
180	2.665	3.093	3.186	3.146	2.672	3.099	3.199	3.146	170-180	0.2696	688.6	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-16

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.3435A P:8.243W PF:1.000 Freq:0Hz Lamp Flux:688.63x1 lm		
NAME: DF62408NO	TYPE:	WEIGHT:
SPEC.:DF62408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.3435A P:8.243W PF:1.000 Freq:0Hz Lamp Flux:688.63x1 lm		
NAME: DF62408NO	TYPE:	WEIGHT:
SPEC.:DF62408NO-9NWN5A012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Coefficients of Utilization(CU)															
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.03	1.03	1.03	.98	.98	.98	.95
1.0	.99	.93	.88	.96	.91	.86	.91	.87	.83	.86	.83	.79	.81	.79	.76	.74
2.0	.84	.76	.70	.82	.75	.68	.78	.71	.66	.73	.68	.64	.70	.65	.62	.59
3.0	.73	.64	.57	.71	.63	.56	.67	.60	.54	.64	.58	.53	.61	.55	.51	.48
4.0	.64	.55	.47	.63	.54	.47	.59	.52	.45	.56	.50	.44	.54	.48	.43	.41
5.0	.57	.47	.40	.56	.46	.40	.53	.45	.39	.50	.43	.38	.48	.42	.37	.35
6.0	.51	.42	.35	.50	.41	.34	.48	.40	.34	.45	.38	.33	.43	.37	.32	.30
7.0	.46	.37	.30	.45	.36	.30	.43	.35	.30	.41	.34	.29	.39	.33	.28	.26
8.0	.42	.33	.27	.41	.33	.27	.39	.32	.26	.38	.31	.26	.36	.30	.25	.23
9.0	.38	.30	.24	.38	.29	.24	.36	.29	.23	.35	.28	.23	.33	.27	.23	.21
10.0	.35	.27	.22	.35	.27	.22	.33	.26	.21	.32	.26	.21	.31	.25	.21	.19



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## WEC AND CCEC

Test:U:24.00V I:0.3435A P:8.243W PF:1.000 Freq:0Hz Lamp Flux:688.63x1 lm		
NAME: DF62408NO	TYPE:	WEIGHT:
SPEC.:DF62408NO-9NWN5A012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.390	.222	.070	.381	.217	.069	.365	.209	.067	.350	.202	.065	.336	.195	.063	
2.0	.340	.186	.057	.332	.183	.056	.318	.177	.055	.305	.171	.053	.292	.165	.052	
3.0	.303	.161	.048	.296	.159	.048	.283	.153	.047	.271	.149	.046	.260	.144	.045	
4.0	.273	.142	.042	.267	.140	.041	.255	.135	.040	.245	.131	.040	.235	.127	.039	
5.0	.248	.126	.037	.243	.125	.036	.232	.121	.036	.223	.117	.035	.214	.114	.034	
6.0	.227	.114	.033	.222	.112	.032	.213	.109	.032	.204	.106	.031	.196	.103	.031	
7.0	.210	.104	.029	.205	.102	.029	.197	.100	.029	.189	.097	.028	.182	.094	.028	
8.0	.194	.095	.027	.190	.094	.026	.183	.091	.026	.176	.089	.026	.169	.087	.025	
9.0	.181	.088	.024	.178	.087	.024	.171	.084	.024	.164	.082	.024	.158	.080	.023	
10.0	.169	.081	.023	.166	.080	.022	.160	.078	.022	.154	.077	.022	.149	.075	.021	

rcc	80%			70%			50%			30%			10%			0	
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
rfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.225	.225	.225	.192	.192	.192	.131	.131	.131	.075	.075	.075	.024	.024	.024		
1.0	.220	.190	.163	.189	.163	.140	.129	.112	.097	.074	.065	.056	.024	.021	.018		
2.0	.214	.166	.127	.183	.143	.110	.125	.099	.077	.072	.058	.045	.023	.019	.015		
3.0	.206	.150	.105	.176	.129	.091	.121	.090	.064	.070	.052	.038	.022	.017	.012		
4.0	.198	.137	.090	.170	.118	.078	.117	.082	.055	.068	.048	.033	.022	.016	.011		
5.0	.190	.127	.080	.163	.110	.069	.112	.077	.049	.065	.045	.029	.021	.015	.010		
6.0	.182	.118	.073	.157	.103	.063	.108	.072	.045	.063	.042	.027	.020	.014	.009		
7.0	.175	.112	.067	.151	.097	.059	.104	.068	.041	.060	.040	.025	.020	.013	.008		
8.0	.168	.106	.063	.145	.092	.055	.100	.064	.039	.058	.038	.023	.019	.012	.008		
9.0	.162	.101	.060	.139	.088	.052	.096	.062	.037	.056	.036	.022	.018	.012	.007		
10.0	.156	.097	.057	.134	.084	.050	.093	.059	.036	.054	.035	.021	.018	.011	.007		

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.3435A P:8.243W PF:1.000 Freq:0Hz Lamp Flux:688.63x1 lm										
NAME: DF62408NO					TYPE:			WEIGHT:		
SPEC.:DF62408NO-9NWN5A012WC0100					DIM.: 1000*8*1.5mm			SERIAL No.:		
MFR.: COLORS					SUR.:1000*8mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.4	27.0	25.7	27.2	27.6	24.5	26.1	24.8	26.4	26.7
3H	27.9	29.4	28.3	29.7	30.0	26.2	27.6	26.5	28.0	28.3
4H	29.2	30.6	29.6	31.0	31.4	26.8	28.2	27.2	28.6	29.0
6H	30.7	32.0	31.1	32.4	32.8	27.3	28.6	27.7	29.0	29.4
8H	31.5	32.8	31.9	33.1	33.5	27.5	28.7	27.9	29.1	29.5
12H	32.3	33.5	32.7	33.9	34.3	27.5	28.8	28.0	29.2	29.6
4H 2H	26.1	27.5	26.5	27.8	28.2	25.4	26.8	25.8	27.2	27.5
3H	28.8	30.0	29.2	30.4	30.8	27.4	28.6	27.8	29.0	29.4
4H	30.3	31.5	30.8	31.9	32.3	28.3	29.4	28.7	29.8	30.3
6H	32.0	33.0	32.4	33.4	33.9	29.0	30.0	29.4	30.4	30.9
8H	32.9	33.8	33.3	34.3	34.8	29.2	30.2	29.7	30.6	31.1
12H	33.8	34.7	34.3	35.2	35.7	29.3	30.2	29.8	30.7	31.2
8H 4H	30.8	31.7	31.2	32.2	32.7	29.1	30.1	29.6	30.5	31.0
6H	32.7	33.5	33.2	34.0	34.5	30.1	31.0	30.7	31.4	32.0
8H	33.7	34.5	34.3	35.0	35.5	30.6	31.3	31.1	31.8	32.4
12H	34.9	35.6	35.5	36.1	36.7	30.9	31.6	31.5	32.1	32.7
12H 4H	30.8	31.7	31.3	32.2	32.7	29.3	30.2	29.8	30.7	31.2
6H	32.8	33.6	33.4	34.1	34.6	30.6	31.3	31.1	31.8	32.4
8H	34.0	34.6	34.5	35.2	35.8	31.2	31.8	31.7	32.3	32.9
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1				
1.5H	+ 0.2 / - 0.2					+ 0.2 / - 0.3				
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.4				

CIE Pub.117, 688.6 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -1.3)

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.3435A P:8.243W PF:1.000 Freq:0Hz Lamp Flux:688.63x1 lm		
NAME: DF62408NO	TYPE:	WEIGHT:
SPEC.:DF62408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	52	39	32	51	39	32	50	39	32	25
0.80	61	48	40	60	48	40	58	47	40	32
1.00	69	57	48	68	56	48	65	57	47	39
1.25	76	64	56	74	63	55	71	61	54	46
1.50	81	70	61	79	68	61	76	66	59	51
2.00	88	78	70	86	77	69	82	74	67	58
2.50	93	83	76	90	81	75	86	78	72	63
3.00	96	88	81	94	86	79	89	82	77	67
4.00	101	94	87	98	91	86	93	88	83	72
5.00	104	97	92	101	95	90	96	91	87	76
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## ISOCANDELA DIAGRAM

Test:U:24.00V I:0.3435A P:8.243W PF:1.000 Freq:0Hz Lamp Flux:688.63x1 lm		
NAME: DF62408NO	TYPE:	WEIGHT:
SPEC.:DF62408NO-9NWN5A012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-16


Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:



AAI Figure

Test:U:24.00V I:0.3435A P:8.243W PF:1.000 Freq:0Hz Lamp Flux:688.63x1 lm		
NAME: DF62408NO	TYPE:	WEIGHT:
SPEC.:DF62408NO-9NWSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Flux out:517.0 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM


Test:U:24.00V I:0.3435A P:8.243W PF:1.000 Freq:0Hz Lamp Flux:688.63x1 lm		
NAME: DF62408NO	TYPE:	WEIGHT:
SPEC.:DF62408NO-9NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2020-09-16

deg Range: 0 - 180DEG  
deg Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.3435A P:8.243W PF:1.000 Freq:0Hz Lamp Flux:688.63x1 lm		
NAME: DF62408NO	TYPE:	WEIGHT:
SPEC.:DF62408NO-9NWN5A012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	181	181	181	181	181	181	181	181										
5	179	180	181	181	181	181	180	179										
10	177	178	179	180	180	179	178	177										
15	173	174	176	178	178	176	174	173										
20	169	170	171	174	175	172	169	167										
25	164	164	165	169	171	167	162	161										
30	158	157	158	163	166	161	154	154										
35	151	150	149	156	160	154	145	146										
40	144	142	139	148	154	145	135	137										
45	137	133	128	139	147	136	124	128										
50	130	123	115	130	140	127	111	118										
55	122	113	102	119	132	117	97.1	107										
60	114	103	86.8	109	124	107	82.4	96.8										
65	105	93.1	71.0	98.0	116	96.3	66.9	86.6										
70	96.3	83.0	54.5	87.6	108	86.5	50.7	76.4										
75	86.6	72.4	37.7	77.7	101	77.2	34.5	65.7										
80	76.1	61.3	21.6	68.8	94.4	69.0	19.2	54.9										
85	61.8	49.1	8.33	61.0	83.6	61.3	6.95	42.7										
90	45.8	32.9	1.20	46.5	69.7	47.0	0.83	27.6										
95	28.5	15.0	0.72	30.5	57.4	31.5	0.26	8.65										
100	3.83	1.92	0.67	1.95	14.9	1.06	0.44	1.11										
105	2.39	1.86	0.75	1.79	1.47	1.08	0.64	1.16										
110	2.31	1.79	0.92	1.70	1.57	1.18	0.86	1.26										
115	2.20	1.74	1.18	1.58	1.65	1.24	1.04	1.41										
120	2.12	1.82	1.39	1.54	1.74	1.35	1.19	1.60										
125	2.24	1.94	1.61	1.64	1.84	1.46	1.34	1.68										
130	2.30	2.04	1.76	1.74	1.96	1.60	1.48	1.70										
135	2.36	2.13	1.90	1.84	2.04	1.71	1.60	1.78										
140	2.42	2.20	2.02	1.97	2.13	1.86	1.68	1.79										
145	2.44	2.23	2.10	2.11	2.19	2.02	1.79	1.80										
150	2.52	2.27	2.24	2.26	2.25	2.24	1.95	1.84										
155	2.56	2.35	2.32	2.43	2.37	2.35	2.19	1.92										
160	2.67	2.40	2.54	2.56	2.48	2.48	2.43	2.10										
165	2.74	2.48	2.70	2.69	2.55	2.66	2.63	2.36										
170	2.77	2.69	2.86	2.82	2.43	2.75	2.85	2.64										
175	2.68	2.91	3.03	2.99	2.45	2.91	3.04	2.91										
180	2.67	3.09	3.19	3.15	2.67	3.10	3.20	3.15										

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-16

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks: