


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.1830A P:4.392W PF:1.000 Freq:0Hz Lamp Flux:481.064x1 lm		
NAME: DJ602408NO	TYPE:	WEIGHT:
SPEC.:DJ602408NO-8SWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 109.53 lm/W			
MODEL	DJ602408NO	I _{max} (cd)	160.4	S/MH(C0/180)	1.28
NOMINAL POWER(W)	4.4	LOR(%)	100.0	S/MH(C90/270)	1.27
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	481.06	h UP,DN(C0-180)	0.8,49.6
NOMINAL FLUX(lm)	481.064	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,48.9
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.4	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-08-28

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	157.6	158.1	158.1	158.4	157.9	157.7	157.4	157.3	0~ 10	15.18	15.18	3.16,3.16
20	150.1	150.9	151.1	151.6	150.6	150.2	149.7	149.4	10~ 20	43.70	58.88	12.2,12.2
30	137.6	138.7	139.3	139.9	138.5	137.8	137.3	136.7	20~ 30	66.82	125.7	26.1,26.1
40	120.4	121.9	122.6	123.5	121.9	120.9	120.2	119.4	30~ 40	81.55	207.3	43.1,43.1
50	98.89	100.4	101.4	102.6	100.7	99.67	98.82	97.67	40~ 50	85.75	293.0	60.9,60.9
60	73.32	74.92	76.10	77.55	75.65	74.49	73.49	72.13	50~ 60	78.42	371.4	77.2,77.2
70	44.70	46.21	47.49	49.20	47.46	46.31	45.20	43.64	60~ 70	60.04	431.5	89.7,89.7
80	16.67	17.66	18.72	20.31	19.26	18.27	17.27	15.88	70~ 80	33.56	465.0	96.7,96.7
90	0.9492	1.142	0.9970	1.755	1.431	1.155	0.4649	0.5778	80~ 90	8.554	473.6	98.4,98.4
100	0.5344	0.5812	0.5210	0.5545	0.3678	0.3134	0.3878	0.3856	90~100	0.5400	474.1	98.6,98.6
110	0.8734	0.8964	0.7276	0.8162	0.7754	0.6340	0.7956	0.7146	100~110	0.6383	474.8	98.7,98.7
120	1.295	1.303	1.156	1.196	1.149	0.9615	1.116	1.095	110~120	0.9633	475.7	98.9,98.9
130	1.669	1.603	1.442	1.470	1.476	1.269	1.396	1.383	120~130	1.179	476.9	99.1,99.1
140	1.904	1.804	1.676	1.731	1.757	1.609	1.590	1.563	130~140	1.227	478.1	99.4,99.4
150	2.111	1.911	1.803	1.991	1.918	1.903	1.790	1.676	140~150	1.125	479.3	99.6,99.6
160	2.331	2.038	2.111	2.258	2.111	2.231	2.192	1.850	150~160	0.9286	480.2	99.8,99.8
170	2.412	2.392	2.471	2.525	2.238	2.438	2.538	2.337	160~170	0.6440	480.8	100,100
180	2.344	2.765	2.752	2.832	2.331	2.745	2.799	2.785	170~180	0.2378	481.1	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-28

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.1830A P:4.392W PF:1.000 Freq:0Hz Lamp Flux:481.064x1 lm		
NAME: DJ602408NO	TYPE:	WEIGHT:
SPEC.:DJ602408NO-8SWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.1830A P:4.392W PF:1.000 Freq:0Hz Lamp Flux:481.064x1 lm		
NAME: DJ602408NO	TYPE:	WEIGHT:
SPEC.:DJ602408NO-8SWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.94	.97	.93	.90	.92	.90	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.82	.76	.84	.79	.74	.81	.76	.72	.77	.74	.70	.68
3.0	.79	.71	.64	.77	.69	.63	.74	.67	.62	.71	.65	.61	.68	.63	.59	.57
4.0	.70	.61	.54	.68	.60	.54	.66	.58	.53	.63	.57	.52	.61	.55	.51	.49
5.0	.62	.53	.46	.61	.52	.46	.59	.51	.45	.56	.50	.45	.54	.49	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.40	.51	.44	.39	.49	.43	.39	.37
7.0	.51	.42	.36	.50	.41	.35	.48	.40	.35	.46	.40	.35	.45	.39	.34	.32
8.0	.46	.38	.32	.45	.37	.31	.44	.36	.31	.43	.36	.31	.41	.35	.31	.29
9.0	.42	.34	.28	.42	.34	.28	.40	.33	.28	.39	.33	.28	.38	.32	.28	.26
10.0	.39	.31	.26	.38	.31	.26	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-08-28

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:24.00V I:0.1830A P:4.392W PF:1.000 Freq:0Hz Lamp Flux:481.064x1 lm		
NAME: DJ602408NO	TYPE:	WEIGHT:
SPEC.:DJ602408NO-8SWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.310	.176	.056	.303	.173	.055	.289	.166	.053	.276	.159	.051	.264	.153	.049	
2.0	.293	.160	.049	.286	.157	.049	.273	.152	.047	.262	.147	.046	.251	.142	.045	
3.0	.271	.144	.043	.265	.142	.043	.254	.138	.042	.244	.133	.041	.234	.130	.040	
4.0	.250	.130	.038	.245	.128	.038	.235	.125	.037	.226	.121	.037	.217	.118	.036	
5.0	.231	.118	.034	.226	.116	.034	.218	.113	.033	.209	.110	.033	.202	.108	.032	
6.0	.214	.107	.031	.210	.106	.031	.202	.104	.030	.195	.101	.030	.188	.099	.029	
7.0	.199	.099	.028	.196	.097	.028	.189	.095	.027	.182	.093	.027	.176	.091	.027	
8.0	.186	.091	.026	.183	.090	.025	.176	.088	.025	.171	.086	.025	.165	.085	.025	
9.0	.174	.084	.024	.171	.084	.023	.166	.082	.023	.160	.080	.023	.155	.079	.023	
10.0	.164	.079	.022	.161	.078	.022	.156	.076	.022	.151	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.202	.202	.202	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.192	.168	.146	.165	.144	.126	.113	.099	.087	.065	.057	.051	.021	.018	.016	
2.0	.184	.144	.110	.158	.124	.095	.108	.086	.066	.062	.050	.039	.020	.016	.013	
3.0	.177	.126	.086	.152	.109	.075	.104	.076	.052	.060	.044	.031	.019	.014	.010	
4.0	.169	.113	.070	.145	.098	.061	.100	.068	.043	.058	.040	.025	.019	.013	.008	
5.0	.162	.103	.059	.139	.089	.052	.096	.062	.036	.055	.036	.022	.018	.012	.007	
6.0	.155	.094	.051	.133	.082	.045	.092	.057	.032	.053	.034	.019	.017	.011	.006	
7.0	.148	.088	.045	.127	.076	.040	.088	.053	.028	.051	.031	.017	.016	.010	.006	
8.0	.141	.082	.041	.122	.071	.036	.084	.050	.025	.049	.029	.015	.016	.010	.005	
9.0	.135	.077	.037	.117	.067	.033	.081	.047	.023	.047	.028	.014	.015	.009	.005	
10.0	.130	.073	.035	.112	.063	.030	.078	.044	.022	.045	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.1830A P:4.392W PF:1.000 Freq:0Hz Lamp Flux:481.064x1 lm											
NAME: DJ602408NO					TYPE:			WEIGHT:			
SPEC.:DJ602408NO-8SWNSA012WC0100					DIM.: 1000*8*1.5mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*8mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.6	27.1	25.9	27.3	27.6	25.7	27.2	26.0	27.5	27.7	
	3H	27.1	28.5	27.4	28.7	29.0	27.3	28.7	27.6	28.9	29.2
	4H	27.6	28.9	28.0	29.2	29.5	27.9	29.2	28.2	29.5	29.8
	6H	28.0	29.2	28.3	29.5	29.8	28.2	29.5	28.6	29.8	30.1
	8H	28.0	29.2	28.4	29.6	29.9	28.4	29.6	28.7	29.9	30.2
	12H	28.1	29.2	28.4	29.5	29.9	28.4	29.6	28.8	29.9	30.2
4H	2H	26.2	27.6	26.6	27.8	28.1	26.3	27.7	26.7	27.9	28.2
	3H	27.9	29.0	28.3	29.4	29.7	28.0	29.2	28.4	29.5	29.9
	4H	28.5	29.6	28.9	29.9	30.3	28.7	29.8	29.1	30.2	30.5
	6H	29.0	29.9	29.4	30.3	30.7	29.2	30.2	29.7	30.6	31.0
	8H	29.1	30.0	29.5	30.4	30.8	29.4	30.3	29.8	30.7	31.1
	12H	29.2	30.0	29.6	30.4	30.8	29.5	30.3	29.9	30.7	31.1
8H	4H	28.8	29.7	29.2	30.1	30.5	29.0	29.8	29.4	30.2	30.7
	6H	29.4	30.1	29.8	30.5	31.0	29.6	30.3	30.1	30.8	31.2
	8H	29.6	30.2	30.0	30.6	31.1	29.8	30.5	30.3	30.9	31.4
	12H	29.7	30.2	30.2	30.7	31.2	30.0	30.5	30.5	31.0	31.5
12H	4H	28.8	29.6	29.2	30.0	30.4	29.0	29.8	29.4	30.2	30.6
	6H	29.4	30.0	29.9	30.5	31.0	29.6	30.3	30.1	30.7	31.2
	8H	29.6	30.2	30.1	30.7	31.2	29.9	30.4	30.4	30.9	31.4
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 481.1 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.5)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.1830A P:4.392W PF:1.000 Freq:0Hz Lamp Flux:481.064x1 lm		
NAME: DJ602408NO	TYPE:	WEIGHT:
SPEC.:DJ602408NO-8SWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	57	45	38	56	45	38	54	44	38	31
0.80	67	55	47	66	54	47	64	54	47	40
1.00	75	64	56	74	63	56	71	65	56	48
1.25	82	72	64	81	71	64	78	69	63	55
1.50	87	77	70	86	76	70	82	74	68	61
2.00	94	86	79	92	84	78	89	82	77	68
2.50	98	90	84	96	89	83	92	86	81	73
3.00	102	95	89	99	93	88	95	90	86	77
4.00	106	100	95	103	98	94	99	94	91	81
5.00	108	103	99	106	101	97	101	97	94	85
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.1830A P:4.392W PF:1.000 Freq:0Hz Lamp Flux:481.064x1 lm		
NAME: DJ602408NO	TYPE:	WEIGHT:
SPEC.:DJ602408NO-8SWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-28

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.1830A P:4.392W PF:1.000 Freq:0Hz Lamp Flux:481.064x1 lm		
NAME: DJ602408NO	TYPE:	WEIGHT:
SPEC.:DJ602408NO-8SWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Flux out:356.9 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.1830A P:4.392W PF:1.000 Freq:0Hz Lamp Flux:481.064x1 lm		
NAME: DJ602408NO	TYPE:	WEIGHT:
SPEC.:DJ602408NO-8SWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-08-28

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-28

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.1830A P:4.392W PF:1.000 Freq:0Hz Lamp Flux:481.064x1 lm		
NAME: DJ602408NO	TYPE:	WEIGHT:
SPEC.:DJ602408NO-8SWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	160	160	160	160	160	160	160	160										
5	160	160	160	160	160	160	159	159										
10	158	158	158	158	158	158	157	157										
15	155	155	155	156	155	155	154	154										
20	150	151	151	152	151	150	150	149										
25	144	145	146	146	145	145	144	144										
30	138	139	139	140	139	138	137	137										
35	130	131	132	132	131	130	129	129										
40	120	122	123	124	122	121	120	119										
45	110	112	113	114	112	111	110	109										
50	98.9	100	101	103	101	99.7	98.8	97.7										
55	86.5	88.1	89.2	90.5	88.6	87.5	86.6	85.4										
60	73.3	74.9	76.1	77.6	75.7	74.5	73.5	72.1										
65	59.3	60.9	62.1	63.7	61.8	60.7	59.6	58.2										
70	44.7	46.2	47.5	49.2	47.5	46.3	45.2	43.6										
75	30.1	31.4	32.7	34.4	33.0	31.8	30.7	29.2										
80	16.7	17.7	18.7	20.3	19.3	18.3	17.3	15.9										
85	6.06	6.86	7.40	8.74	7.92	7.28	6.43	5.63										
90	0.95	1.14	1.00	1.76	1.43	1.15	0.46	0.58										
95	0.53	0.53	0.55	0.57	0.34	0.28	0.21	0.27										
100	0.53	0.58	0.52	0.55	0.37	0.31	0.39	0.39										
105	0.67	0.72	0.55	0.66	0.57	0.48	0.60	0.53										
110	0.87	0.90	0.73	0.82	0.78	0.63	0.80	0.71										
115	1.09	1.12	0.94	1.02	0.96	0.82	0.97	0.91										
120	1.29	1.30	1.16	1.20	1.15	0.96	1.12	1.09										
125	1.48	1.46	1.29	1.34	1.32	1.14	1.26	1.26										
130	1.67	1.60	1.44	1.47	1.48	1.27	1.40	1.38										
135	1.79	1.72	1.58	1.60	1.63	1.45	1.50	1.46										
140	1.90	1.80	1.68	1.73	1.76	1.61	1.59	1.56										
145	1.99	1.86	1.74	1.86	1.85	1.76	1.66	1.59										
150	2.11	1.91	1.80	1.99	1.92	1.90	1.79	1.68										
155	2.23	1.98	1.97	2.13	2.02	2.06	1.98	1.73										
160	2.33	2.04	2.11	2.26	2.11	2.23	2.19	1.85										
165	2.42	2.18	2.32	2.40	2.24	2.32	2.38	2.08										
170	2.41	2.39	2.47	2.53	2.24	2.44	2.54	2.34										
175	2.26	2.59	2.63	2.69	2.16	2.56	2.69	2.58										
180	2.34	2.77	2.75	2.83	2.33	2.75	2.80	2.79										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-28

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: