


## LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1040.63x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 119.61 lm/W			
MODEL	DJ1202408NO	I <sub>max</sub> (cd)	341.2	S/MH(C0/180)	1.30
NOMINAL POWER(W)	8.8	LOR(%)	100.0	S/MH(C90/270)	1.29
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1040.6	h UP,DN(C0-180)	0.8,49.7
NOMINAL FLUX(lm)	1040.63	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,48.8
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	h down(%)	98.4	CIBSE SHR MAX	1.50

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-09-04

g Range: 0 - 180DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	336.9	337.4	336.9	337.0	335.8	335.8	335.8	336.2	0- 10	32.34	32.34	3.11,3.11
20	322.5	323.4	322.8	322.8	320.8	320.5	320.8	321.2	10- 20	93.32	125.7	12.1,12.1
30	298.1	299.3	298.7	298.7	295.8	295.3	295.8	296.0	20- 30	143.3	269.0	25.8,25.8
40	263.2	264.8	264.2	264.6	260.8	260.2	260.7	260.6	30- 40	175.8	444.8	42.7,42.7
50	218.1	219.9	219.5	220.2	215.9	215.2	215.6	215.1	40- 50	185.9	630.7	60.6,60.6
60	163.3	165.3	165.1	166.3	162.0	161.0	161.2	160.2	50- 60	170.9	801.6	77,77
70	100.9	102.9	102.8	104.6	100.7	99.72	99.32	97.85	60- 70	131.2	932.8	89.6,89.6
80	38.57	40.01	40.06	41.80	39.20	38.41	37.89	36.15	70- 80	73.16	1006	96.7,96.7
90	2.210	2.543	1.495	2.717	1.886	1.874	0.7626	1.165	80- 90	18.23	1024	98.4,98.4
100	1.142	1.257	1.115	1.223	0.8696	0.7991	0.8485	0.8142	90-100	1.061	1025	98.5,98.5
110	1.948	1.946	1.701	1.837	1.740	1.533	1.744	1.682	100-110	1.444	1027	98.7,98.7
120	2.851	2.806	2.636	2.687	2.581	2.290	2.493	2.545	110-120	2.177	1029	98.9,98.9
130	3.606	3.394	3.245	3.313	3.307	2.959	3.075	3.172	120-130	2.638	1032	99.1,99.1
140	4.155	3.815	3.714	3.861	3.888	3.632	3.494	3.513	130-140	2.724	1034	99.4,99.4
150	4.521	4.035	4.054	4.416	4.216	4.274	3.854	3.740	140-150	2.481	1037	99.6,99.6
160	4.903	4.295	4.742	4.944	4.623	4.861	4.636	4.107	150-160	2.023	1039	99.8,99.8
170	5.057	5.058	5.436	5.371	4.722	5.282	5.352	5.015	160-170	1.383	1040	100,100
180	4.903	5.858	5.965	5.985	4.909	5.865	5.978	5.978	170-180	0.5081	1041	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1040.63x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	20408	22164
80	27764	28836
75	33164	34073
70	36878	37581
65	39301	39854
60	40832	41268
55	41822	42163
50	42415	42684
45	42772	42978


C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1040.63x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.94	.96	.93	.90	.92	.90	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.82	.76	.84	.79	.74	.81	.76	.72	.77	.74	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.61	.68	.63	.59	.57
4.0	.70	.61	.54	.68	.60	.53	.65	.58	.52	.63	.57	.52	.61	.55	.51	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.45	.54	.49	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.42	.35	.50	.41	.35	.48	.40	.35	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.34	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.26
10.0	.39	.31	.26	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-09-04

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

## WEC AND CCEC

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1040.63x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Wall Exitance Coefficients(WEC)															
0.0																
1.0	.311	.177	.056	.303	.173	.055	.289	.166	.053	.276	.159	.051	.264	.153	.049	
2.0	.293	.161	.049	.287	.158	.049	.274	.152	.047	.262	.147	.046	.252	.142	.045	
3.0	.272	.145	.043	.266	.142	.043	.255	.138	.042	.244	.134	.041	.235	.130	.040	
4.0	.251	.130	.038	.245	.128	.038	.235	.125	.037	.226	.122	.037	.218	.118	.036	
5.0	.232	.118	.034	.227	.117	.034	.218	.114	.033	.210	.111	.033	.202	.108	.032	
6.0	.215	.108	.031	.211	.106	.031	.203	.104	.030	.195	.101	.030	.188	.099	.029	
7.0	.200	.099	.028	.196	.098	.028	.189	.096	.028	.182	.093	.027	.176	.091	.027	
8.0	.187	.091	.026	.183	.090	.025	.177	.088	.025	.171	.087	.025	.165	.085	.025	
9.0	.175	.085	.024	.172	.084	.023	.166	.082	.023	.161	.080	.023	.155	.079	.023	
10.0	.164	.079	.022	.162	.078	.022	.156	.077	.022	.151	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.203	.203	.203	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.193	.168	.146	.165	.144	.126	.113	.099	.087	.065	.057	.051	.021	.019	.016	
2.0	.185	.144	.110	.158	.124	.095	.108	.086	.066	.063	.050	.039	.020	.016	.013	
3.0	.177	.127	.086	.152	.109	.075	.104	.076	.053	.060	.044	.031	.019	.014	.010	
4.0	.170	.113	.070	.145	.098	.061	.100	.068	.043	.058	.040	.025	.019	.013	.008	
5.0	.162	.103	.059	.139	.089	.052	.096	.062	.036	.056	.037	.022	.018	.012	.007	
6.0	.155	.095	.051	.133	.082	.045	.092	.057	.032	.053	.034	.019	.017	.011	.006	
7.0	.148	.088	.046	.128	.076	.040	.088	.053	.028	.051	.031	.017	.017	.010	.006	
8.0	.142	.082	.041	.122	.071	.036	.084	.050	.025	.049	.029	.015	.016	.010	.005	
9.0	.136	.077	.038	.117	.067	.033	.081	.047	.023	.047	.028	.014	.015	.009	.005	
10.0	.130	.073	.035	.112	.063	.030	.078	.045	.022	.045	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1040.63x1 lm											
NAME: DJ1202408NO					TYPE:			WEIGHT:			
SPEC.:DJ1202408NO-8NWSA012WC0100					DIM.: 1000*8*1.5mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*8mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	25.7	27.3	26.0	27.5	27.7	25.8	27.3	26.1	27.5	27.8	
	27.3	28.7	27.6	28.9	29.2	27.3	28.7	27.6	29.0	29.3	
	27.8	29.2	28.2	29.4	29.7	27.9	29.2	28.2	29.5	29.8	
	28.2	29.4	28.6	29.7	30.1	28.3	29.5	28.6	29.8	30.2	
	28.3	29.5	28.7	29.8	30.1	28.4	29.6	28.8	29.9	30.2	
	28.3	29.5	28.7	29.8	30.1	28.4	29.6	28.8	29.9	30.3	
4H	2H	26.4	27.7	26.7	28.0	28.3	26.4	27.7	26.7	28.0	28.3
	3H	28.1	29.2	28.4	29.6	29.9	28.1	29.3	28.5	29.6	29.9
	4H	28.8	29.8	29.2	30.2	30.5	28.8	29.9	29.2	30.2	30.6
	6H	29.2	30.2	29.6	30.5	30.9	29.3	30.3	29.7	30.6	31.0
	8H	29.4	30.2	29.8	30.6	31.1	29.5	30.3	29.9	30.7	31.1
	12H	29.4	30.2	29.9	30.6	31.1	29.5	30.3	30.0	30.8	31.2
8H	4H	29.0	29.9	29.4	30.3	30.7	29.1	29.9	29.5	30.3	30.8
	6H	29.6	30.3	30.1	30.8	31.2	29.7	30.4	30.2	30.8	31.3
	8H	29.8	30.5	30.3	30.9	31.4	29.9	30.5	30.4	31.0	31.5
	12H	29.9	30.5	30.4	31.0	31.5	30.0	30.6	30.5	31.1	31.6
12H	4H	29.0	29.8	29.5	30.2	30.7	29.1	29.9	29.5	30.3	30.7
	6H	29.7	30.3	30.1	30.7	31.2	29.7	30.4	30.2	30.8	31.3
	8H	29.9	30.4	30.4	30.9	31.4	30.0	30.5	30.5	31.0	31.5
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 1041 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.1)

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1040.63x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8NWSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	45	38	56	44	37	54	44	37	31
0.80	66	55	47	65	54	47	63	53	47	39
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	81	71	64	78	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	82	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	102	95	89	99	93	88	95	90	85	77
4.00	106	100	95	103	98	94	99	94	91	81
5.00	108	103	99	106	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## ISOCANDELA DIAGRAM

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1040.63x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2020-09-04


deg Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1040.63x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Flux out:785.9 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

# ISOLUX DIAGRAM


Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1040.63x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8NWSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2020-09-04

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1040.63x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8NWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	341	341	341	341	341	341	341	341										
5	340	341	340	340	340	340	340	340										
10	337	337	337	337	336	336	336	336										
15	331	332	331	331	330	329	330	330										
20	323	323	323	323	321	321	321	321										
25	312	313	312	312	310	309	310	310										
30	298	299	299	299	296	295	296	296										
35	282	283	283	283	279	279	280	280										
40	263	265	264	265	261	260	261	261										
45	242	244	243	244	240	239	239	239										
50	218	220	219	220	216	215	216	215										
55	192	194	193	194	190	189	189	189										
60	163	165	165	166	162	161	161	160										
65	133	135	135	136	132	131	131	130										
70	101	103	103	105	101	99.7	99.3	97.8										
75	68.7	70.5	70.5	72.4	69.0	68.1	67.6	65.9										
80	38.6	40.0	40.1	41.8	39.2	38.4	37.9	36.1										
85	14.2	15.9	15.5	17.3	15.1	14.9	14.2	13.0										
90	2.21	2.54	1.49	2.72	1.89	1.87	0.76	1.17										
95	1.12	1.13	1.17	1.16	0.63	0.57	0.45	0.51										
100	1.14	1.26	1.12	1.22	0.87	0.80	0.85	0.81										
105	1.50	1.53	1.28	1.48	1.30	1.16	1.32	1.26										
110	1.95	1.95	1.70	1.84	1.74	1.53	1.74	1.68										
115	2.42	2.41	2.18	2.27	2.16	1.88	2.14	2.12										
120	2.85	2.81	2.64	2.69	2.58	2.29	2.49	2.54										
125	3.27	3.13	2.94	3.01	2.96	2.64	2.81	2.89										
130	3.61	3.39	3.24	3.31	3.31	2.96	3.07	3.17										
135	3.93	3.63	3.50	3.57	3.62	3.29	3.32	3.38										
140	4.15	3.81	3.71	3.86	3.89	3.63	3.49	3.51										
145	4.37	3.93	3.92	4.13	4.09	4.00	3.65	3.61										
150	4.52	4.03	4.05	4.42	4.22	4.27	3.85	3.74										
155	4.72	4.14	4.35	4.70	4.43	4.57	4.23	3.92										
160	4.90	4.29	4.74	4.94	4.62	4.86	4.64	4.11										
165	5.11	4.61	5.10	5.15	4.79	5.02	5.02	4.49										
170	5.06	5.06	5.44	5.37	4.72	5.28	5.35	5.01										
175	4.84	5.56	5.71	5.68	4.62	5.55	5.70	5.58										
180	4.90	5.86	5.96	5.98	4.91	5.86	5.98	5.98										

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks: