


## LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1005.02x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8WWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 115.52 lm/W			
MODEL	DJ1202408NO	I <sub>max</sub> (cd)	331.9	S/MH(C0/180)	1.36
NOMINAL POWER(W)	8.8	LOR(%)	100.0	S/MH(C90/270)	1.29
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1005.0	h UP,DN(C0-180)	1.1,50.7
NOMINAL FLUX(lm)	1005.02	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.9,47.3
LAMPS INSIDE	1	h up(%)	2.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-09-04

g Range: 0 - 180DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	331.1	327.4	320.2	318.6	319.4	318.3	321.0	327.5	0- 10	31.06	31.06	3.09,3.09
20	322.0	317.2	305.2	299.4	298.8	299.0	306.8	317.0	10- 20	89.46	120.5	12,12
30	302.7	296.8	280.7	270.8	268.3	270.3	282.7	296.6	20- 30	137.0	257.5	25.6,25.6
40	273.4	266.6	246.7	233.2	228.9	232.3	249.2	266.3	30- 40	167.5	425.0	42.3,42.3
50	234.4	226.5	203.5	187.3	181.3	185.6	206.4	226.5	40- 50	176.7	601.6	59.9,59.9
60	185.9	177.4	151.8	134.0	126.9	131.9	155.0	177.8	50- 60	162.3	763.9	76,76
70	129.6	120.3	93.65	76.38	68.92	73.98	97.25	121.4	60- 70	125.4	889.3	88.5,88.5
80	69.11	60.04	35.82	24.22	18.94	22.02	40.03	61.77	70- 80	72.62	962.0	95.7,95.7
90	20.42	13.02	1.453	1.805	0.9348	0.9123	2.401	16.42	80- 90	23.33	985.3	98,98
100	6.391	1.596	1.176	1.550	1.358	1.068	0.7912	4.203	90-100	4.073	989.4	98.4,98.4
110	3.789	1.598	1.689	2.199	2.171	1.781	1.624	1.373	100-110	2.173	991.5	98.7,98.7
120	2.908	2.386	2.551	2.899	2.901	2.423	2.313	2.108	110-120	2.250	993.8	98.9,98.9
130	3.071	3.047	3.186	3.421	3.541	2.985	2.873	2.731	120-130	2.522	996.3	99.1,99.1
140	3.693	3.534	3.607	3.881	4.028	3.606	3.247	3.099	130-140	2.598	998.9	99.4,99.4
150	4.128	3.801	3.920	4.383	4.295	4.181	3.595	3.386	140-150	2.371	1001	99.6,99.6
160	4.608	4.082	4.535	4.823	4.629	4.682	4.402	3.740	150-160	1.933	1003	99.8,99.8
170	4.864	4.837	5.096	5.177	4.655	5.109	5.090	4.695	160-170	1.324	1005	100,100
180	4.783	5.658	5.664	5.678	4.789	5.664	5.691	5.671	170-180	0.4870	1005	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-09-04

g Range: 0 - 180DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1005.02x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8WWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:




C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1005.02x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8WWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.00	1.00	1.00	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.86	.88	.86	.84	.81
2.0	.89	.82	.77	.87	.81	.76	.83	.78	.73	.80	.75	.71	.77	.73	.70	.67
3.0	.78	.70	.63	.77	.69	.63	.73	.67	.61	.70	.65	.60	.67	.63	.59	.56
4.0	.69	.60	.53	.68	.59	.53	.65	.58	.52	.62	.56	.51	.60	.55	.50	.48
5.0	.62	.53	.46	.60	.52	.45	.58	.51	.45	.56	.49	.44	.54	.48	.43	.41
6.0	.55	.46	.40	.54	.46	.40	.52	.45	.39	.50	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.34	.46	.39	.34	.44	.38	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.31	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.27	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.25	.23



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-09-04

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### WEC AND CCEC

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1005.02x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8WWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0														
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
rfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.317	.180	.057	.310	.177	.056	.295	.169	.054	.282	.163	.052	.270	.156	.050															
2.0	.297	.163	.050	.290	.160	.049	.277	.154	.048	.265	.149	.047	.254	.144	.045															
3.0	.274	.146	.044	.268	.143	.043	.256	.139	.042	.246	.135	.041	.236	.131	.040															
4.0	.252	.131	.038	.247	.129	.038	.236	.125	.037	.227	.122	.037	.218	.119	.036															
5.0	.233	.118	.034	.228	.117	.034	.219	.114	.034	.210	.111	.033	.202	.108	.033															
6.0	.215	.108	.031	.211	.107	.031	.203	.104	.030	.195	.102	.030	.188	.099	.029															
7.0	.200	.099	.028	.196	.098	.028	.189	.096	.028	.182	.093	.027	.176	.091	.027															
8.0	.187	.091	.026	.183	.090	.026	.177	.088	.025	.171	.087	.025	.165	.085	.025															
9.0	.175	.085	.024	.172	.084	.024	.166	.082	.023	.160	.080	.023	.155	.079	.023															
10.0	.164	.079	.022	.162	.078	.022	.156	.077	.022	.151	.075	.021	.146	.074	.021															

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.205	.205	.205	.176	.176	.176	.120	.120	.120	.069	.069	.069	.022	.022	.022	
1.0	.196	.171	.149	.168	.147	.128	.115	.101	.089	.066	.058	.052	.021	.019	.017	
2.0	.188	.147	.113	.161	.127	.097	.110	.088	.068	.064	.051	.040	.020	.016	.013	
3.0	.180	.130	.089	.155	.112	.077	.106	.078	.054	.061	.045	.032	.020	.015	.010	
4.0	.173	.116	.073	.148	.101	.064	.102	.070	.045	.059	.041	.027	.019	.013	.009	
5.0	.165	.106	.062	.142	.092	.054	.098	.064	.038	.057	.038	.023	.018	.012	.007	
6.0	.158	.098	.054	.136	.085	.047	.094	.059	.033	.054	.035	.020	.018	.011	.007	
7.0	.151	.091	.048	.130	.079	.042	.090	.055	.030	.052	.033	.018	.017	.011	.006	
8.0	.145	.085	.044	.125	.074	.038	.086	.052	.027	.050	.031	.016	.016	.010	.005	
9.0	.139	.080	.041	.120	.070	.035	.083	.049	.025	.048	.029	.015	.016	.009	.005	
10.0	.133	.076	.038	.115	.066	.033	.080	.046	.023	.046	.027	.014	.015	.009	.005	

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1005.02x1 lm											
NAME: DJ1202408NO					TYPE:			WEIGHT:			
SPEC.:DJ1202408NO-8WWNSA012WC0100					DIM.: 1000*8*1.5mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*8mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	26.6	28.1	26.9	28.3	28.6	25.9	27.4	26.2	27.6	27.9	
	3H	28.4	29.8	28.8	30.1	30.4	27.4	28.8	27.7	29.0	29.3
	4H	29.3	30.6	29.6	30.9	31.2	27.9	29.3	28.3	29.6	29.9
	6H	30.0	31.2	30.4	31.6	31.9	28.3	29.6	28.7	29.9	30.2
	8H	30.3	31.5	30.7	31.8	32.2	28.4	29.6	28.8	29.9	30.3
	12H	30.6	31.7	31.0	32.1	32.4	28.5	29.6	28.8	30.0	30.3
4H	2H	27.2	28.5	27.5	28.8	29.1	26.7	28.0	27.0	28.3	28.6
	3H	29.3	30.4	29.6	30.8	31.1	28.4	29.6	28.8	29.9	30.2
	4H	30.2	31.3	30.6	31.7	32.0	29.1	30.2	29.5	30.5	30.9
	6H	31.1	32.1	31.5	32.4	32.9	29.6	30.6	30.0	30.9	31.4
	8H	31.5	32.4	31.9	32.8	33.2	29.8	30.6	30.2	31.1	31.5
	12H	31.8	32.6	32.3	33.1	33.5	29.8	30.7	30.3	31.1	31.5
8H	4H	30.5	31.4	31.0	31.8	32.2	29.6	30.4	30.0	30.8	31.3
	6H	31.6	32.3	32.1	32.8	33.2	30.3	31.0	30.7	31.4	31.9
	8H	32.1	32.7	32.6	33.2	33.7	30.5	31.2	31.0	31.6	32.1
	12H	32.6	33.1	33.1	33.6	34.1	30.7	31.2	31.2	31.7	32.3
12H	4H	30.5	31.4	31.0	31.8	32.2	29.6	30.4	30.1	30.9	31.3
	6H	31.7	32.3	32.2	32.8	33.3	30.4	31.1	30.9	31.5	32.0
	8H	32.2	32.8	32.7	33.3	33.8	30.7	31.3	31.2	31.8	32.3
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.4					
2.0H	+ 0.1 / - 0.3					+ 0.2 / - 0.5					

CIE Pub.117, 1005 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.0)

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1005.02x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8WWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	44	37	55	44	37	54	44	37	30
0.80	66	54	47	65	54	47	63	53	46	39
1.00	75	63	56	73	63	55	71	64	55	47
1.25	82	71	64	80	70	63	77	69	62	55
1.50	87	77	69	85	76	69	82	74	68	60
2.00	94	85	78	92	84	77	88	81	76	67
2.50	98	90	83	96	88	82	91	85	80	72
3.00	101	94	88	99	92	87	94	89	85	76
4.00	105	99	94	103	97	93	98	94	90	81
5.00	108	103	98	105	101	97	100	97	93	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## ISOCANDELA DIAGRAM

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1005.02x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8WWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2020-09-04


Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1005.02x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8WWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Flux out:733.8 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## ISOLUX DIAGRAM


Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1005.02x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8WWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2020-09-04

Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.3660A P:8.700W PF:1.000 Freq:0Hz Lamp Flux:1005.02x1 lm		
NAME: DJ1202408NO	TYPE:	WEIGHT:
SPEC.:DJ1202408NO-8WWNSA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	330	328	325	328	330	328	325	328										
5	332	329	324	325	326	324	324	329										
10	331	327	320	319	319	318	321	327										
15	328	324	314	310	310	310	315	323										
20	322	317	305	299	299	299	307	317										
25	314	308	294	286	285	286	296	308										
30	303	297	281	271	268	270	283	297										
35	289	283	265	253	250	252	267	283										
40	273	267	247	233	229	232	249	266										
45	255	248	226	211	206	210	229	248										
50	234	227	203	187	181	186	206	227										
55	211	203	179	161	155	160	182	203										
60	186	177	152	134	127	132	155	178										
65	159	150	123	105	98.0	103	127	150										
70	130	120	93.7	76.4	68.9	74.0	97.2	121										
75	99.3	90.0	63.7	48.4	41.5	45.9	67.7	91.5										
80	69.1	60.0	35.8	24.2	18.9	22.0	40.0	61.8										
85	41.5	31.5	13.9	7.78	5.15	6.17	17.4	35.4										
90	20.4	13.0	1.45	1.80	0.93	0.91	2.40	16.4										
95	10.1	3.74	1.20	1.45	1.09	0.84	0.45	7.66										
100	6.39	1.60	1.18	1.55	1.36	1.07	0.79	4.20										
105	4.47	1.31	1.31	1.84	1.77	1.47	1.22	2.54										
110	3.79	1.60	1.69	2.20	2.17	1.78	1.62	1.37										
115	3.01	1.96	2.15	2.58	2.55	2.09	1.99	1.72										
120	2.91	2.39	2.55	2.90	2.90	2.42	2.31	2.11										
125	2.70	2.75	2.88	3.17	3.23	2.70	2.61	2.46										
130	3.07	3.05	3.19	3.42	3.54	2.99	2.87	2.73										
135	3.40	3.31	3.40	3.65	3.80	3.31	3.09	2.95										
140	3.69	3.53	3.61	3.88	4.03	3.61	3.25	3.10										
145	3.91	3.67	3.75	4.12	4.19	3.92	3.40	3.29										
150	4.13	3.80	3.92	4.38	4.30	4.18	3.59	3.39										
155	4.37	3.92	4.15	4.62	4.47	4.45	3.99	3.51										
160	4.61	4.08	4.53	4.82	4.63	4.68	4.40	3.74										
165	4.87	4.38	4.82	4.99	4.76	4.88	4.76	4.16										
170	4.86	4.84	5.10	5.18	4.66	5.11	5.09	4.69										
175	4.68	5.30	5.44	5.43	4.56	5.32	5.42	5.25										
180	4.78	5.66	5.66	5.68	4.79	5.66	5.69	5.67										

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-09-04

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks: