


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.2870A P:6.888W PF:1.000 Freq:0Hz Lamp Flux:1096.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 159.25 lm/W			
MODEL	DR8802408NO	I _{max} (cd)	354.4	S/MH(C0/180)	1.33
NOMINAL POWER(W)	6.4	LOR(%)	100.0	S/MH(C90/270)	1.29
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1096.9	h UP,DN(C0-180)	0.8,50.7
NOMINAL FLUX(lm)	1096.89	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,47.7
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	h down(%)	98.4	CIBSE SHR MAX	1.50



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-11-02

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	351.9	352.2	350.3	348.6	346.2	346.6	348.1	350.3	0- 10	33.56	33.56	3.06,3.06
20	340.1	340.5	336.8	333.2	328.6	329.2	332.4	336.6	10- 20	96.95	130.5	11.9,11.9
30	317.8	318.2	313.1	307.6	300.9	301.8	306.7	312.4	20- 30	149.2	279.7	25.5,25.5
40	284.5	285.1	278.7	271.7	263.2	264.4	270.7	277.9	30- 40	183.6	463.3	42.2,42.2
50	240.5	241.0	233.6	225.3	215.5	216.8	224.4	232.6	40- 50	195.0	658.4	60,60
60	185.7	186.2	178.0	169.0	158.4	159.8	168.3	177.1	50- 60	180.3	838.7	76.5,76.5
70	122.0	121.9	113.5	104.7	94.49	95.83	104.1	113.1	60- 70	139.8	978.5	89.2,89.2
80	55.06	52.57	46.51	40.02	32.97	33.46	39.55	47.45	70- 80	79.53	1058	96.5,96.5
90	8.249	6.739	1.884	3.404	2.016	1.802	0.9101	4.680	80- 90	21.51	1080	98.4,98.4
100	1.269	1.303	1.242	1.377	1.091	0.9327	0.8287	0.7927	90-100	1.746	1081	98.6,98.6
110	1.875	1.866	1.780	1.994	1.980	1.701	1.718	1.507	100-110	1.502	1083	98.7,98.7
120	2.757	2.754	2.711	2.767	2.787	2.417	2.445	2.371	110-120	2.202	1085	98.9,98.9
130	3.567	3.420	3.372	3.347	3.481	3.044	3.013	2.986	120-130	2.656	1088	99.2,99.2
140	4.147	3.888	3.880	3.855	4.021	3.700	3.428	3.365	130-140	2.738	1090	99.4,99.4
150	4.555	4.135	4.208	4.436	4.369	4.360	3.854	3.593	140-150	2.500	1093	99.6,99.6
160	5.003	4.388	4.881	4.978	4.770	4.916	4.704	4.034	150-160	2.048	1095	99.8,99.8
170	5.324	5.090	5.544	5.491	4.769	5.416	5.437	5.096	160-170	1.410	1096	100,100
180	5.116	5.965	6.085	6.085	5.123	5.971	6.098	6.085	170-180	0.5191	1097	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-11-02

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.2870A P:6.888W PF:1.000 Freq:0Hz Lamp Flux:1096.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	37994	26878
80	39633	33477
75	42548	38344
70	44578	41464
65	45792	43364
60	46432	44496
55	46727	45124
50	46766	45428
45	46648	45522


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-11-02

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.2870A P:6.888W PF:1.000 Freq:0Hz Lamp Flux:1096.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.78	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.78	.70	.63	.77	.69	.63	.73	.67	.61	.71	.65	.60	.68	.63	.59	.57
4.0	.69	.60	.53	.68	.59	.53	.65	.58	.52	.63	.56	.51	.60	.55	.50	.48
5.0	.62	.53	.46	.60	.52	.45	.58	.51	.45	.56	.49	.44	.54	.48	.44	.41
6.0	.55	.46	.40	.54	.46	.40	.52	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.34	.46	.39	.34	.44	.38	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.31	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.27	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-11-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.2870A P:6.888W PF:1.000 Freq:0Hz Lamp Flux:1096.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.315	.179	.057	.307	.175	.056	.293	.168	.054	.280	.161	.052	.268	.155	.050	
2.0	.296	.162	.050	.289	.159	.049	.277	.154	.048	.265	.149	.047	.254	.144	.045	
3.0	.273	.146	.044	.268	.143	.043	.256	.139	.042	.246	.135	.041	.236	.131	.041	
4.0	.252	.131	.039	.247	.129	.038	.237	.126	.038	.228	.122	.037	.219	.119	.036	
5.0	.233	.119	.034	.228	.117	.034	.219	.114	.034	.211	.111	.033	.203	.109	.033	
6.0	.216	.108	.031	.212	.107	.031	.204	.104	.030	.196	.102	.030	.189	.100	.030	
7.0	.201	.099	.028	.197	.098	.028	.190	.096	.028	.183	.094	.027	.177	.092	.027	
8.0	.187	.091	.026	.184	.091	.026	.177	.089	.025	.171	.087	.025	.166	.085	.025	
9.0	.175	.085	.024	.172	.084	.024	.167	.082	.023	.161	.081	.023	.156	.079	.023	
10.0	.165	.079	.022	.162	.078	.022	.157	.077	.022	.152	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.203	.203	.203	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.193	.168	.146	.165	.144	.126	.113	.099	.087	.065	.057	.051	.021	.019	.016	
2.0	.185	.144	.110	.158	.124	.095	.109	.086	.066	.063	.050	.039	.020	.016	.013	
3.0	.177	.127	.086	.152	.109	.075	.104	.076	.052	.060	.044	.031	.019	.014	.010	
4.0	.170	.113	.070	.146	.098	.061	.100	.068	.043	.058	.040	.025	.019	.013	.008	
5.0	.163	.103	.059	.140	.089	.051	.096	.062	.036	.056	.037	.022	.018	.012	.007	
6.0	.155	.095	.051	.134	.082	.045	.092	.057	.032	.053	.034	.019	.017	.011	.006	
7.0	.149	.088	.045	.128	.076	.040	.088	.053	.028	.051	.031	.017	.017	.010	.006	
8.0	.142	.082	.041	.122	.071	.036	.085	.050	.025	.049	.030	.015	.016	.010	.005	
9.0	.136	.077	.038	.117	.067	.033	.081	.047	.023	.047	.028	.014	.015	.009	.005	
10.0	.130	.073	.035	.112	.063	.030	.078	.045	.022	.045	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-11-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.2870A P:6.888W PF:1.000 Freq:0Hz Lamp Flux:1096.89x1 lm										
NAME: DR8802408NO					TYPE:			WEIGHT:		
SPEC.:DR8802408NO-8NWDA012WC0100					DIM.: 1000*8*1.5mm			SERIAL No.:		
MFR.: COLORS					SUR.:1000*8mm			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	26.2	27.7	26.4	27.9	28.1	26.0	27.5	26.3	27.8	28.0
3H	27.8	29.3	28.2	29.5	29.8	27.6	29.0	27.9	29.3	29.6
4H	28.5	29.9	28.9	30.2	30.4	28.2	29.6	28.6	29.9	30.2
6H	29.1	30.3	29.4	30.6	30.9	28.7	29.9	29.0	30.2	30.5
8H	29.2	30.4	29.6	30.8	31.1	28.8	30.0	29.2	30.3	30.6
12H	29.3	30.5	29.7	30.8	31.2	28.9	30.0	29.2	30.3	30.7
4H 2H	26.8	28.2	27.2	28.4	28.7	26.7	28.0	27.0	28.3	28.6
3H	28.7	29.9	29.1	30.2	30.5	28.5	29.7	28.9	30.0	30.3
4H	29.5	30.6	29.9	30.9	31.3	29.2	30.3	29.6	30.7	31.0
6H	30.1	31.1	30.6	31.5	31.9	29.8	30.7	30.2	31.1	31.5
8H	30.4	31.3	30.8	31.7	32.1	30.0	30.9	30.4	31.2	31.7
12H	30.6	31.4	31.0	31.8	32.2	30.1	30.9	30.5	31.3	31.7
8H 4H	29.8	30.7	30.2	31.1	31.5	29.6	30.4	30.0	30.8	31.3
6H	30.6	31.3	31.1	31.8	32.2	30.3	31.0	30.7	31.4	31.9
8H	30.9	31.6	31.4	32.0	32.5	30.5	31.2	31.0	31.6	32.1
12H	31.2	31.7	31.7	32.2	32.7	30.7	31.3	31.2	31.7	32.3
12H 4H	29.8	30.6	30.3	31.0	31.5	29.6	30.4	30.0	30.8	31.2
6H	30.6	31.3	31.1	31.7	32.2	30.3	31.0	30.8	31.4	31.9
8H	31.0	31.6	31.5	32.0	32.6	30.6	31.2	31.1	31.7	32.2
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.4				

CIE Pub.117, 1097 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.3)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-11-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.2870A P:6.888W PF:1.000 Freq:0Hz Lamp Flux:1096.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	44	37	55	44	37	54	43	37	30
0.80	66	54	47	65	54	47	63	53	46	39
1.00	75	63	56	73	63	56	71	64	55	47
1.25	82	71	64	80	70	63	77	69	62	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	81	76	68
2.50	98	90	84	96	88	83	92	86	81	72
3.00	101	94	89	99	93	87	95	89	85	76
4.00	105	100	95	103	98	93	98	94	90	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-11-02

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.2870A P:6.888W PF:1.000 Freq:0Hz Lamp Flux:1096.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-11-02

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.2870A P:6.888W PF:1.000 Freq:0Hz Lamp Flux:1096.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Flux out:838.7 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-11-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.2870A P:6.888W PF:1.000 Freq:0Hz Lamp Flux:1096.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-11-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-11-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.2870A P:6.888W PF:1.000 Freq:0Hz Lamp Flux:1096.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Table--1

UNIT: cd

C(DEC) g (DEC)	0	45	90	135	180	225	270	315										
0	354	354	354	354	354	354	354	354										
5	354	354	353	353	351	352	352	353										
10	352	352	350	349	346	347	348	350										
15	347	348	345	342	339	339	341	345										
20	340	340	337	333	329	329	332	337										
25	330	331	326	322	316	317	321	326										
30	318	318	313	308	301	302	307	312										
35	303	303	297	291	283	284	290	297										
40	285	285	279	272	263	264	271	278										
45	264	264	258	250	241	242	249	257										
50	240	241	234	225	215	217	224	233										
55	214	215	207	198	188	189	197	206										
60	186	186	178	169	158	160	168	177										
65	155	155	147	138	127	128	137	146										
70	122	122	113	105	94.5	95.8	104	113										
75	88.1	86.9	79.4	71.3	62.2	63.2	71.1	79.6										
80	55.1	52.6	46.5	40.0	33.0	33.5	39.5	47.5										
85	26.5	24.3	18.7	15.5	11.6	11.3	14.1	20.3										
90	8.25	6.74	1.88	3.40	2.02	1.80	0.91	4.68										
95	2.31	1.82	1.32	1.52	0.99	0.87	0.45	0.80										
100	1.27	1.30	1.24	1.38	1.09	0.93	0.83	0.79										
105	1.46	1.51	1.34	1.63	1.54	1.34	1.30	1.13										
110	1.88	1.87	1.78	1.99	1.98	1.70	1.72	1.51										
115	2.31	2.35	2.30	2.41	2.40	2.07	2.11	1.94										
120	2.76	2.75	2.71	2.77	2.79	2.42	2.45	2.37										
125	3.17	3.12	3.06	3.07	3.15	2.74	2.73	2.73										
130	3.57	3.42	3.37	3.35	3.48	3.04	3.01	2.99										
135	3.90	3.68	3.65	3.59	3.78	3.38	3.25	3.19										
140	4.15	3.89	3.88	3.85	4.02	3.70	3.43	3.37										
145	4.36	4.01	4.03	4.14	4.20	4.04	3.60	3.51										
150	4.56	4.14	4.21	4.44	4.37	4.36	3.85	3.59										
155	4.78	4.25	4.45	4.71	4.58	4.65	4.28	3.76										
160	5.00	4.39	4.88	4.98	4.77	4.92	4.70	4.03										
165	5.24	4.63	5.26	5.24	4.92	5.24	5.10	4.51										
170	5.32	5.09	5.54	5.49	4.77	5.42	5.44	5.10										
175	5.06	5.59	5.84	5.80	4.73	5.66	5.80	5.62										
180	5.12	5.96	6.09	6.09	5.12	5.97	6.10	6.09										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-11-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: