


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.2785A P:6.683W PF:1.000 Freq:0Hz Lamp Flux:1005.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 150.51 lm/W			
MODEL	DR8802408NO	I <sub>max</sub> (cd)	314.5	S/MH(C0/180)	1.34
NOMINAL POWER(W)	6.4	LOR(%)	100.0	S/MH(C90/270)	1.32
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1005.9	h UP,DN(C0-180)	0.9,49.9
NOMINAL FLUX(lm)	1005.89	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,48.5
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	h down(%)	98.4	CIBSE SHR MAX	1.50



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-11-02

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	312.2	312.6	311.6	311.3	309.8	310.3	310.6	311.8	0- 10	29.86	29.86	2.97,2.97
20	302.1	302.6	300.9	300.0	297.5	297.8	298.8	300.6	10- 20	86.68	116.5	11.6,11.6
30	283.0	283.7	281.3	280.0	276.5	276.7	278.3	280.7	20- 30	134.3	250.8	24.9,24.9
40	254.0	255.0	252.2	250.6	246.1	246.3	248.3	251.1	30- 40	166.7	417.6	41.5,41.5
50	214.4	215.7	212.9	211.0	205.8	206.0	208.4	211.1	40- 50	178.8	596.4	59.3,59.3
60	164.2	165.7	163.1	161.4	155.7	155.8	158.3	160.7	50- 60	166.8	763.2	75.9,75.9
70	104.8	106.3	104.3	103.1	97.59	97.48	99.73	101.6	60- 70	130.4	893.6	88.8,88.8
80	43.28	43.40	43.59	42.97	38.86	38.63	40.16	41.13	70- 80	75.04	968.7	96.3,96.3
90	5.280	5.704	2.239	5.113	3.536	3.664	1.667	5.046	80- 90	21.18	989.8	98.4,98.4
100	1.203	1.270	1.202	1.310	0.8952	0.8079	0.7763	0.8077	90-100	1.783	991.6	98.6,98.6
110	1.856	1.865	1.660	1.825	1.718	1.495	1.585	1.476	100-110	1.406	993.0	98.7,98.7
120	2.678	2.659	2.518	2.552	2.479	2.142	2.225	2.262	110-120	2.051	995.1	98.9,98.9
130	3.357	3.227	3.117	3.073	3.120	2.745	2.759	2.791	120-130	2.459	997.5	99.2,99.2
140	3.827	3.587	3.566	3.541	3.600	3.345	3.127	3.079	130-140	2.514	1000	99.4,99.4
150	4.128	3.754	3.780	4.028	3.914	3.921	3.475	3.273	140-150	2.272	1002	99.6,99.6
160	4.455	3.921	4.354	4.483	4.262	4.428	4.216	3.647	150-160	1.844	1004	99.8,99.8
170	4.709	4.522	4.916	4.910	4.248	4.796	4.836	4.555	160-170	1.258	1005	100,100
180	4.495	5.337	5.404	5.450	4.489	5.330	5.397	5.437	170-180	0.4613	1006	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-11-02

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.2785A P:6.683W PF:1.000 Freq:0Hz Lamp Flux:1005.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WVDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	26895	27161
80	31153	31381
75	35446	35383
70	38295	38106
65	40051	39797
60	41049	40777
55	41540	41250
50	41690	41397
45	41642	41341


C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-11-02

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.2785A P:6.683W PF:1.000 Freq:0Hz Lamp Flux:1005.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WNTA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.89	.82	.76	.87	.81	.75	.83	.78	.73	.80	.75	.71	.77	.73	.70	.67
3.0	.78	.70	.63	.76	.69	.62	.73	.66	.61	.70	.64	.60	.67	.63	.58	.56
4.0	.69	.60	.53	.67	.59	.53	.65	.57	.52	.62	.56	.51	.60	.54	.50	.48
5.0	.61	.52	.45	.60	.51	.45	.58	.50	.44	.56	.49	.44	.54	.48	.43	.41
6.0	.55	.46	.39	.54	.45	.39	.52	.44	.39	.50	.43	.38	.48	.42	.38	.36
7.0	.50	.41	.35	.49	.40	.34	.47	.40	.34	.46	.39	.34	.44	.38	.33	.31
8.0	.45	.37	.31	.45	.36	.31	.43	.36	.30	.42	.35	.30	.40	.34	.30	.28
9.0	.42	.33	.28	.41	.33	.27	.40	.32	.27	.38	.32	.27	.37	.31	.27	.25
10.0	.38	.30	.25	.38	.30	.25	.37	.29	.25	.35	.29	.24	.34	.29	.24	.22



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-11-02

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.2785A P:6.683W PF:1.000 Freq:0Hz Lamp Flux:1005.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WVDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.318	.181	.057	.311	.177	.056	.297	.170	.054	.283	.163	.052	.271	.157	.051	
2.0	.299	.164	.050	.292	.161	.050	.279	.155	.048	.268	.150	.047	.257	.145	.046	
3.0	.276	.147	.044	.270	.144	.043	.258	.140	.043	.248	.136	.042	.238	.132	.041	
4.0	.254	.132	.039	.249	.130	.038	.239	.127	.038	.229	.123	.037	.221	.120	.037	
5.0	.234	.119	.035	.230	.118	.034	.221	.115	.034	.212	.112	.033	.205	.109	.033	
6.0	.217	.109	.031	.213	.107	.031	.205	.105	.031	.197	.103	.030	.190	.100	.030	
7.0	.202	.100	.028	.198	.099	.028	.191	.096	.028	.184	.094	.027	.178	.092	.027	
8.0	.188	.092	.026	.185	.091	.026	.178	.089	.025	.172	.087	.025	.167	.086	.025	
9.0	.176	.085	.024	.173	.084	.024	.167	.083	.023	.162	.081	.023	.157	.080	.023	
10.0	.165	.079	.022	.163	.079	.022	.157	.077	.022	.152	.076	.022	.148	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.203	.203	.203	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.193	.168	.146	.165	.144	.126	.113	.099	.087	.065	.058	.051	.021	.019	.016	
2.0	.185	.144	.110	.159	.124	.095	.109	.086	.066	.063	.050	.039	.020	.016	.013	
3.0	.178	.127	.086	.153	.109	.074	.105	.076	.052	.060	.044	.031	.019	.014	.010	
4.0	.170	.114	.070	.146	.098	.061	.101	.068	.043	.058	.040	.025	.019	.013	.008	
5.0	.163	.103	.059	.140	.089	.051	.096	.062	.036	.056	.037	.022	.018	.012	.007	
6.0	.156	.095	.051	.134	.082	.045	.092	.058	.032	.054	.034	.019	.017	.011	.006	
7.0	.149	.088	.045	.128	.076	.040	.089	.054	.028	.051	.032	.017	.017	.010	.006	
8.0	.143	.082	.041	.123	.071	.036	.085	.050	.025	.049	.030	.015	.016	.010	.005	
9.0	.136	.077	.038	.117	.067	.033	.081	.047	.023	.047	.028	.014	.015	.009	.005	
10.0	.131	.073	.035	.113	.064	.030	.078	.045	.022	.046	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-11-02

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.2785A P:6.683W PF:1.000 Freq:0Hz Lamp Flux:1005.89x1 lm											
NAME: DR8802408NO					TYPE:			WEIGHT:			
SPEC.:DR8802408NO-8WNTA012WC0100					DIM.: 1000*8*1.5mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*8mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.9	27.5	26.2	27.7	27.9	25.9	27.4	26.2	27.7	27.9	
	3H	27.6	29.0	27.9	29.2	29.5	27.5	28.9	27.9	29.2	29.5
	4H	28.2	29.5	28.5	29.8	30.1	28.2	29.5	28.5	29.8	30.1
	6H	28.6	29.9	29.0	30.2	30.5	28.6	29.9	29.0	30.2	30.5
	8H	28.7	30.0	29.1	30.3	30.6	28.7	30.0	29.1	30.3	30.6
	12H	28.8	30.0	29.2	30.3	30.7	28.8	30.0	29.2	30.3	30.7
4H	2H	26.6	27.9	26.9	28.2	28.5	26.6	27.9	26.9	28.2	28.5
	3H	28.4	29.6	28.8	29.9	30.2	28.4	29.5	28.7	29.9	30.2
	4H	29.1	30.2	29.5	30.6	30.9	29.1	30.2	29.5	30.5	30.9
	6H	29.7	30.6	30.1	31.0	31.4	29.7	30.6	30.1	31.0	31.4
	8H	29.9	30.8	30.3	31.2	31.6	29.9	30.8	30.3	31.1	31.6
	12H	30.0	30.8	30.4	31.2	31.7	30.0	30.8	30.4	31.2	31.7
8H	4H	29.4	30.3	29.9	30.7	31.1	29.4	30.3	29.8	30.7	31.1
	6H	30.1	30.8	30.6	31.3	31.7	30.1	30.8	30.6	31.3	31.7
	8H	30.4	31.0	30.9	31.5	32.0	30.4	31.0	30.8	31.5	32.0
	12H	30.6	31.1	31.1	31.6	32.1	30.6	31.1	31.1	31.6	32.1
12H	4H	29.4	30.2	29.9	30.7	31.1	29.4	30.2	29.9	30.6	31.1
	6H	30.2	30.8	30.6	31.3	31.8	30.2	30.8	30.6	31.3	31.8
	8H	30.5	31.0	31.0	31.5	32.0	30.5	31.0	31.0	31.5	32.0
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 1006 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.0)

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-11-02

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.2785A P:6.683W PF:1.000 Freq:0Hz Lamp Flux:1005.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WNTDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	44	37	55	44	37	54	43	36	30
0.80	66	54	46	65	53	46	63	52	46	38
1.00	74	63	55	73	62	55	70	63	54	47
1.25	81	71	63	80	70	63	77	68	62	54
1.50	87	76	69	85	75	68	81	73	67	59
2.00	94	85	78	92	83	77	88	81	76	67
2.50	98	90	83	95	88	82	91	85	80	71
3.00	101	94	88	99	92	87	94	89	85	76
4.00	105	99	95	103	97	93	98	94	90	81
5.00	108	103	99	105	101	97	100	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2021-11-02

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

## ISOCANDELA DIAGRAM

Test:U:24.00V I:0.2785A P:6.683W PF:1.000 Freq:0Hz Lamp Flux:1005.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WNTA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-11-02


Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:24.00V I:0.2785A P:6.683W PF:1.000 Freq:0Hz Lamp Flux:1005.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WVDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Flux out:778.3 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-11-02

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM


Test:U:24.00V I:0.2785A P:6.683W PF:1.000 Freq:0Hz Lamp Flux:1005.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WVDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-11-02

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2021-11-02

Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.2785A P:6.683W PF:1.000 Freq:0Hz Lamp Flux:1005.89x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WNTA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Table--1

UNIT: cd

C(DEC) g (DEC)	0	45	90	135	180	225	270	315										
0	314	314	314	314	314	314	314	314										
5	314	314	314	314	313	313	313	314										
10	312	313	312	311	310	310	311	312										
15	308	309	307	307	305	305	306	307										
20	302	303	301	300	298	298	299	301										
25	294	294	292	291	288	288	290	292										
30	283	284	281	280	276	277	278	281										
35	270	271	268	266	263	263	265	267										
40	254	255	252	251	246	246	248	251										
45	236	237	234	232	227	227	230	232										
50	214	216	213	211	206	206	208	211										
55	191	192	189	187	182	182	185	187										
60	164	166	163	161	156	156	158	161										
65	135	137	135	133	127	127	130	132										
70	105	106	104	103	97.6	97.5	99.7	102										
75	73.4	74.8	73.3	72.2	67.3	67.1	69.1	70.5										
80	43.3	43.4	43.6	43.0	38.9	38.6	40.2	41.1										
85	18.8	18.7	18.9	19.2	15.9	16.0	16.8	17.6										
90	5.28	5.70	2.24	5.11	3.54	3.66	1.67	5.05										
95	1.85	1.92	1.27	1.64	0.92	1.08	0.43	1.19										
100	1.20	1.27	1.20	1.31	0.90	0.81	0.78	0.81										
105	1.45	1.50	1.30	1.50	1.30	1.15	1.20	1.13										
110	1.86	1.86	1.66	1.82	1.72	1.50	1.58	1.48										
115	2.28	2.27	2.12	2.19	2.09	1.86	1.93	1.88										
120	2.68	2.66	2.52	2.55	2.48	2.14	2.23	2.26										
125	3.03	2.97	2.84	2.82	2.81	2.45	2.51	2.56										
130	3.36	3.23	3.12	3.07	3.12	2.75	2.76	2.79										
135	3.61	3.44	3.37	3.29	3.38	3.06	2.97	2.97										
140	3.83	3.59	3.57	3.54	3.60	3.35	3.13	3.08										
145	4.01	3.69	3.65	3.77	3.77	3.63	3.28	3.17										
150	4.13	3.75	3.78	4.03	3.91	3.92	3.48	3.27										
155	4.34	3.83	4.02	4.26	4.09	4.17	3.84	3.41										
160	4.46	3.92	4.35	4.48	4.26	4.43	4.22	3.65										
165	4.68	4.12	4.66	4.68	4.43	4.59	4.56	4.05										
170	4.71	4.52	4.92	4.91	4.25	4.80	4.84	4.55										
175	4.47	4.96	5.23	5.18	4.19	5.03	5.14	5.02										
180	4.50	5.34	5.40	5.45	4.49	5.33	5.40	5.44										

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2021-11-02

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks: