


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.2850A P:6.840W PF:1.000 Freq:0Hz Lamp Flux:1115.02x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WWNDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 163.02 lm/W			
MODEL	DR8802408NO	I _{max} (cd)	365.8	S/MH(C0/180)	1.30
NOMINAL POWER(W)	6.4	LOR(%)	100.0	S/MH(C90/270)	1.28
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	1115.0	h UP,DN(C0-180)	0.8,50.2
NOMINAL FLUX(lm)	1115.02	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,48.2
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.4	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-11-02

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	361.6	362.2	361.2	360.6	358.8	358.5	358.9	360.0	0- 10	34.64	34.64	3.11,3.11
20	346.6	347.7	346.2	344.7	341.2	340.7	341.7	343.6	10- 20	99.83	134.5	12.1,12.1
30	320.6	322.2	320.4	318.1	313.0	312.3	314.0	316.4	20- 30	153.0	287.5	25.8,25.8
40	283.8	285.8	283.8	280.9	274.4	273.6	275.9	278.6	30- 40	187.5	475.0	42.6,42.6
50	236.3	238.5	236.5	233.4	225.9	224.9	227.6	230.4	40- 50	198.1	673.1	60.4,60.4
60	179.0	181.2	179.1	176.3	168.2	167.2	170.0	172.8	50- 60	182.2	855.3	76.7,76.7
70	113.7	115.5	113.6	111.3	103.6	102.5	105.1	107.8	60- 70	140.7	996.0	89.3,89.3
80	47.20	47.53	46.99	46.04	39.74	38.53	40.72	42.92	70- 80	79.91	1076	96.5,96.5
90	5.461	4.968	2.087	5.232	3.370	2.659	0.8301	4.504	80- 90	21.69	1098	98.4,98.4
100	1.289	1.317	1.249	1.350	0.9508	0.8546	0.8226	0.8603	90-100	1.678	1099	98.6,98.6
110	1.976	1.964	1.770	1.919	1.853	1.636	1.712	1.621	100-110	1.496	1101	98.7,98.7
120	2.905	2.873	2.737	2.707	2.692	2.357	2.453	2.491	110-120	2.218	1103	98.9,98.9
130	3.705	3.554	3.399	3.314	3.414	3.012	3.048	3.105	120-130	2.685	1106	99.2,99.2
140	4.353	4.022	3.921	3.861	3.988	3.693	3.487	3.498	130-140	2.779	1108	99.4,99.4
150	4.709	4.269	4.255	4.476	4.395	4.415	3.936	3.707	140-150	2.545	1111	99.6,99.6
160	5.235	4.502	4.976	5.056	4.836	4.996	4.810	4.173	150-160	2.091	1113	99.8,99.8
170	5.478	5.257	5.677	5.605	4.883	5.523	5.565	5.243	160-170	1.442	1114	100,100
180	5.243	6.172	6.205	6.265	5.230	6.179	6.239	6.252	170-180	0.5317	1115	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-11-02

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.2850A P:6.840W PF:1.000 Freq:0Hz Lamp Flux:1115.02x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WWNDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	29430	28449
80	33974	33827
75	38458	38406
70	41557	41536
65	43506	43508
60	44760	44767
55	45515	45543
50	45960	45982
45	46201	46208


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-11-02

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.2850A P:6.840W PF:1.000 Freq:0Hz Lamp Flux:1115.02x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WWNDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.79	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.60	.68	.63	.59	.57
4.0	.69	.61	.54	.68	.60	.53	.65	.58	.52	.63	.56	.51	.60	.55	.51	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.44	.54	.48	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.35	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-11-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.2850A P:6.840W PF:1.000 Freq:0Hz Lamp Flux:1115.02x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WWNDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.314	.178	.056	.306	.175	.055	.292	.167	.053	.279	.161	.052	.267	.155	.050	
2.0	.295	.162	.050	.288	.159	.049	.276	.153	.048	.264	.148	.046	.253	.143	.045	
3.0	.273	.145	.043	.267	.143	.043	.255	.138	.042	.245	.134	.041	.236	.130	.040	
4.0	.251	.131	.038	.246	.129	.038	.236	.125	.037	.227	.122	.037	.218	.119	.036	
5.0	.232	.118	.034	.227	.117	.034	.219	.114	.034	.210	.111	.033	.203	.108	.033	
6.0	.215	.108	.031	.211	.107	.031	.203	.104	.030	.196	.102	.030	.189	.099	.030	
7.0	.200	.099	.028	.196	.098	.028	.189	.096	.028	.183	.094	.027	.176	.092	.027	
8.0	.187	.091	.026	.183	.090	.026	.177	.088	.025	.171	.087	.025	.165	.085	.025	
9.0	.175	.085	.024	.172	.084	.024	.166	.082	.023	.161	.081	.023	.156	.079	.023	
10.0	.164	.079	.022	.162	.078	.022	.156	.077	.022	.152	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.202	.202	.202	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.193	.168	.146	.165	.144	.126	.113	.099	.087	.065	.057	.051	.021	.018	.016	
2.0	.185	.144	.110	.158	.124	.095	.108	.086	.066	.063	.050	.039	.020	.016	.013	
3.0	.177	.126	.086	.152	.109	.075	.104	.076	.052	.060	.044	.031	.019	.014	.010	
4.0	.170	.113	.070	.146	.098	.061	.100	.068	.043	.058	.040	.025	.019	.013	.008	
5.0	.162	.103	.059	.139	.089	.051	.096	.062	.036	.056	.037	.022	.018	.012	.007	
6.0	.155	.095	.051	.133	.082	.045	.092	.057	.032	.053	.034	.019	.017	.011	.006	
7.0	.148	.088	.045	.128	.076	.040	.088	.053	.028	.051	.031	.017	.017	.010	.006	
8.0	.142	.082	.041	.122	.071	.036	.084	.050	.025	.049	.029	.015	.016	.010	.005	
9.0	.136	.077	.037	.117	.067	.033	.081	.047	.023	.047	.028	.014	.015	.009	.005	
10.0	.130	.073	.035	.112	.063	.030	.078	.044	.022	.045	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-11-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.2850A P:6.840W PF:1.000 Freq:0Hz Lamp Flux:1115.02x1 lm											
NAME: DR8802408NO					TYPE:			WEIGHT:			
SPEC.:DR8802408NO-8WWNDA012WC0100					DIM.: 1000*8*1.5mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*8mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.9	27.4	26.2	27.6	27.9	25.9	27.4	26.2	27.6	27.9	
	3H	27.5	28.9	27.8	29.1	29.4	27.5	28.9	27.8	29.1	29.4
	4H	28.1	29.4	28.4	29.7	30.0	28.1	29.4	28.4	29.7	30.0
	6H	28.5	29.8	28.9	30.1	30.4	28.5	29.8	28.9	30.1	30.4
	8H	28.6	29.9	29.0	30.2	30.5	28.6	29.8	29.0	30.2	30.5
	12H	28.7	29.9	29.1	30.2	30.5	28.7	29.9	29.1	30.2	30.5
4H	2H	26.5	27.8	26.9	28.1	28.4	26.5	27.8	26.9	28.1	28.4
	3H	28.3	29.5	28.7	29.8	30.1	28.3	29.5	28.7	29.8	30.1
	4H	29.0	30.1	29.4	30.4	30.8	29.0	30.1	29.4	30.4	30.8
	6H	29.6	30.5	30.0	30.9	31.3	29.6	30.5	30.0	30.9	31.3
	8H	29.8	30.6	30.2	31.0	31.5	29.8	30.6	30.2	31.0	31.4
	12H	29.9	30.7	30.3	31.1	31.5	29.9	30.7	30.3	31.1	31.5
8H	4H	29.3	30.2	29.7	30.6	31.0	29.3	30.2	29.7	30.6	31.0
	6H	30.0	30.7	30.5	31.2	31.6	30.0	30.7	30.5	31.2	31.6
	8H	30.3	30.9	30.7	31.4	31.8	30.2	30.9	30.7	31.3	31.8
	12H	30.4	31.0	30.9	31.5	32.0	30.4	31.0	30.9	31.5	32.0
12H	4H	29.3	30.1	29.8	30.5	31.0	29.3	30.1	29.8	30.5	31.0
	6H	30.0	30.7	30.5	31.1	31.6	30.0	30.7	30.5	31.1	31.6
	8H	30.3	30.9	30.8	31.4	31.9	30.3	30.9	30.8	31.4	31.9
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 1115 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 0.4)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-11-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.2850A P:6.840W PF:1.000 Freq:0Hz Lamp Flux:1115.02x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WWNDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	45	38	55	44	37	54	44	37	31
0.80	66	55	47	65	54	47	63	53	46	39
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	80	70	64	78	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	82	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	101	94	89	99	93	88	95	90	85	76
4.00	106	100	95	103	98	93	99	94	91	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-11-02

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.2850A P:6.840W PF:1.000 Freq:0Hz Lamp Flux:1115.02x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WWNDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-11-02

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.2850A P:6.840W PF:1.000 Freq:0Hz Lamp Flux:1115.02x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WWNDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Flux out:838.6 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-11-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.2850A P:6.840W PF:1.000 Freq:0Hz Lamp Flux:1115.02x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WWNDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-11-02

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: JYH
 Test Date: 2021-11-02

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity: 65.0%
 Test Distance: 10.950m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.2850A P:6.840W PF:1.000 Freq:0Hz Lamp Flux:1115.02x1 lm		
NAME: DR8802408NO	TYPE:	WEIGHT:
SPEC.:DR8802408NO-8WWNDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	366	366	365	366	366	366	365	366										
5	365	365	365	364	363	363	363	364										
10	362	362	361	361	359	359	359	360										
15	355	356	355	354	351	351	352	353										
20	347	348	346	345	341	341	342	344										
25	335	336	335	333	328	328	329	331										
30	321	322	320	318	313	312	314	316										
35	304	305	303	301	295	294	296	299										
40	284	286	284	281	274	274	276	279										
45	261	263	261	258	251	250	253	256										
50	236	238	236	233	226	225	228	230										
55	209	211	209	206	198	197	200	203										
60	179	181	179	176	168	167	170	173										
65	147	149	147	145	137	135	138	141										
70	114	116	114	111	104	103	105	108										
75	79.6	81.1	79.5	77.8	70.6	69.4	71.9	74.3										
80	47.2	47.5	47.0	46.0	39.7	38.5	40.7	42.9										
85	20.5	19.9	19.8	20.1	15.5	14.4	15.7	17.9										
90	5.46	4.97	2.09	5.23	3.37	2.66	0.83	4.50										
95	1.58	1.53	1.32	1.74	0.90	0.84	0.46	1.27										
100	1.29	1.32	1.25	1.35	0.95	0.85	0.82	0.86										
105	1.56	1.56	1.36	1.57	1.41	1.26	1.29	1.23										
110	1.98	1.96	1.77	1.92	1.85	1.64	1.71	1.62										
115	2.45	2.45	2.31	2.35	2.26	1.99	2.11	2.04										
120	2.91	2.87	2.74	2.71	2.69	2.36	2.45	2.49										
125	3.34	3.24	3.12	3.03	3.07	2.72	2.76	2.84										
130	3.71	3.55	3.40	3.31	3.41	3.01	3.05	3.10										
135	4.03	3.81	3.70	3.57	3.73	3.37	3.30	3.30										
140	4.35	4.02	3.92	3.86	3.99	3.69	3.49	3.50										
145	4.53	4.15	4.11	4.16	4.20	4.05	3.68	3.61										
150	4.71	4.27	4.25	4.48	4.40	4.41	3.94	3.71										
155	4.94	4.38	4.54	4.78	4.62	4.71	4.36	3.92										
160	5.23	4.50	4.98	5.06	4.84	5.00	4.81	4.17										
165	5.41	4.76	5.36	5.32	5.01	5.26	5.22	4.66										
170	5.48	5.26	5.68	5.60	4.88	5.52	5.56	5.24										
175	5.19	5.74	5.96	5.94	4.83	5.79	5.94	5.78										
180	5.24	6.17	6.21	6.27	5.23	6.18	6.24	6.25										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-11-02

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: