


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:48.00V I:0.0700A P:3.360W PF:1.000 Freq:0Hz Lamp Flux:332.057x1 lm		
NAME: DS8724810NO	TYPE:	WEIGHT:
SPEC.:DS8724810NO-9NWDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 98.83 lm/W			
MODEL	DS8724810NO	I _{max} (cd)	109.0	S/MH(C0/180)	1.29
NOMINAL POWER(W)	3.36	LOR(%)	100.0	S/MH(C90/270)	1.28
RATED VOLTAGE(V)	48	TOTAL FLUX(lm)	332.06	h UP,DN(C0-180)	0.8,49.9
NOMINAL FLUX(lm)	332.057	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,48.6
LAMPS INSIDE	1	h up(%)	1.5	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	48	h down(%)	98.5	CIBSE SHR MAX	1.50

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-07-08

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	107.6	107.9	107.7	107.7	107.1	107.1	107.1	107.5	0- 10	10.33	10.33	3.11,3.11
20	102.9	103.6	103.3	103.1	102.2	102.0	102.1	102.6	10- 20	29.80	40.12	12.1,12.1
30	95.09	95.95	95.70	95.35	94.16	93.78	94.00	94.44	20- 30	45.73	85.85	25.9,25.9
40	83.76	85.02	84.77	84.43	83.01	82.43	82.71	83.01	30- 40	56.07	141.9	42.7,42.7
50	69.25	70.61	70.62	70.27	68.73	68.12	68.26	68.41	40- 50	59.26	201.2	60.6,60.6
60	51.61	53.14	53.34	53.31	51.77	50.97	50.98	50.83	50- 60	54.46	255.6	77,77
70	31.71	33.20	33.62	33.83	32.60	31.69	31.39	30.97	60- 70	41.88	297.5	89.6,89.6
80	11.86	13.11	13.42	13.97	13.28	12.47	11.64	11.43	70- 80	23.54	321.1	96.7,96.7
90	0.8960	0.9316	0.5143	1.300	1.153	0.9933	0.3100	0.5629	80- 90	6.045	327.1	98.5,98.5
100	0.3206	0.3881	0.3607	0.3675	0.2541	0.2071	0.2609	0.2070	90-100	0.3863	327.5	98.6,98.6
110	0.5807	0.6016	0.5207	0.5485	0.4949	0.4140	0.5214	0.4135	100-110	0.4207	327.9	98.8,98.8
120	0.8215	0.8685	0.8210	0.7684	0.7217	0.6343	0.7214	0.6143	110-120	0.6270	328.5	98.9,98.9
130	1.049	1.083	1.029	0.9756	0.9420	0.8613	0.8889	0.8215	120-130	0.7646	329.3	99.2,99.2
140	1.256	1.209	1.142	1.182	1.129	1.075	1.016	0.9419	130-140	0.8046	330.1	99.4,99.4
150	1.369	1.303	1.262	1.363	1.250	1.276	1.182	1.042	140-150	0.7447	330.9	99.6,99.6
160	1.523	1.389	1.443	1.536	1.410	1.469	1.436	1.182	150-160	0.6187	331.5	99.8,99.8
170	1.677	1.570	1.676	1.697	1.463	1.663	1.684	1.516	160-170	0.4282	331.9	100,100
180	1.603	1.803	1.857	1.884	1.576	1.803	1.884	1.877	170-180	0.1596	332.1	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:48.00V I:0.0700A P:3.360W PF:1.000 Freq:0Hz Lamp Flux:332.057x1 lm		
NAME: DS8724810NO	TYPE:	WEIGHT:
SPEC.:DS8724810NO-9NWCDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	5079	6187
80	6829	7730
75	8281	9006
70	9270	9829
65	9902	10341
60	10323	10668
55	10597	10869
50	10773	10987
45	10880	11051


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:48.00V I:0.0700A P:3.360W PF:1.000 Freq:0Hz Lamp Flux:332.057x1 lm		
NAME: DS8724810NO	TYPE:	WEIGHT:
SPEC.:DS8724810NO-9NWDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-07-08

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:48.00V I:0.0700A P:3.360W PF:1.000 Freq:0Hz Lamp Flux:332.057x1 lm		
NAME: DS8724810NO	TYPE:	WEIGHT:
SPEC.:DS8724810NO-9NWCDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.312	.177	.056	.304	.174	.055	.290	.166	.053	.277	.160	.051	.265	.154	.050	
2.0	.294	.161	.049	.287	.158	.049	.275	.153	.047	.263	.148	.046	.252	.143	.045	
3.0	.272	.145	.043	.266	.142	.043	.255	.138	.042	.245	.134	.041	.235	.130	.040	
4.0	.251	.130	.038	.246	.129	.038	.236	.125	.037	.227	.122	.037	.218	.118	.036	
5.0	.232	.118	.034	.227	.117	.034	.218	.114	.033	.210	.111	.033	.203	.108	.033	
6.0	.215	.108	.031	.211	.106	.031	.203	.104	.030	.196	.102	.030	.189	.099	.029	
7.0	.200	.099	.028	.196	.098	.028	.189	.096	.028	.183	.094	.027	.176	.092	.027	
8.0	.187	.091	.026	.183	.090	.026	.177	.088	.025	.171	.087	.025	.165	.085	.025	
9.0	.175	.085	.024	.172	.084	.024	.166	.082	.023	.161	.081	.023	.156	.079	.023	
10.0	.164	.079	.022	.162	.078	.022	.156	.077	.022	.152	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.202	.202	.202	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.192	.168	.146	.164	.144	.125	.112	.099	.087	.065	.057	.050	.021	.018	.016	
2.0	.184	.143	.109	.158	.123	.094	.108	.085	.066	.062	.050	.039	.020	.016	.013	
3.0	.176	.126	.086	.151	.109	.074	.104	.075	.052	.060	.044	.031	.019	.014	.010	
4.0	.169	.113	.070	.145	.097	.061	.100	.068	.043	.058	.040	.025	.019	.013	.008	
5.0	.162	.102	.059	.139	.089	.051	.096	.062	.036	.055	.036	.021	.018	.012	.007	
6.0	.154	.094	.051	.133	.081	.044	.092	.057	.031	.053	.034	.019	.017	.011	.006	
7.0	.148	.087	.045	.127	.076	.039	.088	.053	.028	.051	.031	.016	.016	.010	.005	
8.0	.141	.081	.040	.121	.071	.035	.084	.050	.025	.049	.029	.015	.016	.010	.005	
9.0	.135	.076	.037	.116	.066	.032	.081	.047	.023	.047	.028	.014	.015	.009	.005	
10.0	.129	.072	.034	.111	.063	.030	.077	.044	.021	.045	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:48.00V I:0.0700A P:3.360W PF:1.000 Freq:0Hz Lamp Flux:332.057x1 lm										
NAME: DS8724810NO					TYPE:			WEIGHT:		
SPEC.:DS8724810NO-9NWDA012WC0100					DIM.: 1000*10*1.5			SERIAL No.:		
MFR.: COLORS					SUR.:1000*10			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.0	26.5	25.3	26.7	26.9	25.1	26.6	25.4	26.8	27.1
3H	26.5	27.9	26.8	28.1	28.4	26.6	28.0	27.0	28.3	28.6
4H	27.0	28.4	27.4	28.6	28.9	27.2	28.6	27.6	28.9	29.1
6H	27.4	28.6	27.7	28.9	29.2	27.6	28.9	28.0	29.2	29.5
8H	27.5	28.7	27.8	29.0	29.3	27.8	29.0	28.1	29.3	29.6
12H	27.5	28.6	27.9	29.0	29.3	27.8	29.0	28.2	29.3	29.6
4H 2H	25.6	26.9	25.9	27.2	27.5	25.7	27.0	26.0	27.3	27.6
3H	27.3	28.4	27.7	28.8	29.1	27.4	28.6	27.8	28.9	29.3
4H	28.0	29.0	28.4	29.4	29.7	28.2	29.2	28.6	29.6	29.9
6H	28.4	29.4	28.8	29.7	30.1	28.7	29.6	29.1	30.0	30.4
8H	28.5	29.4	29.0	29.8	30.2	28.8	29.7	29.3	30.1	30.5
12H	28.6	29.4	29.1	29.8	30.3	28.9	29.7	29.4	30.1	30.6
8H 4H	28.2	29.1	28.7	29.5	29.9	28.4	29.3	28.8	29.7	30.1
6H	28.8	29.5	29.3	30.0	30.4	29.1	29.8	29.5	30.2	30.7
8H	29.0	29.7	29.5	30.1	30.6	29.3	29.9	29.8	30.4	30.9
12H	29.1	29.7	29.6	30.2	30.7	29.4	30.0	29.9	30.5	31.0
12H 4H	28.2	29.0	28.7	29.4	29.9	28.4	29.2	28.9	29.6	30.1
6H	28.9	29.5	29.3	30.0	30.4	29.1	29.7	29.6	30.2	30.7
8H	29.1	29.7	29.6	30.1	30.6	29.4	29.9	29.9	30.4	30.9
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.2					+ 0.1 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.3				

CIE Pub.117, 332.1 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -3.8)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:48.00V I:0.0700A P:3.360W PF:1.000 Freq:0Hz Lamp Flux:332.057x1 lm		
NAME: DS8724810NO	TYPE:	WEIGHT:
SPEC.:DS8724810NO-9NWCDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	45	38	56	44	37	54	44	37	31
0.80	66	55	47	65	54	47	63	53	47	39
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	81	71	64	78	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	82	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	102	95	89	99	93	88	95	90	85	77
4.00	106	100	95	103	98	94	99	94	91	81
5.00	108	103	99	106	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:48.00V I:0.0700A P:3.360W PF:1.000 Freq:0Hz Lamp Flux:332.057x1 lm		
NAME: DS8724810NO	TYPE:	WEIGHT:
SPEC.:DS8724810NO-9NWCDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-08

deg Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:48.00V I:0.0700A P:3.360W PF:1.000 Freq:0Hz Lamp Flux:332.057x1 lm		
NAME: DS8724810NO	TYPE:	WEIGHT:
SPEC.:DS8724810NO-9NWCDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Flux out:250.6 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:48.00V I:0.0700A P:3.360W PF:1.000 Freq:0Hz Lamp Flux:332.057x1 lm		
NAME: DS8724810NO	TYPE:	WEIGHT:
SPEC.:DS8724810NO-9NWDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:48.00V I:0.0700A P:3.360W PF:1.000 Freq:0Hz Lamp Flux:332.057x1 lm		
NAME: DS8724810NO	TYPE:	WEIGHT:
SPEC.:DS8724810NO-9NWCDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	9964
L_0~180(75)av	8523
L_0~180(85)av	5719
L_90~270(65)av	10069
L_90~270(75)av	8626
L_90~270(85)av	5477
L_45(65)av	10049
L_45(75)av	8615
L_45(85)av	5777

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-07-08

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:48.00V I:0.0700A P:3.360W PF:1.000 Freq:0Hz Lamp Flux:332.057x1 lm		
NAME: DS8724810NO	TYPE:	WEIGHT:
SPEC.:DS8724810NO-9NWCDA012WC0100	DIM.: 1000*10*1.5	SERIAL No.:
MFR.: COLORS	SUR.:1000*10	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	109	109	109	109	109	109	109	109										
5	109	109	109	109	108	108	108	109										
10	108	108	108	108	107	107	107	107										
15	106	106	106	106	105	105	105	105										
20	103	104	103	103	102	102	102	103										
25	99.5	100	99.9	99.6	98.6	98.3	98.5	98.9										
30	95.1	96.0	95.7	95.3	94.2	93.8	94.0	94.4										
35	89.8	90.9	90.6	90.3	89.0	88.5	88.8	89.1										
40	83.8	85.0	84.8	84.4	83.0	82.4	82.7	83.0										
45	76.9	78.3	78.1	77.8	76.2	75.6	75.9	76.1										
50	69.2	70.6	70.6	70.3	68.7	68.1	68.3	68.4										
55	60.8	62.3	62.3	62.2	60.6	59.9	60.0	60.0										
60	51.6	53.1	53.3	53.3	51.8	51.0	51.0	50.8										
65	41.8	43.5	43.7	43.8	42.4	41.5	41.4	41.1										
70	31.7	33.2	33.6	33.8	32.6	31.7	31.4	31.0										
75	21.4	22.8	23.3	23.7	22.7	21.8	21.3	20.9										
80	11.9	13.1	13.4	14.0	13.3	12.5	11.6	11.4										
85	4.43	5.27	5.39	5.89	5.54	4.95	4.16	4.03										
90	0.90	0.93	0.51	1.30	1.15	0.99	0.31	0.56										
95	0.35	0.35	0.37	0.34	0.22	0.25	0.15	0.17										
100	0.32	0.39	0.36	0.37	0.25	0.21	0.26	0.21										
105	0.42	0.48	0.40	0.45	0.36	0.30	0.39	0.31										
110	0.58	0.60	0.52	0.55	0.49	0.41	0.52	0.41										
115	0.70	0.73	0.66	0.66	0.61	0.53	0.63	0.52										
120	0.82	0.87	0.82	0.77	0.72	0.63	0.72	0.61										
125	0.93	0.98	0.92	0.88	0.83	0.79	0.81	0.71										
130	1.05	1.08	1.03	0.98	0.94	0.86	0.89	0.82										
135	1.15	1.16	1.07	1.08	1.04	1.01	0.96	0.86										
140	1.26	1.21	1.14	1.18	1.13	1.08	1.02	0.94										
145	1.32	1.26	1.21	1.28	1.18	1.23	1.08	0.97										
150	1.37	1.30	1.26	1.36	1.25	1.28	1.18	1.04										
155	1.48	1.34	1.35	1.46	1.33	1.38	1.32	1.07										
160	1.52	1.39	1.44	1.54	1.41	1.47	1.44	1.18										
165	1.59	1.45	1.56	1.60	1.48	1.55	1.56	1.36										
170	1.68	1.57	1.68	1.70	1.46	1.66	1.68	1.52										
175	1.60	1.72	1.78	1.79	1.49	1.72	1.79	1.70										
180	1.60	1.80	1.86	1.88	1.58	1.80	1.88	1.88										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-08

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: