


## LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:48.00V I:0.4100A P:19.68W PF:1.000 Freq:0Hz Lamp Flux:2196.75x1 lm		
NAME: DS81504810NO	TYPE:	WEIGHT:
SPEC.:DS81504810NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 111.62 lm/W			
MODEL	DS81504810NO	I <sub>max</sub> (cd)	726.8	S/MH(C0/180)	1.31
NOMINAL POWER(W)	20	LOR(%)	100.0	S/MH(C90/270)	1.28
RATED VOLTAGE(V)	48	TOTAL FLUX(lm)	2196.7	h UP,DN(C0-180)	0.9,49.8
NOMINAL FLUX(lm)	2196.75	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,48.5
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	48	h down(%)	98.4	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-08-06

g Range: 0 - 180DEG  
 Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	720.7	720.4	714.4	709.5	710.1	711.3	713.1	715.2	0- 10	68.69	68.69	3.13,3.13
20	692.9	691.7	682.5	674.7	672.7	674.3	680.2	685.2	10- 20	197.9	266.6	12.1,12.1
30	642.9	641.0	629.0	619.0	614.4	616.7	626.0	633.7	20- 30	303.2	569.7	25.9,25.9
40	570.3	567.8	554.2	542.9	536.3	538.9	550.9	560.5	30- 40	370.9	940.7	42.8,42.8
50	475.5	472.7	458.1	446.9	439.0	441.5	455.5	465.8	40- 50	391.2	1332	60.6,60.6
60	360.8	354.9	342.4	329.9	321.7	326.5	338.8	352.1	50- 60	358.1	1690	76.9,76.9
70	230.1	223.6	210.7	202.1	195.4	197.7	210.4	223.2	60- 70	274.3	1964	89.4,89.4
80	98.20	89.61	80.69	78.55	76.33	75.39	84.07	94.00	70- 80	154.0	2118	96.4,96.4
90	16.38	11.08	3.525	7.182	5.862	5.856	1.548	12.22	80- 90	42.72	2161	98.4,98.4
100	3.076	2.554	2.471	2.819	2.048	1.796	1.585	1.595	90-100	3.937	2165	98.5,98.5
110	3.914	3.924	3.792	4.113	3.862	3.387	3.356	3.123	100-110	3.033	2168	98.7,98.7
120	5.728	5.736	5.719	5.760	5.587	4.878	4.805	4.793	110-120	4.512	2172	98.9,98.9
130	7.341	7.162	7.059	6.994	7.116	6.237	5.932	5.983	120-130	5.442	2178	99.1,99.1
140	8.555	8.176	8.087	8.098	8.338	7.630	6.775	6.699	130-140	5.634	2183	99.4,99.4
150	9.416	8.724	8.701	9.266	9.078	8.950	7.684	7.207	140-150	5.147	2189	99.6,99.6
160	10.37	9.272	9.885	10.29	9.959	10.06	9.499	8.185	150-160	4.217	2193	99.8,99.8
170	11.01	10.49	11.25	11.14	9.998	10.95	10.98	10.38	160-170	2.890	2196	100,100
180	10.66	12.18	12.39	12.50	10.67	12.18	12.40	12.50	170-180	1.061	2197	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-08-06

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:48.00V I:0.4100A P:19.68W PF:1.000 Freq:0Hz Lamp Flux:2196.75x1 lm		
NAME: DS81504810NO	TYPE:	WEIGHT:
SPEC.:DS81504810NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	43167	28955
80	47127	38723
75	52030	46043
70	56070	51339
65	58545	54851
60	60134	57059
55	61112	58462
50	61650	59391
45	61930	59957


C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-08-06

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:48.00V I:0.4100A P:19.68W PF:1.000 Freq:0Hz Lamp Flux:2196.75x1 lm		
NAME: DS81504810NO	TYPE:	WEIGHT:
SPEC.:DS81504810NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.90	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.79	.74	.80	.76	.72	.77	.74	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.61	.68	.63	.59	.57
4.0	.70	.61	.54	.68	.60	.53	.65	.58	.52	.63	.57	.52	.60	.55	.51	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.45	.54	.49	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.39	.36
7.0	.50	.42	.35	.50	.41	.35	.48	.40	.35	.46	.40	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.29
9.0	.42	.34	.28	.41	.34	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.26
10.0	.39	.31	.26	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-08-06

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

## WEC AND CCEC

Test:U:48.00V I:0.4100A P:19.68W PF:1.000 Freq:0Hz Lamp Flux:2196.75x1 lm		
NAME: DS81504810NO	TYPE:	WEIGHT:
SPEC.:DS81504810NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0														
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
rfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.312	.178	.056	.305	.174	.055	.291	.167	.053	.278	.160	.051	.265	.154	.050															
2.0	.294	.161	.049	.287	.158	.049	.274	.153	.047	.263	.147	.046	.252	.143	.045															
3.0	.272	.145	.043	.266	.142	.043	.255	.138	.042	.244	.134	.041	.235	.130	.040															
4.0	.251	.130	.038	.245	.128	.038	.235	.125	.037	.226	.121	.037	.218	.118	.036															
5.0	.232	.118	.034	.227	.116	.034	.218	.114	.033	.210	.111	.033	.202	.108	.032															
6.0	.215	.108	.031	.210	.106	.031	.203	.104	.030	.195	.101	.030	.188	.099	.029															
7.0	.200	.099	.028	.196	.098	.028	.189	.095	.027	.182	.093	.027	.176	.091	.027															
8.0	.186	.091	.026	.183	.090	.025	.177	.088	.025	.171	.086	.025	.165	.085	.025															
9.0	.175	.084	.024	.172	.084	.023	.166	.082	.023	.160	.080	.023	.155	.079	.023															
10.0	.164	.079	.022	.161	.078	.022	.156	.077	.022	.151	.075	.021	.147	.074	.021															

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.203	.203	.203	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.193	.169	.147	.165	.145	.126	.113	.100	.087	.065	.058	.051	.021	.019	.016	
2.0	.185	.145	.110	.159	.124	.095	.109	.086	.067	.063	.050	.039	.020	.016	.013	
3.0	.178	.127	.087	.152	.110	.075	.104	.076	.053	.060	.044	.031	.019	.014	.010	
4.0	.170	.114	.071	.146	.098	.062	.100	.069	.043	.058	.040	.026	.019	.013	.008	
5.0	.163	.103	.060	.140	.089	.052	.096	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.155	.095	.052	.134	.082	.045	.092	.058	.032	.053	.034	.019	.017	.011	.006	
7.0	.149	.088	.046	.128	.076	.040	.088	.054	.028	.051	.032	.017	.017	.010	.006	
8.0	.142	.082	.041	.122	.072	.036	.085	.050	.026	.049	.030	.015	.016	.010	.005	
9.0	.136	.078	.038	.117	.067	.033	.081	.047	.024	.047	.028	.014	.015	.009	.005	
10.0	.130	.073	.035	.112	.064	.031	.078	.045	.022	.045	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-08-06

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## UGR(Unified Glare Rating) Table

Test:U:48.00V I:0.4100A P:19.68W PF:1.000 Freq:0Hz Lamp Flux:2196.75x1 lm											
NAME: DS81504810NO					TYPE:			WEIGHT:			
SPEC.:DS81504810NO-9NWN5A012WC0100					DIM.: 1000*12*1.5			SERIAL No.:01			
MFR.: COLORS					SUR.:1000*12			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	24.6	26.1	24.8	26.3	26.5	24.4	25.9	24.7	26.1	26.3	
	3H	26.2	27.5	26.5	27.8	28.1	25.9	27.3	26.2	27.5	27.8
	4H	26.8	28.1	27.1	28.4	28.7	26.4	27.8	26.8	28.0	28.3
	6H	27.2	28.5	27.6	28.8	29.1	26.8	28.0	27.1	28.3	28.7
	8H	27.4	28.6	27.7	28.9	29.2	26.9	28.1	27.2	28.4	28.7
	12H	27.5	28.6	27.8	28.9	29.3	26.9	28.1	27.3	28.4	28.7
4H	2H	25.2	26.5	25.5	26.8	27.1	25.0	26.3	25.4	26.6	26.9
	3H	26.9	28.1	27.3	28.4	28.8	26.7	27.9	27.1	28.2	28.5
	4H	27.7	28.7	28.1	29.1	29.5	27.4	28.4	27.8	28.8	29.2
	6H	28.2	29.2	28.7	29.6	30.0	27.8	28.8	28.3	29.2	29.6
	8H	28.4	29.3	28.9	29.7	30.1	28.0	28.9	28.4	29.3	29.7
	12H	28.6	29.4	29.0	29.8	30.2	28.1	28.9	28.5	29.3	29.7
8H	4H	27.9	28.8	28.3	29.2	29.6	27.6	28.5	28.1	28.9	29.3
	6H	28.6	29.3	29.1	29.8	30.2	28.3	29.0	28.7	29.4	29.9
	8H	28.9	29.5	29.4	30.0	30.5	28.5	29.1	29.0	29.6	30.1
	12H	29.1	29.7	29.6	30.2	30.7	28.6	29.2	29.1	29.6	30.1
12H	4H	27.9	28.7	28.4	29.1	29.6	27.7	28.5	28.1	28.9	29.3
	6H	28.7	29.3	29.2	29.8	30.3	28.3	29.0	28.8	29.4	29.9
	8H	29.0	29.5	29.5	30.0	30.5	28.6	29.1	29.1	29.6	30.1
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.4					

CIE Pub.117, 2197 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 2.7)

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-08-06

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### UTILIZATION FACTORS TABLE

Test:U:48.00V I:0.4100A P:19.68W PF:1.000 Freq:0Hz Lamp Flux:2196.75x1 lm		
NAME: DS81504810NO	TYPE:	WEIGHT:
SPEC.:DS81504810NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	45	38	56	44	38	54	44	37	31
0.80	66	55	47	65	54	47	63	53	47	39
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	81	71	64	78	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	82	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	102	95	89	99	93	88	95	90	85	76
4.00	106	100	95	103	98	94	99	94	91	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-08-06

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## ISOCANDELA DIAGRAM

Test:U:48.00V I:0.4100A P:19.68W PF:1.000 Freq:0Hz Lamp Flux:2196.75x1 lm		
NAME: DS81504810NO	TYPE:	WEIGHT:
SPEC.:DS81504810NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-08-06


Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:48.00V I:0.4100A P:19.68W PF:1.000 Freq:0Hz Lamp Flux:2196.75x1 lm		
NAME: DS81504810NO	TYPE:	WEIGHT:
SPEC.:DS81504810NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

Flux out:1657 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-08-06

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

# ISOLUX DIAGRAM


Test:U:48.00V I:0.4100A P:19.68W PF:1.000 Freq:0Hz Lamp Flux:2196.75x1 lm		
NAME: DS81504810NO	TYPE:	WEIGHT:
SPEC.:DS81504810NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-08-06

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2020-08-06

Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:48.00V I:0.4100A P:19.68W PF:1.000 Freq:0Hz Lamp Flux:2196.75x1 lm		
NAME: DS81504810NO	TYPE:	WEIGHT:
SPEC.:DS81504810NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

Table--1

UNIT: cd

C(DEC) g (DEC)	0	45	90	135	180	225	270	315										
0	726	726	724	723	726	726	724	723										
5	726	726	722	719	721	721	721	722										
10	721	720	714	709	710	711	713	715										
15	710	709	701	695	694	695	699	703										
20	693	692	682	675	673	674	680	685										
25	671	669	659	650	646	648	656	662										
30	643	641	629	619	614	617	626	634										
35	609	607	594	584	578	580	591	600										
40	570	568	554	543	536	539	551	561										
45	525	523	509	497	490	493	506	516										
50	476	473	458	447	439	441	456	466										
55	421	417	402	389	381	386	399	411										
60	361	355	342	330	322	326	339	352										
65	297	291	278	267	259	264	276	289										
70	230	224	211	202	195	198	210	223										
75	162	153	143	137	133	133	145	156										
80	98.2	89.6	80.7	78.6	76.3	75.4	84.1	94.0										
85	45.1	39.3	30.3	33.1	31.3	31.1	33.5	42.2										
90	16.4	11.1	3.52	7.18	5.86	5.86	1.55	12.2										
95	7.29	4.01	2.53	2.78	1.60	1.44	0.83	3.76										
100	3.08	2.55	2.47	2.82	2.05	1.80	1.59	1.59										
105	3.01	3.10	2.88	3.33	2.94	2.62	2.54	2.34										
110	3.91	3.92	3.79	4.11	3.86	3.39	3.36	3.12										
115	4.84	4.86	4.85	4.99	4.72	4.14	4.14	4.02										
120	5.73	5.74	5.72	5.76	5.59	4.88	4.81	4.79										
125	6.59	6.51	6.42	6.41	6.38	5.54	5.41	5.45										
130	7.34	7.16	7.06	6.99	7.12	6.24	5.93	5.98										
135	8.00	7.73	7.65	7.54	7.78	6.93	6.39	6.41										
140	8.55	8.18	8.09	8.10	8.34	7.63	6.78	6.70										
145	9.02	8.48	8.42	8.66	8.75	8.30	7.12	6.93										
150	9.42	8.72	8.70	9.27	9.08	8.95	7.68	7.21										
155	9.90	8.96	9.18	9.81	9.55	9.58	8.55	7.55										
160	10.4	9.27	9.89	10.3	9.96	10.1	9.50	8.19										
165	10.9	9.73	10.6	10.7	10.3	10.5	10.3	9.20										
170	11.0	10.5	11.3	11.1	10.00	10.9	11.0	10.4										
175	10.5	11.4	11.9	11.8	9.84	11.5	11.7	11.5										
180	10.7	12.2	12.4	12.5	10.7	12.2	12.4	12.5										

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-08-06

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks: