


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3639.9x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-8NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 126.39 lm/W			
MODEL	DS82404812NO	I _{max} (cd)	1196	S/MH(C0/180)	1.30
NOMINAL POWER(W)	30	LOR(%)	100.0	S/MH(C90/270)	1.30
RATED VOLTAGE(V)	48	TOTAL FLUX(lm)	3639.9	h UP,DN(C0-180)	0.8,49.3
NOMINAL FLUX(lm)	3639.9	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,49.2
LAMPS INSIDE	1	h up(%)	1.5	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	48	h down(%)	98.5	CIBSE SHR MAX	1.50

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-07-31

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	1183	1181	1176	1172	1178	1175	1174	1172	0- 10	113.0	113.0	3.11,3.11
20	1134	1133	1127	1123	1126	1123	1124	1122	10- 20	326.5	439.5	12.1,12.1
30	1048	1049	1043	1041	1041	1037	1038	1035	20- 30	501.9	941.4	25.9,25.9
40	923.1	927.0	922.6	923.3	920.6	916.5	916.9	911.5	30- 40	616.4	1558	42.8,42.8
50	760.7	767.4	766.2	771.4	766.8	761.8	760.0	750.7	40- 50	652.4	2210	60.7,60.7
60	562.6	572.3	575.2	586.2	581.6	575.4	569.4	555.1	50- 60	599.7	2810	77.2,77.2
70	337.5	345.6	355.8	369.7	366.5	361.6	349.1	333.0	60- 70	459.4	3269	89.8,89.8
80	116.9	119.8	134.4	152.6	151.9	145.7	135.5	117.5	70- 80	253.5	3523	96.8,96.8
90	4.250	5.834	5.692	12.09	9.989	9.573	3.009	2.804	80- 90	62.38	3585	98.5,98.5
100	4.068	4.167	3.807	3.722	2.533	2.401	2.457	2.832	90-100	3.447	3589	98.6,98.6
110	7.007	6.569	6.485	5.739	5.167	4.882	5.451	5.304	100-110	4.725	3593	98.7,98.7
120	9.831	9.527	9.597	8.261	7.796	7.454	7.835	7.649	110-120	7.117	3600	98.9,98.9
130	12.28	11.73	11.98	10.54	10.24	9.987	9.775	9.558	120-130	8.649	3609	99.2,99.2
140	14.29	13.16	13.53	12.76	12.24	12.44	11.20	10.85	130-140	9.042	3618	99.4,99.4
150	15.67	14.02	14.53	14.97	13.60	14.82	12.96	11.81	140-150	8.332	3626	99.6,99.6
160	17.28	14.99	16.75	16.94	15.44	16.90	15.92	13.64	150-160	6.913	3633	99.8,99.8
170	18.11	17.38	18.97	18.66	16.34	18.58	18.57	17.26	160-170	4.793	3638	100,100
180	17.71	20.64	20.81	20.95	17.71	20.61	20.83	20.95	170-180	1.776	3640	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3639.9x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-8NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	33889	47005
80	56100	64522
75	71753	78132
70	82224	86689
65	89180	92299
60	93772	95869
55	96759	98030
50	98615	99338
45	99770	100057


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3639.9x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-8NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.94	.97	.93	.90	.92	.90	.87	.89	.86	.84	.82
2.0	.90	.83	.77	.88	.82	.76	.84	.79	.74	.81	.76	.72	.77	.74	.70	.68
3.0	.79	.71	.64	.77	.69	.63	.74	.67	.62	.71	.65	.61	.68	.63	.59	.57
4.0	.70	.61	.54	.68	.60	.53	.65	.58	.53	.63	.57	.52	.61	.55	.51	.49
5.0	.62	.53	.46	.61	.52	.46	.59	.51	.45	.56	.50	.45	.54	.49	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.39	.36
7.0	.50	.42	.35	.50	.41	.35	.48	.40	.35	.46	.40	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.29
9.0	.42	.34	.28	.41	.34	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.26
10.0	.39	.31	.26	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-07-31

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3639.9x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-8NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.310	.176	.056	.303	.173	.055	.289	.166	.053	.276	.159	.051	.264	.153	.049	
2.0	.293	.161	.049	.286	.158	.049	.274	.152	.047	.262	.147	.046	.252	.142	.045	
3.0	.271	.144	.043	.265	.142	.043	.254	.138	.042	.244	.134	.041	.235	.130	.040	
4.0	.251	.130	.038	.245	.128	.038	.235	.125	.037	.226	.121	.037	.218	.118	.036	
5.0	.232	.118	.034	.227	.117	.034	.218	.114	.033	.210	.111	.033	.202	.108	.032	
6.0	.215	.108	.031	.211	.106	.031	.203	.104	.030	.195	.102	.030	.188	.099	.029	
7.0	.200	.099	.028	.196	.098	.028	.189	.096	.028	.182	.094	.027	.176	.092	.027	
8.0	.187	.091	.026	.183	.090	.025	.177	.088	.025	.171	.087	.025	.165	.085	.025	
9.0	.175	.085	.024	.172	.084	.023	.166	.082	.023	.161	.081	.023	.156	.079	.023	
10.0	.164	.079	.022	.162	.078	.022	.156	.077	.022	.151	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.202	.202	.202	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.192	.168	.146	.164	.144	.126	.112	.099	.087	.065	.057	.050	.021	.018	.016	
2.0	.184	.144	.110	.158	.124	.095	.108	.085	.066	.062	.050	.039	.020	.016	.013	
3.0	.176	.126	.086	.151	.109	.074	.104	.076	.052	.060	.044	.031	.019	.014	.010	
4.0	.169	.113	.070	.145	.097	.061	.100	.068	.043	.058	.040	.025	.019	.013	.008	
5.0	.162	.102	.059	.139	.089	.051	.096	.062	.036	.055	.036	.021	.018	.012	.007	
6.0	.154	.094	.051	.133	.082	.044	.092	.057	.031	.053	.034	.019	.017	.011	.006	
7.0	.148	.087	.045	.127	.076	.039	.088	.053	.028	.051	.031	.017	.016	.010	.005	
8.0	.141	.081	.040	.122	.071	.035	.084	.050	.025	.049	.029	.015	.016	.010	.005	
9.0	.135	.077	.037	.116	.066	.032	.081	.047	.023	.047	.028	.014	.015	.009	.005	
10.0	.129	.072	.034	.112	.063	.030	.077	.044	.021	.045	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3639.9x1 lm											
NAME: DS82404812NO					TYPE:			WEIGHT:			
SPEC.:DS82404812NO-8NWN5A012WC0100					DIM.: 1000*12*1.5			SERIAL No.:01			
MFR.: COLORS					SUR.:1000*12			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	24.3	25.8	24.6	26.0	26.3	24.3	25.9	24.6	26.1	26.3	
	3H	25.7	27.1	26.0	27.4	27.6	25.9	27.3	26.2	27.5	27.8
	4H	26.2	27.6	26.6	27.8	28.1	26.4	27.7	26.8	28.0	28.3
	6H	26.5	27.8	26.9	28.1	28.4	26.8	28.0	27.1	28.3	28.6
	8H	26.6	27.8	26.9	28.1	28.4	26.9	28.1	27.2	28.4	28.7
	12H	26.6	27.7	26.9	28.1	28.4	26.9	28.0	27.3	28.4	28.7
4H	2H	24.9	26.2	25.2	26.5	26.8	24.9	26.3	25.3	26.6	26.8
	3H	26.5	27.7	26.9	28.0	28.3	26.6	27.8	27.0	28.1	28.4
	4H	27.1	28.2	27.5	28.5	28.9	27.3	28.3	27.7	28.7	29.1
	6H	27.5	28.4	27.9	28.8	29.2	27.7	28.7	28.2	29.1	29.5
	8H	27.6	28.5	28.0	28.9	29.3	27.9	28.7	28.3	29.1	29.5
	12H	27.6	28.4	28.1	28.8	29.3	27.9	28.7	28.4	29.1	29.6
8H	4H	27.3	28.2	27.8	28.6	29.0	27.5	28.4	27.9	28.7	29.2
	6H	27.8	28.5	28.3	29.0	29.4	28.0	28.8	28.5	29.2	29.7
	8H	28.0	28.6	28.5	29.1	29.5	28.2	28.9	28.7	29.3	29.8
	12H	28.0	28.6	28.5	29.1	29.6	28.4	28.9	28.9	29.4	29.9
12H	4H	27.3	28.1	27.8	28.5	29.0	27.5	28.3	27.9	28.7	29.1
	6H	27.9	28.5	28.3	28.9	29.4	28.1	28.7	28.5	29.2	29.6
	8H	28.0	28.6	28.5	29.1	29.6	28.3	28.8	28.8	29.3	29.8
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 3640 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 4.5$)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3639.9x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-8NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	45	38	56	44	37	54	44	37	31
0.80	66	55	47	65	54	47	63	53	47	39
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	72	64	81	71	64	78	69	63	55
1.50	87	77	70	85	76	70	82	74	68	60
2.00	94	86	79	92	84	78	89	82	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	102	95	89	99	93	88	95	90	86	77
4.00	106	100	95	103	98	94	99	94	91	82
5.00	108	103	99	106	101	97	101	97	94	85
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3639.9x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-8NWSA012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-31

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3639.9x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-8NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

Flux out:2755 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3639.9x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-8NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-07-31

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3639.9x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-8NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	1195	1193	1190	1187	1195	1193	1190	1187										
5	1194	1191	1187	1183	1190	1188	1186	1184										
10	1183	1181	1176	1172	1178	1175	1174	1172										
15	1163	1161	1156	1152	1157	1153	1153	1152										
20	1134	1133	1127	1123	1126	1123	1124	1122										
25	1095	1096	1090	1087	1088	1084	1086	1083										
30	1048	1049	1043	1041	1041	1037	1038	1035										
35	990	993	987	986	985	981	982	978										
40	923	927	923	923	921	917	917	912										
45	847	852	849	852	848	844	843	836										
50	761	767	766	771	767	762	760	751										
55	666	674	675	683	678	672	669	657										
60	563	572	575	586	582	575	569	555										
65	452	463	468	482	478	471	463	446										
70	337	346	356	370	366	362	349	333										
75	223	224	243	258	257	251	238	220										
80	117	120	134	153	152	146	136	117										
85	35.4	43.0	49.2	65.6	63.0	60.7	51.6	37.7										
90	4.25	5.83	5.69	12.1	9.99	9.57	3.01	2.80										
95	3.33	3.57	3.72	3.64	1.90	1.80	1.31	1.73										
100	4.07	4.17	3.81	3.72	2.53	2.40	2.46	2.83										
105	5.47	5.22	4.84	4.59	3.82	3.60	4.02	4.07										
110	7.01	6.57	6.48	5.74	5.17	4.88	5.45	5.30										
115	8.42	8.05	8.17	7.06	6.46	6.17	6.68	6.54										
120	9.83	9.53	9.60	8.26	7.80	7.45	7.84	7.65										
125	11.1	10.8	10.8	9.43	9.05	8.71	8.84	8.61										
130	12.3	11.7	12.0	10.5	10.2	9.99	9.77	9.56										
135	13.3	12.5	12.9	11.7	11.3	11.2	10.6	10.3										
140	14.3	13.2	13.5	12.8	12.2	12.4	11.2	10.9										
145	15.0	13.6	14.0	13.9	13.0	13.6	11.9	11.3										
150	15.7	14.0	14.5	15.0	13.6	14.8	13.0	11.8										
155	16.5	14.4	15.5	16.0	14.5	16.0	14.5	12.5										
160	17.3	15.0	16.7	16.9	15.4	16.9	15.9	13.6										
165	18.1	15.8	17.9	17.8	16.3	17.7	17.2	15.4										
170	18.1	17.4	19.0	18.7	16.3	18.6	18.6	17.3										
175	17.3	19.1	20.1	19.8	16.4	19.6	19.8	19.2										
180	17.7	20.6	20.8	20.9	17.7	20.6	20.8	21.0										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-07-31

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: