


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3202.72x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 111.21 lm/W			
MODEL	DS82404812NO	I _{max} (cd)	1061	S/MH(C0/180)	1.29
NOMINAL POWER(W)	30	LOR(%)	100.0	S/MH(C90/270)	1.29
RATED VOLTAGE(V)	48	TOTAL FLUX(lm)	3202.7	h UP,DN(C0-180)	0.9,49.0
NOMINAL FLUX(lm)	3202.72	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.7,49.4
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	48	h down(%)	98.4	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-06

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	1048	1047	1041	1039	1042	1043	1043	1042	0- 10	100.3	100.3	3.13,3.13
20	1003	1001	993.4	990.6	991.6	993.6	996.2	995.0	10- 20	289.0	389.3	12.2,12.2
30	924.5	922.6	913.8	911.6	911.2	913.9	918.3	916.4	20- 30	442.6	831.9	26,26
40	813.6	811.6	803.3	803.1	801.6	805.0	810.0	806.6	30- 40	541.5	1373	42.9,42.9
50	670.4	668.6	662.1	664.8	663.3	666.7	671.6	665.5	40- 50	570.8	1944	60.7,60.7
60	497.6	497.0	492.1	499.7	499.2	502.9	506.3	496.7	50- 60	523.2	2467	77,77
70	304.6	299.9	296.8	309.9	312.2	317.9	316.3	305.7	60- 70	400.3	2868	89.5,89.5
80	117.0	108.4	106.5	125.3	129.7	132.0	130.3	119.2	70- 80	223.7	3091	96.5,96.5
90	11.21	8.608	4.138	13.37	15.57	14.27	2.780	9.370	80- 90	59.87	3151	98.4,98.4
100	3.746	3.990	3.600	3.931	2.653	2.412	2.274	2.629	90-100	4.542	3156	98.5,98.5
110	6.165	6.136	5.684	5.730	5.240	4.629	4.872	4.866	100-110	4.437	3160	98.7,98.7
120	8.826	8.728	8.490	8.150	7.759	6.808	6.937	7.353	110-120	6.621	3167	98.9,98.9
130	11.12	10.75	10.46	10.03	10.10	8.902	8.580	9.083	120-130	7.987	3175	99.1,99.1
140	12.81	12.16	11.95	11.65	12.00	11.04	9.835	10.12	130-140	8.272	3183	99.4,99.4
150	13.97	12.90	12.81	13.36	13.12	13.02	11.22	10.77	140-150	7.554	3191	99.6,99.6
160	15.27	13.60	14.50	14.95	14.44	14.71	13.95	12.17	150-160	6.178	3197	99.8,99.8
170	16.06	15.55	16.54	16.30	14.63	16.12	16.21	15.32	160-170	4.240	3201	100,100
180	15.48	18.05	18.17	18.35	15.52	18.05	18.25	18.26	170-180	1.561	3203	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-06

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3202.72x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	45287	34247
80	56128	51094
75	66742	63393
70	74215	72314
65	79337	78090
60	82933	82021
55	85368	84312
50	86917	85831
45	87860	86771


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-06

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3202.72x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.90	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.82	.76	.84	.79	.74	.81	.76	.72	.77	.74	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.61	.68	.63	.59	.57
4.0	.70	.61	.54	.68	.60	.53	.65	.58	.53	.63	.57	.52	.61	.55	.51	.49
5.0	.62	.53	.46	.61	.52	.46	.59	.51	.45	.56	.50	.45	.54	.49	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.40	.51	.44	.39	.49	.43	.39	.36
7.0	.50	.42	.35	.50	.41	.35	.48	.40	.35	.46	.40	.35	.45	.39	.34	.32
8.0	.46	.37	.32	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.31	.29
9.0	.42	.34	.28	.42	.34	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.26
10.0	.39	.31	.26	.38	.31	.26	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-08-06

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3202.72x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0														
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
rfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.311	.177	.056	.304	.173	.055	.290	.166	.053	.277	.160	.051	.265	.153	.049															
2.0	.293	.161	.049	.287	.158	.049	.274	.152	.047	.262	.147	.046	.252	.142	.045															
3.0	.271	.144	.043	.265	.142	.043	.254	.138	.042	.244	.134	.041	.234	.130	.040															
4.0	.250	.130	.038	.245	.128	.038	.235	.125	.037	.226	.121	.037	.217	.118	.036															
5.0	.231	.118	.034	.227	.116	.034	.218	.113	.033	.210	.111	.033	.202	.108	.032															
6.0	.215	.108	.031	.210	.106	.031	.202	.104	.030	.195	.101	.030	.188	.099	.029															
7.0	.200	.099	.028	.196	.098	.028	.189	.095	.027	.182	.093	.027	.176	.091	.027															
8.0	.186	.091	.026	.183	.090	.025	.177	.088	.025	.171	.086	.025	.165	.085	.025															
9.0	.175	.084	.024	.172	.084	.023	.166	.082	.023	.160	.080	.023	.155	.079	.023															
10.0	.164	.079	.022	.161	.078	.022	.156	.077	.022	.151	.075	.021	.147	.074	.021															

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.203	.203	.203	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.193	.168	.147	.165	.145	.126	.113	.099	.087	.065	.058	.051	.021	.019	.016	
2.0	.185	.144	.110	.158	.124	.095	.109	.086	.066	.063	.050	.039	.020	.016	.013	
3.0	.177	.127	.087	.152	.109	.075	.104	.076	.053	.060	.044	.031	.019	.014	.010	
4.0	.170	.114	.071	.146	.098	.061	.100	.068	.043	.058	.040	.026	.019	.013	.008	
5.0	.162	.103	.060	.139	.089	.052	.096	.062	.037	.056	.037	.022	.018	.012	.007	
6.0	.155	.095	.052	.133	.082	.045	.092	.058	.032	.053	.034	.019	.017	.011	.006	
7.0	.148	.088	.046	.128	.076	.040	.088	.053	.028	.051	.032	.017	.017	.010	.006	
8.0	.142	.082	.041	.122	.071	.036	.085	.050	.026	.049	.030	.015	.016	.010	.005	
9.0	.136	.077	.038	.117	.067	.033	.081	.047	.023	.047	.028	.014	.015	.009	.005	
10.0	.130	.073	.035	.112	.063	.031	.078	.045	.022	.045	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-06

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3202.72x1 lm											
NAME: DS82404812NO					TYPE:			WEIGHT:			
SPEC.:DS82404812NO-9NWN5A012WC0100					DIM.: 1000*12*1.5			SERIAL No.:01			
MFR.: COLORS					SUR.:1000*12			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	24.3	25.8	24.6	26.0	26.2	24.2	25.7	24.5	26.0	26.2	
	3H	25.7	27.1	26.1	27.4	27.7	25.7	27.1	26.0	27.3	27.6
	4H	26.3	27.6	26.6	27.9	28.2	26.2	27.5	26.5	27.8	28.1
	6H	26.6	27.9	27.0	28.2	28.5	26.5	27.7	26.9	28.0	28.4
	8H	26.7	27.9	27.1	28.3	28.6	26.6	27.8	26.9	28.1	28.4
	12H	26.8	27.9	27.2	28.3	28.6	26.6	27.7	27.0	28.1	28.4
4H	2H	24.9	26.2	25.2	26.5	26.8	24.8	26.1	25.2	26.4	26.7
	3H	26.5	27.7	26.9	28.0	28.3	26.4	27.6	26.8	27.9	28.3
	4H	27.2	28.2	27.6	28.6	28.9	27.1	28.1	27.5	28.5	28.8
	6H	27.6	28.6	28.0	28.9	29.3	27.5	28.4	27.9	28.8	29.2
	8H	27.8	28.6	28.2	29.0	29.5	27.6	28.5	28.0	28.9	29.3
	12H	27.8	28.6	28.3	29.1	29.5	27.6	28.4	28.1	28.9	29.3
8H	4H	27.4	28.3	27.8	28.7	29.1	27.3	28.2	27.7	28.6	29.0
	6H	28.0	28.7	28.4	29.1	29.6	27.8	28.5	28.3	29.0	29.4
	8H	28.2	28.8	28.6	29.3	29.7	28.0	28.6	28.5	29.1	29.6
	12H	28.3	28.9	28.8	29.3	29.8	28.1	28.6	28.6	29.1	29.6
12H	4H	27.4	28.2	27.8	28.6	29.0	27.3	28.1	27.7	28.5	28.9
	6H	28.0	28.6	28.5	29.1	29.6	27.9	28.5	28.3	29.0	29.4
	8H	28.2	28.8	28.7	29.2	29.8	28.1	28.6	28.6	29.1	29.6
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2				+ 0.2 / - 0.2						
1.5H	+ 0.2 / - 0.3				+ 0.2 / - 0.3						
2.0H	+ 0.2 / - 0.3				+ 0.2 / - 0.3						

CIE Pub.117, 3203 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 4.0)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-06

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3202.72x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	45	38	56	44	38	54	44	37	31
0.80	67	55	47	65	54	47	63	53	47	40
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	81	71	64	78	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	82	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	102	95	89	99	93	88	95	90	85	76
4.00	106	100	95	103	98	94	99	94	91	81
5.00	108	103	99	106	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-06

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3202.72x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-06

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3202.72x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

Flux out:2419 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-06

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3202.72x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-06

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-08-06

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:48.00V I:0.6000A P:28.80W PF:1.000 Freq:0Hz Lamp Flux:3202.72x1 lm		
NAME: DS82404812NO	TYPE:	WEIGHT:
SPEC.:DS82404812NO-9NWN5A012WC0100	DIM.: 1000*12*1.5	SERIAL No.:01
MFR.: COLORS	SUR.:1000*12	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	1061	1060	1057	1056	1061	1060	1057	1056										
5	1058	1058	1053	1051	1055	1055	1054	1053										
10	1048	1047	1041	1039	1042	1043	1043	1042										
15	1030	1028	1021	1019	1021	1022	1023	1022										
20	1003	1001	993	991	992	994	996	995										
25	968	966	958	955	955	958	961	960										
30	925	923	914	912	911	914	918	916										
35	873	871	863	861	860	863	868	866										
40	814	812	803	803	802	805	810	807										
45	746	744	736	737	736	739	744	740										
50	670	669	662	665	663	667	672	665										
55	588	586	580	585	584	588	592	584										
60	498	497	492	500	499	503	506	497										
65	402	400	396	406	408	413	413	403										
70	305	300	297	310	312	318	316	306										
75	207	201	197	214	218	222	220	209										
80	117	108	106	125	130	132	130	119										
85	47.4	40.9	35.8	54.2	57.5	58.6	54.3	48.4										
90	11.2	8.61	4.14	13.4	15.6	14.3	2.78	9.37										
95	3.58	3.69	3.64	4.55	3.74	2.78	1.18	2.15										
100	3.75	3.99	3.60	3.93	2.65	2.41	2.27	2.63										
105	4.82	4.88	4.30	4.64	3.88	3.50	3.65	3.67										
110	6.16	6.14	5.68	5.73	5.24	4.63	4.87	4.87										
115	7.51	7.50	7.22	7.00	6.47	5.73	6.00	6.21										
120	8.83	8.73	8.49	8.15	7.76	6.81	6.94	7.35										
125	10.1	9.83	9.56	9.13	8.95	7.87	7.81	8.30										
130	11.1	10.8	10.5	10.0	10.1	8.90	8.58	9.08										
135	12.0	11.5	11.3	10.8	11.1	9.99	9.27	9.70										
140	12.8	12.2	11.9	11.7	12.0	11.0	9.83	10.1										
145	13.4	12.6	12.5	12.5	12.7	12.1	10.3	10.4										
150	14.0	12.9	12.8	13.4	13.1	13.0	11.2	10.8										
155	14.6	13.2	13.5	14.2	13.8	13.9	12.6	11.2										
160	15.3	13.6	14.5	14.9	14.4	14.7	14.0	12.2										
165	16.0	14.3	15.6	15.6	15.0	15.4	15.1	13.6										
170	16.1	15.6	16.5	16.3	14.6	16.1	16.2	15.3										
175	15.3	17.0	17.5	17.3	14.4	17.0	17.3	17.0										
180	15.5	18.0	18.2	18.3	15.5	18.1	18.2	18.3										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-08-06

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: