


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.4000A P:9.600W PF:1.000 Freq:0Hz Lamp Flux:988.758x1 lm		
NAME: FD1282408NO	TYPE:	WEIGHT:
SPEC.:FD1282408NO-8WWNSA012BC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 103.00 lm/W			
MODEL	FD1282408NO	I _{max} (cd)	254.9	S/MH(C0/180)	1.30
NOMINAL POWER(W)	9.6	LOR(%)	100.0	S/MH(C90/270)	1.31
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	988.76	h UP,DN(C0-180)	2.1,47.8
NOMINAL FLUX(lm)	988.758	CIE CLASS	DIRECT	h UP,DN(C180-360)	2.0,48.1
LAMPS INSIDE	1	h up(%)	4.1	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	h down(%)	95.9	CIBSE SHR MAX	1.50



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-14

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	251.0	248.8	245.4	242.9	252.2	245.8	245.3	246.0	0- 10	23.75	23.75	2.4,2.4
20	240.3	240.3	236.0	232.1	242.7	234.9	235.4	237.4	10- 20	68.69	92.44	9.35,9.35
30	223.0	225.3	220.4	215.6	226.8	217.8	219.1	222.5	20- 30	106.2	198.6	20.1,20.1
40	199.9	204.6	199.0	194.0	205.3	195.2	197.2	201.8	30- 40	132.2	330.8	33.5,33.5
50	173.2	179.6	173.4	168.7	179.5	169.0	171.3	176.9	40- 50	144.5	475.3	48.1,48.1
60	145.3	153.1	145.8	141.7	151.5	141.4	143.9	150.6	50- 60	143.6	619.0	62.6,62.6
70	119.2	127.8	118.7	115.5	125.2	114.8	116.6	125.1	60- 70	132.1	751.0	76,76
80	94.05	107.1	87.51	95.59	100.9	94.04	89.02	103.3	70- 80	114.9	866.0	87.6,87.6
90	59.61	67.34	2.315	57.42	65.16	57.10	8.357	67.02	80- 90	82.51	948.5	95.9,95.9
100	7.428	6.046	2.556	2.971	1.690	1.755	1.470	10.02	90-100	25.14	973.6	98.5,98.5
110	2.732	2.644	2.131	2.631	1.964	1.790	1.904	6.560	100-110	3.344	977.0	98.8,98.8
120	2.645	2.498	2.477	2.438	2.265	2.116	2.165	2.415	110-120	2.547	979.5	99.1,99.1
130	2.979	2.786	2.752	2.686	2.652	2.451	2.453	2.244	120-130	2.231	981.7	99.3,99.3
140	3.313	3.026	3.005	3.013	2.979	2.863	2.672	2.498	130-140	2.149	983.9	99.5,99.5
150	3.536	3.146	3.166	3.367	3.193	3.279	2.920	2.638	140-150	1.903	985.8	99.7,99.7
160	3.832	3.333	3.599	3.734	3.508	3.653	3.507	2.872	150-160	1.534	987.3	99.9,99.9
170	4.001	3.788	4.048	4.055	3.596	3.961	4.035	3.627	160-170	1.042	988.4	100,100
180	3.854	4.462	4.489	4.489	3.881	4.375	4.489	4.469	170-180	0.3832	988.8	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-14

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.4000A P:9.600W PF:1.000 Freq:0Hz Lamp Flux:988.758x1 lm		
NAME: FD1282408NO	TYPE:	WEIGHT:
SPEC.:FD1282408NO-8WWNSA012BC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	112626	79773
80	67704	62994
75	51745	51009
70	43559	43370
65	38921	39011
60	36317	36447
55	34713	34792
50	33684	33716
45	33033	32965


C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2021-01-14

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.4000A P:9.600W PF:1.000 Freq:0Hz Lamp Flux:988.758x1 lm		
NAME: FD1282408NO	TYPE:	WEIGHT:
SPEC.:FD1282408NO-8WWNSA012BC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.03	1.03	1.03	.98	.98	.98	.96
1.0	.98	.92	.87	.95	.90	.85	.90	.86	.82	.85	.82	.79	.81	.78	.75	.73
2.0	.83	.75	.68	.81	.73	.67	.77	.70	.65	.73	.67	.63	.69	.65	.61	.58
3.0	.72	.63	.55	.70	.61	.54	.67	.59	.53	.63	.57	.51	.60	.55	.50	.47
4.0	.63	.53	.46	.62	.52	.45	.59	.51	.44	.56	.49	.43	.53	.47	.42	.40
5.0	.56	.46	.39	.55	.46	.39	.52	.44	.38	.50	.42	.37	.47	.41	.36	.34
6.0	.50	.41	.34	.49	.40	.33	.47	.39	.33	.45	.38	.32	.43	.36	.31	.29
7.0	.45	.36	.29	.44	.36	.29	.42	.34	.29	.41	.33	.28	.39	.33	.28	.25
8.0	.41	.32	.26	.40	.32	.26	.39	.31	.25	.37	.30	.25	.36	.29	.25	.23
9.0	.38	.29	.23	.37	.29	.23	.36	.28	.23	.34	.27	.22	.33	.27	.22	.20
10.0	.35	.27	.21	.34	.26	.21	.33	.26	.21	.32	.25	.20	.30	.24	.20	.18



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-14

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.4000A P:9.600W PF:1.000 Freq:0Hz Lamp Flux:988.758x1 lm		
NAME: FD1282408NO	TYPE:	WEIGHT:
SPEC.:FD1282408NO-8WWNSA012BC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.405	.231	.073	.397	.226	.072	.381	.218	.070	.366	.211	.068	.352	.204	.066	
2.0	.350	.192	.059	.342	.189	.058	.328	.182	.057	.315	.177	.055	.302	.171	.054	
3.0	.310	.165	.049	.303	.162	.049	.290	.157	.048	.278	.152	.047	.267	.148	.046	
4.0	.278	.144	.042	.272	.142	.042	.260	.138	.041	.250	.134	.040	.240	.130	.040	
5.0	.252	.128	.037	.246	.126	.037	.236	.123	.036	.227	.120	.036	.218	.116	.035	
6.0	.230	.115	.033	.225	.114	.033	.216	.111	.032	.208	.108	.032	.200	.105	.031	
7.0	.212	.105	.030	.208	.103	.029	.199	.101	.029	.192	.098	.029	.184	.096	.028	
8.0	.196	.096	.027	.192	.095	.027	.185	.092	.026	.178	.090	.026	.171	.088	.026	
9.0	.183	.088	.025	.179	.087	.024	.172	.085	.024	.166	.083	.024	.160	.081	.023	
10.0	.171	.082	.023	.168	.081	.023	.161	.079	.022	.156	.077	.022	.150	.076	.022	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.222	.222	.222	.189	.189	.189	.129	.129	.129	.074	.074	.074	.024	.024	.024	
1.0	.218	.187	.158	.187	.160	.136	.128	.110	.094	.074	.064	.055	.024	.021	.018	
2.0	.211	.163	.122	.181	.140	.106	.124	.097	.074	.072	.057	.043	.023	.018	.014	
3.0	.204	.146	.100	.175	.126	.087	.120	.088	.061	.069	.051	.036	.022	.017	.012	
4.0	.196	.133	.086	.168	.115	.075	.115	.080	.053	.067	.047	.031	.021	.015	.010	
5.0	.188	.123	.076	.161	.107	.066	.111	.075	.047	.064	.044	.028	.021	.014	.009	
6.0	.180	.115	.069	.155	.100	.060	.107	.070	.042	.062	.041	.025	.020	.013	.008	
7.0	.172	.108	.064	.148	.094	.055	.102	.066	.039	.060	.039	.023	.019	.013	.008	
8.0	.165	.103	.060	.142	.089	.052	.099	.063	.037	.057	.037	.022	.019	.012	.007	
9.0	.159	.098	.056	.137	.085	.049	.095	.060	.035	.055	.035	.021	.018	.012	.007	
10.0	.153	.093	.054	.132	.081	.047	.091	.057	.033	.053	.034	.020	.017	.011	.007	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-14

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.4000A P:9.600W PF:1.000 Freq:0Hz Lamp Flux:988.758x1 lm											
NAME: FD1282408NO					TYPE:			WEIGHT:			
SPEC.:FD1282408NO-8WWNSA012BC0100					DIM.: 1000*8*1.5mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*8mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	25.0	26.6	25.4	26.9	27.2	25.0	26.6	25.4	26.9	27.2	
	3H	27.4	28.9	27.7	29.2	29.5	27.4	28.9	27.7	29.2	29.5
	4H	28.7	30.1	29.0	30.4	30.8	28.6	30.1	29.0	30.4	30.8
	6H	30.1	31.4	30.5	31.8	32.1	29.9	31.3	30.3	31.7	32.0
	8H	30.8	32.1	31.2	32.5	32.9	30.6	31.9	31.0	32.2	32.6
	12H	31.6	32.9	32.0	33.3	33.7	31.1	32.4	31.5	32.8	33.2
4H	2H	25.9	27.3	26.3	27.7	28.0	25.9	27.3	26.3	27.7	28.0
	3H	28.5	29.8	28.9	30.1	30.5	28.5	29.8	28.9	30.1	30.5
	4H	30.0	31.1	30.4	31.5	32.0	29.9	31.1	30.4	31.5	31.9
	6H	31.5	32.6	32.0	33.0	33.5	31.4	32.5	31.9	32.9	33.4
	8H	32.4	33.4	32.9	33.8	34.3	32.2	33.2	32.6	33.6	34.1
	12H	33.3	34.2	33.8	34.7	35.2	32.8	33.7	33.3	34.2	34.7
8H	4H	30.6	31.6	31.1	32.1	32.6	30.6	31.6	31.1	32.0	32.5
	6H	32.5	33.4	33.0	33.9	34.4	32.4	33.3	32.9	33.7	34.3
	8H	33.6	34.3	34.1	34.8	35.4	33.3	34.1	33.9	34.6	35.2
	12H	34.7	35.4	35.3	35.9	36.5	34.2	34.9	34.7	35.4	36.0
12H	4H	30.8	31.7	31.3	32.2	32.7	30.8	31.7	31.3	32.2	32.7
	6H	32.8	33.6	33.3	34.1	34.6	32.7	33.5	33.2	34.0	34.5
	8H	34.0	34.7	34.5	35.2	35.7	33.8	34.4	34.3	35.0	35.5
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 988.8 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.0)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-14

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.4000A P:9.600W PF:1.000 Freq:0Hz Lamp Flux:988.758x1 lm		
NAME: FD1282408NO	TYPE:	WEIGHT:
SPEC.:FD1282408NO-8WWNSA012BC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	51	39	31	51	39	31	49	38	31	24
0.80	61	48	40	59	47	39	57	46	39	31
1.00	68	56	47	67	55	47	64	57	46	38
1.25	75	63	55	74	62	54	71	60	53	45
1.50	80	69	60	79	68	60	75	65	58	49
2.00	88	77	69	86	76	68	81	73	66	57
2.50	92	82	75	90	81	74	85	78	71	61
3.00	96	87	80	93	85	78	88	82	76	66
4.00	101	93	87	98	91	85	93	87	82	71
5.00	103	97	91	101	95	89	95	90	86	75
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-14

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.4000A P:9.600W PF:1.000 Freq:0Hz Lamp Flux:988.758x1 lm		
NAME: FD1282408NO	TYPE:	WEIGHT:
SPEC.:FD1282408NO-8WWNSA012BC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-14

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.4000A P:9.600W PF:1.000 Freq:0Hz Lamp Flux:988.758x1 lm		
NAME: FD1282408NO	TYPE:	WEIGHT:
SPEC.:FD1282408NO-8WWNSA012BC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Flux out:713.1 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-14

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.4000A P:9.600W PF:1.000 Freq:0Hz Lamp Flux:988.758x1 lm		
NAME: FD1282408NO	TYPE:	WEIGHT:
SPEC.:FD1282408NO-8WWNSA012BC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-14

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2021-01-14

deg Range: 0 - 180DEG
deg Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.4000A P:9.600W PF:1.000 Freq:0Hz Lamp Flux:988.758x1 lm		
NAME: FD1282408NO	TYPE:	WEIGHT:
SPEC.:FD1282408NO-8WWNSA012BC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	255	251	249	248	255	251	249	248										
5	254	250	248	246	254	249	248	248										
10	251	249	245	243	252	246	245	246										
15	246	245	242	238	248	241	241	243										
20	240	240	236	232	243	235	235	237										
25	232	234	229	225	236	227	228	231										
30	223	225	220	216	227	218	219	223										
35	212	216	210	205	217	207	209	213										
40	200	205	199	194	205	195	197	202										
45	187	192	186	182	193	182	185	190										
50	173	180	173	169	179	169	171	177										
55	159	166	160	155	166	155	158	164										
60	145	153	146	142	152	141	144	151										
65	132	140	132	128	138	128	130	137										
70	119	128	119	116	125	115	117	125										
75	107	117	106	105	114	104	104	114										
80	94.1	107	87.5	95.6	101	94.0	89.0	103										
85	78.5	91.9	55.6	81.6	85.9	81.5	62.2	88.7										
90	59.6	67.3	2.31	57.4	65.2	57.1	8.36	67.0										
95	35.8	33.1	2.52	14.2	39.8	9.68	1.01	33.2										
100	7.43	6.05	2.56	2.97	1.69	1.76	1.47	10.0										
105	2.77	2.97	2.43	2.79	1.82	1.75	1.74	7.78										
110	2.73	2.64	2.13	2.63	1.96	1.79	1.90	6.56										
115	2.68	2.39	2.32	2.33	2.08	1.92	2.06	5.68										
120	2.64	2.50	2.48	2.44	2.27	2.12	2.16	2.42										
125	2.84	2.64	2.65	2.57	2.48	2.27	2.29	2.10										
130	2.98	2.79	2.75	2.69	2.65	2.45	2.45	2.24										
135	3.17	2.92	2.89	2.83	2.83	2.65	2.59	2.41										
140	3.31	3.03	3.01	3.01	2.98	2.86	2.67	2.50										
145	3.40	3.10	3.07	3.17	3.10	3.09	2.77	2.55										
150	3.54	3.15	3.17	3.37	3.19	3.28	2.92	2.64										
155	3.64	3.23	3.35	3.57	3.36	3.49	3.21	2.74										
160	3.83	3.33	3.60	3.73	3.51	3.65	3.51	2.87										
165	3.93	3.51	3.83	3.87	3.64	3.84	3.79	3.18										
170	4.00	3.79	4.05	4.05	3.60	3.96	4.04	3.63										
175	3.83	4.12	4.26	4.27	3.57	4.15	4.28	4.05										
180	3.85	4.46	4.49	4.49	3.88	4.38	4.49	4.47										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2021-01-14

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: