


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.1966A P:4.718W PF:1.000 Freq:0Hz Lamp Flux:739.212x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-8NWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 156.68 lm/W			
MODEL	D8642408NO	I <sub>max</sub> (cd)	236.5	S/MH(C0/180)	1.30
NOMINAL POWER(W)	4.3	LOR(%)	100.0	S/MH(C90/270)	1.31
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	739.21	h UP,DN(C0-180)	0.9,48.6
NOMINAL FLUX(lm)	739.212	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,49.7
LAMPS INSIDE	1	h up(%)	1.7	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	h down(%)	98.3	CIBSE SHR MAX	1.50



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03

Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	233.1	233.4	233.2	233.8	233.3	233.6	233.6	233.3	0- 10	22.43	22.43	3.03,3.03
20	223.2	223.5	223.4	224.4	223.9	224.3	224.3	223.5	10- 20	64.81	87.24	11.8,11.8
30	206.4	206.8	206.8	208.4	207.9	208.4	208.2	206.7	20- 30	99.83	187.1	25.3,25.3
40	182.3	182.9	183.4	185.6	185.2	185.8	185.2	182.9	30- 40	123.1	310.1	42,42
50	150.9	151.7	152.8	155.9	155.9	156.4	155.4	151.9	40- 50	131.0	441.1	59.7,59.7
60	112.5	113.4	115.3	119.6	120.1	120.5	118.9	114.1	50- 60	121.6	562.7	76.1,76.1
70	68.37	69.43	71.88	77.40	78.65	78.94	76.56	70.65	60- 70	94.77	657.5	88.9,88.9
80	24.44	25.33	27.86	33.22	34.99	35.27	32.55	26.77	70- 80	54.49	711.9	96.3,96.3
90	1.633	2.236	1.387	3.703	4.000	4.113	1.519	1.628	80- 90	14.96	726.9	98.3,98.3
100	0.9552	1.029	0.8884	0.9560	0.5833	0.5074	0.5889	0.6466	90-100	1.128	728.0	98.5,98.5
110	1.488	1.511	1.274	1.411	1.277	1.081	1.256	1.181	100-110	1.086	729.1	98.6,98.6
120	2.102	2.079	1.890	2.019	1.904	1.595	1.792	1.803	110-120	1.600	730.7	98.9,98.9
130	2.644	2.506	2.318	2.506	2.465	2.102	2.204	2.350	120-130	1.926	732.6	99.1,99.1
140	2.998	2.765	2.638	2.853	2.873	2.638	2.532	2.565	130-140	1.986	734.6	99.4,99.4
150	3.213	2.906	2.885	3.193	3.107	3.071	2.779	2.672	140-150	1.791	736.4	99.6,99.6
160	3.460	3.053	3.379	3.554	3.340	3.400	3.320	2.878	150-160	1.446	737.9	99.8,99.8
170	3.594	3.581	3.834	3.848	3.286	3.714	3.828	3.507	160-170	0.9821	738.9	100,100
180	3.493	4.175	4.262	4.275	3.500	4.155	4.268	4.262	170-180	0.3601	739.2	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-12-03

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.1966A P:4.718W PF:1.000 Freq:0Hz Lamp Flux:739.212x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-8NWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	1204	1511
80	1759	2006
75	2203	2378
70	2499	2627
65	2690	2785
60	2812	2882
55	2889	2939
50	2935	2972
45	2961	2987


C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-12-03

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.1966A P:4.718W PF:1.000 Freq:0Hz Lamp Flux:739.212x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-8NWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.89	.82	.77	.87	.81	.76	.84	.78	.74	.80	.76	.72	.77	.73	.70	.67
3.0	.78	.70	.63	.77	.69	.63	.73	.67	.61	.70	.65	.60	.68	.63	.59	.56
4.0	.69	.60	.53	.68	.59	.53	.65	.58	.52	.62	.56	.51	.60	.55	.50	.48
5.0	.62	.52	.46	.60	.52	.45	.58	.50	.45	.56	.49	.44	.54	.48	.43	.41
6.0	.55	.46	.40	.54	.46	.39	.52	.45	.39	.50	.44	.38	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.47	.40	.34	.46	.39	.34	.44	.38	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.31	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.33	.28	.41	.33	.28	.40	.33	.27	.39	.32	.27	.37	.31	.27	.25
10.0	.38	.30	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.24	.23



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.1966A P:4.718W PF:1.000 Freq:0Hz Lamp Flux:739.212x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-8NWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0	
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
rfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.316	.180	.057	.309	.176	.056	.294	.169	.054	.281	.162	.052	.269	.156	.050		
2.0	.297	.163	.050	.290	.160	.049	.278	.154	.048	.266	.149	.047	.255	.144	.046		
3.0	.274	.146	.044	.268	.144	.043	.257	.139	.042	.247	.135	.041	.237	.131	.041		
4.0	.253	.131	.039	.247	.129	.038	.237	.126	.038	.228	.123	.037	.220	.119	.036		
5.0	.233	.119	.034	.229	.117	.034	.220	.114	.034	.211	.112	.033	.204	.109	.033		
6.0	.216	.108	.031	.212	.107	.031	.204	.105	.030	.196	.102	.030	.190	.100	.030		
7.0	.201	.099	.028	.197	.098	.028	.190	.096	.028	.183	.094	.027	.177	.092	.027		
8.0	.187	.092	.026	.184	.091	.026	.178	.089	.025	.172	.087	.025	.166	.085	.025		
9.0	.176	.085	.024	.172	.084	.024	.167	.082	.023	.161	.081	.023	.156	.079	.023		
10.0	.165	.079	.022	.162	.078	.022	.157	.077	.022	.152	.075	.021	.147	.074	.021		

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.203	.203	.203	.174	.174	.174	.119	.119	.119	.068	.068	.068	.022	.022	.022	
1.0	.194	.169	.147	.166	.145	.126	.113	.100	.087	.065	.058	.051	.021	.019	.016	
2.0	.186	.145	.110	.159	.125	.095	.109	.086	.066	.063	.050	.039	.020	.016	.013	
3.0	.178	.127	.087	.153	.110	.075	.105	.076	.053	.061	.045	.031	.019	.014	.010	
4.0	.171	.114	.071	.147	.099	.061	.101	.069	.043	.058	.040	.026	.019	.013	.008	
5.0	.163	.104	.060	.140	.090	.052	.097	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.156	.095	.052	.134	.083	.045	.093	.058	.032	.054	.034	.019	.017	.011	.006	
7.0	.149	.089	.046	.128	.077	.040	.089	.054	.028	.052	.032	.017	.017	.010	.006	
8.0	.143	.083	.042	.123	.072	.036	.085	.050	.026	.049	.030	.015	.016	.010	.005	
9.0	.137	.078	.038	.118	.068	.033	.082	.048	.024	.048	.028	.014	.015	.009	.005	
10.0	.131	.074	.035	.113	.064	.031	.078	.045	.022	.046	.027	.013	.015	.009	.004	

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.1966A P:4.718W PF:1.000 Freq:0Hz Lamp Flux:739.212x1 lm											
NAME: D8642408NO						TYPE:			WEIGHT:		
SPEC.:D8642408NO-8NWDA012WC0100						DIM.: 1000*8*1.6mm			SERIAL No.:		
MFR.: COLORS						SUR.:1000*8			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	17.5	19.1	17.8	19.3	19.5	17.6	19.1	17.9	19.4	19.6	
	3H	19.0	20.4	19.3	20.7	21.0	19.2	20.6	19.5	20.8	21.1
	4H	19.5	20.9	19.9	21.2	21.5	19.7	21.1	20.1	21.4	21.6
	6H	19.9	21.1	20.2	21.4	21.7	20.1	21.4	20.5	21.7	22.0
	8H	19.9	21.1	20.3	21.5	21.8	20.2	21.4	20.6	21.7	22.1
	12H	19.9	21.1	20.3	21.4	21.8	20.2	21.4	20.6	21.7	22.1
4H	2H	18.1	19.5	18.5	19.8	20.1	18.2	19.5	18.5	19.8	20.1
	3H	19.8	21.0	20.2	21.3	21.6	19.9	21.1	20.3	21.4	21.8
	4H	20.4	21.5	20.8	21.9	22.2	20.6	21.7	21.0	22.0	22.4
	6H	20.9	21.8	21.3	22.2	22.6	21.1	22.0	21.5	22.4	22.8
	8H	21.0	21.9	21.4	22.2	22.7	21.2	22.1	21.7	22.5	22.9
	12H	21.0	21.8	21.5	22.2	22.7	21.3	22.1	21.8	22.5	23.0
8H	4H	20.7	21.6	21.1	22.0	22.4	20.8	21.7	21.3	22.1	22.5
	6H	21.2	21.9	21.7	22.4	22.8	21.4	22.2	21.9	22.6	23.1
	8H	21.4	22.0	21.9	22.5	23.0	21.6	22.3	22.1	22.7	23.2
	12H	21.5	22.0	22.0	22.5	23.0	21.8	22.3	22.3	22.8	23.3
12H	4H	20.7	21.5	21.1	21.9	22.3	20.8	21.6	21.3	22.0	22.5
	6H	21.2	21.9	21.7	22.4	22.8	21.5	22.1	21.9	22.6	23.0
	8H	21.4	22.0	21.9	22.5	23.0	21.7	22.2	22.2	22.7	23.2
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 739.2 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -1.0)

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.1966A P:4.718W PF:1.000 Freq:0Hz Lamp Flux:739.212x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-8NWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	44	37	55	44	37	54	43	37	30
0.80	66	54	47	65	54	46	63	53	46	39
1.00	74	63	56	73	62	55	71	64	55	47
1.25	82	71	64	80	70	63	77	68	62	54
1.50	87	77	69	85	76	69	82	74	68	60
2.00	94	85	78	92	84	77	88	81	76	67
2.50	98	90	84	96	88	83	91	85	80	72
3.00	101	94	88	99	92	87	95	89	85	76
4.00	105	100	95	103	98	93	98	94	90	81
5.00	108	103	99	105	101	97	100	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-12-03

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### ISOCANDELA DIAGRAM

Test:U:24.00V I:0.1966A P:4.718W PF:1.000 Freq:0Hz Lamp Flux:739.212x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-8NWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03


Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:



## AAI Figure

Test:U:24.00V I:0.1966A P:4.718W PF:1.000 Freq:0Hz Lamp Flux:739.212x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-8NWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

Flux out:562.7 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM


Test:U:24.00V I:0.1966A P:4.718W PF:1.000 Freq:0Hz Lamp Flux:739.212x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-8NWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-12-03

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2020-12-03

deg Range: 0 - 180DEG  
deg Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.1966A P:4.718W PF:1.000 Freq:0Hz Lamp Flux:739.212x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-8NWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	236	236	236	237	236	236	236	237										
5	236	236	236	236	235	236	236	236										
10	233	233	233	234	233	234	234	233										
15	229	229	229	230	229	230	230	229										
20	223	224	223	224	224	224	224	223										
25	216	216	216	217	217	217	217	216										
30	206	207	207	208	208	208	208	207										
35	195	196	196	198	197	198	198	196										
40	182	183	183	186	185	186	185	183										
45	167	168	169	172	171	172	171	168										
50	151	152	153	156	156	156	155	152										
55	133	133	135	139	139	139	138	134										
60	112	113	115	120	120	121	119	114										
65	91.0	92.0	94.2	99.1	99.9	100	98.3	92.9										
70	68.4	69.4	71.9	77.4	78.7	78.9	76.6	70.7										
75	45.6	46.6	49.2	55.0	56.6	56.8	54.2	47.9										
80	24.4	25.3	27.9	33.2	35.0	35.3	32.6	26.8										
85	8.40	9.16	10.5	14.7	16.1	16.4	14.0	9.84										
90	1.63	2.24	1.39	3.70	4.00	4.11	1.52	1.63										
95	0.96	1.01	0.91	1.23	0.71	0.65	0.31	0.63										
100	0.96	1.03	0.89	0.96	0.58	0.51	0.59	0.65										
105	1.17	1.23	0.98	1.15	0.94	0.80	0.96	0.95										
110	1.49	1.51	1.27	1.41	1.28	1.08	1.26	1.18										
115	1.80	1.81	1.60	1.72	1.60	1.35	1.54	1.51										
120	2.10	2.08	1.89	2.02	1.90	1.60	1.79	1.80										
125	2.42	2.31	2.10	2.26	2.18	1.86	2.00	2.09										
130	2.64	2.51	2.32	2.51	2.47	2.10	2.20	2.35										
135	2.86	2.66	2.48	2.70	2.69	2.35	2.40	2.43										
140	3.00	2.77	2.64	2.85	2.87	2.64	2.53	2.56										
145	3.11	2.84	2.75	3.03	3.02	2.83	2.65	2.64										
150	3.21	2.91	2.89	3.19	3.11	3.07	2.78	2.67										
155	3.32	2.95	3.09	3.37	3.23	3.23	3.02	2.78										
160	3.46	3.05	3.38	3.55	3.34	3.40	3.32	2.88										
165	3.59	3.27	3.61	3.69	3.39	3.59	3.58	3.17										
170	3.59	3.58	3.83	3.85	3.29	3.71	3.83	3.51										
175	3.43	3.91	4.05	4.07	3.23	3.92	4.07	3.92										
180	3.49	4.17	4.26	4.27	3.50	4.15	4.27	4.26										

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-03

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks: