


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.2007A P:4.816W PF:1.000 Freq:0Hz Lamp Flux:600.316x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 124.64 lm/W			
MODEL	D8642408NO	I <sub>max</sub> (cd)	194.9	S/MH(C0/180)	1.32
NOMINAL POWER(W)	4.3	LOR(%)	100.0	S/MH(C90/270)	1.28
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	600.32	h UP,DN(C0-180)	0.9,50.4
NOMINAL FLUX(lm)	600.316	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,48.0
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	h down(%)	98.4	CIBSE SHR MAX	1.50



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-09

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	193.0	193.4	192.6	192.0	190.7	190.8	191.4	192.3	0- 10	18.46	18.46	3.08,3.08
20	185.7	186.5	185.0	183.7	181.4	181.3	182.6	184.1	10- 20	53.27	71.73	11.9,11.9
30	172.7	173.7	171.7	169.7	166.5	166.2	168.1	170.2	20- 30	81.85	153.6	25.6,25.6
40	153.8	155.0	152.6	150.0	146.2	145.8	148.1	150.7	30- 40	100.6	254.2	42.3,42.3
50	128.9	130.4	127.8	124.8	120.5	119.9	122.5	125.4	40- 50	106.7	360.8	60.1,60.1
60	98.47	100.2	97.36	94.32	89.91	89.09	91.90	94.86	50- 60	98.59	459.4	76.5,76.5
70	63.30	64.91	61.33	59.35	55.17	54.27	56.97	59.75	60- 70	76.48	535.9	89.3,89.3
80	26.71	28.05	24.24	23.59	20.46	19.74	21.78	23.87	70- 80	43.43	579.3	96.5,96.5
90	2.253	2.495	1.116	1.678	0.8592	0.8964	0.6239	1.419	80- 90	11.16	590.5	98.4,98.4
100	0.7214	0.7613	0.6813	0.7754	0.5816	0.5395	0.5030	0.4726	90-100	0.7497	591.3	98.5,98.5
110	1.049	1.077	0.9677	1.150	1.157	0.9805	1.037	0.9208	100-110	0.8638	592.1	98.6,98.6
120	1.569	1.597	1.549	1.637	1.644	1.395	1.443	1.396	110-120	1.284	593.4	98.8,98.8
130	2.030	1.978	1.923	1.998	2.071	1.783	1.744	1.716	120-130	1.547	594.9	99.1,99.1
140	2.418	2.265	2.231	2.285	2.432	2.196	1.984	1.923	130-140	1.601	596.5	99.4,99.4
150	2.631	2.445	2.431	2.612	2.632	2.538	2.238	2.044	140-150	1.465	598.0	99.6,99.6
160	2.872	2.592	2.759	2.912	2.832	2.871	2.732	2.324	150-160	1.192	599.2	99.8,99.8
170	3.026	2.953	3.179	3.173	2.758	3.073	3.173	2.872	160-170	0.8140	600.0	100,100
180	2.986	3.453	3.507	3.533	2.979	3.413	3.527	3.500	170-180	0.2993	600.3	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-12-09

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.2007A P:4.816W PF:1.000 Freq:0Hz Lamp Flux:600.316x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	16232	13647
80	19224	17452
75	21606	20626
70	23133	22415
65	24079	23739
60	24618	24341
55	24924	24683
50	25076	24844
45	25106	24907


C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-12-09

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.2007A P:4.816W PF:1.000 Freq:0Hz Lamp Flux:600.316x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

r <sub>cc</sub>	80%			70%			50%			30%			10%			0
r <sub>w</sub>	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r <sub>fc</sub>	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.89	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.78	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.78	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.60	.68	.63	.59	.57
4.0	.69	.60	.54	.68	.60	.53	.65	.58	.52	.63	.56	.51	.60	.55	.50	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.49	.44	.54	.48	.44	.41
6.0	.56	.46	.40	.54	.46	.40	.52	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.35	.46	.39	.34	.45	.38	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.27	.38	.32	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.25	.23



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-09

g Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.2007A P:4.816W PF:1.000 Freq:0Hz Lamp Flux:600.316x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.314	.178	.056	.306	.174	.055	.292	.167	.053	.279	.161	.052	.267	.155	.050	
2.0	.295	.162	.050	.288	.159	.049	.276	.153	.048	.264	.148	.046	.254	.143	.045	
3.0	.273	.145	.044	.267	.143	.043	.256	.139	.042	.245	.135	.041	.236	.131	.040	
4.0	.252	.131	.038	.246	.129	.038	.236	.125	.037	.227	.122	.037	.219	.119	.036	
5.0	.233	.118	.034	.228	.117	.034	.219	.114	.034	.211	.111	.033	.203	.108	.033	
6.0	.215	.108	.031	.211	.107	.031	.203	.104	.030	.196	.102	.030	.189	.099	.030	
7.0	.200	.099	.028	.197	.098	.028	.189	.096	.028	.183	.094	.027	.177	.092	.027	
8.0	.187	.091	.026	.184	.090	.026	.177	.089	.025	.171	.087	.025	.166	.085	.025	
9.0	.175	.085	.024	.172	.084	.024	.166	.082	.023	.161	.081	.023	.156	.079	.023	
10.0	.165	.079	.022	.162	.078	.022	.157	.077	.022	.152	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.203	.203	.203	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.193	.169	.147	.165	.145	.126	.113	.100	.087	.065	.058	.051	.021	.019	.016	
2.0	.185	.145	.110	.159	.124	.095	.109	.086	.066	.063	.050	.039	.020	.016	.013	
3.0	.178	.127	.087	.152	.110	.075	.105	.076	.053	.060	.044	.031	.019	.014	.010	
4.0	.170	.114	.071	.146	.098	.061	.100	.069	.043	.058	.040	.026	.019	.013	.008	
5.0	.163	.103	.060	.140	.090	.052	.096	.063	.037	.056	.037	.022	.018	.012	.007	
6.0	.156	.095	.052	.134	.082	.045	.092	.058	.032	.054	.034	.019	.017	.011	.006	
7.0	.149	.088	.046	.128	.077	.040	.088	.054	.028	.051	.032	.017	.017	.010	.006	
8.0	.142	.083	.041	.123	.072	.036	.085	.050	.026	.049	.030	.015	.016	.010	.005	
9.0	.136	.078	.038	.117	.067	.033	.081	.047	.024	.047	.028	.014	.015	.009	.005	
10.0	.131	.073	.035	.113	.064	.031	.078	.045	.022	.046	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-09

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.2007A P:4.816W PF:1.000 Freq:0Hz Lamp Flux:600.316x1 lm											
NAME: D8642408NO						TYPE:			WEIGHT:		
SPEC.:D8642408NO-9NWDA012WC0100						DIM.: 1000*8*1.5mm			SERIAL No.:		
MFR.: COLORS						SUR.:1000*8			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	26.0	27.5	26.3	27.8	28.0	26.0	27.5	26.3	27.7	28.0	
	3H	27.6	29.0	28.0	29.3	29.6	27.6	29.0	27.9	29.2	29.5
	4H	28.3	29.6	28.6	29.9	30.2	28.2	29.5	28.5	29.8	30.1
	6H	28.7	30.0	29.1	30.3	30.6	28.6	29.8	28.9	30.1	30.4
	8H	28.9	30.1	29.2	30.4	30.7	28.7	29.9	29.1	30.2	30.5
	12H	28.9	30.1	29.3	30.4	30.8	28.7	29.9	29.1	30.2	30.6
4H	2H	26.7	28.0	27.0	28.3	28.6	26.6	28.0	27.0	28.2	28.5
	3H	28.5	29.6	28.9	30.0	30.3	28.4	29.6	28.8	29.9	30.2
	4H	29.3	30.3	29.7	30.7	31.0	29.2	30.2	29.6	30.6	30.9
	6H	29.8	30.8	30.3	31.2	31.6	29.7	30.6	30.1	31.0	31.4
	8H	30.0	30.9	30.5	31.3	31.7	29.8	30.7	30.3	31.1	31.5
	12H	30.1	30.9	30.6	31.4	31.8	29.9	30.7	30.4	31.2	31.6
8H	4H	29.5	30.4	30.0	30.8	31.2	29.5	30.3	29.9	30.7	31.2
	6H	30.3	31.0	30.7	31.4	31.9	30.1	30.9	30.6	31.3	31.8
	8H	30.6	31.2	31.0	31.7	32.1	30.4	31.0	30.9	31.5	32.0
	12H	30.8	31.3	31.3	31.8	32.3	30.5	31.1	31.0	31.6	32.1
12H	4H	29.6	30.4	30.0	30.8	31.2	29.5	30.3	29.9	30.7	31.1
	6H	30.3	31.0	30.8	31.4	31.9	30.2	30.8	30.7	31.3	31.8
	8H	30.7	31.2	31.2	31.7	32.2	30.5	31.0	31.0	31.5	32.0
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 600.3 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -1.8)

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-09

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.2007A P:4.816W PF:1.000 Freq:0Hz Lamp Flux:600.316x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	44	37	55	44	37	54	44	37	30
0.80	66	54	47	65	54	47	63	53	46	39
1.00	75	63	56	73	63	56	71	64	55	48
1.25	82	71	64	80	70	63	77	69	62	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	81	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	101	94	89	99	93	88	95	90	85	76
4.00	106	100	95	103	98	93	98	94	91	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-12-09

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### ISOCANDELA DIAGRAM

Test:U:24.00V I:0.2007A P:4.816W PF:1.000 Freq:0Hz Lamp Flux:600.316x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-09


Range: 0 - 180DEG  
Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:24.00V I:0.2007A P:4.816W PF:1.000 Freq:0Hz Lamp Flux:600.316x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

Flux out:459.4 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-09

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM


Test:U:24.00V I:0.2007A P:4.816W PF:1.000 Freq:0Hz Lamp Flux:600.316x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:



C Range: 0 - 360DEG  
 C Interval: 45.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:JYH  
 Test Date:2020-12-09

g Range: 0 - 180DEG  
 g Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
 Humidity:65.0%  
 Test Distance:10.950m [K=1.0000]  
 Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: JYH  
Test Date: 2020-12-09

deg Range: 0 - 180DEG  
deg Interval: 1.0DEG  
Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity: 65.0%  
Test Distance: 10.950m [K=1.0000]  
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.2007A P:4.816W PF:1.000 Freq:0Hz Lamp Flux:600.316x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-9NWDA012WC0100	DIM.: 1000*8*1.5mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	194	195	195	195	194	195	195	195										
5	194	195	194	194	193	193	194	194										
10	193	193	193	192	191	191	191	192										
15	190	191	190	189	187	187	188	189										
20	186	186	185	184	181	181	183	184										
25	180	181	179	177	175	174	176	178										
30	173	174	172	170	167	166	168	170										
35	164	165	163	161	157	157	159	161										
40	154	155	153	150	146	146	148	151										
45	142	143	141	138	134	133	136	139										
50	129	130	128	125	121	120	123	125										
55	114	116	113	110	106	105	108	111										
60	98.5	100	97.4	94.3	89.9	89.1	91.9	94.9										
65	81.4	83.1	80.3	77.3	72.9	72.1	74.8	77.7										
70	63.3	64.9	61.3	59.3	55.2	54.3	57.0	59.8										
75	44.7	46.3	42.7	41.1	37.3	36.4	38.9	41.4										
80	26.7	28.0	24.2	23.6	20.5	19.7	21.8	23.9										
85	11.3	12.2	9.52	9.18	7.01	6.64	7.79	9.23										
90	2.25	2.49	1.12	1.68	0.86	0.90	0.62	1.42										
95	0.76	0.81	0.72	0.77	0.49	0.45	0.27	0.40										
100	0.72	0.76	0.68	0.78	0.58	0.54	0.50	0.47										
105	0.85	0.88	0.73	0.93	0.88	0.75	0.79	0.65										
110	1.05	1.08	0.97	1.15	1.16	0.98	1.04	0.92										
115	1.35	1.34	1.26	1.41	1.41	1.19	1.26	1.16										
120	1.57	1.60	1.55	1.64	1.64	1.39	1.44	1.40										
125	1.82	1.80	1.75	1.84	1.86	1.58	1.60	1.58										
130	2.03	1.98	1.92	2.00	2.07	1.78	1.74	1.72										
135	2.23	2.14	2.10	2.15	2.26	1.99	1.88	1.88										
140	2.42	2.26	2.23	2.29	2.43	2.20	1.98	1.92										
145	2.56	2.38	2.34	2.48	2.53	2.35	2.07	2.02										
150	2.63	2.44	2.43	2.61	2.63	2.54	2.24	2.04										
155	2.77	2.51	2.56	2.77	2.74	2.68	2.48	2.12										
160	2.87	2.59	2.76	2.91	2.83	2.87	2.73	2.32										
165	2.99	2.71	2.99	3.03	2.87	2.99	2.95	2.58										
170	3.03	2.95	3.18	3.17	2.76	3.07	3.17	2.87										
175	2.95	3.23	3.41	3.35	2.73	3.23	3.37	3.19										
180	2.99	3.45	3.51	3.53	2.98	3.41	3.53	3.50										

C Range: 0 - 360DEG  
C Interval: 45.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:JYH  
Test Date:2020-12-09

g Range: 0 - 180DEG  
g Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.362  
Humidity:65.0%  
Test Distance:10.950m [K=1.0000]  
Remarks: