


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:24.00V I:0.1907A P:4.576W PF:1.000 Freq:0Hz Lamp Flux:568.449x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-HNWNDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 124.21 lm/W			
MODEL	D8642408NO	I _{max} (cd)	187.4	S/MH(C0/180)	1.31
NOMINAL POWER(W)	4.3	LOR(%)	100.0	S/MH(C90/270)	1.29
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	568.45	h UP,DN(C0-180)	0.9,49.6
NOMINAL FLUX(lm)	568.449	CIE CLASS	DIRECT	h UP,DN(C180-360)	0.8,48.8
LAMPS INSIDE	1	h up(%)	1.6	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	98.4	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-03

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	185.1	185.2	184.3	184.0	183.2	183.7	184.4	184.9	0- 10	17.73	17.73	3.12,3.12
20	177.6	177.4	175.9	175.1	173.9	174.5	176.0	176.9	10- 20	51.07	68.80	12.1,12.1
30	164.4	164.0	161.9	160.8	159.0	160.0	162.1	163.3	20- 30	78.19	147.0	25.9,25.9
40	145.6	145.0	142.5	141.0	139.0	140.2	142.8	144.3	30- 40	95.65	242.6	42.7,42.7
50	121.5	120.7	117.7	116.1	114.0	115.4	118.5	120.1	40- 50	100.9	343.6	60.4,60.4
60	92.44	91.48	88.14	86.55	84.61	86.16	89.50	91.02	50- 60	92.83	436.4	76.8,76.8
70	59.35	58.16	54.63	53.19	51.61	53.24	56.57	58.06	60- 70	71.67	508.1	89.4,89.4
80	25.09	23.90	20.81	19.86	18.95	20.38	23.16	24.29	70- 80	40.64	548.7	96.5,96.5
90	2.230	2.027	1.022	1.392	0.7991	1.110	0.8761	1.812	80- 90	10.51	559.2	98.4,98.4
100	0.6434	0.7020	0.6785	0.7226	0.5486	0.4403	0.4230	0.3923	90-100	0.6849	559.9	98.5,98.5
110	0.9884	1.037	0.9618	1.123	1.082	0.8672	0.9227	0.8131	100-110	0.8001	560.7	98.6,98.6
120	1.488	1.523	1.455	1.584	1.536	1.262	1.309	1.269	110-120	1.193	561.9	98.9,98.9
130	1.923	1.898	1.844	1.931	1.951	1.650	1.623	1.616	120-130	1.453	563.4	99.1,99.1
140	2.290	2.158	2.104	2.198	2.272	2.004	1.857	1.817	130-140	1.505	564.9	99.4,99.4
150	2.511	2.325	2.311	2.505	2.485	2.364	2.098	1.937	140-150	1.380	566.3	99.6,99.6
160	2.738	2.471	2.650	2.792	2.692	2.665	2.599	2.210	150-160	1.131	567.4	99.8,99.8
170	2.846	2.846	3.065	3.040	2.658	2.992	3.026	2.778	160-170	0.7766	568.2	99.9,99.9
180	2.792	3.306	3.360	3.366	2.792	3.313	3.380	3.393	170-180	0.2866	568.4	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-12-03

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.1907A P:4.576W PF:1.000 Freq:0Hz Lamp Flux:568.449x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-HNWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:



LUMINANCE cd/(m2)		
G(180)	C0/180	C90/270
85	1540	1078
80	1806	1498
75	2026	1801
70	2169	1996
65	2256	2123
60	2311	2203
55	2345	2257
50	2362	2290
45	2372	2310


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-03

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.1907A P:4.576W PF:1.000 Freq:0Hz Lamp Flux:568.449x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-HNWNDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.10	1.10	1.10	1.05	1.05	1.05	1.01	1.01	1.01	.98
1.0	1.03	.99	.95	1.01	.97	.93	.96	.93	.90	.92	.90	.87	.88	.86	.84	.82
2.0	.90	.83	.77	.88	.81	.76	.84	.79	.74	.80	.76	.72	.77	.73	.70	.68
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.65	.60	.68	.63	.59	.57
4.0	.69	.61	.54	.68	.60	.53	.65	.58	.52	.63	.57	.51	.60	.55	.51	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.44	.54	.48	.44	.42
6.0	.56	.47	.40	.55	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.42	.35	.49	.41	.35	.48	.40	.35	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.36	.31	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.28	.38	.32	.27	.26
10.0	.39	.31	.26	.38	.31	.25	.37	.30	.25	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-03

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:24.00V I:0.1907A P:4.576W PF:1.000 Freq:0Hz Lamp Flux:568.449x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-HNWNDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.312	.178	.056	.305	.174	.055	.291	.167	.053	.278	.160	.051	.266	.154	.050	
2.0	.294	.161	.049	.287	.158	.049	.275	.153	.047	.263	.148	.046	.253	.143	.045	
3.0	.272	.145	.043	.266	.143	.043	.255	.138	.042	.245	.134	.041	.235	.130	.040	
4.0	.251	.130	.038	.246	.129	.038	.236	.125	.037	.227	.122	.037	.218	.118	.036	
5.0	.232	.118	.034	.227	.117	.034	.218	.114	.033	.210	.111	.033	.202	.108	.032	
6.0	.215	.108	.031	.211	.106	.031	.203	.104	.030	.195	.102	.030	.188	.099	.029	
7.0	.200	.099	.028	.196	.098	.028	.189	.096	.028	.182	.094	.027	.176	.092	.027	
8.0	.187	.091	.026	.183	.090	.025	.177	.088	.025	.171	.087	.025	.165	.085	.025	
9.0	.175	.085	.024	.172	.084	.023	.166	.082	.023	.161	.080	.023	.155	.079	.023	
10.0	.164	.079	.022	.162	.078	.022	.156	.077	.022	.151	.075	.021	.147	.074	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.203	.203	.203	.173	.173	.173	.118	.118	.118	.068	.068	.068	.022	.022	.022	
1.0	.193	.169	.147	.165	.145	.126	.113	.100	.087	.065	.058	.051	.021	.019	.016	
2.0	.185	.144	.110	.159	.124	.095	.109	.086	.066	.063	.050	.039	.020	.016	.013	
3.0	.177	.127	.087	.152	.109	.075	.104	.076	.053	.060	.044	.031	.019	.014	.010	
4.0	.170	.114	.071	.146	.098	.061	.100	.068	.043	.058	.040	.026	.019	.013	.008	
5.0	.163	.103	.060	.140	.089	.052	.096	.062	.037	.056	.037	.022	.018	.012	.007	
6.0	.155	.095	.052	.134	.082	.045	.092	.058	.032	.053	.034	.019	.017	.011	.006	
7.0	.149	.088	.046	.128	.076	.040	.088	.054	.028	.051	.032	.017	.017	.010	.006	
8.0	.142	.082	.041	.122	.071	.036	.085	.050	.026	.049	.030	.015	.016	.010	.005	
9.0	.136	.077	.038	.117	.067	.033	.081	.047	.023	.047	.028	.014	.015	.009	.005	
10.0	.130	.073	.035	.112	.064	.031	.078	.045	.022	.045	.026	.013	.015	.009	.004	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-03

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.1907A P:4.576W PF:1.000 Freq:0Hz Lamp Flux:568.449x1 lm											
NAME: D8642408NO					TYPE:			WEIGHT:			
SPEC.:D8642408NO-HNWNDA012WC0100					DIM.: 1000*8*1.6mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*8			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	17.9	19.4	18.2	19.6	19.9	17.7	19.2	18.0	19.5	19.7	
	3H	19.5	20.9	19.8	21.2	21.4	19.3	20.7	19.6	20.9	21.2
	4H	20.2	21.5	20.5	21.8	22.1	19.8	21.2	20.2	21.4	21.7
	6H	20.6	21.9	21.0	22.2	22.5	20.2	21.4	20.6	21.7	22.1
	8H	20.7	22.0	21.1	22.3	22.6	20.3	21.5	20.6	21.8	22.1
	12H	20.8	22.0	21.2	22.3	22.7	20.3	21.5	20.7	21.8	22.1
4H	2H	18.5	19.8	18.9	20.1	20.4	18.4	19.7	18.7	20.0	20.3
	3H	20.3	21.5	20.7	21.8	22.1	20.1	21.3	20.5	21.6	21.9
	4H	21.1	22.1	21.5	22.5	22.9	20.8	21.9	21.2	22.2	22.6
	6H	21.7	22.6	22.1	23.0	23.4	21.3	22.2	21.7	22.6	23.0
	8H	21.8	22.7	22.3	23.1	23.5	21.4	22.3	21.8	22.7	23.1
	12H	22.0	22.8	22.4	23.2	23.6	21.5	22.3	21.9	22.7	23.1
8H	4H	21.3	22.2	21.8	22.6	23.0	21.1	22.0	21.5	22.4	22.8
	6H	22.1	22.8	22.5	23.2	23.7	21.7	22.4	22.2	22.9	23.3
	8H	22.3	23.0	22.8	23.4	23.9	21.9	22.6	22.4	23.0	23.5
	12H	22.5	23.1	23.0	23.6	24.1	22.0	22.6	22.5	23.1	23.6
12H	4H	21.3	22.1	21.8	22.6	23.0	21.1	21.9	21.5	22.3	22.8
	6H	22.1	22.7	22.6	23.2	23.7	21.8	22.4	22.3	22.9	23.4
	8H	22.4	23.0	22.9	23.4	23.9	22.0	22.6	22.5	23.0	23.6
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2				+ 0.1 / - 0.2						
1.5H	+ 0.2 / - 0.3				+ 0.2 / - 0.3						
2.0H	+ 0.2 / - 0.3				+ 0.2 / - 0.4						

CIE Pub.117, 568.4 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -2.0)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-03

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.1907A P:4.576W PF:1.000 Freq:0Hz Lamp Flux:568.449x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-HNWNDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	56	45	38	56	44	37	54	44	37	31
0.80	66	55	47	65	54	47	63	53	46	39
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	80	71	64	78	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	82	76	68
2.50	98	90	84	96	89	83	92	86	81	72
3.00	102	95	89	99	93	88	95	90	85	76
4.00	106	100	95	103	98	94	99	94	91	81
5.00	108	103	99	105	101	97	101	97	94	84
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-12-03

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.1907A P:4.576W PF:1.000 Freq:0Hz Lamp Flux:568.449x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-HNWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-03

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.1907A P:4.576W PF:1.000 Freq:0Hz Lamp Flux:568.449x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-HNWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

Flux out:427.9 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-03

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.1907A P:4.576W PF:1.000 Freq:0Hz Lamp Flux:568.449x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-HNWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-03

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-12-03

deg Range: 0 - 180DEG
deg Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.1907A P:4.576W PF:1.000 Freq:0Hz Lamp Flux:568.449x1 lm		
NAME: D8642408NO	TYPE:	WEIGHT:
SPEC.:D8642408NO-HNWDA012WC0100	DIM.: 1000*8*1.6mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*8	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	187	187	187	187	187	187	187	187										
5	187	187	186	186	186	186	186	187										
10	185	185	184	184	183	184	184	185										
15	182	182	181	180	179	180	181	182										
20	178	177	176	175	174	175	176	177										
25	172	171	170	169	167	168	170	171										
30	164	164	162	161	159	160	162	163										
35	156	155	153	152	150	151	153	154										
40	146	145	142	141	139	140	143	144										
45	134	133	131	129	127	128	131	133										
50	121	121	118	116	114	115	118	120										
55	108	107	104	102	99.9	101	104	106										
60	92.4	91.5	88.1	86.5	84.6	86.2	89.5	91.0										
65	76.3	75.3	71.8	70.2	68.4	70.0	73.4	74.9										
70	59.3	58.2	54.6	53.2	51.6	53.2	56.6	58.1										
75	41.9	40.7	37.3	36.0	34.7	36.3	39.5	40.9										
80	25.1	23.9	20.8	19.9	18.9	20.4	23.2	24.3										
85	10.7	9.79	7.52	7.14	6.52	7.53	9.34	10.1										
90	2.23	2.03	1.02	1.39	0.80	1.11	0.88	1.81										
95	0.65	0.71	0.68	0.71	0.43	0.37	0.22	0.32										
100	0.64	0.70	0.68	0.72	0.55	0.44	0.42	0.39										
105	0.75	0.84	0.71	0.90	0.82	0.66	0.71	0.61										
110	0.99	1.04	0.96	1.12	1.08	0.87	0.92	0.81										
115	1.25	1.30	1.21	1.36	1.31	1.07	1.14	1.03										
120	1.49	1.52	1.45	1.58	1.54	1.26	1.31	1.27										
125	1.71	1.73	1.64	1.77	1.75	1.47	1.48	1.46										
130	1.92	1.90	1.84	1.93	1.95	1.65	1.62	1.62										
135	2.10	2.05	1.94	2.07	2.12	1.81	1.74	1.74										
140	2.29	2.16	2.10	2.20	2.27	2.00	1.86	1.82										
145	2.38	2.24	2.21	2.37	2.40	2.19	1.95	1.90										
150	2.51	2.32	2.31	2.51	2.49	2.36	2.10	1.94										
155	2.67	2.38	2.42	2.65	2.59	2.54	2.33	2.02										
160	2.74	2.47	2.65	2.79	2.69	2.66	2.60	2.21										
165	2.86	2.61	2.85	2.92	2.76	2.79	2.82	2.44										
170	2.85	2.85	3.07	3.04	2.66	2.99	3.03	2.78										
175	2.78	3.11	3.19	3.23	2.64	3.08	3.23	3.07										
180	2.79	3.31	3.36	3.37	2.79	3.31	3.38	3.39										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-12-03

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: