


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:48.00V I:0.1500A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:399.574x1 lm		
NAME: NM3D1515	TYPE:	WEIGHT:
SPEC.:NM3D1515-9WW48CSN050CC0100	DIM.: 1000*15*15mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*15mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 55.50 lm/W			
MODEL	NM3D1515	I _{max} (cd)	133.9	S/MH(C0/180)	1.26
NOMINAL POWER(W)	7.2	LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	48	TOTAL FLUX(lm)	399.57	h UP,DN(C0-180)	1.6,48.5
NOMINAL FLUX(lm)	399.574	CIE CLASS	DIRECT	h UP,DN(C180-360)	1.5,48.4
LAMPS INSIDE	1	h up(%)	3.1	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	48	h down(%)	96.9	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-04

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	131.5	131.1	130.5	130.9	131.9	131.1	130.5	130.4	0- 10	12.62	12.62	3.16,3.16
20	124.5	124.0	123.0	124.0	125.2	124.1	122.8	123.1	10- 20	36.12	48.74	12.2,12.2
30	113.0	112.4	111.3	112.9	114.0	112.6	110.7	111.6	20- 30	54.65	103.4	25.9,25.9
40	97.95	97.39	96.15	98.17	99.16	97.56	95.53	96.59	30- 40	65.82	169.2	42.3,42.3
50	80.11	79.48	77.96	80.50	81.31	79.61	77.76	78.76	40- 50	68.39	237.6	59.5,59.5
60	60.22	59.53	57.79	60.81	61.22	59.66	57.62	58.92	50- 60	62.27	299.9	75,75
70	38.79	38.14	36.30	39.51	39.64	38.24	36.60	37.56	60- 70	48.37	348.2	87.2,87.2
80	17.62	17.15	15.60	18.15	18.40	17.50	15.67	16.66	70- 80	28.90	377.1	94.4,94.4
90	4.767	4.591	2.422	4.975	4.935	4.587	1.775	3.963	80- 90	10.13	387.3	96.9,96.9
100	3.541	2.597	0.6080	3.357	3.533	3.055	0.3079	2.738	90-100	3.446	390.7	97.8,97.8
110	2.846	1.589	0.6212	2.304	2.695	2.012	0.6288	1.864	100-110	2.251	393.0	98.3,98.3
120	2.179	1.590	0.9284	1.547	1.790	1.443	0.8955	1.351	110-120	1.660	394.6	98.8,98.8
130	1.984	1.410	1.176	1.470	1.710	1.309	1.129	1.270	120-130	1.273	395.9	99.1,99.1
140	1.950	1.590	1.349	1.677	1.757	1.489	1.296	1.363	130-140	1.159	397.0	99.4,99.4
150	2.030	1.637	1.469	1.757	1.797	1.643	1.423	1.469	140-150	1.010	398.1	99.6,99.6
160	2.050	1.717	1.756	1.857	1.797	1.790	1.757	1.603	150-160	0.7922	398.9	99.8,99.8
170	2.025	1.977	2.031	2.011	1.770	1.957	2.044	1.896	160-170	0.5284	399.4	100,100
180	1.857	2.211	2.304	2.284	1.823	2.211	2.298	2.258	170-180	0.1934	399.6	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-09-04

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:48.00V I:0.1500A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:399.574x1 lm		
NAME: NM3D1515	TYPE:	WEIGHT:
SPEC.:NM3D1515-9WW48CSN050CC0100	DIM.: 1000*15*15mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*15mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:48.00V I:0.1500A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:399.574x1 lm		
NAME: NM3D1515	TYPE:	WEIGHT:
SPEC.:NM3D1515-9WW48CSN050CC0100	DIM.: 1000*15*15mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*15mm	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.04	1.04	1.04	.99	.99	.99	.97
1.0	1.03	.98	.94	1.00	.96	.92	.95	.92	.89	.91	.88	.86	.87	.85	.83	.80
2.0	.89	.82	.76	.87	.81	.75	.83	.78	.73	.79	.75	.71	.76	.72	.69	.66
3.0	.78	.70	.63	.76	.69	.63	.73	.66	.61	.70	.64	.60	.67	.62	.58	.56
4.0	.69	.60	.53	.68	.59	.53	.65	.58	.52	.62	.56	.51	.59	.54	.50	.48
5.0	.62	.53	.46	.60	.52	.46	.58	.50	.45	.56	.49	.44	.53	.48	.43	.41
6.0	.56	.46	.40	.54	.46	.40	.52	.45	.39	.50	.44	.39	.48	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.35	.46	.39	.34	.44	.38	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.31	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.33	.28	.39	.32	.27	.37	.32	.27	.25
10.0	.39	.31	.26	.38	.31	.25	.37	.30	.25	.36	.29	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:48.00V I:0.1500A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:399.574x1 lm		
NAME: NM3D1515	TYPE:	WEIGHT:
SPEC.:NM3D1515-9WW48CSN050CC0100	DIM.: 1000*15*15mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*15mm	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.318	.181	.057	.310	.177	.056	.295	.169	.054	.281	.162	.052	.269	.156	.050	
2.0	.296	.162	.050	.289	.159	.049	.276	.153	.048	.263	.148	.046	.252	.142	.045	
3.0	.273	.145	.043	.266	.143	.043	.254	.138	.042	.243	.133	.041	.233	.129	.040	
4.0	.251	.130	.038	.245	.128	.038	.235	.124	.037	.225	.121	.036	.216	.117	.036	
5.0	.231	.118	.034	.226	.116	.034	.217	.113	.033	.208	.110	.033	.200	.107	.032	
6.0	.214	.107	.031	.210	.106	.030	.201	.103	.030	.193	.100	.030	.186	.098	.029	
7.0	.199	.098	.028	.195	.097	.028	.187	.095	.027	.180	.092	.027	.174	.090	.027	
8.0	.186	.091	.026	.182	.090	.025	.175	.088	.025	.169	.086	.025	.163	.084	.024	
9.0	.174	.084	.024	.171	.083	.023	.165	.081	.023	.159	.080	.023	.153	.078	.022	
10.0	.164	.078	.022	.161	.078	.022	.155	.076	.021	.150	.074	.021	.145	.073	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.214	.214	.214	.183	.183	.183	.125	.125	.125	.072	.072	.072	.023	.023	.023	
1.0	.205	.180	.157	.175	.154	.135	.120	.106	.094	.069	.061	.054	.022	.020	.018	
2.0	.197	.156	.121	.168	.134	.105	.115	.093	.073	.067	.054	.043	.021	.017	.014	
3.0	.189	.138	.098	.162	.119	.085	.111	.083	.060	.064	.048	.035	.021	.016	.011	
4.0	.181	.125	.082	.156	.108	.071	.107	.075	.050	.062	.044	.030	.020	.014	.010	
5.0	.174	.115	.071	.149	.099	.062	.103	.069	.044	.060	.041	.026	.019	.013	.009	
6.0	.167	.106	.063	.143	.092	.055	.099	.065	.039	.057	.038	.023	.019	.012	.008	
7.0	.160	.100	.057	.137	.086	.050	.095	.061	.035	.055	.036	.021	.018	.012	.007	
8.0	.153	.094	.053	.132	.081	.046	.091	.057	.033	.053	.034	.020	.017	.011	.006	
9.0	.147	.089	.050	.127	.077	.043	.088	.054	.031	.051	.032	.018	.017	.011	.006	
10.0	.142	.085	.047	.122	.074	.041	.085	.052	.029	.049	.031	.017	.016	.010	.006	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:48.00V I:0.1500A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:399.574x1 lm											
NAME: NM3D1515					TYPE:			WEIGHT:			
SPEC.:NM3D1515-9WW48CSN050CC0100					DIM.: 1000*15*15mm			SERIAL No.:			
MFR.: COLORS					SUR.:1000*15mm			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise				Viewed endwise					
x = 2H y = 2H	23.2	24.7	23.5	24.9	25.2	23.1	24.5	23.4	24.8	25.1	
	3H	24.8	26.2	25.1	26.5	26.8	24.6	26.0	24.9	26.3	26.6
	4H	25.5	26.8	25.8	27.1	27.4	25.2	26.5	25.6	26.8	27.1
	6H	26.0	27.2	26.3	27.5	27.9	25.6	26.9	26.0	27.2	27.5
	8H	26.1	27.3	26.5	27.7	28.0	25.8	27.0	26.2	27.3	27.7
	12H	26.3	27.4	26.7	27.8	28.1	25.9	27.0	26.3	27.4	27.8
4H	2H	23.8	25.1	24.2	25.4	25.7	23.7	25.0	24.1	25.3	25.6
	3H	25.6	26.7	26.0	27.1	27.5	25.4	26.6	25.8	26.9	27.3
	4H	26.4	27.4	26.8	27.8	28.2	26.2	27.2	26.6	27.6	28.0
	6H	27.0	27.9	27.5	28.3	28.8	26.7	27.7	27.2	28.1	28.5
	8H	27.3	28.1	27.7	28.5	29.0	26.9	27.8	27.4	28.2	28.7
	12H	27.5	28.2	27.9	28.7	29.2	27.1	27.9	27.6	28.3	28.8
8H	4H	26.6	27.5	27.1	27.9	28.4	26.5	27.3	26.9	27.7	28.2
	6H	27.4	28.2	27.9	28.6	29.1	27.2	27.9	27.7	28.4	28.9
	8H	27.8	28.4	28.3	28.9	29.4	27.5	28.1	28.0	28.6	29.1
	12H	28.1	28.6	28.6	29.1	29.7	27.7	28.3	28.3	28.8	29.3
12H	4H	26.7	27.5	27.1	27.9	28.4	26.5	27.3	26.9	27.7	28.2
	6H	27.5	28.1	28.0	28.6	29.1	27.3	27.9	27.8	28.4	28.9
	8H	27.9	28.4	28.4	29.0	29.5	27.6	28.2	28.1	28.7	29.2
Variations with the observer position at spacings:											
S = 1.0H		+ 0.1 / - 0.2				+ 0.1 / - 0.2					
1.5H		+ 0.2 / - 0.3				+ 0.2 / - 0.3					
2.0H		+ 0.1 / - 0.3				+ 0.1 / - 0.3					

CIE Pub.117, 399.6 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -3.2)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:48.00V I:0.1500A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:399.574x1 lm		
NAME: NM3D1515	TYPE:	WEIGHT:
SPEC.:NM3D1515-9WW48CSN050CC0100	DIM.: 1000*15*15mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*15mm	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	44	37	55	44	37	54	44	37	31
0.80	66	54	47	65	54	47	63	53	46	39
1.00	74	63	56	73	62	55	71	64	55	47
1.25	81	71	63	80	70	63	77	68	62	54
1.50	86	76	69	85	75	68	81	73	67	59
2.00	93	84	78	91	83	77	87	81	75	67
2.50	97	89	83	95	88	82	91	85	80	71
3.00	101	94	88	98	92	87	94	89	84	75
4.00	105	99	94	102	97	92	97	93	89	80
5.00	107	102	98	105	100	96	100	96	93	83
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:48.00V I:0.1500A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:399.574x1 lm		
NAME: NM3D1515	TYPE:	WEIGHT:
SPEC.:NM3D1515-9WW48CSN050CC0100	DIM.: 1000*15*15mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*15mm	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-04

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:48.00V I:0.1500A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:399.574x1 lm		
NAME: NM3D1515	TYPE:	WEIGHT:
SPEC.:NM3D1515-9WW48CSN050CC0100	DIM.: 1000*15*15mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*15mm	Shielding Angle:

Flux out:276.2 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:48.00V I:0.1500A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:399.574x1 lm		
NAME: NM3D1515	TYPE:	WEIGHT:
SPEC.:NM3D1515-9WW48CSN050CC0100	DIM.: 1000*15*15mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*15mm	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-09-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:48.00V I:0.1500A P:7.200W PF:1.000 Freq:0Hz Lamp Flux:399.574x1 lm		
NAME: NM3D1515	TYPE:	WEIGHT:
SPEC.:NM3D1515-9WW48CSN050CC0100	DIM.: 1000*15*15mm	SERIAL No.:
MFR.: COLORS	SUR.:1000*15mm	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	134	133	133	133	134	133	133	133										
5	133	133	132	133	133	133	132	132										
10	131	131	130	131	132	131	130	130										
15	129	128	127	128	129	128	127	127										
20	124	124	123	124	125	124	123	123										
25	119	119	118	119	120	119	117	118										
30	113	112	111	113	114	113	111	112										
35	106	105	104	106	107	106	103	105										
40	97.9	97.4	96.1	98.2	99.2	97.6	95.5	96.6										
45	89.3	88.7	87.4	89.6	90.5	88.8	87.0	87.9										
50	80.1	79.5	78.0	80.5	81.3	79.6	77.8	78.8										
55	70.4	69.7	68.1	70.9	71.5	69.9	67.9	69.1										
60	60.2	59.5	57.8	60.8	61.2	59.7	57.6	58.9										
65	49.6	49.0	47.3	50.3	50.6	49.1	47.2	48.3										
70	38.8	38.1	36.3	39.5	39.6	38.2	36.6	37.6										
75	27.9	27.3	25.6	28.6	28.7	27.5	26.0	26.7										
80	17.6	17.1	15.6	18.1	18.4	17.5	15.7	16.7										
85	9.25	8.94	7.38	9.51	9.73	9.16	6.68	8.34										
90	4.77	4.59	2.42	4.98	4.93	4.59	1.78	3.96										
95	3.81	3.39	2.02	3.88	3.80	3.52	1.50	3.03										
100	3.54	2.60	0.61	3.36	3.53	3.06	0.31	2.74										
105	3.22	1.88	0.50	2.76	3.18	2.51	0.47	2.47										
110	2.85	1.59	0.62	2.30	2.70	2.01	0.63	1.86										
115	2.48	1.59	0.81	2.11	2.17	1.82	0.76	1.80										
120	2.18	1.59	0.93	1.55	1.79	1.44	0.90	1.35										
125	2.05	1.36	1.04	1.35	1.71	1.43	1.02	1.28										
130	1.98	1.41	1.18	1.47	1.71	1.31	1.13	1.27										
135	1.95	1.57	1.26	1.62	1.72	1.38	1.20	1.35										
140	1.95	1.59	1.35	1.68	1.76	1.49	1.30	1.36										
145	1.97	1.61	1.44	1.74	1.80	1.60	1.35	1.42										
150	2.03	1.64	1.47	1.76	1.80	1.64	1.42	1.47										
155	2.03	1.68	1.60	1.79	1.80	1.70	1.58	1.49										
160	2.05	1.72	1.76	1.86	1.80	1.79	1.76	1.60										
165	2.08	1.80	1.90	1.92	1.79	1.86	1.91	1.68										
170	2.02	1.98	2.03	2.01	1.77	1.96	2.04	1.90										
175	1.87	2.14	2.14	2.14	1.74	2.06	2.19	2.11										
180	1.86	2.21	2.30	2.28	1.82	2.21	2.30	2.26										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-09-04

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: