


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:12.00V I:0.5960A P:7.100W PF:1.000 Freq:0Hz Lamp Flux:207.592x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-9SW12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 29.24 lm/W			
MODEL	NMS0410	I _{max} (cd)	71.90	S/MH(C0/180)	1.20
NOMINAL POWER(W)	7.2	LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	12	TOTAL FLUX(lm)	207.59	h UP,DN(C0-180)	1.6,50.4
NOMINAL FLUX(lm)	207.592	CIE CLASS	DIRECT	h UP,DN(C180-360)	1.1,47.0
LAMPS INSIDE	1	h up(%)	2.7	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	12	h down(%)	97.3	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-05-19

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	71.26	71.01	70.30	69.79	69.54	69.50	69.91	70.63	0- 10	6.771	6.771	3.26,3.26
20	67.96	67.72	66.35	65.44	64.74	64.72	65.74	67.01	10- 20	19.34	26.11	12.6,12.6
30	62.20	61.87	60.08	58.56	57.43	57.69	59.19	61.06	20- 30	29.14	55.25	26.6,26.6
40	54.40	54.06	51.78	49.78	48.28	48.71	50.84	53.18	30- 40	34.88	90.13	43.4,43.4
50	45.16	44.73	41.89	39.41	37.68	38.31	41.03	43.79	40- 50	35.93	126.1	60.7,60.7
60	34.84	34.36	30.84	28.00	26.17	26.95	30.21	33.34	50- 60	32.31	158.4	76.3,76.3
70	23.95	23.18	19.09	16.11	14.49	15.23	18.74	22.21	60- 70	24.62	183.0	88.1,88.1
80	13.08	11.11	7.552	5.407	4.768	4.878	7.568	11.22	70- 80	14.25	197.2	95,95
90	4.704	3.412	0.6706	0.6933	0.7192	0.5513	0.6276	3.123	80- 90	4.843	202.1	97.3,97.3
100	1.738	1.503	0.2004	0.5210	0.5010	0.4275	0.1471	1.229	90-100	1.232	203.3	97.9,97.9
110	1.530	1.363	0.2873	0.6014	0.6144	0.5063	0.2947	1.005	100-110	0.8123	204.1	98.3,98.3
120	1.496	1.154	0.4541	0.6413	0.7080	0.5210	0.4409	0.8892	110-120	0.7781	204.9	98.7,98.7
130	1.389	0.9752	0.6340	0.7349	0.8016	0.6346	0.5413	0.8082	120-130	0.7127	205.6	99,99
140	1.383	0.7882	0.7216	0.7952	0.8683	0.7147	0.6213	0.8148	130-140	0.6437	206.3	99.4,99.4
150	1.089	0.8750	0.8212	0.9285	0.8683	0.8483	0.7421	0.6947	140-150	0.5348	206.8	99.6,99.6
160	1.082	0.9086	0.9417	1.022	0.9487	0.9417	0.9351	0.7214	150-160	0.4128	207.2	99.8,99.8
170	1.082	1.042	1.069	1.115	0.9819	1.062	1.122	0.9418	160-170	0.2810	207.5	99.9,99.9
180	1.075	1.176	1.242	1.196	1.075	1.162	1.256	1.182	170-180	0.1047	207.6	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-05-19

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:12.00V I:0.5960A P:7.100W PF:1.000 Freq:0Hz Lamp Flux:207.592x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-9SW12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	23715	8729
80	18827	10873
75	17772	12692
70	17504	13955
65	17415	14807
60	17421	15422
55	17486	15909
50	17563	16293
45	17652	16616


C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-05-19

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:12.00V I:0.5960A P:7.100W PF:1.000 Freq:0Hz Lamp Flux:207.592x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-9SW12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-05-19

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:12.00V I:0.5960A P:7.100W PF:1.000 Freq:0Hz Lamp Flux:207.592x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-9SW12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.313	.178	.056	.305	.174	.055	.290	.167	.053	.277	.160	.051	.264	.153	.049	
2.0	.292	.160	.049	.285	.157	.048	.272	.151	.047	.260	.146	.046	.249	.141	.044	
3.0	.270	.144	.043	.264	.141	.042	.252	.137	.041	.241	.132	.041	.231	.128	.040	
4.0	.249	.129	.038	.243	.127	.038	.233	.123	.037	.223	.120	.036	.214	.116	.035	
5.0	.230	.117	.034	.225	.115	.034	.215	.112	.033	.207	.109	.032	.199	.106	.032	
6.0	.213	.107	.031	.208	.105	.030	.200	.103	.030	.192	.100	.029	.185	.097	.029	
7.0	.198	.098	.028	.194	.097	.028	.187	.094	.027	.180	.092	.027	.173	.090	.026	
8.0	.185	.090	.025	.181	.089	.025	.175	.087	.025	.168	.085	.025	.162	.083	.024	
9.0	.173	.084	.023	.170	.083	.023	.164	.081	.023	.158	.079	.023	.153	.078	.022	
10.0	.163	.078	.022	.160	.077	.022	.155	.076	.021	.149	.074	.021	.144	.073	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.211	.211	.211	.180	.180	.180	.123	.123	.123	.071	.071	.071	.023	.023	.023	
1.0	.201	.177	.154	.172	.151	.133	.118	.104	.092	.068	.060	.053	.022	.019	.017	
2.0	.193	.152	.118	.165	.131	.102	.113	.091	.071	.065	.053	.042	.021	.017	.014	
3.0	.185	.135	.095	.159	.116	.082	.109	.081	.058	.063	.047	.034	.020	.015	.011	
4.0	.177	.122	.079	.152	.105	.069	.105	.073	.048	.061	.043	.029	.019	.014	.009	
5.0	.170	.111	.068	.146	.096	.059	.101	.067	.042	.058	.040	.025	.019	.013	.008	
6.0	.163	.103	.060	.140	.089	.052	.097	.062	.037	.056	.037	.022	.018	.012	.007	
7.0	.156	.096	.054	.134	.083	.047	.093	.058	.033	.054	.034	.020	.017	.011	.007	
8.0	.150	.090	.050	.129	.078	.043	.089	.055	.031	.052	.032	.018	.017	.011	.006	
9.0	.144	.085	.046	.124	.074	.040	.086	.052	.029	.050	.031	.017	.016	.010	.006	
10.0	.138	.081	.044	.119	.071	.038	.082	.050	.027	.048	.029	.016	.016	.010	.005	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-05-19

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:12.00V I:0.5960A P:7.100W PF:1.000 Freq:0Hz Lamp Flux:207.592x1 lm											
NAME: NMS0410					TYPE:			WEIGHT:			
SPEC.:NMS0410-9SW12CSN050CC0100					DIM.: 1000*04*10			SERIAL No.:01			
MFR.: COLORS					SUR.:1000*04			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	28.5	30.0	28.8	30.2	30.5	28.1	29.5	28.4	29.8	30.0	
	30.2	31.6	30.6	31.9	32.2	29.6	30.9	29.9	31.2	31.5	
	31.1	32.4	31.4	32.7	33.0	30.2	31.5	30.5	31.8	32.1	
	31.8	33.0	32.1	33.3	33.6	30.5	31.8	30.9	32.1	32.4	
	32.1	33.3	32.5	33.6	33.9	30.6	31.8	31.0	32.2	32.5	
	32.4	33.5	32.8	33.9	34.2	30.7	31.8	31.1	32.2	32.5	
4H	2H	29.1	30.4	29.5	30.7	31.0	28.8	30.1	29.1	30.4	30.7
	3H	31.1	32.2	31.5	32.6	32.9	30.5	31.7	30.9	32.0	32.4
	4H	32.0	33.1	32.4	33.4	33.8	31.2	32.3	31.7	32.7	33.0
	6H	32.9	33.8	33.3	34.2	34.6	31.8	32.7	32.2	33.1	33.5
	8H	33.3	34.1	33.7	34.5	35.0	31.9	32.8	32.4	33.2	33.6
	12H	33.7	34.4	34.1	34.9	35.3	32.0	32.8	32.5	33.3	33.7
8H	4H	32.3	33.2	32.8	33.6	34.1	31.7	32.5	32.1	32.9	33.4
	6H	33.4	34.1	33.8	34.5	35.0	32.4	33.1	32.8	33.5	34.0
	8H	33.9	34.5	34.4	35.0	35.5	32.6	33.3	33.1	33.7	34.2
	12H	34.4	35.0	34.9	35.5	36.0	32.8	33.4	33.3	33.9	34.4
12H	4H	32.3	33.1	32.8	33.6	34.0	31.7	32.5	32.2	32.9	33.4
	6H	33.4	34.1	33.9	34.5	35.1	32.5	33.1	33.0	33.6	34.1
	8H	34.0	34.6	34.5	35.1	35.6	32.8	33.4	33.3	33.9	34.4
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.4					
2.0H	+ 0.1 / - 0.3					+ 0.2 / - 0.4					

CIE Pub.117, 207.6 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -5.5)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-05-19

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:12.00V I:0.5960A P:7.100W PF:1.000 Freq:0Hz Lamp Flux:207.592x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-9SW12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	57	45	38	56	45	38	55	44	38	31
0.80	67	55	48	66	55	47	64	54	47	40
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	80	71	64	78	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	79	92	84	78	88	81	76	68
2.50	98	90	84	96	88	83	91	85	81	72
3.00	101	94	89	99	92	87	94	89	85	76
4.00	105	99	95	103	97	93	98	94	90	80
5.00	108	103	99	105	101	97	100	97	93	83
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-05-19

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:12.00V I:0.5960A P:7.100W PF:1.000 Freq:0Hz Lamp Flux:207.592x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-9SW12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-05-19

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:12.00V I:0.5960A P:7.100W PF:1.000 Freq:0Hz Lamp Flux:207.592x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-9SW12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

Flux out:146.2 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-05-19

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:12.00V I:0.5960A P:7.100W PF:1.000 Freq:0Hz Lamp Flux:207.592x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-9SW12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-05-19

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:12.00V I:0.5960A P:7.100W PF:1.000 Freq:0Hz Lamp Flux:207.592x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-9SW12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:


AvgL	cd/m2
L_0~180(65)av	14706
L_0~180(75)av	13292
L_0~180(85)av	14693
L_90~270(65)av	14655
L_90~270(75)av	12623
L_90~270(85)av	8618
L_45(65)av	14756
L_45(75)av	13021
L_45(85)av	12193

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-05-19

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-05-19

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.00V I:0.5960A P:7.100W PF:1.000 Freq:0Hz Lamp Flux:207.592x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-9SW12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

Table--1

UNIT: cd

C(DEC) g (DEC)	0	45	90	135	180	225	270	315										
0	71.7	71.7	71.5	71.5	71.7	71.7	71.5	71.5										
5	71.9	71.6	71.3	71.0	71.0	70.9	71.0	71.5										
10	71.3	71.0	70.3	69.8	69.5	69.5	69.9	70.6										
15	69.9	69.7	68.7	67.9	67.5	67.4	68.1	69.1										
20	68.0	67.7	66.3	65.4	64.7	64.7	65.7	67.0										
25	65.3	65.1	63.4	62.2	61.3	61.5	62.7	64.3										
30	62.2	61.9	60.1	58.6	57.4	57.7	59.2	61.1										
35	58.5	58.2	56.1	54.4	53.1	53.4	55.2	57.3										
40	54.4	54.1	51.8	49.8	48.3	48.7	50.8	53.2										
45	49.9	49.5	47.0	44.8	43.1	43.7	46.1	48.6										
50	45.2	44.7	41.9	39.4	37.7	38.3	41.0	43.8										
55	40.1	39.6	36.5	33.8	32.0	32.7	35.7	38.7										
60	34.8	34.4	30.8	28.0	26.2	26.9	30.2	33.3										
65	29.4	28.8	25.0	22.1	20.3	21.1	24.5	27.8										
70	23.9	23.2	19.1	16.1	14.5	15.2	18.7	22.2										
75	18.4	17.3	13.1	10.4	9.12	9.63	13.0	16.6										
80	13.1	11.1	7.55	5.41	4.77	4.88	7.57	11.2										
85	8.27	6.75	3.04	2.07	1.98	1.70	2.97	6.49										
90	4.70	3.41	0.67	0.69	0.72	0.55	0.63	3.12										
95	2.61	1.87	0.45	0.50	0.47	0.39	0.53	1.57										
100	1.74	1.50	0.20	0.52	0.50	0.43	0.15	1.23										
105	1.54	1.44	0.20	0.55	0.55	0.44	0.23	1.13										
110	1.53	1.36	0.29	0.60	0.61	0.51	0.29	1.00										
115	1.51	1.31	0.40	0.62	0.67	0.51	0.37	0.92										
120	1.50	1.15	0.45	0.64	0.71	0.52	0.44	0.89										
125	1.46	0.97	0.52	0.70	0.76	0.63	0.49	0.81										
130	1.39	0.98	0.63	0.73	0.80	0.63	0.54	0.81										
135	1.38	0.95	0.65	0.76	0.87	0.64	0.59	0.85										
140	1.38	0.79	0.72	0.80	0.87	0.71	0.62	0.81										
145	1.36	0.83	0.74	0.88	0.87	0.83	0.67	0.73										
150	1.09	0.87	0.82	0.93	0.87	0.85	0.74	0.69										
155	1.08	0.89	0.84	0.98	0.91	0.91	0.85	0.69										
160	1.08	0.91	0.94	1.02	0.95	0.94	0.94	0.72										
165	1.08	0.96	1.03	1.06	0.98	1.06	1.03	0.83										
170	1.08	1.04	1.07	1.12	0.98	1.06	1.12	0.94										
175	1.08	1.14	1.16	1.18	1.00	1.13	1.20	1.06										
180	1.08	1.18	1.24	1.20	1.08	1.16	1.26	1.18										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-05-19

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: