


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:12.00V I:0.6090A P:7.300W PF:1.000 Freq:0Hz Lamp Flux:81.0072x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0R12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 11.10 lm/W			
MODEL	NMS0410	Imax(cd)	28.30	S/MH(C0/180)	1.21
NOMINAL POWER(W)	7.2	LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	12	TOTAL FLUX(lm)	81.007	h UP,DN(C0-180)	1.7,49.9
NOMINAL FLUX(lm)	81.0072	CIE CLASS	DIRECT	h UP,DN(C180-360)	1.3,47.2
LAMPS INSIDE	1	h up(%)	3.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	12	h down(%)	97.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-06-01

Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	28.06	27.53	27.18	26.93	27.41	27.18	27.01	27.15	0~ 10	2.632	2.632	3.25,3.25
20	26.71	26.15	25.63	25.32	25.61	25.39	25.41	25.67	10~ 20	7.518	10.15	12.5,12.5
30	24.38	23.80	23.14	22.71	22.88	22.67	22.90	23.29	20~ 30	11.33	21.48	26.5,26.5
40	21.20	20.64	19.86	19.35	19.33	19.25	19.64	20.17	30~ 40	13.54	35.02	43.2,43.2
50	17.52	16.96	16.03	15.38	15.17	15.18	15.83	16.62	40~ 50	13.94	48.95	60.4,60.4
60	13.42	12.98	11.77	11.04	10.73	10.79	11.61	12.67	50~ 60	12.53	61.48	75.9,75.9
70	9.101	8.738	7.209	6.458	6.161	6.221	7.143	8.419	60~ 70	9.562	71.04	87.7,87.7
80	4.945	4.520	2.827	2.322	2.259	2.171	2.984	4.282	70~ 80	5.594	76.64	94.6,94.6
90	1.894	1.444	0.2088	0.3388	0.4204	0.3609	0.2461	1.333	80~ 90	1.972	78.61	97.97
100	0.8628	0.7214	0.0869	0.2606	0.2739	0.2538	0.0668	0.6748	90~100	0.5687	79.18	97.7,97.7
110	0.7347	0.4936	0.0868	0.2807	0.2941	0.2538	0.1137	0.5490	100~110	0.3878	79.57	98.2,98.2
120	0.6813	0.4141	0.1870	0.3006	0.3139	0.2538	0.1537	0.4351	110~120	0.3489	79.91	98.7,98.7
130	0.6349	0.4141	0.2137	0.3006	0.3206	0.2538	0.2136	0.3874	120~130	0.3063	80.22	99.99
140	0.6145	0.3407	0.2738	0.3274	0.3206	0.2735	0.2473	0.3607	130~140	0.2652	80.49	99.4,99.4
150	0.4476	0.3340	0.2939	0.3542	0.3408	0.2939	0.2873	0.2939	140~150	0.2121	80.70	99.6,99.6
160	0.4207	0.3540	0.3337	0.4075	0.3941	0.3874	0.3343	0.3006	150~160	0.1591	80.86	99.8,99.8
170	0.4208	0.4075	0.4141	0.4408	0.4074	0.4141	0.4142	0.3873	160~170	0.1099	80.97	100,100
180	0.4008	0.4408	0.4342	0.4475	0.4074	0.4408	0.4542	0.4342	170~180	0.0403	81.01	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:12.00V I:0.6090A P:7.300W PF:1.000 Freq:0Hz Lamp Flux:81.0072x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0R12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:12.00V I:0.6090A P:7.300W PF:1.000 Freq:0Hz Lamp Flux:81.0072x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0R12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.04	1.04	1.04	.99	.99	.99	.97
1.0	1.03	.99	.95	1.00	.96	.93	.96	.92	.89	.91	.88	.86	.87	.85	.83	.81
2.0	.90	.83	.77	.87	.81	.76	.83	.78	.74	.80	.75	.71	.76	.73	.69	.67
3.0	.79	.70	.64	.77	.69	.63	.73	.67	.62	.70	.65	.60	.67	.63	.59	.56
4.0	.70	.61	.54	.68	.60	.54	.65	.58	.52	.63	.56	.51	.60	.55	.50	.48
5.0	.62	.53	.47	.61	.52	.46	.58	.51	.45	.56	.50	.45	.54	.48	.44	.42
6.0	.56	.47	.41	.55	.46	.40	.53	.45	.40	.51	.44	.39	.49	.43	.39	.36
7.0	.51	.42	.36	.50	.41	.36	.48	.41	.35	.46	.40	.35	.45	.39	.34	.32
8.0	.46	.38	.32	.45	.37	.32	.44	.37	.31	.42	.36	.31	.41	.35	.31	.29
9.0	.42	.34	.29	.42	.34	.29	.40	.33	.28	.39	.33	.28	.38	.32	.28	.26
10.0	.39	.31	.26	.39	.31	.26	.37	.30	.26	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-06-01

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:12.00V I:0.6090A P:7.300W PF:1.000 Freq:0Hz Lamp Flux:81.0072x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0R12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.314	.179	.057	.306	.175	.056	.291	.167	.053	.278	.160	.051	.265	.154	.050	
2.0	.293	.161	.049	.286	.157	.049	.273	.152	.047	.260	.146	.046	.249	.141	.044	
3.0	.270	.144	.043	.264	.141	.043	.252	.137	.042	.241	.132	.041	.231	.128	.040	
4.0	.249	.129	.038	.243	.127	.038	.233	.123	.037	.223	.120	.036	.214	.116	.035	
5.0	.230	.117	.034	.225	.115	.034	.215	.112	.033	.207	.109	.032	.198	.106	.032	
6.0	.213	.107	.031	.208	.105	.030	.200	.103	.030	.192	.100	.029	.185	.097	.029	
7.0	.198	.098	.028	.194	.097	.028	.186	.094	.027	.179	.092	.027	.173	.090	.026	
8.0	.185	.090	.025	.181	.089	.025	.174	.087	.025	.168	.085	.025	.162	.083	.024	
9.0	.173	.084	.023	.170	.083	.023	.164	.081	.023	.158	.079	.023	.153	.077	.022	
10.0	.163	.078	.022	.160	.077	.022	.154	.076	.021	.149	.074	.021	.144	.072	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.213	.213	.213	.182	.182	.182	.124	.124	.124	.071	.071	.071	.023	.023	.023	
1.0	.203	.179	.157	.174	.153	.135	.119	.106	.093	.069	.061	.054	.022	.020	.018	
2.0	.195	.155	.121	.167	.133	.104	.115	.092	.073	.066	.054	.043	.021	.017	.014	
3.0	.188	.137	.097	.161	.118	.084	.110	.082	.059	.064	.048	.035	.020	.016	.011	
4.0	.180	.124	.081	.154	.107	.071	.106	.075	.050	.061	.044	.029	.020	.014	.010	
5.0	.172	.114	.070	.148	.098	.061	.102	.069	.043	.059	.040	.026	.019	.013	.008	
6.0	.165	.105	.063	.142	.091	.054	.098	.064	.039	.057	.038	.023	.018	.012	.008	
7.0	.158	.099	.057	.136	.085	.049	.094	.060	.035	.055	.035	.021	.018	.012	.007	
8.0	.152	.093	.052	.131	.081	.045	.091	.057	.032	.053	.033	.019	.017	.011	.006	
9.0	.146	.088	.049	.126	.076	.042	.087	.054	.030	.051	.032	.018	.016	.010	.006	
10.0	.140	.084	.046	.121	.073	.040	.084	.051	.028	.049	.030	.017	.016	.010	.006	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:12.00V I:0.6090A P:7.300W PF:1.000 Freq:0Hz Lamp Flux:81.0072x1 lm										
NAME: NMS0410					TYPE:			WEIGHT:		
SPEC.:NMS0410-0R12CSN050CC0100					DIM.: 1000*04*10			SERIAL No.:01		
MFR.: COLORS					SUR.:1000*04			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	28.3	29.8	28.6	30.1	30.3	27.9	29.4	28.2	29.6	29.9
3H	30.1	31.5	30.4	31.7	32.0	29.4	30.7	29.7	31.0	31.3
4H	30.9	32.2	31.2	32.5	32.8	29.9	31.2	30.3	31.6	31.9
6H	31.6	32.8	32.0	33.1	33.5	30.3	31.6	30.7	31.9	32.2
8H	31.9	33.1	32.3	33.4	33.8	30.4	31.6	30.8	32.0	32.3
12H	32.2	33.3	32.6	33.7	34.1	30.5	31.6	30.9	32.0	32.3
4H 2H	29.0	30.3	29.3	30.6	30.9	28.6	29.9	29.0	30.2	30.5
3H	30.9	32.0	31.3	32.4	32.8	30.3	31.5	30.7	31.8	32.2
4H	31.8	32.9	32.3	33.3	33.7	31.0	32.1	31.5	32.5	32.8
6H	32.7	33.6	33.2	34.0	34.5	31.6	32.5	32.0	32.9	33.3
8H	33.1	34.0	33.6	34.4	34.8	31.7	32.6	32.2	33.0	33.5
12H	33.5	34.3	34.0	34.7	35.2	31.8	32.6	32.3	33.0	33.5
8H 4H	32.2	33.0	32.6	33.4	33.9	31.5	32.3	31.9	32.7	33.2
6H	33.2	33.9	33.7	34.4	34.9	32.2	32.9	32.7	33.4	33.9
8H	33.7	34.4	34.2	34.9	35.4	32.5	33.1	33.0	33.6	34.1
12H	34.3	34.8	34.8	35.3	35.9	32.6	33.2	33.2	33.7	34.2
12H 4H	32.2	33.0	32.7	33.4	33.9	31.5	32.3	32.0	32.7	33.2
6H	33.3	33.9	33.8	34.4	34.9	32.3	33.0	32.8	33.4	34.0
8H	33.9	34.4	34.4	34.9	35.5	32.7	33.2	33.2	33.7	34.3
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.1 / - 0.3					+ 0.2 / - 0.4				

CIE Pub.117, 81.01 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -8.7)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:12.00V I:0.6090A P:7.300W PF:1.000 Freq:0Hz Lamp Flux:81.0072x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0R12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	57	45	38	56	45	38	54	44	38	31
0.80	67	55	47	65	54	47	63	53	47	40
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	80	70	64	77	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	78	92	84	77	88	81	76	67
2.50	98	90	84	95	88	82	91	85	80	71
3.00	101	94	88	99	92	87	94	89	85	75
4.00	105	99	94	102	97	93	98	93	90	80
5.00	108	103	98	105	100	97	100	96	93	83
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:12.00V I:0.6090A P:7.300W PF:1.000 Freq:0Hz Lamp Flux:81.0072x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0R12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:12.00V I:0.6090A P:7.300W PF:1.000 Freq:0Hz Lamp Flux:81.0072x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0R12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

Flux out:55.50 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:12.00V I:0.6090A P:7.300W PF:1.000 Freq:0Hz Lamp Flux:81.0072x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0R12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-06-01

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-06-01

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.00V I:0.6090A P:7.300W PF:1.000 Freq:0Hz Lamp Flux:81.0072x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0R12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

Table--1

UNIT: cd

C(DEG) g (DEG)	0	45	90	135	180	225	270	315										
0	28.3	27.9	27.6	27.6	28.3	27.9	27.6	27.6										
5	28.3	27.8	27.6	27.4	28.0	27.7	27.4	27.5										
10	28.1	27.5	27.2	26.9	27.4	27.2	27.0	27.2										
15	27.5	27.0	26.5	26.3	26.6	26.4	26.3	26.5										
20	26.7	26.2	25.6	25.3	25.6	25.4	25.4	25.7										
25	25.7	25.1	24.5	24.1	24.4	24.1	24.3	24.6										
30	24.4	23.8	23.1	22.7	22.9	22.7	22.9	23.3										
35	22.9	22.3	21.6	21.1	21.2	21.0	21.3	21.8										
40	21.2	20.6	19.9	19.4	19.3	19.3	19.6	20.2										
45	19.4	18.9	18.0	17.4	17.3	17.3	17.8	18.5										
50	17.5	17.0	16.0	15.4	15.2	15.2	15.8	16.6										
55	15.5	15.0	13.9	13.2	13.0	13.0	13.8	14.7										
60	13.4	13.0	11.8	11.0	10.7	10.8	11.6	12.7										
65	11.3	10.9	9.52	8.75	8.42	8.48	9.39	10.6										
70	9.10	8.74	7.21	6.46	6.16	6.22	7.14	8.42										
75	6.96	6.61	4.96	4.27	4.05	4.07	4.96	6.30										
80	4.94	4.52	2.83	2.32	2.26	2.17	2.98	4.28										
85	3.19	2.70	1.07	0.94	1.03	0.90	1.22	2.53										
90	1.89	1.44	0.21	0.34	0.42	0.36	0.25	1.33										
95	1.16	0.88	0.16	0.25	0.27	0.27	0.13	0.72										
100	0.86	0.72	0.09	0.26	0.27	0.25	0.07	0.67										
105	0.76	0.51	0.09	0.27	0.28	0.25	0.09	0.61										
110	0.73	0.49	0.09	0.28	0.29	0.25	0.11	0.55										
115	0.71	0.43	0.14	0.29	0.31	0.25	0.13	0.57										
120	0.68	0.41	0.19	0.30	0.31	0.25	0.15	0.44										
125	0.67	0.41	0.19	0.30	0.31	0.25	0.18	0.39										
130	0.63	0.41	0.21	0.30	0.32	0.25	0.21	0.39										
135	0.62	0.41	0.23	0.31	0.32	0.25	0.23	0.37										
140	0.61	0.34	0.27	0.33	0.32	0.27	0.25	0.36										
145	0.55	0.33	0.29	0.34	0.32	0.29	0.26	0.29										
150	0.45	0.33	0.29	0.35	0.34	0.29	0.29	0.29										
155	0.40	0.33	0.29	0.37	0.37	0.35	0.31	0.31										
160	0.42	0.35	0.33	0.41	0.39	0.39	0.33	0.30										
165	0.42	0.37	0.38	0.43	0.41	0.41	0.39	0.31										
170	0.42	0.41	0.41	0.44	0.41	0.41	0.41	0.39										
175	0.40	0.44	0.41	0.45	0.41	0.42	0.45	0.42										
180	0.40	0.44	0.43	0.45	0.41	0.44	0.45	0.43										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: