


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:12.00V I:0.6300A P:7.500W PF:1.000 Freq:0Hz Lamp Flux:303.048x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0G12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 40.41 lm/W			
MODEL	NMS0410	I _{max} (cd)	104.1	S/MH(C0/180)	1.24
NOMINAL POWER(W)	7.2	LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	12	TOTAL FLUX(lm)	303.05	h UP,DN(C0-180)	1.5,49.2
NOMINAL FLUX(lm)	303.048	CIE CLASS	DIRECT	h UP,DN(C180-360)	1.1,48.1
LAMPS INSIDE	1	h up(%)	2.7	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	12	h down(%)	97.3	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-06-01

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	102.2	102.2	102.0	102.2	102.3	101.9	101.6	101.7	0- 10	9.831	9.831	3.24,3.24
20	96.42	96.49	96.24	96.63	96.41	95.93	95.55	95.68	10- 20	28.09	37.92	12.5,12.5
30	87.18	87.44	86.95	87.50	87.08	86.47	86.20	86.33	20- 30	42.35	80.27	26.5,26.5
40	75.28	75.57	74.79	75.33	74.69	74.16	74.07	74.35	30- 40	50.75	131.0	43.2,43.2
50	61.49	61.54	60.45	60.81	60.02	59.67	59.78	60.43	40- 50	52.36	183.4	60.5,60.5
60	46.29	46.15	44.40	44.71	43.83	43.58	43.98	45.05	50- 60	47.17	230.6	76.1,76.1
70	30.43	29.72	27.29	27.60	26.99	26.60	27.17	28.76	60- 70	36.05	266.6	88,88
80	15.60	13.89	10.70	11.57	11.81	10.84	10.88	13.46	70- 80	21.08	287.7	94.9,94.9
90	5.828	3.647	0.5556	2.199	3.045	1.861	0.5548	3.840	80- 90	7.283	295.0	97.3,97.3
100	2.934	1.716	0.3008	0.7882	1.008	0.7014	0.2605	1.958	90-100	1.817	296.8	97.9,97.9
110	2.471	1.510	0.4599	0.8483	0.9887	0.7216	0.4546	1.584	100-110	1.215	298.0	98.3,98.3
120	2.138	1.329	0.7012	0.9154	1.095	0.8282	0.6353	1.177	110-120	1.123	299.1	98.7,98.7
130	2.178	1.463	0.9350	1.016	1.156	0.8615	0.7882	1.149	120-130	1.025	300.2	99,99
140	1.964	1.376	1.069	1.129	1.176	1.028	0.9285	1.155	130-140	0.9396	301.1	99.4,99.4
150	1.664	1.363	1.156	1.296	1.223	1.235	1.096	1.062	140-150	0.7811	301.9	99.6,99.6
160	1.590	1.363	1.363	1.463	1.369	1.376	1.356	1.209	150-160	0.6100	302.5	99.8,99.8
170	1.623	1.550	1.576	1.583	1.423	1.523	1.590	1.456	160-170	0.4142	302.9	99.9,99.9
180	1.523	1.750	1.797	1.763	1.503	1.723	1.810	1.750	170-180	0.1527	303.0	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:12.00V I:0.6300A P:7.500W PF:1.000 Freq:0Hz Lamp Flux:303.048x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0G12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:12.00V I:0.6300A P:7.500W PF:1.000 Freq:0Hz Lamp Flux:303.048x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0G12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.10	1.10	1.10	1.04	1.04	1.04	.00	.00	.00	.97
1.0	1.03	.99	.95	1.00	.96	.93	.96	.92	.89	.91	.89	.86	.87	.85	.83	.81
2.0	.90	.83	.77	.88	.81	.76	.84	.78	.74	.80	.75	.72	.76	.73	.70	.67
3.0	.79	.70	.64	.77	.69	.63	.73	.67	.62	.70	.65	.60	.67	.63	.59	.57
4.0	.70	.61	.54	.68	.60	.53	.65	.58	.52	.63	.56	.51	.60	.55	.50	.48
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.45	.54	.48	.44	.42
6.0	.56	.47	.41	.55	.46	.40	.53	.45	.40	.51	.44	.39	.49	.43	.39	.36
7.0	.51	.42	.36	.50	.41	.36	.48	.41	.35	.46	.40	.35	.45	.39	.34	.32
8.0	.46	.38	.32	.45	.37	.32	.44	.37	.31	.42	.36	.31	.41	.35	.31	.29
9.0	.42	.34	.29	.42	.34	.29	.40	.33	.28	.39	.33	.28	.38	.32	.28	.26
10.0	.39	.31	.26	.39	.31	.26	.37	.30	.26	.36	.30	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-06-01

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:12.00V I:0.6300A P:7.500W PF:1.000 Freq:0Hz Lamp Flux:303.048x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0G12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.314	.179	.057	.307	.175	.056	.292	.167	.053	.278	.160	.051	.266	.154	.050	
2.0	.293	.161	.049	.286	.158	.049	.273	.152	.047	.261	.146	.046	.250	.141	.045	
3.0	.270	.144	.043	.264	.142	.043	.253	.137	.042	.242	.132	.041	.232	.128	.040	
4.0	.249	.129	.038	.244	.127	.038	.233	.124	.037	.224	.120	.036	.215	.117	.036	
5.0	.230	.117	.034	.225	.116	.034	.216	.112	.033	.207	.109	.033	.199	.106	.032	
6.0	.213	.107	.031	.209	.105	.030	.200	.103	.030	.193	.100	.029	.185	.098	.029	
7.0	.198	.098	.028	.194	.097	.028	.187	.094	.027	.180	.092	.027	.173	.090	.026	
8.0	.185	.090	.025	.182	.089	.025	.175	.087	.025	.169	.085	.025	.163	.083	.024	
9.0	.173	.084	.023	.170	.083	.023	.164	.081	.023	.158	.079	.023	.153	.078	.022	
10.0	.163	.078	.022	.160	.077	.022	.155	.076	.021	.149	.074	.021	.144	.073	.021	

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.211	.211	.211	.180	.180	.180	.123	.123	.123	.071	.071	.071	.023	.023	.023	
1.0	.201	.177	.154	.172	.152	.133	.118	.104	.092	.068	.060	.053	.022	.019	.017	
2.0	.193	.153	.118	.165	.131	.102	.113	.091	.071	.065	.053	.042	.021	.017	.014	
3.0	.185	.135	.095	.159	.116	.082	.109	.081	.058	.063	.047	.034	.020	.015	.011	
4.0	.178	.122	.079	.152	.105	.069	.105	.073	.048	.061	.043	.029	.020	.014	.009	
5.0	.170	.111	.068	.146	.096	.059	.101	.067	.042	.058	.040	.025	.019	.013	.008	
6.0	.163	.103	.060	.140	.089	.052	.097	.063	.037	.056	.037	.022	.018	.012	.007	
7.0	.156	.096	.054	.134	.083	.047	.093	.059	.034	.054	.034	.020	.017	.011	.007	
8.0	.150	.091	.050	.129	.079	.043	.089	.055	.031	.052	.033	.018	.017	.011	.006	
9.0	.144	.086	.046	.124	.074	.040	.086	.052	.029	.050	.031	.017	.016	.010	.006	
10.0	.138	.081	.044	.119	.071	.038	.083	.050	.027	.048	.029	.016	.016	.010	.005	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:12.00V I:0.6300A P:7.500W PF:1.000 Freq:0Hz Lamp Flux:303.048x1 lm											
NAME: NMS0410					TYPE:			WEIGHT:			
SPEC.:NMS0410-0G12CSN050CC0100					DIM.: 1000*04*10			SERIAL No.:01			
MFR.: COLORS					SUR.:1000*04			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	27.9	29.4	28.2	29.7	29.9	27.8	29.3	28.1	29.5	29.8	
	3H	29.6	30.9	29.9	31.2	31.5	29.3	30.6	29.6	30.9	31.2
	4H	30.3	31.6	30.6	31.9	32.2	29.9	31.2	30.2	31.5	31.8
	6H	30.9	32.1	31.2	32.4	32.7	30.2	31.5	30.6	31.8	32.1
	8H	31.1	32.3	31.5	32.6	33.0	30.3	31.5	30.7	31.9	32.2
	12H	31.4	32.5	31.8	32.9	33.2	30.4	31.5	30.8	31.9	32.2
4H	2H	28.5	29.8	28.9	30.1	30.5	28.4	29.7	28.8	30.0	30.3
	3H	30.4	31.5	30.7	31.8	32.2	30.1	31.3	30.5	31.6	32.0
	4H	31.2	32.2	31.6	32.6	33.0	30.8	31.9	31.2	32.2	32.6
	6H	31.9	32.9	32.4	33.3	33.7	31.3	32.3	31.8	32.7	33.1
	8H	32.3	33.1	32.7	33.6	34.0	31.5	32.4	31.9	32.8	33.2
	12H	32.6	33.4	33.1	33.8	34.3	31.6	32.4	32.0	32.8	33.3
8H	4H	31.5	32.3	31.9	32.8	33.2	31.1	32.0	31.6	32.4	32.9
	6H	32.4	33.1	32.9	33.6	34.1	31.8	32.5	32.3	33.0	33.5
	8H	32.8	33.5	33.3	34.0	34.5	32.1	32.7	32.6	33.2	33.7
	12H	33.3	33.9	33.8	34.4	34.9	32.3	32.8	32.8	33.3	33.8
12H	4H	31.5	32.3	32.0	32.7	33.2	31.2	32.0	31.6	32.4	32.9
	6H	32.5	33.1	33.0	33.6	34.1	31.9	32.6	32.4	33.0	33.5
	8H	33.0	33.5	33.5	34.0	34.5	32.2	32.8	32.8	33.3	33.8
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.1 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 303.0 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -4.1)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:12.00V I:0.6300A P:7.500W PF:1.000 Freq:0Hz Lamp Flux:303.048x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0G12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	57	45	38	56	45	38	55	44	38	31
0.80	67	55	48	65	54	47	64	53	47	40
1.00	75	64	56	74	63	56	71	64	55	48
1.25	82	71	64	80	71	64	77	69	63	55
1.50	87	77	70	85	76	69	82	74	68	60
2.00	94	85	78	92	84	78	88	81	76	67
2.50	98	90	84	96	88	83	91	85	80	72
3.00	101	94	88	99	92	87	94	89	85	76
4.00	105	99	94	103	97	93	98	94	90	80
5.00	108	103	98	105	100	97	100	96	93	83
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:12.00V I:0.6300A P:7.500W PF:1.000 Freq:0Hz Lamp Flux:303.048x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0G12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:12.00V I:0.6300A P:7.500W PF:1.000 Freq:0Hz Lamp Flux:303.048x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0G12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

Flux out:212.7 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:12.00V I:0.6300A P:7.500W PF:1.000 Freq:0Hz Lamp Flux:303.048x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0G12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

Range: 0 - 180DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-06-01

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:12.00V I:0.6300A P:7.500W PF:1.000 Freq:0Hz Lamp Flux:303.048x1 lm		
NAME: NMS0410	TYPE:	WEIGHT:
SPEC.:NMS0410-0G12CSN050CC0100	DIM.: 1000*04*10	SERIAL No.:01
MFR.: COLORS	SUR.:1000*04	Shielding Angle:

Table--1

UNIT: cd

C(DEC) g (DEC)	0	45	90	135	180	225	270	315										
0	104	104	104	104	104	104	104	104										
5	104	104	103	104	104	103	103	103										
10	102	102	102	102	102	102	102	102										
15	99.8	99.8	99.6	100.0	99.9	99.4	99.1	99.1										
20	96.4	96.5	96.2	96.6	96.4	95.9	95.6	95.7										
25	92.2	92.4	92.0	92.5	92.2	91.6	91.3	91.4										
30	87.2	87.4	86.9	87.5	87.1	86.5	86.2	86.3										
35	81.5	81.8	81.2	81.7	81.2	80.6	80.5	80.6										
40	75.3	75.6	74.8	75.3	74.7	74.2	74.1	74.4										
45	68.6	68.8	67.9	68.4	67.6	67.2	67.1	67.6										
50	61.5	61.5	60.4	60.8	60.0	59.7	59.8	60.4										
55	54.0	54.0	52.6	52.9	52.1	51.7	52.0	52.9										
60	46.3	46.1	44.4	44.7	43.8	43.6	44.0	45.0										
65	38.4	38.0	35.9	36.2	35.4	35.1	35.6	37.0										
70	30.4	29.7	27.3	27.6	27.0	26.6	27.2	28.8										
75	22.7	21.5	18.8	19.2	19.0	18.3	18.8	20.8										
80	15.6	13.9	10.7	11.6	11.8	10.8	10.9	13.5										
85	9.78	7.60	4.02	5.58	6.29	5.02	4.22	7.51										
90	5.83	3.65	0.56	2.20	3.04	1.86	0.55	3.84										
95	3.72	2.03	0.46	0.98	1.48	0.87	0.28	2.37										
100	2.93	1.72	0.30	0.79	1.01	0.70	0.26	1.96										
105	2.64	1.56	0.33	0.82	0.96	0.70	0.31	1.77										
110	2.47	1.51	0.46	0.85	0.99	0.72	0.45	1.58										
115	2.26	1.43	0.61	0.85	1.05	0.71	0.53	1.65										
120	2.14	1.33	0.70	0.92	1.10	0.83	0.64	1.18										
125	2.15	1.37	0.83	0.97	1.12	0.83	0.72	1.15										
130	2.18	1.46	0.94	1.02	1.16	0.86	0.79	1.15										
135	2.02	1.51	1.02	1.06	1.18	0.94	0.86	1.15										
140	1.96	1.38	1.07	1.13	1.18	1.03	0.93	1.16										
145	1.96	1.36	1.13	1.20	1.18	1.11	0.97	1.07										
150	1.66	1.36	1.16	1.30	1.22	1.24	1.10	1.06										
155	1.60	1.36	1.27	1.38	1.31	1.30	1.21	1.16										
160	1.59	1.36	1.36	1.46	1.37	1.38	1.36	1.21										
165	1.66	1.41	1.48	1.54	1.43	1.46	1.48	1.28										
170	1.62	1.55	1.58	1.58	1.42	1.52	1.59	1.46										
175	1.54	1.69	1.69	1.70	1.44	1.68	1.72	1.65										
180	1.52	1.75	1.80	1.76	1.50	1.72	1.81	1.75										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-06-01

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: