


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:24.00V I:0.3300A P:7.900W PF:1.000 Freq:0Hz Lamp Flux:242.143x1 lm		
NAME: NMT1312-Plus-EP	TYPE:	WEIGHT:
SPEC.:NMT1312-0RGBM24CSS020CC0100-Plus-EP-G	DIM.: 1000*13*12mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 30.65 lm/W			
MODEL	NMT1312-Plus-EP	I _{max} (cd)	78.74	S/MH(C0/180)	1.28
NOMINAL POWER(W)	8	LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	24	TOTAL FLUX(lm)	242.14	h UP,DN(C0-180)	2.3,47.9
NOMINAL FLUX(lm)	242.143	CIE CLASS	DIRECT	h UP,DN(C180-360)	2.3,47.5
LAMPS INSIDE	1	h up(%)	4.7	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	24	h down(%)	95.3	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-03-13

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


g	C0	C45	C90	C135	C180	C225	C270	C315	g	F zone	F total	%lum,lamp
10	77.50	77.47	77.24	77.66	77.66	77.29	76.99	77.35	0- 10	7.452	7.452	3.08,3.08
20	73.76	73.59	72.81	73.87	74.08	73.10	72.46	73.26	10- 20	21.37	28.82	11.9,11.9
30	67.53	67.00	65.80	67.40	67.87	66.44	65.26	66.72	20- 30	32.42	61.25	25.3,25.3
40	59.03	58.29	56.51	58.77	59.44	57.57	56.00	57.97	30- 40	39.15	100.4	41.5,41.5
50	48.68	47.72	45.60	48.25	49.11	46.89	45.14	47.39	40- 50	40.76	141.2	58.3,58.3
60	36.95	35.58	33.37	36.32	37.36	34.92	33.00	35.52	50- 60	37.11	178.3	73.6,73.6
70	24.33	22.95	20.48	23.61	24.71	22.22	20.13	22.96	60- 70	28.74	207.0	85.5,85.5
80	12.15	10.69	7.977	11.26	12.54	10.13	7.803	10.86	70- 80	17.29	224.3	92.6,92.6
90	4.674	3.009	0.4945	4.017	5.328	3.279	0.2385	3.395	80- 90	6.579	230.9	95.3,95.3
100	3.767	2.191	0.1692	3.165	4.341	2.645	0.1606	2.437	90-100	2.794	233.7	96.5,96.5
110	3.487	1.930	0.2824	2.845	3.954	2.379	0.3412	2.290	100-110	2.385	236.1	97.5,97.5
120	3.066	1.576	0.4898	2.328	3.479	1.944	0.4810	1.818	110-120	2.031	238.1	98.3,98.3
130	2.592	1.034	0.6209	1.942	2.791	1.090	0.5813	1.476	120-130	1.571	239.7	99,99
140	1.894	0.8817	0.7811	0.9485	1.929	0.8080	0.6748	0.7934	130-140	0.9974	240.7	99.4,99.4
150	1.107	0.9315	0.8812	1.049	0.9620	0.9216	0.8152	0.8291	140-150	0.5968	241.3	99.6,99.6
160	1.149	1.022	1.035	1.172	1.069	1.068	1.029	0.9019	150-160	0.4593	241.7	99.8,99.8
170	1.156	1.176	1.196	1.269	1.115	1.189	1.223	1.035	160-170	0.3137	242.0	100,100
180	1.156	1.349	1.369	1.363	1.156	1.343	1.369	1.329	170-180	0.1159	242.1	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-03-13

g Range: 0 - 180DEG
 Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:24.00V I:0.3300A P:7.900W PF:1.000 Freq:0Hz Lamp Flux:242.143x1 lm		
NAME: NMT1312-Plus-EP	TYPE:	WEIGHT:
SPEC.:NMT1312-0RGBM24CSS020CC0100-Plus-EP-G	DIM.: 1000*13*12mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*13	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-13

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:24.00V I:0.3300A P:7.900W PF:1.000 Freq:0Hz Lamp Flux:242.143x1 lm		
NAME: NMT1312-Plus-EP	TYPE:	WEIGHT:
SPEC.:NMT1312-0RGBM24CSS020CC0100-Plus-EP-G	DIM.: 1000*13*12mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

r _{cc}	80%			70%			50%			30%			10%			0
r _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
r _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.18	1.18	1.18	1.15	1.15	1.15	1.09	1.09	1.09	1.03	1.03	1.03	.98	.98	.98	.95
1.0	1.02	.98	.94	.90	.95	.92	.94	.91	.88	.90	.87	.85	.85	.83	.81	.79
2.0	.89	.82	.76	.87	.80	.75	.82	.77	.72	.78	.74	.70	.75	.71	.68	.65
3.0	.78	.70	.63	.76	.68	.62	.72	.66	.60	.69	.63	.59	.66	.61	.57	.55
4.0	.69	.60	.53	.67	.59	.53	.64	.57	.51	.61	.55	.50	.58	.53	.49	.47
5.0	.61	.52	.46	.60	.52	.45	.57	.50	.44	.55	.48	.43	.53	.47	.42	.40
6.0	.55	.46	.40	.54	.46	.39	.52	.44	.39	.50	.43	.38	.48	.42	.37	.35
7.0	.50	.41	.35	.49	.41	.35	.47	.40	.34	.45	.39	.34	.43	.38	.33	.31
8.0	.46	.37	.31	.45	.37	.31	.43	.36	.30	.41	.35	.30	.40	.34	.30	.28
9.0	.42	.34	.28	.41	.33	.28	.40	.32	.27	.38	.32	.27	.37	.31	.27	.25
10.0	.39	.31	.25	.38	.30	.25	.37	.30	.25	.35	.29	.25	.34	.28	.24	.22



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-03-13

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:24.00V I:0.3300A P:7.900W PF:1.000 Freq:0Hz Lamp Flux:242.143x1 lm		
NAME: NMT1312-Plus-EP	TYPE:	WEIGHT:
SPEC.:NMT1312-0RGBM24CSS020CC0100-Plus-EP-G	DIM.: 1000*13*12mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

rcc	80%			70%			50%			30%			10%			0														
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
rfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.320	.182	.058	.311	.178	.056	.295	.169	.054	.281	.162	.052	.267	.155	.050															
2.0	.296	.162	.050	.289	.159	.049	.275	.153	.047	.262	.147	.046	.250	.141	.044															
3.0	.273	.145	.043	.266	.142	.043	.253	.137	.042	.241	.132	.041	.231	.128	.040															
4.0	.251	.130	.038	.245	.128	.038	.233	.124	.037	.223	.120	.036	.213	.116	.035															
5.0	.231	.118	.034	.226	.116	.034	.216	.112	.033	.206	.109	.032	.197	.105	.032															
6.0	.214	.107	.031	.209	.106	.030	.200	.103	.030	.192	.100	.029	.184	.097	.029															
7.0	.199	.098	.028	.195	.097	.028	.186	.094	.027	.179	.092	.027	.171	.089	.026															
8.0	.186	.091	.025	.182	.089	.025	.174	.087	.025	.167	.085	.024	.161	.082	.024															
9.0	.174	.084	.023	.170	.083	.023	.163	.081	.023	.157	.079	.023	.151	.077	.022															
10.0	.163	.078	.022	.160	.077	.022	.154	.075	.021	.148	.074	.021	.143	.072	.021															

rcc	80%			70%			50%			30%			10%			0
rw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
rfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.226	.226	.226	.193	.193	.193	.132	.132	.132	.076	.076	.076	.024	.024	.024	
1.0	.217	.192	.169	.185	.165	.146	.127	.113	.101	.073	.066	.059	.023	.021	.019	
2.0	.209	.168	.133	.179	.144	.115	.123	.100	.080	.071	.058	.047	.023	.019	.015	
3.0	.201	.150	.110	.172	.130	.095	.118	.090	.067	.068	.053	.039	.022	.017	.013	
4.0	.194	.137	.094	.166	.119	.082	.114	.083	.058	.066	.048	.034	.021	.016	.011	
5.0	.186	.127	.084	.160	.110	.073	.110	.077	.051	.064	.045	.030	.021	.015	.010	
6.0	.179	.119	.076	.154	.103	.066	.106	.072	.047	.062	.042	.028	.020	.014	.009	
7.0	.172	.112	.070	.148	.097	.061	.102	.068	.043	.059	.040	.026	.019	.013	.008	
8.0	.166	.106	.065	.143	.092	.057	.099	.065	.040	.057	.038	.024	.019	.013	.008	
9.0	.160	.101	.062	.137	.088	.054	.095	.062	.038	.055	.037	.023	.018	.012	.008	
10.0	.154	.097	.059	.133	.084	.052	.092	.059	.037	.054	.035	.022	.017	.012	.007	

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-13

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:24.00V I:0.3300A P:7.900W PF:1.000 Freq:0Hz Lamp Flux:242.143x1 lm										
NAME: NMT1312-Plus-EP					TYPE:			WEIGHT:		
SPEC.:NMT1312-0RGBM24CSS020CC0100-Plus-EP-G					DIM.: 1000*13*12mm			SERIAL No.:01		
MFR.: COLORS					SUR.:1000*13			Shielding Angle:		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise				Viewed endwise				
x = 2H y = 2H	23.7	25.1	24.0	25.4	25.7	23.3	24.8	23.6	25.1	25.4
	25.3	26.7	25.7	27.0	27.3	24.8	26.1	25.1	26.5	26.8
	26.0	27.3	26.4	27.7	28.0	25.3	26.6	25.7	27.0	27.3
	26.6	27.8	27.0	28.2	28.6	25.7	26.9	26.1	27.3	27.7
	26.9	28.0	27.3	28.4	28.8	25.8	27.0	26.2	27.3	27.7
	27.1	28.2	27.5	28.6	29.0	25.8	27.0	26.3	27.4	27.8
4H	24.2	25.5	24.6	25.9	26.2	24.0	25.3	24.4	25.6	25.9
	26.1	27.2	26.5	27.6	28.0	25.6	26.8	26.1	27.1	27.5
	26.9	28.0	27.4	28.4	28.8	26.3	27.3	26.8	27.8	28.2
	27.7	28.6	28.1	29.0	29.5	26.8	27.7	27.3	28.2	28.6
	28.0	28.8	28.5	29.3	29.8	27.0	27.8	27.5	28.3	28.8
	28.3	29.1	28.8	29.5	30.0	27.1	27.8	27.6	28.3	28.8
8H	27.2	28.0	27.7	28.5	29.0	26.7	27.5	27.1	28.0	28.4
	28.1	28.8	28.6	29.3	29.8	27.3	28.0	27.8	28.5	29.0
	28.5	29.1	29.0	29.7	30.2	27.6	28.2	28.1	28.7	29.2
	29.0	29.5	29.5	30.0	30.6	27.7	28.3	28.3	28.8	29.4
12H	27.2	28.0	27.7	28.4	28.9	26.7	27.5	27.2	27.9	28.4
	28.1	28.8	28.7	29.3	29.8	27.4	28.0	27.9	28.6	29.1
	28.6	29.2	29.2	29.7	30.3	27.7	28.3	28.3	28.8	29.4
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.2				+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3				+ 0.2 / - 0.3					
2.0H	+ 0.1 / - 0.3				+ 0.2 / - 0.4					

CIE Pub.117, 242.1 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -4.9)

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-13

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:24.00V I:0.3300A P:7.900W PF:1.000 Freq:0Hz Lamp Flux:242.143x1 lm		
NAME: NMT1312-Plus-EP	TYPE:	WEIGHT:
SPEC.:NMT1312-0RGBM24CSS020CC0100-Plus-EP-G	DIM.: 1000*13*12mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*13	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	44	37	55	43	37	53	43	36	30
0.80	65	54	46	64	53	46	62	52	45	38
1.00	74	62	55	72	62	54	70	63	54	46
1.25	81	70	63	79	69	62	76	67	61	53
1.50	86	75	68	84	74	68	80	72	66	58
2.00	93	84	77	91	82	76	87	80	74	65
2.50	97	89	82	94	87	81	90	84	79	69
3.00	100	93	87	98	91	86	93	88	83	73
4.00	104	98	93	102	96	92	97	92	88	78
5.00	107	102	97	104	99	95	99	95	92	81
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-13

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:24.00V I:0.3300A P:7.900W PF:1.000 Freq:0Hz Lamp Flux:242.143x1 lm		
NAME: NMT1312-Plus-EP	TYPE:	WEIGHT:
SPEC.:NMT1312-0RGBM24CSS020CC0100-Plus-EP-G	DIM.: 1000*13*12mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*13	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-03-13

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

AAI Figure

Test:U:24.00V I:0.3300A P:7.900W PF:1.000 Freq:0Hz Lamp Flux:242.143x1 lm		
NAME: NMT1312-Plus-EP	TYPE:	WEIGHT:
SPEC.:NMT1312-0RGBM24CSS020CC0100-Plus-EP-G	DIM.: 1000*13*12mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

Flux out:167.8 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-13

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:24.00V I:0.3300A P:7.900W PF:1.000 Freq:0Hz Lamp Flux:242.143x1 lm		
NAME: NMT1312-Plus-EP	TYPE:	WEIGHT:
SPEC.:NMT1312-0RGBM24CSS020CC0100-Plus-EP-G	DIM.: 1000*13*12mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*13	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 45.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:JYH
 Test Date:2020-03-13

g Range: 0 - 180DEG
 g Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:10.950m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: JYH
Test Date: 2020-03-13

Range: 0 - 180DEG
Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 10.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:24.00V I:0.3300A P:7.900W PF:1.000 Freq:0Hz Lamp Flux:242.143x1 lm		
NAME: NMT1312-Plus-EP	TYPE:	WEIGHT:
SPEC.:NMT1312-0RGBM24CSS020CC0100-Plus-EP-G	DIM.: 1000*13*12mm	SERIAL No.:01
MFR.: COLORS	SUR.:1000*13	Shielding Angle:

Table--1

UNIT: cd

C(DEC) g (DEC)	0	45	90	135	180	225	270	315										
0	78.7	78.7	78.6	78.7	78.7	78.7	78.6	78.7										
5	78.4	78.4	78.4	78.5	78.5	78.4	78.2	78.4										
10	77.5	77.5	77.2	77.7	77.7	77.3	77.0	77.3										
15	76.0	75.9	75.4	76.1	76.2	75.5	75.1	75.6										
20	73.8	73.6	72.8	73.9	74.1	73.1	72.5	73.3										
25	70.9	70.6	69.6	70.9	71.3	70.1	69.1	70.3										
30	67.5	67.0	65.8	67.4	67.9	66.4	65.3	66.7										
35	63.5	62.9	61.4	63.3	63.9	62.3	60.9	62.6										
40	59.0	58.3	56.5	58.8	59.4	57.6	56.0	58.0										
45	54.0	53.2	51.3	53.7	54.5	52.4	50.8	52.9										
50	48.7	47.7	45.6	48.3	49.1	46.9	45.1	47.4										
55	43.0	41.9	39.6	42.5	43.4	41.0	39.2	41.6										
60	37.0	35.6	33.4	36.3	37.4	34.9	33.0	35.5										
65	30.7	29.2	27.0	30.0	31.1	28.6	26.6	29.3										
70	24.3	22.9	20.5	23.6	24.7	22.2	20.1	23.0										
75	18.0	16.6	14.0	17.2	18.4	15.9	13.8	16.7										
80	12.1	10.7	7.98	11.3	12.5	10.1	7.80	10.9										
85	7.43	5.82	3.15	6.56	7.90	5.56	2.92	6.11										
90	4.67	3.01	0.49	4.02	5.33	3.28	0.24	3.40										
95	3.89	2.33	0.21	3.39	4.51	2.81	0.12	2.75										
100	3.77	2.19	0.17	3.16	4.34	2.65	0.16	2.44										
105	3.62	2.08	0.18	2.99	4.15	2.51	0.24	2.20										
110	3.49	1.93	0.28	2.84	3.95	2.38	0.34	2.29										
115	3.08	1.77	0.38	2.53	3.74	2.06	0.40	2.26										
120	3.07	1.58	0.49	2.33	3.48	1.94	0.48	1.82										
125	2.92	1.48	0.54	2.19	3.08	1.74	0.54	1.61										
130	2.59	1.03	0.62	1.94	2.79	1.09	0.58	1.48										
135	2.39	0.87	0.72	1.16	2.51	0.90	0.64	0.88										
140	1.89	0.88	0.78	0.95	1.93	0.81	0.67	0.79										
145	1.10	0.90	0.83	0.98	1.14	0.85	0.74	0.81										
150	1.11	0.93	0.88	1.05	0.96	0.92	0.82	0.83										
155	1.11	0.98	0.94	1.11	1.02	1.04	0.93	0.85										
160	1.15	1.02	1.03	1.17	1.07	1.07	1.03	0.90										
165	1.16	1.10	1.15	1.21	1.10	1.14	1.12	0.94										
170	1.16	1.18	1.20	1.27	1.11	1.19	1.22	1.04										
175	1.13	1.28	1.26	1.32	1.13	1.26	1.32	1.16										
180	1.16	1.35	1.37	1.36	1.16	1.34	1.37	1.33										

C Range: 0 - 360DEG
C Interval: 45.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:JYH
Test Date:2020-03-13

g Range: 0 - 180DEG
g Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:10.950m [K=1.0000]
Remarks: